

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Page 1/9



Revision: 15.11.2022

Safety data sheet according to 1907/2006/EC, Article 31 Printing date 15.11.2022 Version number 1 Trade name: Aerosol Oberflaechenkontrollspray (Contd. of page 1) · Hazard pictograms GHS02 GHS07 · Signal word Danger · Hazard-determining components of labelling: EC927-241-2 Naphtha (petroleum), hydrotreated light (<0,1% benzene) · Hazard statements H222 Extremely flammable aerosol. H229 Pressurised container: May burst if heated. H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting effects. · Precautionary statements P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P103 Read carefully and follow all instructions. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment. *P312* Call a POISON CENTER/doctor if you feel unwell. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. • Additional information: Without adequate ventilation, explosive atmosphere/gas mix may be created. Warning! Hazardous respirable droplets may be formed when sprayed Do not breathe spray or mist

SECTION 3: Composition/	information on ingredients	
• 3.2 Mixtures • Description • Mixture of substance	es listed below with nonhazardous additions.	
· Dangerous components:	s isica below with nonnagardous datations.	
EC number: 927-241-2 Reg.nr.: 01-2119471843-32-xxxx	EC927-241-2 Naphtha (petroleum), hydrotreated light (<0,1% benzene)	50-100
C .	� Flam. Liq. 3, H226; � Asp. Tox. 1, H304; � STOT SE 3, H336; Aquatic Chronic 3, H412, EUH066	
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane 🚸 Flam. Gas IA, H220; Press. Gas (Comp.), H280, EUH018	10-<25
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane (containing ≤ 0,1 % butadiene (203-450-8)) ♦ Flam. Gas IA, H220; Press. Gas (Comp.), H280, EUH018	10-<25
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane (containing ≤ 0,1 % butadiene (203-450-8)) � Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	5-<10

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Oberflaechenkontrollspray

(Contd. of page 2)

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media -

- Suitable extinguishing agents: Cool container whit water
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions:
- Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace.
- Information about fire and explosion protection: Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke.
 Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:
- Observe official regulations on storing packagings with pressurised containers. • Information about storage in one common storage facility: Not required.

GB

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

(Contd. of page 3)

Trade name: Aerosol Oberflaechenkontrollspray

- Further information about storage conditions: None.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

106-97-8 butane (containing ≤0,1 % butadiene (203-450-8))

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work.
- Respiratory protection:



When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

· Hand protection



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- · Material of gloves Nitrile rubber, NBR
- Penetration time of glove material

Gloves must be changed after every contamination.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- \cdot For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:
- butyl rubber, 0,7mm
- Eye/face protection Not required.

SECTION 9: Physical and chemical properties

• General Information	
Physical state	Aerosol
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and	l boiling
range	-44 °C

(Contd. on page 5)

GB

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Oberflaechenkontrollspray

	(Contd. of page	
Flammability	Not applicable.	
Lower and upper explosion limit		
Lower:	1.5 Vol % (106-97-8 butane (containing $\leq 0,1$ % butadiene (203-450-8)))	
Upper:	10.9 Vol % (74-98-6 propane)	
Flash point:	-97 °C (74-98-6 propane)	
Ignition temperature:	$365 \ ^{\circ}C (106-97-8 \ butane \ (containing \le 0,1 \ \% \ butadien (203-450-8)))$	
Decomposition temperature:	Not determined.	
рН	Not determined.	
Viscosity:		
Kinematic viscosity	Not determined.	
Dynamic:	Not determined.	
Solubility	Noi determined.	
water:	Not miscible or difficult to mix.	
	Not misciple of afficult to mix. Not determined.	
Partition coefficient n-octanol/water (log value)		
Vapour pressure at 20 °C:	3,600 hPa (74-98-6 propane)	
Density and/or relative density	No.4 dotamin d	
Relative density	Not determined.	
Vapour density	Not determined.	
9.2 Other information		
Appearance:		
Form:	Aerosol	
Important information on protection of health and environment, and on safety.	d	
Auto-ignition temperature:	Product is not selfigniting.	
• •	Product is not explosive. However, formation of	
Explosive properties:	explosive air/vapour mixtures are possible. Not determined.	
Solvent content:		
Organic solvents:	100.0 %	
5	With propellant gas. Content given by weight.	
VOC (EU)	100.00 %	
Solids content:	0.0 %	
Change in condition		
Evaporation rate	Not applicable.	
-		
Information with regard to physical hazard classe		
Explosives	Void Void	
Flammable gases	Void	
Aerosols	Extremely flammable aerosol. Pressurised container	
a	May burst if heated.	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Void	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flammable		
gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Droanic norovidos		

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Oberflaechenkontrollspray

		(Contd. of page 5)
• Corrosive to metals • Desensitised explosives	Void Void	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- \cdot 10.4 Conditions to avoid No further relevant information available.
- \cdot 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · STOT-single exposure May cause drowsiness or dizziness.
- · Aspiration hazard May be fatal if swallowed and enters airways.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Ikke relevant.
- · 12.6 Endocrine disrupting properties
- The product does not contain substances with endocrine disrupting properties.
- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7) GB

Printing date 15.11.2022

*

Version number 1

Revision: 15.11.2022

(Contd. of page 6)

Trade name: Aerosol Oberflaechenkontrollspray

• Uncleaned packaging: • Recommendation: Disposal must be made according to official regulations.

· 14.1 UN number or ID number	
· ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name	
ADR	1950 AEROSOLS
·IMDG	AEROSOLS
· IATA	AEROSOLS, flammable
· 14.3 Transport hazard class(es)	
ADR	
· Class	2 5F Gases.
· Label	2.1 2.1
· IMDG, IATA	
· Class	2.1 Gases.
· Label	2.1
· 14.4 Packing group	
· ADR, IMDĞ, IATA	Void
	not classified
· 14.5 Environmental hazards:	
• Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Gases.
• Hazard identification number (Kemler code):	-
	not classified
· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of
	litre: Category A. For AEROSOLS with a maximum capacity of
	1 litre: Category B. For WASTE AEROSOLS: Catego
	C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity o
	litre:
	Segregation as for class 9. Stow "separated from" clas
	except for division 1.4.
	<i>For AEROSOLS with a capacity above 1 litre:</i>
	Segregation as for the appropriate subdivision of class For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Oberflaechenkontrollspray

	(Contd. of pag	
· 14.7 Maritime transport in bulk accord instruments	•	
instruments	Not applicable.	
• Transport/Additional information:		
$\cdot ADR$		
· Limited quantities (LQ)	1L	
\cdot Excepted quantities ($\widetilde{E}Q$)	Code: E0	
	Not permitted as Excepted Quantity	
· Transport category	2	
· Tunnel restriction code	D	
· IMDG		
· Limited quantities (LQ)	1L	
\cdot Excepted quantities (\widetilde{EQ})	Code: E0	
	Not permitted as Excepted Quantity	
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1	

SECTION 15: Regulatory information

- \cdot 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture VOC: <840g/l
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· National regulations:

• Technical instructions (air):

ClassShare in %NK50-100

- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H220 Extremely flammable gas.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H336 May cause drowsiness or dizziness.
- H412 Harmful to aquatic life with long lasting effects.
- EUH018 In use may form flammable/explosive vapour-air mixture.
- EUH066 Repeated exposure may cause skin dryness or cracking.

· Department issuing SDS: Product safety department

• Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 9)

GB

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Oberflaechenkontrollspray

(Contd. of page 8) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases - Category 1A Aerosol 1: Aerosols – Category 1 : Aerosols - Category 3 Press. Gas (Comp.): Gases under pressure - Compressed gas Flam. Liq. 3: Flammable liquids – Category 3 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard - Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 \cdot * Data compared to the previous version altered. GB