

**SAFETY DATA SHEET** according to regulation 1907/2006**Product name: Superschaumreiniger**

product ID. REZ1202

**Creation date: 11.10.2021, Revision: 04.11.2022, version: 2.0****SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING****1.1 Product identifier**

Product name

Superschaumreiniger

<https://my.chemius.net/p/yIU5Cm/en/pd/en>**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Relevant identified uses

Cleaning agent.

Uses advised against

No information.

**1.3 Details of the supplier of the safety data sheet**

Supplier

Peter Kwasny GmbH

Heilbronner Str. 96

D-74831 Gundelsheim, Germany

049-(0)6269-95-20

labor@kwasny.de

**1.4 Emergency Telephone Number**

Emergency

112

Supplier

+49 6269 95 20

**SECTION 2: HAZARDS IDENTIFICATION****2.1 Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008 (CLP)

Aerosol 1; H222 Extremely flammable aerosol.

Aerosol 1; H229.1 Pressurised container: May burst if heated.

Eye Irrit. 2; H319 Causes serious eye irritation.

**2.2 Label elements**

Labelling according to Regulation (EC) No 1272/2008 [CLP]



**Signal word: Danger**

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

**2.3 Other hazards**

No information.

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS****3.1 Substances**

For mixtures see 3.2.

**3.2 Mixtures**

Name	CAS EC Index Reach	%	Classification according to Regulation (EC) No 1272/2008 (CLP)	Specific Conc. Limits	Notes for substances
propan-2-ol	67-63-0 200-661-7 603-117-00-0 01-2119457558-25	10-<20	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	/	/
isobutane	75-28-5 200-857-2 601-004-00-0 01-2119485395-27	2,5-10	Flam. Gas 1; H220 Press. Gas; H280	/	C, U
propane	74-98-6 200-827-9 601-003-00-5 01-2119486944-21	<2,5	Flam. Gas 1; H220 Press. Gas; H280	/	U
2-butoxyethanol	111-76-2 203-905-0 603-014-00-0 01-2119475108-36	<1	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute Tox. 4; H332	/	/
sodium N-lauroylsarcosinate	137-16-6 205-281-5 -	<1	Skin Irrit. 2; H315 Eye Dam. 1; H318 Acute Tox. 2; H330.2	/	/
ammonia	1336-21-6 215-647-6 007-001-01-2	<1	Skin Corr. 1B; H314.1B Aquatic Acute 1; H400; M = 1	STOT SE 3; H335; C ≥ 5%	B

**Notes for substances**

<b>B</b>	<p>Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations.</p> <p>In Part 3 entries with Note B have a general designation of the following type: "nitric acid ... %".</p> <p>In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis.</p>
----------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

C	Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers.  In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
U	When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.) Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).

## SECTION 4: FIRST AID MEASURES

### 4.1 First aid measures

#### General notes

When in doubt or if feeling unwell seek medical assistance. Show the safety data sheet and label to the physician. No action shall be taken involving any personal risk or without suitable training.

#### Following inhalation

Leave contaminated area - breathe fresh air. If symptoms develop and persist, seek medical attention.

#### Following skin contact

Take off all contaminated clothing. Areas of the body that have come into contact with the product must be rinsed with water and soap. If symptoms develop and persist, seek medical attention. Wash contaminated clothes and shoes before reuse.

#### Following eye contact

Immediately flush eyes with running water, keeping eyelids apart. If irritation persists, seek professional medical attention.

#### Following ingestion

Not likely. Accidental ingestion: Rinse mouth thoroughly with water. Do not induce vomiting without prior consultation with a doctor. In case of doubt or if feeling unwell seek medical help. Show the physician the safety data sheet or label.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Following inhalation

Excessive exposure to spray mist, fog, or vapours may cause respiratory irritation. Coughing, sneezing, nasal discharge, labored breathing.

#### Following skin contact

Contact with skin may cause irritation (redness, itching).

#### Following eye contact

Strongly irritates the eyes. Redness, tearing, pain.

#### Following ingestion

Ingestion is unlikely because it is an aerosol. Accidental ingestion: May cause abdominal discomfort. May cause nausea/vomiting and diarrhea. Irritates mucous membranes in the mouth, throat, esophagus and in gastrointestinal area.

### 4.3 Indication of any immediate medical attention and special treatment needed

No information.

## SECTION 5: FIREFIGHTING MEASURES

### 5.1 Extinguishing media

### Suitable extinguishing media

Carbon dioxide (CO<sub>2</sub>).

Fire extinguishing powder. Extinguish large fires with water spray or alcohol-resistant foam.

### Unsuitable extinguishing media

Full water jet.

## 5.2 Special hazards arising from the substance or mixture

### Hazardous combustion products

In case of a fire toxic gases can be generated; do not inhale gases/smoke. In the event of fire the following can be generated: carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>).

## 5.3 Advice for firefighters

### Protective actions

In case of fire or heating do not breathe fumes/vapours. Prolonged heating can cause an explosion. In case of fire aerosols can explode and be propelled to considerable distances in different directions. Cool containers at risk with water spray. If possible remove containers from endangered area. No action shall be taken involving any personal risk or without suitable training.

### Special protective equipment for fire-fighters

Firefighters should wear appropriate protective clothing for firefighters (including helmets, protective boots and gloves) (EN 469) and self-contained breathing apparatus (SCBA) with a full face-piece (EN 137).

### Additional information

No information.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

##### Protective equipment

Use personal protective equipment (Section 8).

##### Precautionary measures

Ensure adequate ventilation. Keep away from sources of ignition and/or heat; No smoking! Take precautionary measures against static discharges.

##### Emergency procedures

Prevent access to unauthorised personnel. Prevent access to unprotected personnel. Avoid contact with skin and eyes. Do not breathe vapour or mist.

#### For emergency responders

Use personal protective equipment.

### 6.2 Environmental precautions

Do not allow product to reach water/drains/sewage systems or permeable soil. If accidental large entry into water or ground occurs, inform responsible authorities.

### 6.3 Methods and material for containment and cleaning up

#### For containment

Stem the spill if this does not pose risks.

#### For cleaning up

Collect the spray cans and hand them over to an authorized waste disposal contractor. Release of liquid because of damaged aerosol can (release of large quantities): In case of bigger spill, dam the spillage, pump the liquid into appropriate labelled containers, absorb a residue with absorbent material and dispose of according to local regulations. Do not absorb spillage with sawdust or other combustible material. Dispose in accordance with applicable regulations

(see Section 13).

#### OTHER INFORMATION

No information.

#### 6.4 Reference to other sections

See also sections 8 and 13.

## SECTION 7: HANDLING AND STORAGE

### 7.1 Precautions for safe handling

#### Protective measures

#### Measures to prevent fire

Ensure adequate ventilation. Take precautionary measures against static discharges. Ensure proper grounding of the equipment. Keep away from sources of ignition - no smoking.

#### Measures to prevent aerosol and dust generation

Use general or local exhaust ventilation to prevent inhaling vapours and aerosols.

#### Measures to protect the environment

No information.

#### Other measures

No information.

#### Advice on general occupational hygiene

Consider measures required in Section 8 of this safety data sheet. Use personal protective equipment. Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Avoid contact with skin, eyes and clothes. Do not breathe vapours/mist.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Technical measures and storage conditions

Store in accordance with local regulations. Keep in well closed containers. Keep in cool and well ventilated area. Protect from open fire, heat and direct sunlight. Keep away from sources of ignition. Keep away from oxidising substances. Keep away from food, drink and animal feeding stuffs.

#### Packaging materials

No information.

#### Requirements for storage rooms and vessels

Do not store in unlabelled containers.

#### Storage class

No information.

#### Further information on storage conditions

No information.

### 7.3 Specific end use(s)

#### Recommendations

No information.

#### Industrial sector specific solutions

No information.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

#### Occupational Exposure limit values

Name	mg/m <sup>3</sup>	ml/m <sup>3</sup>	Short-term value mg/m <sup>3</sup>	Short-term value ml/m <sup>3</sup>	Remark	Biological Tolerance Values
2-Butoxyethanol (111-76-2)	123	25	246	50	Sk, BMGV	240 mmol butoxyacetic acid/mol creatinine in urine - Post shift 240 mmol butoxyacetic acid/mol creatinine in urine - Post shift
Ammonia (1336-21-6)	18	25	25	35	/	/
Propan-2-ol (67-63-0)	999	400	1250	500	/	/
Propane-1,2-diol particulates (57-55-6)	10	/	/	/	/	/
Propane-1,2-diol total vapour and particulates (57-55-6)	474	150	/	/	/	/

#### Information on monitoring procedures

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. BS EN 482:2021 Workplace exposure. Procedures for the determination of the concentration of chemical agents. Basic performance requirements.

#### DNEL/DMEL values

##### For product

No information.

##### For components

Name	Type	Exposure route	exp. frequency	Remark	value
propan-2-ol	Worker	inhalation	long term systemic effects	/	500 mg/m <sup>3</sup>
propan-2-ol	Worker	dermal	long term systemic effects	/	888 mg/kg bw/day
propan-2-ol	Consumer	inhalation	long term systemic effects	/	89 mg/m <sup>3</sup>
propan-2-ol	Consumer	dermal	long term systemic effects	/	319 mg/kg bw/day
propan-2-ol	Consumer	oral	long term systemic effects	/	26 mg/kg bw/day
2-butoxyethanol	Worker	inhalation	long term systemic effects	/	98 mg/m <sup>3</sup>
2-butoxyethanol	Worker	inhalation	short term systemic effects	/	1091 mg/m <sup>3</sup>
2-butoxyethanol	Worker	inhalation	short term local effects	/	246 mg/m <sup>3</sup>
2-butoxyethanol	Worker	dermal	long term systemic effects	/	125 mg/kg bw/day
2-butoxyethanol	Worker	dermal	short term systemic effects	/	89 mg/kg bw/day
2-butoxyethanol	Consumer	inhalation	long term systemic effects	/	59 mg/m <sup>3</sup>
2-butoxyethanol	Consumer	inhalation	short term systemic effects	/	426 mg/m <sup>3</sup>
2-butoxyethanol	Consumer	inhalation	short term local effects	/	147 mg/m <sup>3</sup>
2-butoxyethanol	Consumer	dermal	long term systemic effects	/	75 mg/kg bw/day
2-butoxyethanol	Consumer	dermal	short term systemic effects	/	89 mg/kg bw/day
2-butoxyethanol	Consumer	oral	long term systemic effects	/	6.3 mg/kg bw/day
2-butoxyethanol	Consumer	oral	short term systemic effects	/	26.7 mg/kg bw/day

#### PNEC values

**For product**

No information.

**For components**

Name	Exposure route	Remark	value
propan-2-ol	fresh water	/	140.9 mg/L
propan-2-ol	water, intermittent release	fresh water	140.9 mg/L
propan-2-ol	marine water	/	140.9 mg/L
propan-2-ol	water treatment plant	/	2251 mg/L
propan-2-ol	fresh water sediment	dry weight	552 mg/kg
propan-2-ol	marine water sediment	dry weight	552 mg/kg
propan-2-ol	soil	dry weight	28 mg/kg
propan-2-ol	food chain	oral	160 mg/kg feed
2-butoxyethanol	fresh water	/	8.8 mg/L
2-butoxyethanol	marine water	/	0.88 mg/L
2-butoxyethanol	water, intermittent release	fresh water	26.4 mg/L
2-butoxyethanol	water treatment plant	/	463 mg/L
2-butoxyethanol	fresh water sediment	dry weight	34.6 mg/kg
2-butoxyethanol	marine water sediment	dry weight	3.46 mg/kg
2-butoxyethanol	soil	dry weight	2.33 mg/kg
2-butoxyethanol	food chain	oral	20 mg/kg feed

**8.2 Exposure controls****Appropriate engineering control****Substance/mixture related measures to prevent exposure during identified uses**

Use good personal hygiene practices – wash hands at breaks and when done working with material. Do not eat, drink or smoke while working. Avoid contact with skin, eyes and clothes. Do not breathe vapours/aerosols. Keep away from foodstuffs, beverages and feed.

**Structural measures to prevent exposure**

No information.

**Organisational measures to prevent exposure**

No information.

**Technical measures to prevent exposure**

Provide good ventilation and local exhaust in areas with increased concentration.

**Personal protective equipment****Eye and face protection**

Safety glasses with side protection (EN ISO 16321-1:2022).

**Hand protection**

Protective gloves (EN 374). The product consists of various substances, therefore the resistance of gloves can not be calculated and has to be tested before use.

**Appropriate materials****Skin protection**

Cotton protective clothing and shoes that cover the entire foot (EN ISO 20345). Protective antistatic clothing EN 1149 (1:2006, 2:1998 and 3:2004, 5:2008), protective antistatic shoes (EN 20345:2012). Choose body protection according to the activity and possible exposure.

**Respiratory protection**

In case of insufficient ventilation wear suitable respiratory protection. If the concentration limit values are exceeded, it is necessary to wear appropriate respiratory protection. Wear suitable protective breathing mask (EN 136) with filter A2-P2 (EN 14387). For dust/gas/ vapor concentrations above the applicable filter limit, in case of oxygen concentrations below 17% or in vague conditions, autonomous self-contained breathing apparatus should be used, according to standard EN 137, EN 138.

**Thermal hazards**

No information.

**Environmental exposure controls****Substance/mixture related measures to prevent exposure**

No information.

Instruction measures to prevent exposure

No information.

Organisational measures to prevent exposure

No information.

Technical measures to prevent exposure

No information.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

Physical state

liquid - aerosol

Colour

colourless yellow

Odour

No information.

Important health, safety and environmental information

Odour threshold	No information.
pH	No information.
Melting point/Freezing point	No information.
Initial boiling point/boiling range	No information.
Flash point	No information.
Evaporation rate	No information.
Flammability (solid, gas)	No information.
Explosion limits (vol%)	1.5 – 10.9 vol % (propellant)
Vapour pressure	< 0.00001 hPa at 25 °C (Hostapur OSB)
Vapour density	No information.
Density / weight	Density: 0.953 kg/L at 20 °C (data refers to the liquid portion of the product)
Solubility	No information.
Partition coefficient	No information.
Auto-ignition temperature	No information.
Decomposition temperature	No information.
Viscosity	No information.
Explosive properties	No information.
Oxidising properties	No information.

### 9.2 OTHER INFORMATION

Weight organic solvents	205 g/l (VOC) 22 % (VOC)
-------------------------	-----------------------------

## SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity

Stable under recommended transport or storage conditions.

### 10.2 Chemical stability



Product is stable under normal conditions of use, recommended handling and storage conditions.

### 10.3 Possibility of hazardous reactions

The product is stable under recommended storage and handling conditions.

### 10.4 Conditions to avoid

Avoid all possible sources of ignition (spark or flame). Do not expose to heat and direct sunlight.

### 10.5 Incompatible materials

Strong oxidising agents. Halogens. Halogenated compounds. Strong inorganic acids. Aldehydes. Oxidants.

### 10.6 Hazardous decomposition products

In case of fire/explosion vapours/gases that pose a health hazard are released.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects

#### (a) Acute toxicity

For components

Name	Exposure route	Type	Species	Time	value	Method	Remark
propan-2-ol	inhalation	LC <sub>50</sub>	rat	4 h	> 20 mg/l	/	/
propan-2-ol	dermal	LD <sub>50</sub>	rabbit	/	> 2000 mg/kg	/	/
propan-2-ol	oral	LD <sub>50</sub>	rat	/	> 2000 mg/kg	/	/
2-butoxyethanol	oral	LD <sub>50</sub>	rat	/	300 - 2000 mg/kg	/	/
2-butoxyethanol	dermal	LD <sub>50</sub>	rat	/	1000 - 2000 mg/kg	/	/
2-butoxyethanol	inhalation	LC <sub>50</sub>	rat	/	2 - 20 mg/l	/	/

#### Additional information

The product is not classified for acute toxicity.

#### (b) Skin corrosion/irritation

For components

Name	Species	Time	result	Method	Remark
propan-2-ol	/	/	Non-irritant.	/	/
2-butoxyethanol	/	/	Irritating to skin.	/	/

#### Additional information

The product is not classified as irritating to the skin.

#### (c) Serious eye damage/irritation

For components

Name	Exposure route	Species	Time	result	Method	Remark
propan-2-ol	/	/	/	Moderately irritating.	/	/
2-butoxyethanol	/	/	/	Causes severe eye irritation.	/	/

#### Additional information

Causes serious eye irritation.

#### (d) Respiratory or skin sensitisation

## For components

Name	Exposure route	Species	Time	result	Method	Remark
propan-2-ol	-	/	/	According to known data the substance is not a chemical sensitizer.	/	/

## Additional information

The product is not classified as sensitising.

## (e) (Germ cell) mutagenicity

## For components

Name	Type	Species	Time	result	Method	Remark
propan-2-ol	/	/	/	The chemical is not classified as mutagenic.	/	/

## (f) Carcinogenicity

## For components

Name	Exposure route	Type	Species	Time	value	result	Method	Remark
propan-2-ol	/	/	/	/	/	Substance is not classified as carcinogenic.	/	/

## (g) Reproductive toxicity

## For components

Name	Reproductive toxicity type	Type	Species	Time	value	result	Method	Remark
propan-2-ol	/	/	/	/	/	The chemical is not classified as toxic for reproduction.	/	/

## Summary of evaluation of the CMR properties

The product is not classified as carcinogenic, mutagenic or toxic for reproduction.

## (h) STOT-single exposure

No information.

## Additional information

STOT SE (single exposure): Not classified.

## (i) STOT-repeated exposure

No information.

## Additional information

STOT RE (repeated exposure): Not classified.

## (j) Aspiration hazard

No information.

## Additional information

Aspiration hazard: Not classified.

## SECTION 12: ECOLOGICAL INFORMATION

## 12.1 Toxicity

## Acute (short-term) toxicity

## For components

Name	Type	value	Exposure time	Species	organism	Method	Remark
propan-2-ol	LC/EC/IC <sub>50</sub>	100 - 1000 mg/L	/	fish	/	/	/
propan-2-ol	LC/EC/IC <sub>50</sub>	> 1000 mg/L	/	invertebrates	/	/	/
propan-2-ol	LC/EC/IC <sub>50</sub>	> 1000 mg/L	/	algae	/	/	/
propan-2-ol	LC/EC/IC <sub>50</sub>	> 1000 mg/L	/	bacteria	/	/	/

2-butoxyethanol	LC <sub>50</sub>	100 mg/L	/	algae	/	/	/
2-butoxyethanol	LC <sub>50</sub>	100 mg/L	/	bacteria	/	/	/
2-butoxyethanol	LC <sub>50</sub>	10000 mg/L	/	<i>Daphnia</i>	/	/	/
2-butoxyethanol	LC <sub>50</sub>	1000 mg/L	/	fish	/	/	/

#### Chronic (long-term) toxicity

No information.

### 12.2 Persistence and degradability

#### Abiotic degradation, physical- and photo-chemical elimination

No information.

#### Biodegradation

##### For components

Name	Type	Rate	Time	Evaluation	Method	Remark
propan-2-ol	biodegradability	84 %	28 days	/	/	closed cup

### 12.3 Bioaccumulative potential

#### Partition coefficient

##### For components

Name	Media	value	Temperature °C	pH	Concentration	Method
propan-2-ol	Octanol-water	0.05	/	/	/	/

#### Bioconcentration factor (BCF)

No information.

### 12.4 Mobility in soil

#### Known or predicted distribution to environmental compartments

No information.

#### Surface tension

No information.

#### Adsorption/Desorption

No information.

### 12.5 Results of PBT and vPvB assessment

No evaluation.

### 12.6 Other adverse effects

No information.

### 12.7 Additional information

#### For product

Product is not classified as dangerous for environment. Water hazard class 2 (self-assessment): hazardous for water. Handle in accordance with good working practices so that the product is not released into the environment.

#### For components

##### **propan-2-ol**

Low bioaccumulation potential. Soluble in water. It evaporates or dissolves in water within 24 hours. Larger amounts can penetrate the soil and pollute groundwater.

**2-butoxyethanol**

Water hazard class 1 (Self-assessment): slightly hazardous for water

**SECTION 13: DISPOSAL CONSIDERATIONS****13.1 Waste treatment methods****Product / Packaging disposal****Waste chemical**

Avoid release to the environment. Product and container must be disposed of safely. Dispose of in accordance with applicable waste disposal regulation. Disposal must be made according to official regulations: deliver it to authorised collector/remover/transformer of hazardous waste.

**Waste codes / waste designations according to LoW**

16 05 04\* - gases in pressure containers (including halons) containing dangerous substances

**Packaging**

Uncleaned containers should not be perforated, cut or welded. Pressurized container. Do not pierce or burn, even after use. Dispose of in accordance with applicable waste disposal regulation. Deliver completely emptied containers to approved waste disposal authorities.

**Waste codes / waste designations according to LoW**

15 01 11\* - metallic packaging containing a dangerous solid porous matrix (for example asbestos), including empty pressure containers

**Waste treatment-relevant information**

No information.

**Sewage disposal-relevant information**

No information.

**Other disposal recommendations**

No information.

**SECTION 14: TRANSPORT INFORMATION**

ADR/RID	IMDG	IATA	ADN
<b>14.1 UN number</b>			
UN 1950	UN 1950	UN 1950	UN 1950
<b>14.2 UN proper shipping name</b>			
AEROSOLS	AEROSOLS	AEROSOLS	AEROSOLS
<b>14.3 Transport hazard class(es)</b>			
2	2	2	2
			
<b>14.4 Packing group</b>			
Not given/not applicable	Not given/not applicable	Not given/not applicable	Not given/not applicable
<b>14.5 Environmental hazards</b>			
NO	NO	NO	NO

<b>14.6 Special precautions for user</b>			
Limited quantities 1 L Special provisions 190, 327, 344, 625 Packing Instructions P207, LP200 Special packing provisions PP87, RR6, L2 Transport category 2 Tunnel restriction code (D)	Limited quantities 1 L EmS F-D, S-U	Limited Quantity, Packing Instructions (Ltd Qty, Pkg Inst) Y203 Limited Quantity, Maximum Net Quantity/Package (Ltd Qty, Max Net Qty/Pkg) 30 kg G Packing Instructions (Pkg Inst) 203 Maximum Net Quantity/Package (Max Net Qty/Pkg) 25 kg Special provisions A145, A167, A802	Limited quantities 1 L
<b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>			
Goods may not be carried in bulk in bulk containers, containers or vehicles.	Goods may not be carried in bulk in bulk containers, containers or vehicles.	Not given/not applicable	Not given/not applicable

## SECTION 15: REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (including last amendment Commission Regulation (EU) 2015/830)

- Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

Information according 2004/42/EC about limitation of emissions of volatile organic compounds (VOC-guideline)  
not applicable

#### Regulation EC 648/2004 on detergents

5% - < 15%: perfumes (Citral), aliphatic hydrocarbons;< 5%: anionic surfactants

#### Special instructions

Water hazard class 2 (self-assessment): hazardous for water. Seveso III, P3a: flammable aerosols.

### 15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

## SECTION 16: OTHER INFORMATION

### Indication of changes

8.2 Exposure controls 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

### Key literature references and sources for data

No information.

### Abbreviations and acronyms

ATE - Acute Toxicity Estimate

ADR - Agreement concerning the International Carriage of Dangerous Goods by Road

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

CEN - European Committee for Standardisation

C&L - Classification and Labelling

CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008

CAS# - Chemical Abstracts Service number

CMR - Carcinogen, Mutagen, or Reproductive Toxicant

CSA - Chemical Safety Assessment

CSR - Chemical Safety Report  
DMEL - Derived Minimal Effect Level  
DNEL - Derived No Effect Level  
DPD - Dangerous Preparations Directive 1999/45/EC  
DSD - Dangerous Substances Directive 67/548/EEC  
DU - Downstream User  
EC - European Community  
ECHA - European Chemicals Agency  
EC-Number - EINECS and ELINCS Number (see also EINECS and ELINCS)  
EEA - European Economic Area (EU + Iceland, Liechtenstein and Norway)  
EEC - European Economic Community  
EINECS - European Inventory of Existing Commercial Substances  
ELINCS - European List of notified Chemical Substances  
EN - European Standard  
EQS - Environmental Quality Standard  
EU - European Union  
Euphrac - European Phrase Catalogue  
EWC - European Waste Catalogue (replaced by LoW – see below)  
GES - Generic Exposure Scenario  
GHS - Globally Harmonized System  
IATA - International Air Transport Association  
ICAO-TI - Technical Instructions for the Safe Transport of Dangerous Goods by Air  
IMDG - International Maritime Dangerous Goods  
IMSBC - International Maritime Solid Bulk Cargoes  
IT - Information Technology  
IUCLID - International Uniform Chemical Information Database  
IUPAC - International Union for Pure Applied Chemistry  
JRC - Joint Research Centre  
Kow - octanol-water partition coefficient  
LC50 - Lethal Concentration to 50 % of a test population  
LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose)  
LE - Legal Entity  
LoW - List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)  
LR - Lead Registrant  
M/I - Manufacturer / Importer  
MS - Member States  
MSDS - Material Safety Data Sheet  
OC - Operational Conditions  
OECD - Organization for Economic Co-operation and Development  
OEL - Occupational Exposure Limit  
OJ - Official Journal  
OR - Only Representative  
OSHA - European Agency for Safety and Health at work  
PBT - Persistent, Bioaccumulative and Toxic substance  
PEC - Predicted Effect Concentration  
PNEC(s) - Predicted No Effect Concentration(s)  
PPE - Personal Protection Equipment  
(Q)SAR - Qualitative Structure Activity Relationship  
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006  
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail  
RIP - REACH Implementation Project  
RMM - Risk Management Measure  
SCBA - Self-Contained Breathing Apparatus  
SDS - Safety data sheet  
SIEF - Substance Information Exchange Forum  
SME - Small and Medium sized Enterprises  
STOT - Specific Target Organ Toxicity  
(STOT) RE - Repeated Exposure  
(STOT) SE - Single Exposure  
SVHC - Substances of Very High Concern  
UN - United Nations  
vPvB - Very Persistent and Very Bioaccumulative

List of relevant H phrases

H220 Extremely flammable gas.  
H225 Highly flammable liquid and vapour.  
H280 Contains gas under pressure; may explode if heated.  
H302 Harmful if swallowed.  
H312 Harmful in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H330 Fatal if inhaled.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H400 Very toxic to aquatic life.  
H411 Toxic to aquatic life with long lasting effects.



- ☑ Provided correct labelling of the product
- ☑ Compliance with the local legislation
- ☑ Provided correct classification of the product
- ☑ Provided adequate transport data

[BENS](#)  
© [Consulting](#) | [www.bens-consulting.com](http://www.bens-consulting.com)

*The information of this SDS is based on the present state of our knowledge and meets the requirements of EU and national laws. The user's working conditions however, are beyond our knowledge and control. The product is not to be used for purposes other than those specified under section 1 without a written permission. It remains the responsibility of the user to ensure that the necessary steps are taken to meet the laws and regulations. Handling of the product may only be done by people above 18 years of age, who are satisfactorily informed of how to do the work, the hazardous properties and necessary safety precautions. The information given in this SDS is to describe the product only in terms of health and safety requirements and should not, therefore, be construed as guaranteeing specific properties.*