


Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Page 1/10



Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Silber hitzefest (D)



- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

· Dangerous components:		
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	10-<25%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane (containing ≤ 0,1 % butadiene (203-450-8)) ♦ Flam. Gas IA, H220; Press. Gas (Comp.), H280, EUH018	10-<25%
	•	(Contd. on page 3)

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Silber hitzefest (D)

CAS: 78-93-3	butanone	(Contd. of page)
	🚸 Flam. Liq. 2, H225; 🚸 Eye Irrit. 2, H319; STOT	10 23 /0
	ethyl acetate	10-<25%
	dimethyl ether 🚸 Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	5-<10%
	n-butyl acetate � Flam. Liq. 3, H226; � STOT SE 3, H336, EUH066	5-<10%
	isobutane (containing ≤ 0,1 % butadiene (203-450-8)) Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	5-<10%
Reg.nr.: 01-2119471843-32-xxxx	EC927-241-2 Naphtha (petroleum), hydrotreated light (<0,1% benzene) Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336; Aquatic Chronic 3, H412, EUH066	5-<10%
	aluminium 🚸 Flam. Sol. 1, H228	1-<2.5%
EINECS: 209-136-7 Reg.nr.: 01-2119529238-36-xxxx	octamethylcyclotetrasiloxane Flam. Liq. 3, H226; & Repr. 2, H361f; Aquatic Chronic 1, H410 (M=10) PBT; vPvB	<i>≥</i> 0.0025-<0.025%

SECTION 4: First aid measures

 \cdot 4.1 Description of first aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- \cdot 4.3 Indication of any immediate medical attention and special treatment needed
- $No\ further\ relevant\ information\ available.$

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media -
- · Suitable extinguishing agents: Cool container whit water
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

(Contd. on page 4)

GB

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Silber hitzefest (D)

(Contd. of page 3)

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

• 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

- 6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace.

• Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:
- Observe official regulations on storing packagings with pressurised containers.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

Ingredients with limit values that require monitoring at the workplace	e:
106-97-8 butane (containing $\leq 0,1$ % butadiene (203-450-8))	
WEL Short-term value: 1810 mg/m ³ , 750 ppm	
Long-term value: 1450 mg/m ³ , 600 ppm	
<i>Carc (if more than 0.1% of buta-1.3-diene)</i>	
78-93-3 butanone	
WEL Short-term value: 899 mg/m ³ , 300 ppm	
Long-term value: 600 mg/m ³ , 200 ppm	
Sk, BMGV	
141-78-6 ethyl acetate	
WEL Short-term value: 1468 mg/m ³ , 400 ppm	
Long-term value: 734 mg/m ³ , 200 ppm	
	(Contd. on page

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

(Contd. of page 4)

Trade name: Aerosol Silber hitzefest (D)

115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

· Ingredients with biological limit values:

78-93-3 butanone

BMGV 70 µmol/L

Medium: urine Sampling time: post shift Parameter: butan-2-one

· Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:



When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

• Hand protection

Protective gloves



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material

Gloves must be changed after every contamination.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:
- butyl rubber, 0,7mm • **Eye/face protection**

Safety glasses



Tightly sealed goggles

(Contd. on page 6)

Printing date 15.11.2022

*

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Silber hitzefest (D)

(Contd. of page 5)

0.1 Information on basis abusis -1 1 -1 1	monouting
9.1 Information on basic physical and chemical p General Information	roperues
Physical state	Aerosol
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling	onacienninea.
range	-44 °C
Flammability	Not applicable.
Lower and upper explosion limit	Noi applicable.
Lower:	1.5 Vol % (106-97-8 butane (containing $\leq 0,1$
Lower.	(100^{-97-8}) butane (containing $\leq 0,1$ butadiene (203-450-8)))
Unnew	11.5 Vol % (78-93-3 butanone)
Upper: Flash point:	<0 °C
Flash point:	Not determined.
Decomposition temperature:	
pH Viscositu	Not determined.
Viscosity:	Not determined
Kinematic viscosity	Not determined. Not determined.
Dynamic:	ivoi delerminea.
Solubility	Nat missible on difficult to min
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure at 20 °C:	3,600 hPa (74-98-6 propane)
Density and/or relative density	
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Aerosol
Important information on protection of health an	d
environment, and on safety.	
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation
K . K . K	explosive air/vapour mixtures are possible.
	Not determined.
Solvent content:	
Organic solvents:	87.7 %
	With propellant gas. Content given by weight.
VOC (EU)	87.68 %
Solids content:	12.3 %
Change in condition	
Evaporation rate	Not applicable.
-	
Information with regard to physical hazard classe	
Explosives	Void
Flammable gases	Void
Aerosols	Extremely flammable aerosol. Pressurised contain
	May burst if heated.
Oxidising gases	Void
	Void
Gases under pressure	
Gases under pressure Flammable liquids	Void
	Void Void

GB

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Silber hitzefest (D)

		(Contd. of page)
· Pyrophoric liquids	Void	
· Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flamm	able	
gases in contact with water	Void	
Oxidising liquids	Void	
• Oxidising solids	Void	
Organic peroxides	Void	
• Corrosive to metals	Void	
· Desensitised explosives	Void	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Serious eye damage/irritation Causes serious eye irritation.
- · STOT-single exposure May cause drowsiness or dizziness.
- \cdot 11.2 Information on other hazards

· Endocrine disrupting properties

556-67-2 octamethylcyclotetrasiloxane

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- **vPvB:** Ikke relevant.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

(Contd. on page 8)

List II, III

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Silber hitzefest (D)

(Contd. of page 7)

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

*

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number	
ADR, IMDG, IATA	UN1950
14.2 UN proper shipping name	
ADR	1950 AEROSOLS
IMDG	AEROSOLS
IATA	AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
Class Label	2 5F Gases. 2.1
IMDG, IATA	
Class	2.1 Gases.
Label	2.1
14.4 Packing group	
ADR, IMDĞ, IATÂ	Void
	not classified
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Gases.
Hazard identification number (Kemler code):	-
	not classified
EMS Number:	F- D , S - U
Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of
	litre: Category A. For AEROSOLS with a capacity abo
	1 litre: Category B. For WASTE AEROSOLS: Catego
Constant Contraction	C, Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of
	litre:
	Segregation as for class 9. Stow "separated from" class
	except for division 1.4. For AEROSOLS with a capacity above 1 litre:

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Silber hitzefest (D)

	(Contd. of page
	Segregation as for the appropriate subdivision of class 2 For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class 2
14.7 Maritime transport in bulk accor	ding to IMO
instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities $(\widetilde{E}Q)$	Code: E0
	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (\widetilde{EQ})	Code: E0
	Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture VOC: <840g/l

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- Technical instructions (air):

Class	Share in %
NK	50-100

- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H228 Flammable solid.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H361f Suspected of damaging fertility.

(Contd. on page 10)

⁻ GB

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Silber hitzefest (D)

	(Contd. of page 9)
H410 Very toxic to aquatic life with long lasting effects.	(Conta. of page 9)
H412 Harmful to aquatic life with long lasting effects.	
EUH018 In use may form flammable/explosive vapour-air mixture.	
EUH066 Repeated exposure may cause skin dryness or cracking.	
Department issuing SDS: Product safety department	
Abbreviations and acronyms:	
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Ag	eement Concerning the
International Carriage of Dangerous Goods by Road)	
IMDG: International Maritime Code for Dangerous Goods	
IATA: International Air Transport Association	
GHS: Globally Harmonised System of Classification and Labelling of Chemicals	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
Flam. Gas 1A: Flammable gases – Category 1A	
Aerosol 1: Aerosols – Category 1	
: Aerosols – Category 3	
Press. Gas (Comp.): Gases under pressure – Compressed gas	
Flam. Liq. 2: Flammable liquids – Category 2	
Flam. Liq. 3: Flammable liquids – Category 3	
Flam. Sol. 1: Flammable solids – Category 1	
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2	
Repr. 2: Reproductive toxicity – Category 2	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
Asp. Tox. 1: Aspiration hazard – Category 1	
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1	
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3	
* Data compared to the previous version altered.	