

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.11.2021

Revision: 23.11.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** Aerosol 1K Unifill S6 dunkelgrau
- (Article number) **product ID.:** REZ1310
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use SU21** Consumer uses: Private households / general public / consumers
- **Application of the substance / the mixture:** painting
- **Uses advised against** No further relevant information available.
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Peter Kwasny GmbH
Heilbronner Str. 96
D-74831 Gundelsheim
- **Further information obtainable from:** Product safety department
- **1.4 Emergency telephone number:** Tel.: +49 6269 95 20
- **national:**
National Poisons Information Service, Birmingham
Tel.: 844 892 0111
- **K-Nr.** 0001

Tel.: 0049-(0)6269-95-20
E-mail: labor@kwasny.de

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Eye Irrit. 2 H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS07

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.11.2021

Revision: 23.11.2021

Trade name: Aerosol 1K Unifill S6 dunkelgrau

(Contd. of page 1)

· **Signal word** Danger· **Hazard-determining components of labelling:**

acetone
maleic anhydride
methyl acetate
butanone
Fatty acids, C14-18 and C16-18-unsatd., maleated

· **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read carefully and follow all instructions.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P302+P352 IF ON SKIN: Wash with plenty of water.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 Call a POISON CENTER/doctor if you feel unwell.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**

Without adequate ventilation, explosive atmosphere/gas mix may be created.
Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

· **2.3 Other hazards**· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	25-<50%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-xxxx	acetone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	10-<25%
CAS: 79-20-9 EINECS: 201-185-2	methyl acetate ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	5-<10%

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.11.2021

Revision: 23.11.2021

Trade name: Aerosol 1K Unifill S6 dunkelgrau

(Contd. of page 2)

CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43-xxxx	butanone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	2.5-<5%
CAS: 110-82-7 EINECS: 203-806-2	cyclohexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; STOT SE 3, H336	1-<2.5%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-xxxx	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226	1-<2.5%
CAS: 85711-46-2 EINECS: 288-306-2 Reg.nr.: 01-2119976378-19-xxxx	Fatty acids, C14-18 and C16-18-unsatd., maleated Skin Irrit. 2, H315; Skin Sens. 1, H317	≥0.1-<1%
CAS: 108-31-6 EINECS: 203-571-6 Reg.nr.: 01-2119472428-31-xxxx	maleic anhydride Resp. Sens. 1, H334; STOT RE 1, H372; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1A, H317	≥0.001-<0.1%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media -**
- **Suitable extinguishing agents:** Cool container with water
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.

(Contd. on page 4)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.11.2021

Revision: 23.11.2021

Trade name: Aerosol 1K Unifill S6 dunkelgrau

(Contd. of page 3)

Ensure adequate ventilation.

- **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

- **Information about fire - and explosion protection:**

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- **7.2 Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

Observe official regulations on storing packagings with pressurised containers.

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:** None.

- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

115-10-6 dimethyl ether	
WEL	Short-term value: 958 mg/m ³ , 500 ppm Long-term value: 766 mg/m ³ , 400 ppm
67-64-1 acetone	
WEL	Short-term value: 3620 mg/m ³ , 1500 ppm Long-term value: 1210 mg/m ³ , 500 ppm
79-20-9 methyl acetate	
WEL	Short-term value: 770 mg/m ³ , 250 ppm Long-term value: 616 mg/m ³ , 200 ppm
78-93-3 butanone	
WEL	Short-term value: 899 mg/m ³ , 300 ppm Long-term value: 600 mg/m ³ , 200 ppm Sk, BMGV
110-82-7 cyclohexane	
WEL	Short-term value: 1050 mg/m ³ , 300 ppm Long-term value: 350 mg/m ³ , 100 ppm
108-31-6 maleic anhydride	
WEL	Short-term value: 3 mg/m ³ Long-term value: 1 mg/m ³ Sen

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.11.2021

Revision: 23.11.2021

Trade name: Aerosol 1K Unifill S6 dunkelgrau

(Contd. of page 4)

· **Ingredients with biological limit values:**

78-93-3 butanone

BMGV	70 µmol/L Medium: urine Sampling time: post shift Parameter: butan-2-one
------	---

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.

· **Respiratory protection:**



When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

· **Protection of hands:**

Protective gloves



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves** Nitrile rubber, NBR

· **Penetration time of glove material**

Gloves must be changed after every contamination.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

butyl rubber, 0,7mm

· **Eye protection:**

Safety glasses



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Aerosol
Colour:	According to product specification
Odour:	Characteristic

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.11.2021

Revision: 23.11.2021

Trade name: Aerosol 1K Unifill S6 dunkelgrau

(Contd. of page 5)

· Odour threshold:	Not determined.
· pH-value:	Mixture is non-polar/aprotic.
· Change in condition Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	-24.9 °C
· Flash point:	-42 °C
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	455 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible. Not determined.
· Explosion limits: Lower:	2.6 Vol %
Upper:	18.6 Vol %
· Vapour pressure at 20 °C:	3,400 hPa
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content: Organic solvents:	83.3 % With propellant gas. Content given by weight.
VOC (EU)	83.30 %
Solids content:	14.3 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

GB

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.11.2021

Revision: 23.11.2021

Trade name: Aerosol 1K Unifill S6 dunkelgrau

(Contd. of page 6)

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Ikke relevant.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN1950

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.11.2021

Revision: 23.11.2021

Trade name: Aerosol 1K Unifill S6 dunkelgrau

(Contd. of page 7)

· 14.2 UN proper shipping name	1950 AEROSOLS
· ADR	AEROSOLS (cyclohexane), MARINE POLLUTANT
· IMDG	AEROSOLS, flammable
· IATA	

· 14.3 Transport hazard class(es)

· ADR



· Class	2.5F Gases.
· Label	2.1

· IMDG



· Class	2.1 Gases.
· Label	2.1

· IATA



· Class	2.1 Gases.
· Label	2.1

· 14.4 Packing group

· ADR, IMDG, IATA

Void
not classified

· 14.5 Environmental hazards:

Product contains environmentally hazardous substances:
cyclohexane

· Marine pollutant:

Yes
Symbol (fish and tree)

· 14.6 Special precautions for user

· Hazard identification number (Kemler code):

Warning: Gases.

-
not classified

· EMS Number:

F-D,S-U

· Stowage Code

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre:
Category A. For AEROSOLS with a capacity above 1 litre:
Category B. For WASTE AEROSOLS: Category C, Clear
of living quarters.

(Contd. on page 9)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.11.2021

Revision: 23.11.2021

Trade name: Aerosol 1K Unifill S6 dunkelgrau

(Contd. of page 8)

· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	

· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D

· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
VOC: <840g/l
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P3a** FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **National regulations:**

- **Technical instructions (air):**

Class	Share in %
NK	50-100

- **Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H302 Harmful if swallowed.

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.11.2021

Revision: 23.11.2021

Trade name: Aerosol 1K Unifill S6 dunkelgrau

(Contd. of page 9)

H304 May be fatal if swallowed and enters airways.
 H314 Causes severe skin burns and eye damage.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 H336 May cause drowsiness or dizziness.
 H372 Causes damage to organs through prolonged or repeated exposure.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.

· **Department issuing SDS:** Product safety department

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Flam. Gas 1A: Flammable gases – Category 1A
 Aerosol 1: Aerosols – Category 1
 Press. Gas (Comp.): Gases under pressure – Compressed gas
 Flam. Liq. 2: Flammable liquids – Category 2
 Flam. Liq. 3: Flammable liquids – Category 3
 Acute Tox. 4: Acute toxicity – Category 4
 Skin Corr. 1B: Skin corrosion/irritation – Category 1B
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 Resp. Sens. 1: Respiratory sensitisation – Category 1
 Skin Sens. 1: Skin sensitisation – Category 1
 Skin Sens. 1A: Skin sensitisation – Category 1A
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
 Asp. Tox. 1: Aspiration hazard – Category 1
 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· *** Data compared to the previous version altered.**