Revision: 16.09.2022

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.09.2022

## Version number 4

```
SECTION 1: Identification of the substance/mixture and of the company/undertaking
· 1.1 Product identifier
· Trade name: SprayTec Steinschlag Spritzware
· valid for: REZ1336
· 1.2 Relevant identified uses of the substance or mixture and uses advised against
No further relevant information available.
· Application of the substance / the mixture Protective coating
· 1.3 Details of the supplier of the safety data sheet
· Manufacturer/Supplier:
 Peter Kwasny GmbH
 Heilbronner Str. 96
D-74831 Gundelsheim
 Tel.: +49 (0) 6269-95-20
 Fax: +49 (0) 6269 95 70
 E-mail: labor@kwasny.de
www.kwasny.de
· 1.4 Emergency telephone number:
 Emergency telephone number: +49 6269 95 20
 National Poisons Information Service, Birmingham: 844 892 0111
SECTION 2: Hazards identification
· 2.1 Classification of the substance or mixture
· Classification according to Regulation (EC) No 1272/2008
          flame
 Flam. Liq. 2
                   H225 Highly flammable liquid and vapour.
          environment
 Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.
 Eye Irrit. 2
                   H319 Causes serious eye irritation.
 STOT SE 3
                   H336 May cause drowsiness or dizziness.
· 2.2 Label elements
· Labelling according to Regulation (EC) No 1272/2008
 The product is classified and labelled according to the GB CLP regulation.
· Hazard pictograms
  GHS02
           GHS07
                     GHS09
· Signal word Danger
· Hazard-determining components of labelling:
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics
 Ethyl acetate
 Hydrocarbons, C9, aromatics
```

(Contd. on page 2)

according to 1907/2006/EC, Article 31

Printing date 16.09.2022

Version number 4

Revision: 16.09.2022

Trade name: SprayTec Steinschlag Spritzware

(Contd. of page 1) · Hazard statements H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. Precautionary statements If medical advice is needed, have product container or label at hand. P101 Keep out of reach of children. P102 P103 Read carefully and follow all instructions. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. Additional information: EUH066 Repeated exposure may cause skin dryness or cracking. EUH208 Contains Fatty acids, C18-unsatd., dimers, reaction products with N,N-dimethyl-1,3-propanediamine and 1,3propanediamine. May produce an allergic reaction. · 2.3 Other hazards

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

#### **SECTION 3: Composition/information on ingredients**

#### · 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

## · Dangerous components:

Dunger ous componentist		
EC number: 920-750-0	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	25-50%
Reg.nr.: 01-2119473851-33	<ul> <li>Flam. Liq. 2, H225;</li> <li>Asp. Tox. 1, H304;</li> <li>Aquatic Chronic 2, H411;</li> <li>STOT SE 3, H336</li> </ul>	
CAS: 141-78-6	Ethyl acetate	10-25%
EINECS: 205-500-4	🚸 Flam. Liq. 2, H225; 🚸 Eye Irrit. 2, H319; STOT SE 3, H336	
Reg.nr.: 01-2119475103-46		
CAS: 64742-95-6	Hydrocarbons, C9, aromatics	5-<10%
EC number: 918-668-5	🚸 Flam. Liq. 3, H226; 🚸 Asp. Tox. 1, H304; 🚯 Aquatic Chronic 2, H411;	
Reg.nr.: 01-2119455851-35	STOT SE 3, H335-H336	
• Additional information: Fo	or the wording of the listed hazard phrases refer to section 16.	

## **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

according to 1907/2006/EC, Article 31

Printing date 16.09.2022

## Version number 4

Revision: 16.09.2022

Trade name: SprayTec Steinschlag Spritzware

(Contd. of page 2)

## **SECTION 5: Firefighting measures**

· 5.1 Extinguishing media

· Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

## **SECTION 6: Accidental release measures**

 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.
- Ensure adequate ventilation.

## 6.4 Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

#### \*

## **SECTION 7: Handling and storage**

## · 7.1 Precautions for safe handling

Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- ·7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:
- Keep container tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- · Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.
- \*
- SECTION 8: Exposure controls/personal protection
- · 8.1 Control parameters

• Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)

GR

according to 1907/2006/EC, Article 31

Printing date 16.09.2022

## Version number 4

Revision: 16.09.2022

(Contd. of page 3)

Trade name: SprayTec Steinschlag Spritzware

Ingredients with limit values that require monitoring at the workplace:

## 141-78-6 Ethyl acetate

WEL Short-term value: 1468 mg/m<sup>3</sup>, 400 ppm

Long-term value: 734 mg/m<sup>3</sup>, 200 ppm

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- $\cdot$  General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

## · Protection of hands:

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

#### Material of gloves

Fluorocarbon rubber (Viton)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

## Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. **Eye protection:** 



Tightly sealed goggles

• 9.1 Information on basic physical an • General Information	d chemical properties	
· Appearance:		
Form:	Fluid	
Colour:	Black	
Odour:	Characteristic	
· Odour threshold:	Not determined.	
· pH-value:	Not determined.	
• Change in condition		
Melting point/freezing point:	Undetermined.	

according to 1907/2006/EC, Article 31

Printing date 16.09.2022

Version number 4

Revision: 16.09.2022

Trade name: SprayTec Steinschlag Spritzware

	(Contd. of page 4
Initial boiling point and boiling range	:: 77-78 °C
· Flash point:	-4 °C (DIN 53213)
· Flammability (solid, gas):	Highly flammable.
· Ignition temperature:	>300 °C (DIN 51794)
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixture are possible.
· Explosion limits:	
Lower:	0.9 Vol %
Upper:	11.5 Vol %
· Vapour pressure at 20 °C:	97 hPa
· Density at 20 °C:	1.139 g/cm <sup>3</sup> (DIN 53217)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic at 20 °C:	690 mPas
Kinematic:	Not determined.
· Solvent content:	
Water:	0.0 %
VOC (EC)	48.98 %
Solids content (weight-%):	51.0 %
9.2 Other information	No further relevant information available.

## **SECTION 10: Stability and reactivity**

• 10.1 Reactivity No further relevant information available.

- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

## **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

(Contd. on page 6)

according to 1907/2006/EC, Article 31

Printing date 16.09.2022

## Version number 4

Revision: 16.09.2022

Trade name: SprayTec Steinschlag Spritzware

- (Contd. of page 5) • Respiratory or skin sensitisation Based on available data, the classification criteria are not met. · Additional toxicological information: · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) · Germ cell mutagenicity Based on available data, the classification criteria are not met. · Carcinogenicity Based on available data, the classification criteria are not met. • Reproductive toxicity Based on available data, the classification criteria are not met. · STOT-single exposure May cause drowsiness or dizziness. • STOT-repeated exposure Based on available data, the classification criteria are not met. · Aspiration hazard Based on available data, the classification criteria are not met. **SECTION 12: Ecological information** · 12.1 Toxicity • Aquatic toxicity: No further relevant information available. • 12.2 Persistence and degradability No further relevant information available. • 12.3 Bioaccumulative potential No further relevant information available. • 12.4 Mobility in soil No further relevant information available. · Ecotoxical effects: · Remark: Toxic for fish · Additional ecological information: · General notes: Water hazard class 2 (German Regulation) : hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies. Toxic for aquatic organisms · 12.5 Results of PBT and vPvB assessment • **PBT:** Not applicable. • **vPvB:** Not applicable. • 12.6 Other adverse effects No further relevant information available.
  - **SECTION 13: Disposal considerations**
  - · 13.1 Waste treatment methods
  - Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

• Recommendation: Disposal must be made according to official regulations.

· 14.1 UN-Number	
· ADR, IMDG, IATA	UN1139
· 14.2 UN proper shipping name	
· ADR	UN1139 COATING SOLUTION, ENVIRONMENTALL
	HAZARDOUS
· IMDG	COATING SOLUTION (Hydrocarbons, C7-C9), MARIN
	POLLUTANT
·IATA	COATING SOLUTION

<sup>·</sup> Uncleaned packaging:

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.09.2022

Version number 4

Revision: 16.09.2022

Trade name: SprayTec Steinschlag Spritzware

	(Contd. of page
· 14.3 Transport hazard class(es)	
· ADR	
$\wedge$	
$\checkmark$	
· Class	3 (F1) Flammable liquids.
·Label	3
·IMDG	
· Class · Label	3 Flammable liquids.
	, 
·IATA	
3	
· Class · Label	3 Flammable liquids. 3
· 14.4 Packing group · ADR, IMDG, IATA	II
· 14.5 Environmental hazards:	Product contains environmentally hazardous substance Hydrocarbons, C7-C9
· Marine pollutant:	Yes
Marine ponutant.	Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Hazard identification number (Kemler code):	33
· EMS Number:	F-E,S-E
· Stowage Category	В
· 14.7 Transport in bulk according to Annex II of Ma	arpol
and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Transport category	2
· Tunnel restriction code	D/E
·IMDG	
· Limited quantities (LQ)	5L
· UN "Model Regulation":	UN 1139 COATING SOLUTION, 3, 1
or model regulation .	ENVIRONMENTALLY HAZARDOUS

(Contd. on page 8)

according to 1907/2006/EC, Article 31

Printing date 16.09.2022

## Version number 4

Revision: 16.09.2022

Trade name: SprayTec Steinschlag Spritzware

(Contd. of page 7)

GB

#### **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

· Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
NK	25-50

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- · Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

- IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
- ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids Category 2
- Flam. Liq. 3: Flammable liquids Category 3 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) Category 3
- Asp. Tox. 1: Aspiration hazard Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment long-term aquatic hazard Category 2
- \* \* Data compared to the previous version altered.