

Page 1/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.11.2022 Version number 1 Revision: 15.11.2022

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Aerosol Hammerschlag
- · (Article number) product ID.: REZ1346
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use SU21 Consumer uses: Private households / general public / consumers
- · Application of the substance / the mixture: painting
- · Uses advised against No further relevant information available.
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Peter Kwasny GmbH

Heilbronner Str. 96

D-74831 Gundelsheim

Tel.: 0049-(0)6269-95-20 E-mail: labor@kwasny.de

- · Further information obtainable from: Product safety department
- · 1.4 Emergency telephone number: Tel.:+49 6269 95 20
- · national:

National Poisons Information Service, Birmingham

Tel.: 844 892 0111

· K-Nr. 0001

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Aerosol 1 H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

(Contd. of page 1)

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.11.2022 Version number 1 Revision: 15.11.2022

Trade name: Aerosol Hammerschlag

#### · Hazard pictograms





# · Signal word Danger

## · Hazard-determining components of labelling:

acetone propan-2-ol

butanone

#### · Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

#### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P271 Use only outdoors or in a well-ventilated area.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell. P337+P313 If eye irritation persists: Get medical advice/attention.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### · Additional information:

Without adequate ventilation, explosive atmosphere/gas mix may be created.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

#### · 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 67-64-1	acetone	25-<50%
EINECS: 200-662-2	🚸 Flam. Liq. 2, H225; 🐠 Eye Irrit. 2, H319; STOT SE	
Reg.nr.: 01-2119471330-49-xxxx	3, H336, EUH066	
CAS: 74-98-6	propane	<i>5-&lt;10%</i>
EINECS: 200-827-9	♠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280,	
Reg.nr.: 01-2119486944-21-xxxx	EUH018	
		(Contd. on pag

(Contd. on page 3)

Printing date 15.11.2022 Version number 1 Revision: 15.11.2022

Trade name: Aerosol Hammerschlag

CAS: 106-97-8	butane (containing $\leq 0.1$ % butadiene (203-450-8))	(Contd. of page 2 5-<10%
EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	(comp.), H280, Press. Gas (Comp.), H280,	
CAS: 9004-70-0 Reg.nr.: no Reach No. availlable	nitrocellulose with water(not less than 25% water, by mass)  Expl. 1.1, H201	5-<10%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx	xylene, mixture of isomers  Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane (containing ≤ 0,1 % butadiene (203-450-8)) ♦ Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	2.5-<5%
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25-xxxx	propan-2-ol	2.5-<5%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35-xxxx	ethylbenzene	1-<2.5%
CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43-xxxx	butanone ♠ Flam. Liq. 2, H225; ♠ Eye Irrit. 2, H319; STOT SE 3, H336	1-<2.5%
CAS: 71839-81-1 Reg.nr.: 01-2120760580-57-xxxx	C.I. Solvent Orange 41  Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≥0.025-<0.25%

· 4.1 Description of first aid measures

SECTION 4: First aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media -
- · Suitable extinguishing agents: Cool container whit water
- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

### SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

Printing date 15.11.2022 Version number 1 Revision: 15.11.2022

Trade name: Aerosol Hammerschlag

(Contd. of page 3)

#### · 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.

Long-term value: 441 mg/m³, 100 ppm

· 7.3 Specific end use(s) No further relevant information available.

# SECTION 8: Exposure controls/personal protection

Ū	Ingredients with limit values that require monitoring at the workplace:	
	64-1 acetone	
WE	L Short-term value: 3620 mg/m³, 1500 ppm	
	Long-term value: 1210 mg/m³, 500 ppm	
106	-97-8 butane (containing ≤0,1 % butadiene (203-450-8))	
WE	L Short-term value: 1810 mg/m³, 750 ppm	
	Long-term value: 1450 mg/m³, 600 ppm	
	Carc (if more than 0.1% of buta-1.3-diene)	
133	0-20-7 xylene, mixture of isomers	
WE	L Short-term value: 441 mg/m³, 100 ppm	
	Long-term value: 220 mg/m³, 50 ppm	
	Sk; BMGV	
67-	63-0 propan-2-ol	
WE	L Short-term value: 1250 mg/m³, 500 ppm	
	Long-term value: 999 mg/m³, 400 ppm	

(Contd. on page 5)

Version number 1 Revision: 15.11.2022 Printing date 15.11.2022

Trade name: Aerosol Hammerschlag

(Contd. of page 4)

#### 78-93-3 butanone

WEL Short-term value: 899 mg/m³, 300 ppm

Long-term value: 600 mg/m³, 200 ppm

Sk, BMGV

#### · Ingredients with biological limit values:

#### 1330-20-7 xylene, mixture of isomers

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: methyl hippuric acid

#### 78-93-3 butanone

BMGV 70 µmol/L

Medium: urine

Sampling time: post shift Parameter: butan-2-one

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:



When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

#### · Hand protection

Protective gloves



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material

Gloves must be changed after every contamination.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

butyl rubber, 0,7mm

· Eve/face protection


Safety glasses

(Contd. on page 6)

Printing date 15.11.2022 Version number 1 Revision: 15.11.2022

Trade name: Aerosol Hammerschlag

(Contd. of page 5)



# SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Aerosol

· Colour: According to product specification

Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

range -44.5 °C · Flammability Not applicable.

· Lower and upper explosion limit

 · Lower:
 2.6 Vol %

 · Upper:
 13 Vol %

 · Flash point:
 <0 °C</td>

 · Ignition temperature:
 365 °C

• Decomposition temperature: Not determined. • pH Not determined.

· Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

 $\cdot \textit{Solubility}$ 

• water: Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log value)
 Vapour pressure at 20 °C:
 Not determined.
 233 hPa

· Density and/or relative density

Relative density
Vapour density
Not determined.
Not determined.

· 9.2 Other information

· Appearance:

· Form: Aerosol

· Important information on protection of health and environment, and on safety.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

Not determined.

· Solvent content:

· Organic solvents: 76.4 %

With propellant gas. Content given by weight.

*· VOC (EU)* 76.45 % *· Solids content:* 17.1 %

· Change in condition

· Evaporation rate Not applicable.

· Information with regard to physical hazard classes

· Explosives Void

(Contd. on page 7)

Printing date 15.11.2022 Version number 1 Revision: 15.11.2022

Trade name: Aerosol Hammerschlag

	(Contd. of page 6
· Flammable gases	Void
· Aerosols	Extremely flammable aerosol. Pressurised container.
	May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammab	ble
gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- $\cdot$  10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity

	-		
· LD/LC50	values rele	vant for classification:	
ATE (Acua	te Toxicity	Estimates)	

- Inhalative LC50/4 h 590 mg/l
- · Serious eye damage/irritation Causes serious eye irritation.
- · STOT-single exposure May cause drowsiness or dizziness.
- · 11.2 Information on other hazards

· Endocrin	e disrupting properties	
540-97-6	Dodecamethylcyclohexasiloxan	List II
541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane	List II
556-67-2	octamethylcyclotetrasiloxane	List II, III

### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.

(Contd. on page 8)

Printing date 15.11.2022 Version number 1 Revision: 15.11.2022

Trade name: Aerosol Hammerschlag

(Contd. of page 7)

- $\cdot \textbf{12.4 Mobility in soil} \ \textit{No further relevant information available}.$
- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Ikke relevant.
- · 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

 $Water\ hazard\ class\ 2\ (German\ Regulation)\ (Self-assessment):\ hazardous\ for\ water$ 

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

# **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

· 14.1 UN number or ID number · ADR, IMDG, IATA	UN1950	
· 14.2 UN proper shipping name		
· ADR	1950 AEROSOLS	
· IMDG	AEROSOLS	
· IATA	AEROSOLS, flammable	
· 14.3 Transport hazard class(es)		
$\cdot ADR$		
· Class · Label	2 5F Gases. 2.1	
· IMDG, IATA	2.1	
· Class	2.1 Gases.	
· Label	2.1	
· 14.4 Packing group		
· ADR, IMDG, IATA	Void	
, -,	not classified	
· 14.5 Environmental hazards:	·	
· Marine pollutant:	No	

Printing date 15.11.2022 Version number 1 Revision: 15.11.2022

Trade name: Aerosol Hammerschlag

	(Contd. of page
14.6 Special precautions for user	Warning: Gases.
Hazard identification number (Kemler code):	-
,	not classified
EMS Number:	F- $D$ , $S$ - $U$
Stowage Code	SW1 Protected from sources of heat.
-	SW2 Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of
	litre:
	Segregation as for class 9. Stow "separated from" class
	except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class
	For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class
14.7 Maritime transport in bulk according to IM	40
instruments	Not applicable.
Transport/Additional information:	
ADR	
	1L
Limited quantities (LQ)	1L Code: E0
Limited quantities (LQ)	Code: E0
Limited quantities (LQ) Excepted quantities (EQ)	12
Limited quantities (LQ) Excepted quantities (EQ) Transport category	Code: E0 Not permitted as Excepted Quantity
Limited quantities (LQ) Excepted quantities (EQ)  Transport category Tunnel restriction code	Code: E0 Not permitted as Excepted Quantity 2
Limited quantities (LQ) Excepted quantities (EQ)  Transport category Tunnel restriction code  IMDG	Code: E0 Not permitted as Excepted Quantity 2 D
ADR Limited quantities (LQ) Excepted quantities (EQ)  Transport category Tunnel restriction code  IMDG Limited quantities (LQ) Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity 2 D
Limited quantities (LQ) Excepted quantities (EQ)  Transport category Tunnel restriction code  IMDG	Code: E0 Not permitted as Excepted Quantity 2 D  1L Code: E0
Limited quantities (LQ) Excepted quantities (EQ)  Transport category Tunnel restriction code  IMDG Limited quantities (LQ)	Code: E0 Not permitted as Excepted Quantity 2 D

# **SECTION 15: Regulatory information**

- $\cdot$  15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture VOC: <840g/l
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	50-100

- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

Printing date 15.11.2022 Version number 1 Revision: 15.11.2022

Trade name: Aerosol Hammerschlag

(Contd. of page 9)

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H201 Explosive; mass explosion hazard.
- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- *H410* Very toxic to aquatic life with long lasting effects.

EUH018 In use may form flammable/explosive vapour-air mixture.

EUH066 Repeated exposure may cause skin dryness or cracking.

#### · Department issuing SDS: Product safety department

#### · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Expl. 1.1: Explosives – Division 1.1

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols – Category 1

: Aerosols – Category 3

Press. Gas (Comp.): Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

 $\cdot$  \* Data compared to the previous version altered.