

Page 1/10

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.11.2022 Version number 1 Revision: 15.11.2022

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Aerosol Terracotta- und Strukturspray div. Farbtoene
- · (Article number) product ID.: REZ1407
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use SU21 Consumer uses: Private households / general public / consumers
- · Application of the substance / the mixture: painting
- · Uses advised against No further relevant information available.
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Peter Kwasny GmbH

Heilbronner Str. 96

D-74831 Gundelsheim

Tel.: 0049-(0)6269-95-20 E-mail: labor@kwasny.de

- · Further information obtainable from: Product safety department
- · 1.4 Emergency telephone number: Tel.:+49 6269 95 20
- · national:

National Poisons Information Service, Birmingham

Tel.: 844 892 0111

· K-Nr. 0001

## SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Aerosol 1 H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

Printing date 15.11.2022 Version number 1 Revision: 15.11.2022

Trade name: Aerosol Terracotta- und Strukturspray div. Farbtoene

(Contd. of page 1)

### · Hazard pictograms





#### · Signal word Danger

### · Hazard-determining components of labelling:

acetone

n-butyl acetate

#### · Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

*P103 Read carefully and follow all instructions.* 

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P271 Use only outdoors or in a well-ventilated area.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell. P337+P313 If eye irritation persists: Get medical advice/attention.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

### · Additional information:

Without adequate ventilation, explosive atmosphere/gas mix may be created.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

#### · 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-xxxx	acetone Flam. Liq. 2, H225; UEye Irrit. 2, H319; STOT SE 3, H336, EUH066	25-<50%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	10-<25%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane (containing ≤ 0,1 % butadiene (203-450-8))  ♦ Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	5-<10%

(Contd. on page 3)

Printing date 15.11.2022 Version number 1 Revision: 15.11.2022

Trade name: Aerosol Terracotta- und Strukturspray div. Farbtoene

		(Contd. of page 2
CAS: 108-65-6	2-methoxy-1-methylethyl acetate	<i>5-&lt;10%</i>
EINECS: 203-603-9	♦ Flam. Liq. 3, H226	
Reg.nr.: 01-2119475791-29-xxxx		
CAS: 75-28-5	isobutane (containing $\leq 0.1$ % butadiene (203-450-8))	5-<10%
EINECS: 200-857-2	<b>♦</b> Flam. Gas 1A, H220; Press. Gas (Comp.), H280,	
Reg.nr.: 01-2119485395-27-xxxx	<i>EUH018</i>	
CAS: 9004-70-0	nitrocellulose with water(not less than 25% water, by	2.5-<5%
Reg.nr.: no Reach No. availlable	mass)	
Ţ.		
CAS: 64-17-5	ethanol	1-<2.5%
EINECS: 200-578-6	♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319	
Reg.nr.: 01-2119457610-43-xxxx	• · · · · · · · · · · · · · · · · · · ·	
CAS: 123-86-4	n-butyl acetate	1-<2.5%
EINECS: 204-658-1	🚯 Flam. Liq. 3, H226; 🚺 STOT SE 3, H336, EUH066	
Reg.nr.: 01-2119485493-29-xxxx	• • • • • • • • • • • • • • • • • • • •	
CAS: 1330-20-7	xylene, mixture of isomers	1-<2.5%
EINECS: 215-535-7	🏵 Flam. Liq. 3, H226; & STOT RE 2, H373; Asp. Tox.	
Reg.nr.: 01-2119488216-32-xxxx	1, H304; (1) Acute Tox. 4, H312; Acute Tox. 4, H332;	
- C	Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	
CAS: 7397-62-8	butyl glycollate	<1%
EINECS: 230-991-7	🗞 Repr. 2, H361; 鉖 Eye Dam. 1, H318	
Reg.nr.: 01-2119514685-36-xxxx		
CAS: 7779-90-0	trizinc bis(orthophosphate)	<i>≥</i> 0.025-<0.25%
EINECS: 231-944-3	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
Reg.nr.: 01-2119485044-40-xxxx	<b>v</b> 1	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- $\cdot \textbf{\textit{After inhalation:}} \ \textit{Supply fresh air; consult doctor in case of complaints.}$
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- $\cdot \textit{4.3 Indication of any immediate medical attention and special treatment needed}$

No further relevant information available.

## SECTION 5: Firefighting measures

- · 5.1 Extinguishing media -
- · Suitable extinguishing agents: Cool container whit water
- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

## SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

Printing date 15.11.2022 Version number 1 Revision: 15.11.2022

Trade name: Aerosol Terracotta- und Strukturspray div. Farbtoene

(Contd. of page 3)

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:

Sk; BMGV

· Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- $\cdot$  7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

### WEL   Short-term value: 3620 mg/m³, 1500 ppm		dients with limit values that require monitoring at the workplace:
Long-term value: 1210 mg/m³, 500 ppm  106-97-8 butane (containing ≤0,1 % butadiene (203-450-8))  WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)  108-65-6 2-methoxy-1-methylethyl acetate  WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk  64-17-5 ethanol  WEL Long-term value: 1920 mg/m³, 1000 ppm  123-86-4 n-butyl acetate  WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm	67-64	-1 acetone
106-97-8 butane (containing ≤0,1 % butadiene (203-450-8))  WEL   Short-term value: 1810 mg/m³, 750 ppm     Long-term value: 1450 mg/m³, 600 ppm     Carc (if more than 0.1% of buta-1.3-diene)  108-65-6 2-methoxy-1-methylethyl acetate  WEL   Short-term value: 548 mg/m³, 100 ppm     Long-term value: 274 mg/m³, 50 ppm     Sk    64-17-5 ethanol  WEL   Long-term value: 1920 mg/m³, 1000 ppm    123-86-4 n-butyl acetate  WEL   Short-term value: 966 mg/m³, 200 ppm     Long-term value: 724 mg/m³, 150 ppm	WEL	
WEL   Short-term value: 1810 mg/m³, 750 ppm   Long-term value: 1450 mg/m³, 600 ppm   Carc (if more than 0.1% of buta-1.3-diene)  108-65-6 2-methoxy-1-methylethyl acetate  WEL   Short-term value: 548 mg/m³, 100 ppm   Long-term value: 274 mg/m³, 50 ppm   Sk  64-17-5 ethanol  WEL   Long-term value: 1920 mg/m³, 1000 ppm  123-86-4 n-butyl acetate  WEL   Short-term value: 966 mg/m³, 200 ppm   Long-term value: 724 mg/m³, 150 ppm	107.0	• • •
Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)  108-65-6 2-methoxy-1-methylethyl acetate  WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk  64-17-5 ethanol  WEL Long-term value: 1920 mg/m³, 1000 ppm  123-86-4 n-butyl acetate  WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm	106-9	7/-8 butane (containing ≤0,1 % butadiene (203-450-8))
Carc (if more than 0.1% of buta-1.3-diene)  108-65-6 2-methoxy-1-methylethyl acetate  WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk  64-17-5 ethanol  WEL Long-term value: 1920 mg/m³, 1000 ppm  123-86-4 n-butyl acetate  WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm	WEL	Short-term value: 1810 mg/m³, 750 ppm
108-65-6 2-methoxy-1-methylethyl acetate  WEL   Short-term value: 548 mg/m³, 100 ppm   Long-term value: 274 mg/m³, 50 ppm   Sk  64-17-5 ethanol  WEL   Long-term value: 1920 mg/m³, 1000 ppm  123-86-4 n-butyl acetate  WEL   Short-term value: 966 mg/m³, 200 ppm   Long-term value: 724 mg/m³, 150 ppm		Long-term value: 1450 mg/m³, 600 ppm
WEL   Short-term value: 548 mg/m³, 100 ppm   Long-term value: 274 mg/m³, 50 ppm   Sk    64-17-5 ethanol   WEL   Long-term value: 1920 mg/m³, 1000 ppm    123-86-4 n-butyl acetate   WEL   Short-term value: 966 mg/m³, 200 ppm   Long-term value: 724 mg/m³, 150 ppm		Carc (if more than 0.1% of buta-1.3-diene)
Long-term value: 274 mg/m³, 50 ppm Sk  64-17-5 ethanol  WEL   Long-term value: 1920 mg/m³, 1000 ppm  123-86-4 n-butyl acetate  WEL   Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm	108-6	5-6 2-methoxy-1-methylethyl acetate
Sk	WEL	Short-term value: 548 mg/m³, 100 ppm
64-17-5 ethanol  WEL   Long-term value: 1920 mg/m³, 1000 ppm  123-86-4 n-butyl acetate  WEL   Short-term value: 966 mg/m³, 200 ppm   Long-term value: 724 mg/m³, 150 ppm		Long-term value: 274 mg/m³, 50 ppm
WEL   Long-term value: 1920 mg/m³, 1000 ppm  123-86-4 n-butyl acetate  WEL   Short-term value: 966 mg/m³, 200 ppm   Long-term value: 724 mg/m³, 150 ppm		Sk
123-86-4 n-butyl acetate  WEL Short-term value: 966 mg/m³, 200 ppm  Long-term value: 724 mg/m³, 150 ppm	64-17	-5 ethanol
WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm	WEL	Long-term value: 1920 mg/m³, 1000 ppm
Long-term value: 724 mg/m³, 150 ppm	123-8	6-4 n-butyl acetate
	WEL	Short-term value: 966 mg/m³, 200 ppm
1330-20-7 xylene, mixture of isomers		Long-term value: 724 mg/m³, 150 ppm
···/··· / ····· - ·// ···· · · ·// ··· · · ·	1330-	20-7 xylene, mixture of isomers
		Long-term value: 220 mg/m³, 50 ppm

(Contd. on page 5)

Printing date 15.11.2022 Version number 1 Revision: 15.11.2022

Trade name: Aerosol Terracotta- und Strukturspray div. Farbtoene

(Contd. of page 4)

### · Ingredients with biological limit values:

### 1330-20-7 xylene, mixture of isomers

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: methyl hippuric acid

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:



When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

· Hand protection

Protective gloves



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material

Gloves must be changed after every contamination.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

butyl rubber, 0,7mm

· Eye/face protection

Safety glasses



Tightly sealed goggles

### SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Physical state Aerosol
- · Colour: According to product specification
- · Odour: Characteristic

(Contd. on page 6)

Printing date 15.11.2022 Version number 1 Revision: 15.11.2022

Trade name: Aerosol Terracotta- und Strukturspray div. Farbtoene

(Contd. of page 5)

· Odour threshold: Not determined.
· Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

range

· Flammability Not applicable.

· Lower and upper explosion limit

*Lower:* 1.7 Vol % (74-98-6 propane)

• Upper: 13 Vol % (67-64-1 acetone)

· Flash point: <0 °C

• Ignition temperature: 460 °C (75-28-5 isobutane (containing  $\leq 0.1$  %

-44 °C

butadiene (203-450-8)))

Decomposition temperature: Not determined.pH Not determined.

· Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

 $\cdot \textit{Solubility}$ 

• water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined.

• Vapour pressure at 20 °C: 3,600 hPa (74-98-6 propane)

· Density and/or relative density

Relative density
Vapour density
Not determined.
Not determined.

· 9.2 Other information

· Appearance:

· Form: Aerosol

· Important information on protection of health and

environment, and on safety.

• Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

Not determined.

· Solvent content:

• Organic solvents: 85.7 %

With propellant gas. Content given by weight.

• Water: 0.0 %
 • VOC (EU) 85.70 %
 • Solids content: 12.1 %

· Change in condition

· Evaporation rate Not applicable.

· Information with regard to physical hazard classes

Explosives VoidFlammable gases Void

· Aerosols Extremely flammable aerosol. Pressurised container:

May burst if heated.

Void· Oxidising gases · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void

(Contd. on page 7)

Printing date 15.11.2022 Version number 1 Revision: 15.11.2022

Trade name: Aerosol Terracotta- und Strukturspray div. Farbtoene

(Contd. of page 6)

· Substances and mixtures, which emit flammable	
gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## **SECTION 11: Toxicological information**

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Serious eye damage/irritation Causes serious eye irritation.
- · STOT-single exposure May cause drowsiness or dizziness.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Ikke relevant.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- GI

Printing date 15.11.2022 Version number 1 Revision: 15.11.2022

Trade name: Aerosol Terracotta- und Strukturspray div. Farbtoene

(Contd. of page 7)

# SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

· 14.1 UN number or ID number · ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name · ADR · IMDG · IATA	1950 AEROSOLS AEROSOLS AEROSOLS, flammable
· 14.3 Transport hazard class(es)	
· ADR	
· Class	2 5F Gases.
· Label	2.1
· Class	2.1 Gases.
· Label	2.1
· 14.4 Packing group · ADR, IMDG, IATA	Void not classified
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · Hazard identification number (Kemler code):	Warning: Gases. - not classified
· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat.

(Contd. on page 9)

Printing date 15.11.2022 Version number 1 Revision: 15.11.2022

Trade name: Aerosol Terracotta- und Strukturspray div. Farbtoene

	(Contd. of page
Segregation Code	SG69 For AEROSOLS with a maximum capacity of litre:
	Segregation as for class 9. Stow "separated from" class except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class 2 For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class 2
14.7 Maritime transport in bulk accord	ding to IMO
instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	IL
Excepted quantities $(\widetilde{EQ})$	Code: E0
	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
IMDG	
Limited quantities (LQ)	1L
Excepted quantities $(\widetilde{EQ})$	Code: E0
- · · ~	Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1950 AEROSOLS. 2.1

## **SECTION 15: Regulatory information**

- $\cdot$  15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture VOC: <840g/l
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	50-100

- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Relevant phrases
- H201 Explosive; mass explosion hazard.
- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.

(Contd. on page 10)

Printing date 15.11.2022 Version number 1 Revision: 15.11.2022

Trade name: Aerosol Terracotta- und Strukturspray div. Farbtoene

(Contd. of page 9) H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H361 Suspected of damaging fertility or the unborn child. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. EUH018 In use may form flammable/explosive vapour-air mixture. EUH066 Repeated exposure may cause skin dryness or cracking. · Department issuing SDS: Product safety department · Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Expl. 1.1: Explosives - Division 1.1 Flam. Gas 1A: Flammable gases - Category 1A Aerosol 1: Aerosols - Category 1 : Aerosols - Category 3 Press. Gas (Comp.): Gases under pressure - Compressed gas Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2 Asp. Tox. 1: Aspiration hazard - Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

\* \* Data compared to the previous version altered.