

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.01.2024

Version number 1

Revision: 30.01.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** Aerosol PU-Wasserlack Klarlack mattiert 4
- **(Article number) product ID.:** REZ1483
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Application of the substance / the mixture:** painting
- **Uses advised against** No further relevant information available.
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Peter Kwasny GmbH
Heilbronner Str. 96
D-74831 Gundelsheim
- **Further information obtainable from:** Product safety department
- **1.4 Emergency telephone number:** Tel.: +49 6269 95 20
- **national:**
National Poisons Information Service, Birmingham
Tel.: 844 892 0111
- **K-Nr.** 0001

Tel.: 0049-(0)6269-95-20
E-mail: labor@kwasny.de

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
Aerosol 3 H229 Pressurised container: May burst if heated.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms** Void
- **Signal word** Warning
- **Hazard statements**
H229 Pressurised container: May burst if heated.
- **Precautionary statements**
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read carefully and follow all instructions.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251 Do not pierce or burn, even after use.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- **Additional information:**
Without adequate ventilation, explosive atmosphere/gas mix may be created.
Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
EUH208 Contains reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.
25.00979 % by mass of the contents are flammable

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.01.2024

Version number 1

Revision: 30.01.2024

Trade name: Aerosol PU-Wasserlack Klarlack mattiert 4

(Contd. of page 1)

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether ----- ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	10- <25%
CAS: 121-44-8 EINECS: 204-469-4	triethylamine ----- ⚠ Flam. Liq. 2, H225; ⚠ Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; ⚠ Skin Corr. 1A, H314; Eye Dam. 1, H318 Specific concentration limit: STOT SE 3; H335: C ≥ 1 %	<1%
CAS: 64-17-5 EINECS: 200-578-6 Reg.nr.: 01-2119457610-43-xxxx	ethanol ----- ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319	<1%
CAS: 112-34-5 EINECS: 203-961-6 Reg.nr.: 01-2119475104-44-xxxx	2-(2-butoxyethoxy)ethanol ----- ⚠ Eye Irrit. 2, H319	<1%
CAS: 55965-84-9 Reg.nr.: 01-2120764691-48-xxxx	reaction mass of 5-chloro-2- methyl-2H-isothiazol- 3-one and 2-methyl-2H-isothiazol-3- one (3:1) ----- ⚠ Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330; ⚠ Skin Corr. 1C, H314; Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); ⚠ Skin Sens. 1A, H317, EUH071 Specific concentration limits: Skin Corr. 1C; H314: C ≥ 0.6 % Skin Irrit. 2; H315: 0.06 % ≤ C < 0.6 % Eye Dam. 1; H318: C ≥ 0.6 % Eye Irrit. 2; H319: 0.06 % ≤ C < 0.6 % Skin Sens. 1A; H317: C ≥ 0.0015 %	≥0.00025- <0.0015%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

GB

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.01.2024

Version number 1

Revision: 30.01.2024

Trade name: Aerosol PU-Wasserlack Klarlack mattiert 4

(Contd. of page 2)

SECTION 5: Firefighting measures

- **5.1 Extinguishing media** -
- **Suitable extinguishing agents:** Cool container with water
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Keep away from heat and direct sunlight.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Protect from frost.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· **Ingredients with limit values that require monitoring at the workplace:**

115-10-6 dimethyl ether

WEL	Short-term value: 958 mg/m ³ , 500 ppm
	Long-term value: 766 mg/m ³ , 400 ppm

64-17-5 ethanol

WEL	Long-term value: 1920 mg/m ³ , 1000 ppm
-----	--

112-34-5 2-(2-butoxyethoxy)ethanol

WEL	Short-term value: 101.2 mg/m ³ , 15 ppm
	Long-term value: 67.5 mg/m ³ , 10 ppm

· **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

· **Appropriate engineering controls** No further data; see section 7.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.01.2024

Version number 1

Revision: 30.01.2024

Trade name: Aerosol PU-Wasserlack Klarlack mattiert 4

(Contd. of page 3)

- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:** Wash hands before breaks and at the end of work.
- **Respiratory protection:**
Use suitable respiratory protective device in case of insufficient ventilation.



When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

- **Hand protection**



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Penetration time of glove material**
Gloves must be changed after every contamination.
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**
butyl rubber, 0,7mm
- **Eyeface protection** Not required.

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Physical state** Aerosol
- **Colour:** Clear
- **Odour:** Weak, characteristic
- **Odour threshold:** Not determined.
- **Melting point/freezing point:** Undetermined.
- **Boiling point or initial boiling point and boiling range** -24,9 °C
- **Flammability** Not applicable.
- **Lower and upper explosion limit**
- **Lower:** 3 Vol % (115-10-6 dimethyl ether)
- **Upper:** 18.6 Vol % (115-10-6 dimethyl ether)
- **Flash point:** -42 °C (115-10-6 dimethyl ether)
- **Auto-ignition temperature:** 235 °C (115-10-6 dimethyl ether)
- **Decomposition temperature:** Not determined.
- **pH** Not determined.
- **Viscosity:**
- **Kinematic viscosity** Not determined.
- **Dynamic:** Not determined.
- **Solubility**
- **water:** Fully miscible.
- **Partition coefficient n-octanol/water (log value)** Not determined.
- **Vapour pressure at 20 °C:** 3,400 hPa (115-10-6 dimethyl ether)
- **Density and/or relative density**
- **Relative density** 0.9225 g/ml
- **Vapour density** Not determined.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.01.2024

Version number 1

Revision: 30.01.2024

Trade name: Aerosol PU-Wasserlack Klarlack mattiert 4

(Contd. of page 4)

· 9.2 Other information	
· Appearance:	
· Form:	Aerosol
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible. Not determined.
· Solvent content:	
· Organic solvents:	25.1 % With propellant gas. Content given by weight.
· Water:	61.4 %
· VOC (EU)	(<840g/l) 25.13 %
· Solids content:	34.2 %
· Change in condition	
· Evaporation rate	Not applicable.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Pressurised container: May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

(Contd. on page 6)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.01.2024

Version number 1

Revision: 30.01.2024

Trade name: Aerosol PU-Wasserlack Klarlack mattiert 4

(Contd. of page 5)

· **LD/LC50 values relevant for classification:**

ATE (Acute Toxicity Estimates)

Oral	LD50	112,949 mg/kg (rat)
Dermal	LD50	139,959 mg/kg (rabbit)
Inhalative	LC50/4 h	737 mg/l

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclotetrasiloxane	List II
556-67-2	octamethylcyclotetrasiloxane	List II; III
540-97-6	Dodecamethylcyclohexasiloxane	List II

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Ikke relevant.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:** Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR, IMDG, IATA** UN1950

(Contd. on page 7)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.01.2024

Version number 1

Revision: 30.01.2024

Trade name: Aerosol PU-Wasserlack Klarlack mattiert 4

(Contd. of page 6)

· 14.2 UN proper shipping name

· ADR

1950 AEROSOLS

· IMDG, IATA

AEROSOLS

· 14.3 Transport hazard class(es)

· ADR



· Class

2.5A Gases.

· Label

2.2

· IMDG, IATA



· Class

2 Gases.

· Label

2.2

· 14.4 Packing group

· ADR, IMDG, IATA

Void
not classified

· 14.5 Environmental hazards:

· Marine pollutant:

No

· 14.6 Special precautions for user

· Hazard identification number (Kemler code):

Warning: Gases.

-
not classified

· EMS Number:

F-D,S-U

· Stowage Code

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

· Segregation Code

SG69 For AEROSOLS with a maximum capacity of 1 litre:

Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.

For AEROSOLS with a capacity above 1 litre:

Segregation as for the appropriate subdivision of class 2.

For WASTE AEROSOLS:

Segregation as for the appropriate subdivision of class 2.

· 14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ)

1L

· Excepted quantities (EQ)

Code: E0

Not permitted as Excepted Quantity

· Transport category

3

· Tunnel restriction code

E

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.01.2024

Version number 1

Revision: 30.01.2024

Trade name: Aerosol PU-Wasserlack Klarlack mattiert 4

(Contd. of page 7)

· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.2

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

VOC: <840g/l

· **Poisons Act**

· **Regulated explosives precursors**

None of the ingredients is listed.

· **Regulated poisons**

None of the ingredients is listed.

· **Reportable explosives precursors**

None of the ingredients is listed.

· **Reportable poisons**

50-00-0	formaldehyde	5%
---------	--------------	----

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **National regulations:**

· **Technical instructions (air):**

Class	Share in %
Wasser	50-100
NK	25-<50

· **Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The safety data sheet may only be passed on to third parties for the manufacturer's brands.

· **Relevant phrases**

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H301 Toxic if swallowed.
- H310 Fatal in contact with skin.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.01.2024

Version number 1

Revision: 30.01.2024

Trade name: Aerosol PU-Wasserlack Klarlack mattiert 4

(Contd. of page 8)

H331 Toxic if inhaled.
 H335 May cause respiratory irritation.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 EUH018 In use may form flammable/explosive vapour-air mixture.
 EUH071 Corrosive to the respiratory tract.

· **Department issuing SDS:** Product safety department

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 3: Aerosols – Category 3

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 2: Acute toxicity – Category 2

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Corr. 1C: Skin corrosion/irritation – Category 1C

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1A: Skin sensitisation – Category 1A

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

· *** Data compared to the previous version altered.**

GB