

1K FillClean Waterborne Series D

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Issue date: 6/7/2017

Revision date: 4/5/2022 update 01/13/2023

Supersedes: 7/31/2019

Version: 1.2

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : 1K FillClean Waterborne Series D
Product code : 3682078 / REZ157

1.2. Recommended use and restrictions on use

Recommended use : Automotive refinish

1.3. Supplier

Manufacturer

Peter Kwasny GmbH
96 Heibronner Str.
Gundelsheim, 74831 - Germany
T 49(0) 6269-95-20

Distributor

Peter Kwasny Inc.
62-64 Enter Lane
Islandia, NY 11749
T 1-844-726-6330 (toll free North America)

Distributor

Peter Kwasny Spraypaint Canada Inc
40 University Avenue, Suite 904
Toronto, ON M5J 1T1

1.4. Emergency telephone number

Emergency number : 352-323-3500 (24h / 7 days a week)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS classification

Flam. Aerosol 1
Press. Gas (Liq.)
Eye Irrit. 2A
Simple Asphy

2.2. GHS Label elements, including precautionary statements

GHS labelling

Hazard pictograms (GHS) :



Signal word (GHS) :

Danger

Hazard statements (GHS) :

Extremely flammable aerosol.
Contains gas under pressure; may explode if heated.
Causes serious eye irritation.
May displace oxygen and cause rapid suffocation

1K FillClean Waterborne Series D

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Precautionary statements (GHS) : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.
Wash hands, forearms and face thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.
Store in a well-ventilated place.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
Dimethyl ether	Dimethyl ether Methane, oxybis- / Methyl ether	CAS-No.: 115-10-6	80 – 100
Isopropyl alcohol	2-Hydroxypropane / 2-Propyl alcohol / Isopropanol / Propan-2-ol	CAS-No.: 67-63-0	10 – 30

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.

First-aid measures after skin contact : If skin irritation occurs: Wash skin with plenty of water. Obtain medical attention if irritation persists.

First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : May cause irritation to the respiratory tract. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Symptoms of oxygen deficiency include respiratory difficulty, headache, dizziness, nausea, unconsciousness or death.

Symptoms/effects after skin contact : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.

Symptoms/effects after eye contact : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

1K FillClean Waterborne Series D

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Symptoms/effects after ingestion : May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

4.3. Immediate medical attention and special treatment, if necessary

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Carbon dioxide (CO₂).
Unsuitable extinguishing media : Do not use water jet.

5.2. Specific hazards arising from the chemical

Fire hazard : Extremely flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon. irritating vapours.
Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. Vapours may form explosive mixture with air.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : DO NOT fight fire when fire reaches explosives. Evacuate area. Move containers away from the fire area if this can be done without risk.
Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Use water spray to keep fire-exposed containers cool. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate every possible source of ignition. Use only non-sparking tools. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so. Remove all sources of ignition. Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.
Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

1K FillClean Waterborne Series D

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Pressurized container: Do not pierce or burn, even after use. Hazardous waste due to potential risk of explosion.
Precautions for safe handling	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid contact with skin, eyes and clothing. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. When using do not eat, drink or smoke. Handle and open container with care. Use only outdoors or in a well-ventilated area.
Hygiene measures	: Take off immediately all contaminated clothing and wash it before reuse. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Proper grounding procedures to avoid static electricity should be followed.
Storage conditions	: Keep out of the reach of children. Store locked up. Keep in fireproof place. Store away from direct sunlight or other heat sources. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a dry, cool and well-ventilated place.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

1K FillClean Waterborne Series D	
No additional information available	
Dimethyl ether (115-10-6)	
No additional information available	
Isopropyl alcohol (67-63-0)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	200 ppm
ACGIH OEL STEL [ppm]	400 ppm
ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA - ACGIH - Biological Exposure Indices	
BEI	40 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift at end of workweek (background, nonspecific)
USA - OSHA - Occupational Exposure Limits	
OSHA PEL TWA [1]	980 mg/m ³
OSHA PEL TWA [2]	400 ppm
USA - IDLH - Occupational Exposure Limits	
IDLH [ppm]	2000 ppm (10% LEL)
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	980 mg/m ³
NIOSH REL TWA [ppm]	400 ppm
NIOSH REL STEL	1225 mg/m ³
NIOSH REL STEL [ppm]	500 ppm

1K FillClean Waterborne Series D

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

8.2. Appropriate engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station. Provide readily accessible eye wash stations and safety showers.
- Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear suitable gloves

Eye protection:

Wear eye/face protection

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol.
Colour	: Clear
Odour	: Characteristic
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: < -18 °C (-0.4 °F)
Flash point	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.68 g/cm ³
Solubility	: No data available
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

No additional information available

1K FillClean Waterborne Series D

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions. Extremely flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat. Sparks. Open flame. Direct sunlight. Incompatible materials.

10.5. Incompatible materials

Oxidizing materials. Acids. Alkalis.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon. irritating vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified.

Acute toxicity (dermal) : Not classified.

Acute toxicity (inhalation) : Not classified.

Dimethyl ether (115-10-6)

LC50 inhalation rat	164000 ppm/4h
---------------------	---------------

ATE CA (Gases (except aerosol dispensers and lighters))	164000 ppmv/4h
---	----------------

Isopropyl alcohol (67-63-0)

LD50 oral rat	5840 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
---------------	--

LD50 dermal rabbit	4059 mg/kg
--------------------	------------

LC50 inhalation rat	> 10000 ppm (Exposure time: 6 h)
---------------------	----------------------------------

ATE CA (oral)	5840 mg/kg bodyweight
---------------	-----------------------

ATE CA (Dermal)	4059 mg/kg bodyweight
-----------------	-----------------------

Skin corrosion/irritation : Not classified.

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : Not classified.

Germ cell mutagenicity : Not classified.

Carcinogenicity : Not classified.

Isopropyl alcohol (67-63-0)

IARC group	3 - Not classifiable
------------	----------------------

Reproductive toxicity : Not classified.

STOT-single exposure : Not classified.

1K FillClean Waterborne Series D

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Isopropyl alcohol (67-63-0)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified.
Aspiration hazard	: Not classified.

1K FillClean Waterborne Series D	
Vaporizer	Aerosol
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Symptoms of oxygen deficiency include respiratory difficulty, headache, dizziness, nausea, unconsciousness or death.
Symptoms/effects after skin contact	: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
Symptoms/effects after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

Dimethyl ether (115-10-6)	
LC50 - Fish [1]	> 4.1 g/l (Exposure time: 96 h - Species: Poecilia reticulata [semi-static])
EC50 - Crustacea [1]	> 4.4 g/l Test organisms (species): Daphnia magna

Isopropyl alcohol (67-63-0)	
LC50 - Fish [1]	10000 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	13299 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 - Fish [2]	9640 mg/l Test organisms (species): Pimephales promelas

12.2. Persistence and degradability

1K FillClean Waterborne Series D	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

1K FillClean Waterborne Series D	
Bioaccumulative potential	Not established.

Dimethyl ether (115-10-6)	
Partition coefficient n-octanol/water	-0.18

Isopropyl alcohol (67-63-0)	
Partition coefficient n-octanol/water	0.05 (at 25 °C)

12.4. Mobility in soil

No additional information available

1K FillClean Waterborne Series D

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

12.5. Other adverse effects

Other information : No other effects known.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. Container under pressure. Do not drill or burn even after use.

Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

In accordance with DOT / TDG

14.1. UN number

DOT NA No : UN1950

UN-No. (TDG) : UN1950

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Aerosols

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 2.1

Hazard labels (DOT) : 2.1



TDG

Transport hazard class(es) (TDG) : 2.1

Hazard labels (TDG) : 2.1



14.4. Packing group

Packing group (DOT) : Not applicable

Packing group (TDG) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.

1K FillClean Waterborne Series D

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

DOT

UN-No.(DOT)	: UN1950
DOT Special Provisions (49 CFR 172.102)	: N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 306
DOT Packaging Non Bulk (49 CFR 173.xxx)	: None
DOT Packaging Bulk (49 CFR 173.xxx)	: None
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 150 kg
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	: 25 - Protected from sources of heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

TDG

UN-No. (TDG)	: UN1950
TDG Special Provisions	: 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment), 107 - (1) These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL. (2) Subsection (1) does not apply to self-defence spray.
Explosive Limit and Limited Quantity Index	: 1 L
Excepted quantities (TDG)	: E0
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 75 L
Emergency Response Guide (ERG) Number	: 126

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

15.2. International regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

1K FillClean Waterborne Series D

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 16: Other information

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Revision date : 04/05/2022
Other information : None.
Prepared by : Nexreg Compliance Inc.
www.Nexreg.com



Full text of H-statements	
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Aerosol 1	Flammable aerosols, Category 1
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
Simple Asphy	Simple Asphyxiant

Indication of changes:
SDS update.

SDS HazCom 2012 - WHMIS 2015 (Nexreg) 2021

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.