

2K FillClean Series G

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022
Issue date: 2017-05-30 Revision date: 2025-10-22 Supersedes: 2022-03-08 Version: 3.0

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Product name : 2K FillClean Series G
Product code : 3680086 / REZ190
Vaporizer : Aerosol

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Automotive refinish
Intended for general public

1.4. Supplier's details

Manufacturer

Peter Kwasny GmbH
96 Heibronner Str.
Gundelsheim, 74831
Germany
T 49(0) 6269-95-20

Distributor

Peter Kwasny, Inc.
12222 Merit Drive, #130
Dallas, TX 75251
USA
T 1-844-426-6330

Distributor

Peter Kwasny Spraypaint Canada Inc
40 University Avenue, Suite 904
Toronto, ON, M5J 1T1
Canada
T +1 844-426-6330

1.5. Emergency phone number

Emergency number : North America
INFOTRAC International +1 (352) 323-5000 24 hr

SECTION 2 Hazard identification

2.1. Classification of the substance or mixture

GHS classification

Aerosol, Category 1
Eye irritation, Category 2A
Skin sensitization, Category 1
Carcinogenicity, Category 2
Reproductive toxicity, Category 2
Specific target organ toxicity – Single exposure, Category 3, Narcosis
Simple asphyxiant, Category 1

2.2. Label elements

GHS labelling

Hazard pictograms (GHS)



2K FillClean Series G

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Signal word (GHS)	: Danger
Hazard statements (GHS)	: Extremely flammable aerosol Pressurized container; may burst if heated May cause an allergic skin reaction Causes serious eye irritation May cause drowsiness or dizziness Suspected of causing cancer. Suspected of damaging the unborn child. May displace oxygen and cause rapid suffocation
Precautionary statements (GHS)	: If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing dust, fume, gas, mist, vapours, spray. Wash hands, forearms and face thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves, protective clothing, eye protection, face protection. If exposed or concerned: Get medical advice/attention. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice or attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C). Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

Other hazards which do not result in classification : Contact with the liquefied gas may cause frostbite.

2.5. Unknown acute toxicity

Not applicable

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

2K FillClean Series G

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	Conc. (% w/w)
Dimethyl ether	Dimethyl ether Methane, oxybis- / Methyl ether / Wood ether / Methoxymethane / Methane, 1,1'-oxybis- / DIMETHYL ETHER / Oxybismethane / Dimethyl oxide / Dimethylether	CAS-No.: 115-10-6	30 - 60
Ethyl acetate	Ethyl acetate Acetic acid, ethyl ester / Ethyl ethanoate / ETHYL ACETATE	CAS-No.: 141-78-6	10 - 30
n-Butyl acetate	n-Butyl acetate 1-Butyl acetate / Butyl acetate, n- / Butyl acetate / BUTYL ACETATE / Acetic acid, n-butyl ester / Acetic acid, butyl ester / Butyl ethanoate / N-butyl acetate	CAS-No.: 123-86-4	10 - 30
Hexamethylene diisocyanate homopolymer	Hexamethylene diisocyanate homopolymer Poly(hexamethylene diisocyanate) / Polymeric hexamethylene diisocyanate / HDI oligomers / HDI oligomers, isocyanurate / Polymer of 1,6-diisocyanatohexane / HDI polyisocyanate / Hexamethylene diisocyanate polymer / Isocyanic acid, hexamethylene ester, polymers / Hexane, 1,6- diisocyanato-, homopolymer / Hexamethylene diisocyanate, oligomers / 1,6-Diisocyanatohexane homopolymer	CAS-No.: 28182-81-2	7 - 13

2K FillClean Series G

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Name	Chemical name / Synonyms	Product identifier	Conc. (% w/w)
Solvent naphtha, petroleum, light aromatic	Solvent naphtha, petroleum, light aromatic Solvent naphtha (petroleum), light aromatic / Light aromatic solvent naphtha / Aromatic 100 / Solvent naphtha, petroleum, light aromatic-low boiling point hydrogen treated naphtha / Light aromatic solvent naphtha (petroleum) (C8-10) / Solvent naphtha, petroleum, light aromatic (A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8-10 and boiling in the range of approximately 135-210°C.) / Aromatic naphtha, type I / Solvent naphtha (petroleum), light aromatic, hydrotreated / Hydrocarbons, C9, aromatics / Solvent naphtha (petroleum), light aromatic; Low boiling point naphtha -unspecified [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).] / Aromatic hydrocarbon solvents - medium flashpoint / solvent naphtha (petroleum, light aromatic)	CAS-No.: 64742-95-6	1 – 5

2K FillClean Series G

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Name	Chemical name / Synonyms	Product identifier	Conc. (% w/w)
Xylenes (o-, m-, p- isomers)	Xylenes (o-, m-, p- isomers) / Benzene, dimethyl- / Dimethylbenzene (mixed isomers) / Xylene / Xylene (all isomers) / Xylene (mixed isomers) / Xylene (o-, m-, p- isomers) / Xylenes / Xylenes (mixed isomers) / Dimethylbenzene / Xylol / Benzene, dimethyl-, mixed isomers / XYLENE / Dimethylbenzenes / Xylene isomers mixture / Dimethylbenzene (2-, 3-, 4-isomers) / Dimethylbenzene (mixed 2-, 3-, 4-isomers) / C8 Disubstituted benzenes / Xylene, mixed isomers / Xylenes (meta-, ortho-, para-) / Xylene (mixture), including m-xylene, o-xylene, p-xylene / Xylene (o-,m-,p- isomer mixture)	CAS-No.: 1330-20-7	1 - 5
Ethylbenzene	Ethylbenzene / Benzene, ethyl- / Phenylethane / ETHYLBENZENE	CAS-No.: 100-41-4	0.1 - 1

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4 First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: If exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. Give oxygen or artificial respiration if necessary.
First-aid measures after skin contact	: IF ON SKIN: Wash with plenty of Water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If frostbite occurs thaw frosted parts with lukewarm water. Do not rub affected area. Do not use hot water.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If frostbite occurs thaw frosted parts with lukewarm water. Do not rub affected area. Do not use hot water.
First-aid measures after ingestion	: Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: May cause irritation to the respiratory tract. May cause drowsiness or dizziness. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Symptoms of oxygen deficiency include respiratory difficulty, headache, dizziness, nausea, unconsciousness or death.
Symptoms/effects after skin contact	: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause an allergic skin reaction. May cause frostbite on contact with the liquefied gas.
Symptoms/effects after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause frostbite on contact with the liquefied gas.

2K FillClean Series G

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: Suspected of causing cancer. Suspected of damaging the unborn child.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
-----------------------------------	--

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	: Do not use water jet.

5.2. Specific hazards arising from the chemical

Fire hazard	: Extremely flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon. Oxides of nitrogen. Hydrogen cyanide. Irritating vapours. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours.
Explosion hazard	: Vapours may form explosive mixture with air. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. Ruptured cylinders may rocket.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Move containers away from the fire area if this can be done without risk. DO NOT fight fire when fire reaches explosives. Evacuate area.
Protection during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Use water spray to keep fire-exposed containers cool. Vapours are heavier than air and may spread along floors.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate every possible source of ignition. Use only non-sparking tools. Use special care to avoid static electric charges.
------------------	---

For non-emergency personnel

No additional information available

For emergency responders

Environmental precautions	: Prevent entry to sewers and public waters.
---------------------------	--

6.2. Methods and materials for containment and cleaning up

For containment	: Stop leak if safe to do so. Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.
Methods for cleaning up	: Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

For further information refer to section 8: "Exposure controls/personal protection"

2K FillClean Series G

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Take precautionary measures against static discharge. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Do not spray on an open flame or other ignition source. Avoid contact with skin, eyes and clothing. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not swallow. When using do not eat, drink or smoke. Handle and open container with care. Use only outdoors or in a well-ventilated area.
Hygiene measures	: Take off immediately all contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace. Wash hands, forearms and face thoroughly after handling.
Additional hazards when processed	: Pressurized container: Do not pierce or burn, even after use. Hazardous waste due to potential risk of explosion.

7.2. Conditions for safe storage, including incompatibilities

Technical measures	: Proper grounding procedures to avoid static electricity should be followed.
Storage conditions	: Keep out of the reach of children. Store locked up. Keep in fireproof place. Store away from direct sunlight or other heat sources. Keep away from clothing and other combustible materials. Do not expose to temperatures exceeding 50 °C/ 122 °F. Protect containers from physical damage. Keep away from incompatible materials. . Store in a dry, cool and well-ventilated place.
Specific end uses	: Not available.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Dimethyl ether (115-10-6)	
USA - AIHA - Occupational Exposure Limits	
WEEL TWA	1000 ppm
Ethyl acetate (141-78-6)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Ethyl acetate
ACGIH® TLV® TWA	400 ppm
Remark (ACGIH®)	TLV® Basis: URT & eye irr
Regulatory reference	ACGIH 2020
USA - OSHA - Occupational Exposure Limits	
Local name	Ethyl acetate
OSHA PEL TWA	1400 mg/m³
OSHA PEL TWA	400 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - IDLH - Occupational Exposure Limits	
IDLH	2000 ppm (10% LEL)

2K FillClean Series G

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Ethyl acetate (141-78-6)	
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	1400 mg/m ³
NIOSH REL TWA	400 ppm
n-Butyl acetate (123-86-4)	
USA - ACGIH - Occupational Exposure Limits	
Local name	n-Butyl acetate
ACGIH® TLV® TWA	50 ppm (Butyl acetates, all isomers)
ACGIH® TLV® STEL	150 ppm (Butyl acetates, all isomers)
Remark (ACGIH®)	TLV® Basis: Eye & URT irr
Regulatory reference	ACGIH 2020
USA - OSHA - Occupational Exposure Limits	
Local name	n-Butyl-acetate
OSHA PEL TWA	710 mg/m ³
OSHA PEL TWA	150 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - IDLH - Occupational Exposure Limits	
IDLH	1700 ppm (10% LEL)
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	710 mg/m ³
NIOSH REL TWA	150 ppm
NIOSH REL STEL	950 mg/m ³
NIOSH REL STEL	200 ppm
Xylenes (o-, m-, p- isomers) (1330-20-7)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH® chemical category	Not Classifiable as a Human Carcinogen
USA - ACGIH - Biological Exposure Indices	
BEI	1.5 g/g creatinine Parameter: Methylhippuric acids - Medium: urine - Sampling time: end of shift (technical or commercial grade)
USA - OSHA - Occupational Exposure Limits	
Local name	Xylenes (o-, m-, p-isomers)
OSHA PEL TWA	435 mg/m ³
OSHA PEL TWA	100 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Ethylbenzene (100-41-4)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Ethyl benzene
ACGIH® TLV® TWA	20 ppm

2K FillClean Series G

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Ethylbenzene (100-41-4)	
Remark (ACGIH®)	TLV® Basis: URT & Eye irr; Kidney eff; Ototoxicity; CNS impair. Notations: OTO (Ototoxicant); A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
ACGIH® chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
Regulatory reference	ACGIH 2025
USA - ACGIH - Biological Exposure Indices	
Local name	Ethyl benzene
BEI	0.15 g/g creatinine Parameter: Sum of mandelic acid and phenylglyoxylic acid - Medium: urine - Sampling time: end of shift (nonspecific)
Regulatory reference	ACGIH 2025
USA - OSHA - Occupational Exposure Limits	
Local name	Ethyl benzene
OSHA PEL TWA	435 mg/m ³
OSHA PEL TWA	100 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - IDLH - Occupational Exposure Limits	
IDLH	800 ppm (10% LEL)
USA - NIOSH - Occupational Exposure Limits	
Local name	Ethyl benzene
NIOSH REL TWA	435 mg/m ³
NIOSH REL TWA	100 ppm
NIOSH REL 10h TWA	100 ppm
NIOSH REL STEL	545 mg/m ³
NIOSH REL STEL	125 ppm
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station. Provide readily accessible eye wash stations and safety showers.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Hand protection:
Wear suitable gloves resistant to chemical penetration. Consult glove manufacturer's product information on material suitability and material thickness.
Eye protection:
Wear eye/face protection
Skin and body protection:
Wear suitable protective clothing

2K FillClean Series G

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. SDSs cannot provide detailed and complete respiratory protection guidelines. Selection of respiratory protection must be done by a qualified person who has assessed the work environment.

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol.
Colour	: Clear
Odour	: Characteristic
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: < -18 °C (-0.4 °F)
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapour pressure	: No data available
Relative vapour density at 20°C/ 68 °F	: No data available
Relative density	: No data available
Density	: 0.76 g/cm ³
Solubility	: No data available
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Explosive limits	: No data available
Particle characteristics	: No data available

Dimethyl ether

Boiling point	-24.9 °C
Flash point	-40.56 °C (closed cup)
Auto-ignition temperature	240 °C
Vapour pressure	5.12 hPa (at 20 °C)
Particle characteristics	No data available

Ethyl acetate

Boiling point	77 °C (at 1 atm)
Flash point	-4 °C (closed cup)
Auto-ignition temperature	426.67 °C
Vapour pressure	91.84 hPa (at 18.7 °C)
Particle characteristics	No data available

2K FillClean Series G

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

n-Butyl acetate	
Boiling point	125 – 126 °C (at 1 atm)
Flash point	22 °C
Auto-ignition temperature	425 °C
Vapour pressure	13 hPa (at 20 °C)
Particle characteristics	No data available

Hexamethylene diisocyanate homopolymer	
Flash point	228 °C
Auto-ignition temperature	460 °C
Vapour pressure	0.002 Pa (at 20 °C)
Particle characteristics	No data available

Solvent naphtha, petroleum, light aromatic	
Boiling point	-20 – 260 °C Atm. press.: 101,325 kPa
Flash point	< -40 °C Atm. press.: 101,325 other:kPa (assumed). Pressure not stipulated in the citation
Auto-ignition temperature	280 – 470 °C (at 1013 hPa)
Vapour pressure	350 – 900 hPa (at 37.8 °C)
Particle characteristics	No data available

Xylenes (o-, m-, p- isomers)	
Boiling point	138.3 – 141.4 °C
Auto-ignition temperature	465 – 525 °C
Vapour pressure	8.8 – 11.9 hPa (at 25 °C)
Particle characteristics	No data available

Ethylbenzene	
Boiling point	136.1 °C (at 1013.3 hPa)
Flash point	12.8 °C (closed cup)
Auto-ignition temperature	432 °C (at 1013 hPa)
Vapour pressure	9.5 hPa (at 20 °C)
Particle characteristics	No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

2K FillClean Series G

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

10.2. Chemical stability

Stable under normal conditions. Extremely flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat. Sparks. Open flame. Direct sunlight. Overheating. Incompatible materials.

10.5. Incompatible materials

Oxidizing materials. Acids. Alkalis.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon. Oxides of nitrogen. Hydrogen cyanide. Irritating vapours.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified.
Acute toxicity (dermal) : Not classified.
Acute toxicity (inhalation) : Not classified.

Dimethyl ether (115-10-6)

LC50 inhalation rat	164000 ppm/4h
---------------------	---------------

Ethyl acetate (141-78-6)

LD50 oral rat	5620 mg/kg (Source: NLM_CIP)
LD50 oral	4934 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 18000 mg/kg (Source: JAPAN_GHS)
LC50 inhalation rat	4000 ppm/4h

n-Butyl acetate (123-86-4)

LD50 oral rat	10768 mg/kg (Source: NLM_CIP)
LD50 dermal rabbit	> 17600 mg/kg (Source: NLM_CIP)
LC50 inhalation rat	0.74 mg/l/4h
LC50 Inhalation - Rat (Vapours)	1.86 mg/l/4h

Hexamethylene diisocyanate homopolymer (28182-81-2)

LD50 oral rat	> 2500 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)
LD50 dermal rat	> 2000 mg/kg (Source: ECHA_API)
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: other:
LC50 inhalation rat	18500 mg/m ³ (Exposure time: 1 h Source: NLM_CIP)

Solvent naphtha, petroleum, light aromatic (64742-95-6)

LD50 oral rat	8400 mg/kg (Source: NLM_CIP)
---------------	------------------------------

2K FillClean Series G

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Solvent naphtha, petroleum, light aromatic (64742-95-6)	
LD50 dermal rabbit	> 2000 mg/kg (Source: IUCLID)
LC50 inhalation rat	> 6193 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Remarks on results: other:
LC50 inhalation rat	3400 ppm/4h

Xylenes (o-, m-, p- isomers) (1330-20-7)	
LD50 oral rat	3500 mg/kg (Source: JAPAN_GHS)
LD50 dermal rabbit	> 4350 mg/kg (Source: JAPAN_GHS)
LD50 dermal	1700 mg/kg
LC50 inhalation rat	29.08 mg/l/4h
LC50 Inhalation - Rat (Vapours)	27.57 mg/l/4h

Ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg (Source: JAPAN_GHS)
LD50 dermal rabbit	15400 mg/kg (Source: JAPAN_GHS)
LC50 inhalation rat	17.4 mg/l/4h

Skin corrosion/irritation : Not classified.

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified.

Carcinogenicity : Suspected of causing cancer.

Xylenes (o-, m-, p- isomers) (1330-20-7)	
IARC group	3 - Not classifiable

Ethylbenzene (100-41-4)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity
In OSHA Hazard Communication Carcinogen list	Yes

Reproductive toxicity : Suspected of damaging the unborn child.

STOT-single exposure : May cause drowsiness or dizziness.

Ethyl acetate (141-78-6)	
STOT-single exposure	May cause drowsiness or dizziness.

n-Butyl acetate (123-86-4)	
STOT-single exposure	May cause drowsiness or dizziness.

Solvent naphtha, petroleum, light aromatic (64742-95-6)	
STOT-single exposure	May cause drowsiness or dizziness.

Xylenes (o-, m-, p- isomers) (1330-20-7)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified.

2K FillClean Series G

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Ethyl acetate (141-78-6)	
LOAEL (oral, rat, 90 days)	3600 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 795.2600 (Subchronic Oral Toxicity Test)
NOAEL (oral, rat, 90 days)	900 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 795.2600 (Subchronic Oral Toxicity Test)
Solvent naphtha, petroleum, light aromatic (64742-95-6)	
NOAEL (oral, rat, 90 days)	600 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
Xylenes (o-, m-, p- isomers) (1330-20-7)	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
Ethylbenzene (100-41-4)	
NOAEL (oral, rat, 90 days)	75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified.
2K FillClean Series G	
Vaporizer	Aerosol
Viscosity, kinematic	No data available
Dimethyl ether (115-10-6)	
Viscosity, kinematic	No data available
Ethyl acetate (141-78-6)	
Viscosity, kinematic	0.5 mm ² /s
n-Butyl acetate (123-86-4)	
Viscosity, kinematic	No data available
Hexamethylene diisocyanate homopolymer (28182-81-2)	
Viscosity, kinematic	≈ 3300.506 mm ² /s
Solvent naphtha, petroleum, light aromatic (64742-95-6)	
Viscosity, kinematic	< 1 mm ² /s Temp.: 'other:37.8°C' Parameter: 'kinematic viscosity (in mm ² /s)'
Xylenes (o-, m-, p- isomers) (1330-20-7)	
Viscosity, kinematic	No data available
Ethylbenzene (100-41-4)	
Viscosity, kinematic	0.6 mm ² /s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm ² /s)' Remarks on result: 'other:'

2K FillClean Series G

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Symptoms/effects after inhalation	: May cause irritation to the respiratory tract. May cause drowsiness or dizziness. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Symptoms of oxygen deficiency include respiratory difficulty, headache, dizziness, nausea, unconsciousness or death.
Symptoms/effects after skin contact	: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause an allergic skin reaction. May cause frostbite on contact with the liquefied gas.
Symptoms/effects after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause frostbite on contact with the liquefied gas.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: Suspected of causing cancer. Suspected of damaging the unborn child.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general	: May cause long-term adverse effects in the aquatic environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified.
Hazardous to the aquatic environment, long-term (chronic)	: Not classified.

Dimethyl ether (115-10-6)	
LC50 - Fish [1]	> 4.1 g/l (Exposure time: 96 h - Species: Poecilia reticulata [semi-static] Source: ECHA)
EC50 - Crustacea [1]	> 4.4 g/l Test organisms (species): Daphnia magna
EC50 96h - Algae [1]	154.917 mg/l Test organisms (species): other:green algae
Ethyl acetate (141-78-6)	
LC50 - Fish [1]	220 – 250 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
EC50 - Crustacea [1]	560 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 - Fish [2]	484 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through] Source: IUCLID)
NOEC (chronic)	2.4 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
n-Butyl acetate (123-86-4)	
LC50 - Fish [1]	100 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static] Source: EPA)
LC50 - Fish [2]	17 – 19 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
EC50 72h - Algae [1]	674.7 mg/l (Species: Desmodesmus subspicatus)
Hexamethylene diisocyanate homopolymer (28182-81-2)	
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): other:
Solvent naphtha, petroleum, light aromatic (64742-95-6)	
LC50 - Fish [1]	9.22 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss Source: IUCLID)
EC50 - Crustacea [1]	6.14 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	0.42 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

2K FillClean Series G

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Solvent naphtha, petroleum, light aromatic (64742-95-6)	
EC50 72h - Algae [2]	0.29 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
Xylenes (o-, m-, p- isomers) (1330-20-7)	
LC50 - Fish [1]	13.4 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
EC50 - Crustacea [1]	3.82 mg/l (Exposure time: 48 h - Species: water flea)
LC50 - Fish [2]	2.661 – 4.093 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: EPA)
EC50 - Crustacea [2]	0.6 mg/l (Exposure time: 48 h - Species: Gammarus lacustris)
LOEC (chronic)	3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'
Ethylbenzene (100-41-4)	
LC50 - Fish [1]	11 – 18 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: EPA)
EC50 - Crustacea [1]	1.8 – 2.4 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 - Fish [2]	4.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static] Source: EPA)
EC50 72h - Algae [1]	4.6 mg/l (Species: Pseudokirchneriella subcapitata)
EC50 72h - Algae [2]	2.6 – 11.3 mg/l (Species: Pseudokirchneriella subcapitata [static])
EC50 96h - Algae [1]	> 438 mg/l (Species: Pseudokirchneriella subcapitata)
EC50 96h - Algae [2]	1.7 – 7.6 mg/l (Species: Pseudokirchneriella subcapitata [static])
LOEC (chronic)	1.7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC (chronic)	0.96 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC chronic crustacea	0.956 mg/l
12.2. Persistence and degradability	
2K FillClean Series G	
Persistence and degradability	Not established.
Dimethyl ether (115-10-6)	
Persistence and degradability	Rapidly degradable
Ethyl acetate (141-78-6)	
Persistence and degradability	Rapidly degradable
n-Butyl acetate (123-86-4)	
Persistence and degradability	Rapidly degradable
Hexamethylene diisocyanate homopolymer (28182-81-2)	
Persistence and degradability	Rapidly degradable
Solvent naphtha, petroleum, light aromatic (64742-95-6)	
Persistence and degradability	Rapidly degradable
Xylenes (o-, m-, p- isomers) (1330-20-7)	
Persistence and degradability	Rapidly degradable

2K FillClean Series G

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Ethylbenzene (100-41-4)	
Persistence and degradability	Rapidly degradable

12.3. Bioaccumulative potential

2K FillClean Series G	
Bioaccumulative potential	Not established.

Dimethyl ether (115-10-6)	
Partition coefficient n-octanol/water	-0.18

Ethyl acetate (141-78-6)	
BCF - Fish [1]	(30 dimensionless)
Partition coefficient n-octanol/water	0.73 (at 20 °C (at pH 7))

n-Butyl acetate (123-86-4)	
Partition coefficient n-octanol/water	1.81 (at 23 °C)

Xylenes (o-, m-, p- isomers) (1330-20-7)	
BCF - Fish [1]	0.6 – 15
Partition coefficient n-octanol/water	2.77 – 3.15

Ethylbenzene (100-41-4)	
BCF - Fish [1]	(15 dimensionless)
Partition coefficient n-octanol/water	3.6 (at 20 °C (at pH 7.84))

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone	: Not classified.
Fluorinated greenhouse gases	: No
Other information	: No other effects known.

SECTION 13 Disposal considerations

Product/Packaging disposal recommendations	: Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. Container under pressure. Do not drill or burn even after use.
Additional information	: Flammable vapours may accumulate in the container.

SECTION 14 Transport information

In accordance with DOT / TDG

14.1. UN Number	
UN-No. (DOT)	: UN1950
UN-No. (TDG)	: UN1950

2K FillClean Series G

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

14.2. UN Proper Shipping Name

Proper Shipping Name (DOT) : Aerosols
Proper Shipping Name (TDG) : AEROSOLS

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 2.1
Hazard labels (DOT) : 2.1



TDG

Transport hazard class(es) (TDG) : 2.1
Hazard labels (TDG) : 2.1



14.4. Packing group

Packing group (DOT) : Not applicable
Packing group (TDG) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.

DOT

UN-No. (DOT) : UN1950
DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.
DOT Packaging Exceptions (49 CFR 173.xxx) : 306
DOT Packaging Non Bulk (49 CFR 173.xxx) : None
DOT Packaging Bulk (49 CFR 173.xxx) : None
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg
DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other : 25 - Protected from sources of heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

TDG

UN-No. (TDG) : UN1950

2K FillClean Series G

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

TDG Special Provisions	: 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment), 107 - (1) These Regulations, except for Parts 1 and 2, do not apply to the offering for transport, handling or transport of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL. (2) Subsection (1) does not apply to self-defence spray.
Explosive Limit and Limited Quantity Index	: 1 L
Excepted quantities (TDG)	: E0
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 75 L
Emergency Response Guide (ERG) Number	: 126

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

15.2. International regulations

No additional information available

15.3. State regulations



WARNING:

This product can expose you to Ethylbenzene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16 Other Information

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Revision date	: 2025-10-22
Issue date	: 2017-05-30
Other information	: None.
Prepared by	: Nexreg Compliance Inc. www.Nexreg.com



Indication of changes:

SDS update .

SDS HazCom 2024 - WHMIS 2022 (Nexreg) 2025

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.