Safety data sheet
according to UK REACH

Printing date 04.05.2026 Revision: 04.05.2026

*

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name: Lackstift 1K-Korrosionsschutzgrund rotbraun**

· **(Article number) product ID.:** REZ20
· **1.2 Relevant identified uses of the substance or mixture and uses advised against**
· **Sector of Use**
SU21 Consumer uses: Private households / general public / consumers
SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· **Application of the substance / the mixture:** painting
· **Uses advised against** No further relevant information available.

· **1.3 Details of the supplier of the safety data sheet**
· **Manufacturer/Supplier:**
Peter Kwasny GmbH
Heilbronner Str. 96
D-74831 Gundelsheim
Tel.: 0049-(0)6269-95-20
E-mail: labor@kwasny.de

· **Further information obtainable from:** Product safety department

· **1.4 Emergency telephone number:** Tel.:+49 6269 95 20 (MO-FR 7.15-15.15)
· **national:**
National Poisons Information Service, Birmingham
Tel.: 844 892 0111
· **K-Nr.** 0001

*

SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**
· **Classification according to Regulation (EC) No 1272/2008**

GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.
STOT SE 3 H336 May cause drowsiness or dizziness.

(Contd. on page 2)

Safety data sheet
according to UK REACH

Printing date 04.05.2026 Revision: 04.05.2026

Trade name: Lackstift 1K-Korrosionsschutzgrund rotbraun

(Contd. of page 1)

· **2.2 Label elements**
· **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
· **Hazard pictograms**

GHS02 GHS07 GHS09

· **Signal word** Danger

· **Hazard-determining components of labelling:**
propan-2-ol
acetone
· **Hazard statements**
H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.
· **Precautionary statements**

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P337+P313	If eye irritation persists: Get medical advice/attention.
P391	Collect spillage.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**
According to 1272/2008/EC I, 1.5.2, no identification on packing drums < 125ml with:
H225, H319, H411, P210, P273, P280, P303+361+353, P305+351+338, P337+313, P391

EUH208 Contains formaldehyde. May produce an allergic reaction.
· **Information concerning particular hazards for human and environment:** 1272/2008/EC, II, 3.2
· **2.3 Other hazards**
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Not applicable

(Contd. on page 3)

Safety data sheet
according to UK REACH

Printing date 04.05.2026 Revision: 04.05.2026

Trade name: Lackstift 1K-Korrosionsschutzgrund rotbraun

(Contd. of page 2)

*
SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**
· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25-xxxx	propan-2-ol Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	50-100%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-xxxx	acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	10-<25%
CAS: 1314-13-2 EINECS: 215-222-5 Reg.nr.: 01-2119463881-32-xxxx	zinc oxide Aquatic Acute 1, H400 (M=1); Aquatic Chronic 1, H410 (M=1)	2.5-<5%
CAS: 7664-38-2 EINECS: 231-633-2 Reg.nr.: 01-2119485924-24-xxxx	phosphoric acid Skin Corr. 1B, H314 Specific concentration limits: Skin Corr. 1B; H314: C ≥ 25 % Skin Irrit. 2; H315: 10 % ≤ C < 25 % Eye Irrit. 2; H319: 10 % ≤ C < 25 %	1-<2.5%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-xxxx	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	<1%
CAS: 108-95-2 EINECS: 203-632-7 Reg.nr.: 01-2119471329-32-xxxx	phenol Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; Muta. 2, H341; STOT RE 2, H373; Skin Corr. 1B, H314 Specific concentration limits: Skin Corr. 1B; H314: C ≥ 3 % Skin Irrit. 2; H315: 1 % ≤ C < 3 % Eye Irrit. 2; H319: 1 % ≤ C < 3 %	<1%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**
· **General information:** Immediately remove any clothing soiled by the product.
· **After inhalation:** Supply fresh air; consult doctor in case of complaints.
· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
· **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
· **After swallowing:** If symptoms persist consult doctor.
· **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
· **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

(Contd. on page 4)

Safety data sheet
according to UK REACH

Printing date 04.05.2026 Revision: 04.05.2026

Trade name: Lackstift 1K-Korrosionsschutzgrund rotbraun

(Contd. of page 3)

SECTION 5: Firefighting measures

· **5.1 Extinguishing media -**
· **Suitable extinguishing agents:**
CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
· **For safety reasons unsuitable extinguishing agents:** Water with full jet
· **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
· **5.3 Advice for firefighters**
· **Protective equipment:** Mouth respiratory protective device.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
· **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Prevent seepage into sewage system, workpits and cellars.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
· **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
· **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

*
SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**
Prevent formation of aerosols.
Take note of emission threshold.
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
· **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

· **7.2 Conditions for safe storage, including any incompatibilities**
· **Storage:**
· **Requirements to be met by storerooms and receptacles:** Store in a cool location.
· **Information about storage in one common storage facility:** Not required
· **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
· **7.3 Specific end use(s)** No further relevant information available.

(Contd. on page 5)

Safety data sheet
according to UK REACH

Printing date 04.05.2026 Revision: 04.05.2026

Trade name: Lackstift 1K-Korrosionsschutzgrund rotbraun

(Contd. of page 4)

*

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**	
67-63-0 propan-2-ol	
WEL	Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm
67-64-1 acetone	
WEL	Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm
7664-38-2 phosphoric acid	
WEL	Short-term value: 2 mg/m³ Long-term value: 1 mg/m³
108-65-6 2-methoxy-1-methylethyl acetate	
WEL	Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk
108-95-2 phenol	
WEL	Short-term value: 16 mg/m³, 4 ppm Long-term value: 7.8 mg/m³, 2 ppm Sk

· **Regulatory information** WEL: EH40/2020
· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**
· **Appropriate engineering controls** No further data; see section 7.
· **Individual protection measures, such as personal protective equipment**
· **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.
· **Respiratory protection:**

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

· **Hand protection**
Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
· **Penetration time of glove material**
Gloves must be changed after every contamination.
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

Safety data sheet
according to UK REACH

Printing date 04.05.2026 Revision: 04.05.2026

Trade name: Lackstift 1K-Korrosionsschutzgrund rotbraun

(Contd. of page 5)

· **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**
butyl rubber, 0,7mm
· **Eye/face protection**

Tightly sealed goggles

*

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**	
· **General Information**	
· **Physical state**	Liquid
· **Colour:**	According to product specification
· **Odour:**	Characteristic
· **Odour threshold:**	Not determined
· **Melting point/freezing point:**	Undetermined
· **Boiling point or initial boiling point and boiling range**	55.8-56.6 °C (67-64-1 acetone)
· **Flammability**	Highly flammable.
· **Lower and upper explosion limit**	
· **Lower:**	2 Vol % (67-63-0 propan-2-ol)
· **Upper:**	13 Vol % (67-64-1 acetone)
· **Flash point:**	-18 °C
· **Auto-ignition temperature:**	425 °C (67-63-0 propan-2-ol)
· **Decomposition temperature:**	Not determined
· **pH**	Mixture is non-polar/aprotic.
· **Viscosity:**	
· **Kinematic viscosity**	Not determined
· **Dynamic:**	Not determined
· **Solubility**	
· **water:**	Not miscible or difficult to mix.
· **Partition coefficient n-octanol/water (log value)**	Not determined
· **Vapour pressure at 20 °C:**	233 hPa (67-64-1 acetone)
· **Density and/or relative density**	
· **Relative density**	1.091 g/ml
· **Vapour density**	Not determined

· **9.2 Other information**	
· **Appearance:**	
· **Form:**	Fluid
· **Important information on protection of health and environment, and on safety.**	
· **Ignition temperature:**	Product is not selfigniting.
· **Explosive properties:**	In use, may form flammable/explosive vapour-air mixture.
· **Solvent content:**	
· **Organic solvents:**	71.2 %
· **VOC (EU)**	(<840g/l) 71.18 %
· **Solids content:**	28.8 %

(Contd. on page 7)

Safety data sheet
according to UK REACH

Printing date 04.05.2026 Revision: 04.05.2026

Trade name: Lackstift 1K-Korrosionsschutzgrund rotbraun

(Contd. of page 6)

· **Change in condition**	
· **Evaporation rate**	Not determined

· **Information with regard to physical hazard classes**	
· **Explosives**	Void
· **Flammable gases**	Void
· **Aerosols**	Void
· **Oxidising gases**	Void
· **Gases under pressure**	Void
· **Flammable liquids**	Highly flammable liquid and vapour.
· **Flammable solids**	Void
· **Self-reactive substances and mixtures**	Void
· **Pyrophoric liquids**	Void
· **Pyrophoric solids**	Void
· **Self-heating substances and mixtures**	Void
· **Substances and mixtures, which emit flammable gases in contact with water**	Void
· **Oxidising liquids**	Void
· **Oxidising solids**	Void
· **Organic peroxides**	Void
· **Corrosive to metals**	Void
· **Desensitised explosives**	Void

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.
· **10.2 Chemical stability**
· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
· **10.3 Possibility of hazardous reactions** Reacts with acids, alkalis and oxidising agents.
· **10.4 Conditions to avoid** No further relevant information available.
· **10.5 Incompatible materials:** No further relevant information available.
· **10.6 Hazardous decomposition products:** Possible in traces.

*
SECTION 11: Toxicological information

· **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
· **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

ATE (Acute Toxicity Estimates)		
Oral	LD50	223,854 mg/kg (rat)
Dermal	LD50	600,240 mg/kg (rabbit)
Inhalative	LC50/4 h	2,118 mg/l

67-63-0 propan-2-ol		
Oral	LD50	5,045 mg/kg (rat)
Dermal	LD50	12,800 mg/kg (rabbit)
Inhalative	LC50/4 h	30 mg/l (rat)

67-64-1 acetone		
Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rabbit)

(Contd. on page 8)

Safety data sheet
according to UK REACH

Printing date 04.05.2026 Revision: 04.05.2026

Trade name: Lackstift 1K-Korrosionsschutzgrund rotbraun

(Contd. of page 7)

1314-13-2 zinc oxide		
Oral	LD50	7,950 mg/kg (mouse)
108-65-6 2-methoxy-1-methylethyl acetate		
Oral	LD50	8,532 mg/kg (rat)
Inhalative	LC50/4 h	35.7 mg/l (rat)
108-95-2 phenol		
Oral	LD50	317 mg/kg (rat)
Dermal	LD50	850 mg/kg (rabbit)
Inhalative	LC50/4 h	3 mg/l (ATE)

· **Primary irritant effect:**
· **Serious eye damage/irritation** Causes serious eye irritation.
· **STOT-single exposure** May cause drowsiness or dizziness.
· **11.2 Information on other hazards**

· **Endocrine disrupting properties**
None of the ingredients is listed.

*
SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**	
1314-13-2 zinc oxide	
LC50/48h	2,246 mg/l (Pimephales promelas)
EC50	2.2 mg/l (daphnia)

· **12.2 Persistence and degradability** No further relevant information available.
· **12.3 Bioaccumulative potential** No further relevant information available.
· **12.4 Mobility in soil** No further relevant information available.
· **12.5 Results of PBT and vPvB assessment**
· **PBT:** Not applicable
· **vPvB:** Ikke relevant.
· **12.6 Endocrine disrupting properties**
The product does not contain substances with endocrine disrupting properties.
· **12.7 Other adverse effects**
· **Remark:** Toxic for fish
· **Additional ecological information:**
· **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms

*
SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**
· **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 9)

Safety data sheet
according to UK REACH

Printing date 04.05.2026 Revision: 04.05.2026

Trade name: Lackstift 1K-Korrosionsschutzgrund rotbraun

(Contd. of page 8)

· **Uncleaned packaging:**
· **Recommendation:** Disposal must be made according to official regulations.

*
SECTION 14: Transport information

· **14.1 UN number or ID number**	
· **ADR, IMDG, IATA**	UN1263
· **14.2 UN proper shipping name**	
· **ADR**	1263 PAINT, special provision 640D, ENVIRONMENTALLY HAZARDOUS
· **IMDG**	PAINT, MARINE POLLUTANT
· **IATA**	PAINT
· **14.3 Transport hazard class(es)**	
· **ADR**	
· **Class**	3 (F1) Flammable liquids.
· **Label**	3
· **IMDG**	
· **Class**	3 Flammable liquids.
· **Label**	3
· **IATA**	
· **Class**	3 Flammable liquids.
· **Label**	3
· **14.4 Packing group**	
· **ADR, IMDG, IATA**	II not classified
· **14.5 Environmental hazards:**	
· **Marine pollutant:**	Yes Symbol (fish and tree)
· **Special marking (ADR):**	Symbol (fish and tree)
· **14.6 Special precautions for user**	Warning: Flammable liquids.
· **Hazard identification number (Kemler code):**	33 not classified
· **EMS Number:**	F-E,S-E
· **Stowage Category**	B

(Contd. on page 10)

Safety data sheet
according to UK REACH

Printing date 04.05.2026 Revision: 04.05.2026

Trade name: Lackstift 1K-Korrosionsschutzgrund rotbraun

(Contd. of page 9)

· **14.7 Maritime transport in bulk according to IMO instruments**	Not applicable
· **Transport/Additional information:**	
· **ADR**	
· **Limited quantities (LQ)**	5L
· **Excepted quantities (EQ)**	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· **Transport category**	2
· **Tunnel restriction code**	D/E
· **IMDG**	
· **Limited quantities (LQ)**	5L
· **Excepted quantities (EQ)**	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· **UN "Model Regulation":**	UN 1263 PAINT, 3, II, ENVIRONMENTALLY HAZARDOUS

*
SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
· **Poisons Act**

· **Regulated explosives precursors**

7664-38-2	phosphoric acid	30%

· **Regulated poisons**

108-95-2	phenol	Listed

· **Reportable explosives precursors**

67-64-1	acetone	Listed

· **Reportable poisons**

108-95-2	phenol	Listed
50-00-0	formaldehyde	5%

· **Directive 2012/18/EU**
· **Named dangerous substances - ANNEX I** None of the ingredients is listed.
· **Seveso category**
E2 Hazardous to the Aquatic Environment
P5c FLAMMABLE LIQUIDS
· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

· **National regulations:**

· **Technical instructions (air):**

Class	Share in %
I	<1
NK	50-100

· **Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.

(Contd. on page 11)

Safety data sheet
according to UK REACH

Printing date 04.05.2026 Revision: 04.05.2026

Trade name: Lackstift 1K-Korrosionsschutzgrund rotbraun

(Contd. of page 10)

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

*
SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.
The safety data sheet may only be passed on to third parties for the manufacturer's brands.

· **Relevant phrases**
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H301 Toxic if swallowed.
H311 Toxic in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H336 May cause drowsiness or dizziness.
H341 Suspected of causing genetic defects.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.

· **Department issuing SDS:** Product safety department
· **Abbreviations and acronyms:**
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organisation
ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
ATE: Acute toxicity estimate values
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 3: Acute toxicity – Category 3
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Muta. 2: Germ cell mutagenicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
· *** Data compared to the previous version altered.**