Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Issue date: 5/30/2017

Revision date: 3/8/2022 update 01/13/2023

Supersedes: 7/31/2019

Version: 2.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture Product name : 1K Gun Cleaner : 3680095 / REZ247 Product code

1.2. Recommended use and restrictions on use

Recommended use : Automotive refinish

1.3. Supplier

Manufacturer

Peter Kwasny GmbH 96 Heibronner Str. Gundelsheim, 74831 - Germany

T 49(0) 6269-95-20

Distributor

Peter Kwasny Inc. 62-64 Enter Lane Islandia, NY 11749

T 1-844-726-6330 (toll free North America)

Distributor

Peter Kwasny Spraypaint Canada Inc 40 University Avenue, Suite 904

Toronto, ON M5J 1T1

1.4. Emergency telephone number

: 352-323-3500 (24h / 7 days a week) **Emergency number**

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS classification

Flam. Aerosol 1 Press. Gas (Liq.) Eye Irrit. 2A Repr. 2 STOT SE 3 Simple Asphy

2.2. GHS Label elements, including precautionary statements

GHS labelling

Hazard pictograms (GHS)









Signal word (GHS) : Danger

Hazard statements (GHS) Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation.

03/08/2022 EN (English) Page 1

Precautionary statements (GHS)

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

May cause drowsiness or dizziness.

Suspected of damaging fertility or the unborn child. May displace oxygen and cause rapid suffocation

: Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Avoid breathing dust/fume/gas/mist/vapours/spray. Wash hands, forearms and face thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection. If inhaled: Remove person to fresh air and keep comfortable for breathing.

Call a poison center or doctor if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

If exposed or concerned: Get medical advice/attention.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : Contact with the liquefied gas may cause frostbite.

2.4. Unknown acute toxicity

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
Dimethyl ether	Dimethyl ether Methane, oxybis- / Methyl ether / Wood ether / Methoxymethane / Methane, 1,1'-oxybis- / DIMETHYL ETHER / Oxybismethane / Dimethyl oxide / Butylene	CAS-No.: 115-10-6	30 – 60
Acetone	Acetone Dimethyl ketone / 2-Propanone / ACETONE / Propan- 2-one / Propanone	CAS-No.: 67-64-1	15 – 40
n-Butyl acetate	n-Butyl acetate 1-Butyl acetate / Butyl acetate, n- / Normal butyl acetate / Butyl acetate / BUTYL ACETATE / Acetic acid, n-butyl ester / Acetic acid, butyl ester / Butyl ethanoate / Acetato de n-butilo	CAS-No.: 123-86-4	10 – 30

03/08/2022 EN (English) 2/14

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Name	Chemical name / Synonyms	Product identifier	%
Xylenes (o-, m-, p- isomers)	Xylenes (o-, m-, p- isomers) Benzene, dimethyl- / Dimethylbenzene (mixed isomers) / Xylene / Xylene (all isomers) / Xylene (mixed isomers) / Xylene (o-, m-, p- isomers) / Xylenes / Xylenes (mixed isomers) / Dimethylbenzene / Xylol / Benzene, dimethyl-, mixed isomers / XYLENE / Dimethylbenzenes / Xylene isomers mixture / Dimethylbenzene (2-, 3-, 4-isomers) / Dimethylbenzene (mixed 2-, 3-, 4-isomers) / C8 Disubstituted benzenes / Xylene, mixed isomers / Xylenes (meta-, ortho-, para-) / Xylene (mixture), including m-xylene, o-xylene, p-xylene	CAS-No.: 1330-20-7	3 – 7
Propylene glycol monomethyl ether acetate	Propylene glycol monomethyl ether acetate Acetate, 1-methoxy-2-propyl / Acetic acid, 2-methoxy- 1-methylethyl ester / 2-Methoxy-1-methylethyl acetate / 1-Methoxy-2-acetoxypropane / 1-Methoxy-2-propanol acetate / 1-Methoxypropyl-2-acetate / 2-Propanol, 1- methoxy-, acetate / Propylene glycol methyl ether acetate / 1-Methoxypropylacetate / 1-Methoxy-2-propyl acetate / Methoxyisopropyl acetate / 1-Methoxypropyl acetate / 2-Propanol, 1-methoxy-, 2-acetate / 2-Acetic acid methoxy-1-methylethyl ester / METHOXYISOPROPYL ACETATE / Propylene glycol methyl ether acetate, .alphaisomer / PGMEA / 1- Methoxypropan-2-yl acetate / Acetic acid, 2- methoxyisopropyl ester / 1-Methoxypropan-2-ol acetate / Propylene glycol methyl ether acetate (all isomers)	CAS-No.: 108-65-6	1 – 5

^{*}Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4: First-aid measures

First-aid measures after ingestion

4.1. Description of first aid measures	
First-aid measures after inhalation	: If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. Give oxygen or artificial respiration if necessary.
First-aid measures after skin contact	: If skin irritation occurs: Wash skin with plenty of water. Obtain medical attention if irritation persists. If frostbite occurs thaw frosted parts with lukewarm water. Do not rub affected area. Do not use hot water.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If frostbite occurs thaw frosted parts with lukewarm water. Do not rub affected area. Do not use hot water.

4.2. Most important symptoms and effects (acute and delayed)		
Symptoms/effects after inhalation :	May cause irritation to the respiratory tract. May cause drowsiness or dizziness. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Symptoms of oxygen deficiency include respiratory difficulty, headache, dizziness, nausea, unconsciousness or death.	
Symptoms/effects after skin contact :	May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause frostbite on contact with the liquefied gas.	

person. Get medical advice/attention if you feel unwell.

: Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious

03/08/2022 3/14 EN (English)

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Symptoms/effects after eye contact

: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause frostbite on contact with the liquefied gas.

Symptoms/effects after ingestion

: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and

diarrhea.

Chronic symptoms

: Suspected of damaging fertility or the unborn child.

4.3. Immediate medical attention and special treatment, if necessary

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media Unsuitable extinguishing media : Water spray. Dry chemical powder. Carbon dioxide (CO2).

: Do not use water jet.

5.2. Specific hazards arising from the chemical

Fire hazard

: Extremely flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon. irritating vapours. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours.

Explosion hazard

 Vapours may form explosive mixture with air. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. Ruptured cylinders may rocket

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions

: Move containers away from the fire area if this can be done without risk. DO NOT fight fire when fire reaches explosives. Evacuate area.

Protection during firefighting

: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Use water spray to keep fire-exposed containers cool. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate every possible source of ignition. Use only non-sparking tools. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment

: Stop leak if safe to do so. Remove all sources of ignition. Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.

Methods for cleaning up

: Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

03/08/2022 EN (English) 4/14

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

: Pressurized container: Do not pierce or burn, even after use. Hazardous waste due to potential risk of explosion.

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Take precautionary measures against static discharge. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Do not spray on an open flame or other ignition source. Avoid contact with skin, eyes and clothing. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. When using do not eat, drink or smoke. Handle and open container with care. Use only outdoors or in a well-ventilated area.

Hygiene measures

: Take off immediately all contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace. Wash hands, forearms and face thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures Storage conditions

- : Proper grounding procedures to avoid static electricity should be followed.
- : Keep out of the reach of children. Store locked up. Keep in fireproof place. Store away from direct sunlight or other heat sources. Keep away from clothing and other combustible materials. Do not expose to temperatures exceeding 50 °C/ 122 °F. Protect containers from physical damage. Keep away from incompatible materials. . Store in a dry, cool and well-ventilated place.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

1K Gun Cleaner

No additional information available

Dimethyl ether (115-10-6)

No additional information available

Acetone (67-64-1)

OSHA PEL TWA [2]

USA - ACGIH - Occupational Exposure Limits

·		
ACGIH OEL TWA [ppm]	250 ppm	
ACGIH OEL STEL [ppm]	500 ppm	
ACGIH chemical category	Not Classifiable as a Human Carcinogen	
USA - ACGIH - Biological Exposure Indices		
BEI	25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift (nonspecific)	
USA - OSHA - Occupational Exposure Limits		
OSHA PEL TWA [1]	2400 mg/m³	

03/08/2022 EN (English) 5/14

1000 ppm

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Acetone (67-64-1)			
USA - IDLH - Occupational Exposure Limits			
IDLH [ppm]	2500 ppm (10% LEL)		
USA - NIOSH - Occupational Exposure Limits	USA - NIOSH - Occupational Exposure Limits		
NIOSH REL TWA	590 mg/m³		
NIOSH REL TWA [ppm]	250 ppm		
n-Butyl acetate (123-86-4)			
USA - ACGIH - Occupational Exposure Limits			
Local name	n-Butyl acetate		
ACGIH OEL TWA [ppm]	50 ppm (Butyl acetates, all isomers)		
ACGIH OEL STEL [ppm]	150 ppm (Butyl acetates, all isomers)		
Remark (ACGIH)	TLV® Basis: Eye & URT irr		
Regulatory reference	ACGIH 2020		
USA - OSHA - Occupational Exposure Limits			
Local name	n-Butyl-acetate		
OSHA PEL TWA [1]	710 mg/m³		
OSHA PEL TWA [2]	150 ppm		
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1		
USA - IDLH - Occupational Exposure Limits			
IDLH [ppm]	1700 ppm (10% LEL)		
USA - NIOSH - Occupational Exposure Limits			
NIOSH REL TWA	710 mg/m³		
NIOSH REL TWA [ppm]	150 ppm		
NIOSH REL STEL	950 mg/m³		
NIOSH REL STEL [ppm]	200 ppm		
Xylenes (o-, m-, p- isomers) (1330-20-7)			
USA - ACGIH - Occupational Exposure Limits			
ACGIH chemical category	Not Classifiable as a Human Carcinogen		
USA - ACGIH - Biological Exposure Indices			
BEI	1.5 g/g creatinine Parameter: Methylhippuric acids - Medium: urine - Sampling time: end of shift		
USA - OSHA - Occupational Exposure Limits			
Local name	Xylenes (o-, m-, p-isomers)		
OSHA PEL TWA [1]	435 mg/m³		
OSHA PEL TWA [2]	100 ppm		
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1		
Propylene glycol monomethyl ether acetate (108-65-6)			
No additional information available			

8.2. Appropriate engineering controls

03/08/2022 EN (English) 6/14

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Appropriate engineering controls : Ensure good ventilation of the work station. Provide readily accessible eye wash stations and

safety showers.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear suitable gloves

Eye protection:

Wear eye/face protection

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid Appearance : Aerosol. Colour Clear Odour Characteristic Odour threshold No data available : No data available pН Melting point · No data available Freezing point : No data available Boiling point : No data available Flash point : < -18 °C (-0.4 °F) Relative evaporation rate (butylacetate=1) : No data available

Flammability (solid, gas) : Extremely flammable aerosol.

Vapour pressure : No data available Relative vapour density at 20 °C : No data available Relative density No data available Density 0.75 g/cm³ Solubility : No data available Partition coefficient n-octanol/water : No data available : No data available Auto-ignition temperature Decomposition temperature : No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available **Explosive limits** : No data available : No data available Explosive properties : No data available Oxidising properties

9.2. Other information

No additional information available

03/08/2022 EN (English) 7/14

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions. Extremely flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat. Sparks. Open flame. Direct sunlight. Overheating. Incompatible materials.

10.5. Incompatible materials

Oxidizing materials. Acids. Alkalis.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified.
Acute toxicity (dermal) : Not classified.
Acute toxicity (inhalation) : Not classified.

Dimethyl ether (115-10-6)		
LC50 inhalation rat	164000 ppm/4h	
ATE CA (Gases (except aerosol dispensers and lighters))	164000 ppmv/4h	
Acetone (67-64-1)		
LD50 oral rat	5800 mg/kg bodyweight Animal: rat, Animal sex: female	
LD50 dermal rabbit	> 15700 mg/kg	
LC50 inhalation rat	76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4	
ATE CA (oral)	5800 mg/kg bodyweight	
n-Butyl acetate (123-86-4)		
LD50 oral rat	10768 mg/kg	
LD50 dermal rabbit	> 17600 mg/kg	
LC50 inhalation rat	0.74 mg/l/4h	
ATE CA (oral)	10768 mg/kg bodyweight	
Xylenes (o-, m-, p- isomers) (1330-20-7)		
LD50 oral rat	3500 mg/kg	

03/08/2022 EN (English) 8/14

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Xylenes (o-, m-, p- isomers) (1330-20-7)		
LC50 inhalation rat	29.08 mg/l/4h	
ATE CA (oral)	3500 mg/kg bodyweight	
ATE CA (Dermal)	1700 mg/kg bodyweight	
ATE CA (Gases (except aerosol dispensers and lighters))	4500 ppmv/4h	
ATE CA (vapours)	11 mg/l/4h	
ATE CA (dust,mist)	1.5 mg/l/4h	
Propylene glycol monomethyl ether acetate (108-65-6)	
LD50 oral rat	8532 mg/kg	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)	
LD50 dermal rabbit	> 5 g/kg	
LC50 inhalation rat	19.596 mg/l 4 h	
ATE CA (oral)	8532 mg/kg bodyweight	
ATE CA (Gases (except aerosol dispensers and lighters))	4500 ppmv/4h	
ATE CA (vapours)	19.596 mg/l/4h	
ATE CA (dust,mist)	1.5 mg/l/4h	
Skin corrosion/irritation :	Not classified.	
Serious eye damage/irritation :	Causes serious eye irritation.	
Respiratory or skin sensitisation :	Not classified.	
Germ cell mutagenicity :	Not classified.	
Carcinogenicity :	Not classified.	
Xylenes (o-, m-, p- isomers) (1330-20-7)		
IARC group	3 - Not classifiable	
Reproductive toxicity :	Suspected of damaging fertility or the unborn child.	
Acetone (67-64-1)		
LOAEL (animal/female, F0/P)	11298 mg/kg bodyweight Animal: mouse, Animal sex: female	
NOAEL (animal/male, F0/P)	900 mg/kg bodyweight Animal: rat, Animal sex: male, Remarks on results: other:Generation not specified (migrated information)	
STOT-single exposure :	May cause drowsiness or dizziness.	
Acetone (67-64-1)		
STOT-single exposure	May cause drowsiness or dizziness.	
n-Butyl acetate (123-86-4)		
STOT-single exposure	May cause drowsiness or dizziness.	
Xylenes (o-, m-, p- isomers) (1330-20-7)		
STOT-single exposure	May cause drowsiness or dizziness.	
STOT-repeated exposure :	Not classified.	

03/08/2022 EN (English) 9/14

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Xylenes (o-, m-, p- isomers) (1330-20-7)			
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)		
Propylene glycol monomethyl ether acetate (108-65-6)		
NOAEL (oral, rat, 90 days)	≥ 1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)		
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)		
Aspiration hazard :	Not classified.		
1K Gun Cleaner	1K Gun Cleaner		
Vaporizer	Aerosol		
Vaporizer Symptoms/effects after inhalation :	Aerosol May cause irritation to the respiratory tract. May cause drowsiness or dizziness. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Symptoms of oxygen deficiency include respiratory difficulty, headache, dizziness, nausea, unconsciousness or death.		
·	May cause irritation to the respiratory tract. May cause drowsiness or dizziness. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Symptoms of oxygen deficiency include respiratory difficulty, headache, dizziness, nausea,		
Symptoms/effects after inhalation : Symptoms/effects after skin contact :	May cause irritation to the respiratory tract. May cause drowsiness or dizziness. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Symptoms of oxygen deficiency include respiratory difficulty, headache, dizziness, nausea, unconsciousness or death. May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the		
Symptoms/effects after inhalation : Symptoms/effects after skin contact :	May cause irritation to the respiratory tract. May cause drowsiness or dizziness. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Symptoms of oxygen deficiency include respiratory difficulty, headache, dizziness, nausea, unconsciousness or death. May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause frostbite on contact with the liquefied gas. Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause frostbite on		

SECTION 12: Ecological information

12.1.	Toxicity	

Ecology - general :	May cause long-term adverse effects in the aquatic environment.	
Dimethyl ether (115-10-6)		
LC50 - Fish [1]	> 4.1 g/l (Exposure time: 96 h - Species: Poecilia reticulata [semi-static])	
EC50 - Crustacea [1]	> 4.4 g/l Test organisms (species): Daphnia magna	
Acetone (67-64-1)		
LC50 - Fish [1]	4.74 – 6.33 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)	
EC50 - Crustacea [1]	10294 – 17704 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])	
LC50 - Fish [2]	6210 – 8120 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])	
EC50 - Crustacea [2]	12600 – 12700 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	
n-Butyl acetate (123-86-4)		
LC50 - Fish [1]	100 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])	
LC50 - Fish [2]	17 – 19 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])	

03/08/2022 EN (English) 10/14

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Xylenes (o-, m-, p- isomers) (1330-20-7)		
LC50 - Fish [1]	13.4 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])	
EC50 - Crustacea [1]	3.82 mg/l (Exposure time: 48 h - Species: water flea)	
LC50 - Fish [2]	2.661 – 4.093 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])	
EC50 - Crustacea [2]	0.6 mg/l (Exposure time: 48 h - Species: Gammarus lacustris)	
LOEC (chronic)	3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'	
Propylene glycol monomethyl ether acetate (108-65-6)		
LC50 - Fish [1]	161 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])	
EC50 - Crustacea [1]	> 500 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
NOEC (chronic)	≥ 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	
NOEC chronic fish	47.5 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'	

12.2. Persistence and degradability

1K Gun Cleaner	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

1K Gun Cleaner		
Bioaccumulative potential	Not established.	
Dimethyl ether (115-10-6)		
Partition coefficient n-octanol/water	-0.18	
Acetone (67-64-1)		
BCF - Fish [1]	0.69	
Partition coefficient n-octanol/water	-0.24	
n-Butyl acetate (123-86-4)		
Partition coefficient n-octanol/water	1.81 (at 23 °C)	
Xylenes (o-, m-, p- isomers) (1330-20-7)		
BCF - Fish [1]	0.6 – 15	
Partition coefficient n-octanol/water	2.77 – 3.15	
Propylene glycol monomethyl ether acetate (108-65-6)		
Partition coefficient n-octanol/water	0.43	

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : No other effects known.

03/08/2022 EN (English) 11/14

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with

local, regional, national and/or international regulation. Container under pressure. Do not drill or

burn even after use.

Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

In accordance with DOT / TDG

14.1. UN number

DOT NA No : UN1950 UN-No. (TDG) : UN1950

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Aerosols

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 2.1 Hazard labels (DOT) : 2.1



TDG

Transport hazard class(es) (TDG) : 2.1 Hazard labels (TDG) : 2.1



14.4. Packing group

Packing group (DOT) : Not applicable Packing group (TDG) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.

DOT

UN-No.(DOT) : UN1950

DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

DOT Packaging Exceptions (49 CFR 173.xxx) : 306
DOT Packaging Non Bulk (49 CFR 173.xxx) : None
DOT Packaging Bulk (49 CFR 173.xxx) : None

03/08/2022 EN (English) 12/14

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

DOT Quantity Limitations Passenger aircraft/rail (49 : 75 kg

CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

DOT Vessel Stowage Other : 25 - Protected from sources of heat,87 - Stow "separated from" Class 1 (explosives) except

Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

TDG

UN-No. (TDG) : UN1950

TDG Special Provisions : 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General

Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment),107 - (1) These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage, if the aerosols or gas cartridges have a

capacity less than or equal to 50 mL.

(2) Subsection (1) does not apply to self-defence spray.

Explosive Limit and Limited Quantity Index : 1 L
Excepted quantities (TDG) : E0
Passenger Carrying Road Vehicle or Passenger : 75 L

Carrying Railway Vehicle Index

Emergency Response Guide (ERG) Number : 126

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

15.2. International regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

 $According \ to \ the \ Hazard \ Communication \ Standard \ (CFR29\ 1910.1200) \ HazCom\ 2012 \ and \ the \ Hazardous \ Products \ Regulations \ (HPR) \ WHMIS\ 2015 \ According to \ the \ Hazardous \ Products \ Regulations \ (HPR) \ WHMIS\ 2015 \ According to \ the \ Hazardous \ Products \ Regulations \ (HPR) \ WHMIS\ 2015 \ According to \ the \ Hazardous \ Products \ Regulations \ (HPR) \ WHMIS\ 2015 \ According to \ the \ Hazardous \ Products \ Regulations \ (HPR) \ WHMIS\ 2015 \ According to \ the \ Hazardous \ Products \ Regulations \ (HPR) \ WHMIS\ 2015 \ According to \ the \ Hazardous \ Products \ Regulations \ (HPR) \ WHMIS\ 2015 \ According to \ the \ Hazardous \ Products \ Regulations \ (HPR) \ WHMIS\ 2015 \ According to \ the \ Hazardous \ Products \ Regulations \ (HPR) \ WHMIS\ 2015 \ According to \ the \ Hazardous \ Products \ Regulations \ (HPR) \ WHMIS\ 2015 \ According to \ the \ Hazardous \ Products \ Regulations \ (HPR) \ WHMIS\ 2015 \ According to \ the \ Hazardous \ Products \ Regulations \ (HPR) \ WHMIS\ 2015 \ According to \ The \$

Revision date : 03/08/2022 Other information : None.

03/08/2022 EN (English) 13/14

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Prepared by

: Nexreg Compliance Inc. www.Nexreg.com



Full text of H-statements	
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Aerosol 1	Flammable aerosols, Category 1
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
Repr. 2	Reproductive toxicity, Category 2
Simple Asphy	Simple Asphyxiant
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis

Indication of changes:

SDS update . GHS classification.

SDS HazCom 2012 - WHMIS 2015 (Nexreg) 2021

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

03/08/2022 EN (English) 14/14