

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.11.2021

Revision: 23.11.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name:** Aerosol KH Klarlack

· (Article number) product ID.: REZ24

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

· **Sector of Use** SU21 Consumer uses: Private households / general public / consumers

· **Application of the substance / the mixture:** painting

· **Uses advised against** No further relevant information available.

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Peter Kwasny GmbH
Heilbronner Str. 96
D-74831 Gundelsheim

Tel.: 0049-(0)6269-95-20

E-mail: labor@kwasny.de

· **Further information obtainable from:** Product safety department

· **1.4 Emergency telephone number:** Tel.: +49 6269 95 20

· **national:**

National Poisons Information Service, Birmingham

Tel.: 844 892 0111

· **K-Nr.** 0001

SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**



flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS02 GHS07

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.11.2021

Revision: 23.11.2021

Trade name: Aerosol KH Klarlack

(Contd. of page 1)

· **Signal word** *Danger*· **Hazard-determining components of labelling:**

butanone
xylene, mixture of isomers
Naphtha (petroleum), hydrotreated light
n-butyl acetate

· **Hazard statements**

H222-H229 *Extremely flammable aerosol. Pressurised container: May burst if heated.*
H319 *Causes serious eye irritation.*
H336 *May cause drowsiness or dizziness.*
H412 *Harmful to aquatic life with long lasting effects.*

· **Precautionary statements**

P101 *If medical advice is needed, have product container or label at hand.*
P102 *Keep out of reach of children.*
P103 *Read carefully and follow all instructions.*
P210 *Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.*
P211 *Do not spray on an open flame or other ignition source.*
P251 *Do not pierce or burn, even after use.*
P271 *Use only outdoors or in a well-ventilated area.*
P273 *Avoid release to the environment.*
P305+P351+P338 *IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*
P312 *Call a POISON CENTER/doctor if you feel unwell.*
P337+P313 *If eye irritation persists: Get medical advice/attention.*
P410+P412 *Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.*
P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Additional information:**

Without adequate ventilation, explosive atmosphere/gas mix may be created.
Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
EUH208 *Contains cobalt(II) 2-ethylhexanoate. May produce an allergic reaction.*

· **2.3 Other hazards**· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

| | | |
|--|---|---------|
| CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43-xxxx | butanone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336 | 10-<25% |
| CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx | propane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280 | 10-<25% |
| CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-xxxx | n-butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336 | 10-<25% |
| CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx | butane (containing ≤ 0,1 % butadiene (203-450-8)) ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280 | 10-<25% |

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 23.11.2021

Revision: 23.11.2021

Trade name: Aerosol KH Klarlack

(Contd. of page 2)

| | | |
|---|--|---------|
| CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46-xxxx | ethyl acetate Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336 | 5-<10% |
| CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx | isobutane (containing ≤ 0,1 % butadiene (203-450-8)) Flam. Gas 1A, H220; Press. Gas (Comp.), H280 | 5-<10% |
| CAS: 64742-49-0 EINECS: 265-151-9 | Naphtha (petroleum), hydrotreated light Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336 | 5-<10% |
| CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx | xylene, mixture of isomers Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 | 2.5-<5% |
| CAS: 108-10-1 EINECS: 203-550-1 Reg.nr.: 01-2119473980-30-xxxx | 4-methylpentan-2-one Flam. Liq. 2, H225; Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H335 | 2.5-<5% |
| CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35-xxxx | ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332 | 1-<2.5% |

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media -**
- **Suitable extinguishing agents:** Cool container with water
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.11.2021

Revision: 23.11.2021

Trade name: Aerosol KH Klarlack

(Contd. of page 3)

- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Additional information about design of technical facilities:** No further data; see item 7.

· **Ingredients with limit values that require monitoring at the workplace:**

| | |
|--|---|
| 78-93-3 butanone | |
| WEL | Short-term value: 899 mg/m ³ , 300 ppm Long-term value: 600 mg/m ³ , 200 ppm Sk, BMGV |
| 123-86-4 n-butyl acetate | |
| WEL | Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm |
| 106-97-8 butane (containing ≤0,1 % butadiene (203-450-8)) | |
| WEL | Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene) |
| 141-78-6 ethyl acetate | |
| WEL | Short-term value: 1468 mg/m ³ , 400 ppm Long-term value: 734 mg/m ³ , 200 ppm |
| 1330-20-7 xylene, mixture of isomers | |
| WEL | Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV |
| 108-10-1 4-methylpentan-2-one | |
| WEL | Short-term value: 416 mg/m ³ , 100 ppm Long-term value: 208 mg/m ³ , 50 ppm Sk, BMGV |

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.11.2021

Revision: 23.11.2021

Trade name: Aerosol KH Klarlack

(Contd. of page 4)

100-41-4 ethylbenzene

| | |
|-----|---|
| WEL | Short-term value: 552 mg/m ³ , 125 ppm Long-term value: 441 mg/m ³ , 100 ppm Sk |
|-----|---|

· **Ingredients with biological limit values:****78-93-3 butanone**

| | |
|------|---|
| BMGV | 70 µmol/L Medium: urine Sampling time: post shift Parameter: butan-2-one |
|------|---|

1330-20-7 xylene, mixture of isomers

| | |
|------|--|
| BMGV | 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid |
|------|--|

108-10-1 4-methylpentan-2-one

| | |
|------|--|
| BMGV | 20 µmol/L Medium: urine Sampling time: post shift Parameter: 4-methylpentan-2-one |
|------|--|

· **Additional information:** The lists valid during the making were used as basis.· **8.2 Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.

· **Respiratory protection:**

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

· **Protection of hands:**

Protective gloves



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves** Nitrile rubber, NBR· **Penetration time of glove material**

Gloves must be changed after every contamination.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

butyl rubber, 0,7mm

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.11.2021

Revision: 23.11.2021

Trade name: Aerosol KH Klarlack

(Contd. of page 5)

- **Eye protection:**
Safety glasses



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

- | | |
|---------------------------|------------------------------------|
| · Form: | Aerosol |
| · Colour: | According to product specification |
| · Odour: | Characteristic |
| · Odour threshold: | Not determined. |

- | | |
|--------------------|-------------------------------|
| · pH-value: | Mixture is non-polar/aprotic. |
|--------------------|-------------------------------|

· Change in condition

- | | |
|---|---------------|
| · Melting point/freezing point: | Undetermined. |
| · Initial boiling point and boiling range: | -44 °C |

- | | |
|-----------------------|-------|
| · Flash point: | <0 °C |
|-----------------------|-------|

- | | |
|-------------------------------------|-----------------|
| · Flammability (solid, gas): | Not applicable. |
|-------------------------------------|-----------------|

- | | |
|--------------------------------|--------|
| · Ignition temperature: | 365 °C |
|--------------------------------|--------|

- | | |
|-------------------------------------|-----------------|
| · Decomposition temperature: | Not determined. |
|-------------------------------------|-----------------|

- | | |
|-------------------------------------|------------------------------|
| · Auto-ignition temperature: | Product is not selfigniting. |
|-------------------------------------|------------------------------|

- | | |
|--------------------------------|--|
| · Explosive properties: | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. Not determined. |
|--------------------------------|--|

· Explosion limits:

- | | |
|-----------------|------------|
| · Lower: | 1.2 Vol % |
| · Upper: | 11.5 Vol % |

- | | |
|------------------------------------|-----------------|
| · Vapour pressure at 20 °C: | 3,600 hPa |
| · Relative density | Not determined. |
| · Vapour density | Not determined. |
| · Evaporation rate | Not applicable. |

· Solubility in / Miscibility with water:

Not miscible or difficult to mix.

- | | |
|--|-----------------|
| · Partition coefficient: n-octanol/water: | Not determined. |
|--|-----------------|

· Viscosity:

- | | |
|---------------------|-----------------|
| · Dynamic: | Not determined. |
| · Kinematic: | Not determined. |

· Solvent content:

- | | |
|----------------------------|---|
| · Organic solvents: | 86.4 % With propellant gas. Content given by weight. |
| · Water: | 0.2 % |
| · VOC (EU) | 86.43 % |

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.11.2021

Revision: 23.11.2021

Trade name: Aerosol KH Klarlack

(Contd. of page 6)

| | |
|------------------------|--------|
| Solids content: | 13.5 % |
|------------------------|--------|

| | |
|--------------------------------|--|
| · 9.2 Other information | No further relevant information available. |
|--------------------------------|--|

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

| | |
|--|--|
| · LD/LC50 values relevant for classification: | |
|--|--|

| | | |
|---------------------------------------|--|--|
| ATE (Acute Toxicity Estimates) | | |
|---------------------------------------|--|--|

| | | |
|------------|----------|--------------|
| Inhalative | LC50/4 h | 186-298 mg/l |
|------------|----------|--------------|

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard**
May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 8)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.11.2021

Revision: 23.11.2021

Trade name: Aerosol KH Klarlack



(Contd. of page 7)

- Harmful to aquatic organisms*
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Ikke relevant.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

| | |
|---|---|
| · 14.1 UN-Number | |
| · ADR, IMDG, IATA | UN1950 |
| · 14.2 UN proper shipping name | |
| · ADR | 1950 AEROSOLS |
| · IMDG | AEROSOLS |
| · IATA | AEROSOLS, flammable |
| · 14.3 Transport hazard class(es) | |
| · ADR | |
|  | |
| · Class | 2.5F Gases. |
| · Label | 2.1 |
| · IMDG, IATA | |
|  | |
| · Class | 2.1 Gases. |
| · Label | 2.1 |
| · 14.4 Packing group | |
| · ADR, IMDG, IATA | Void not classified |
| · 14.5 Environmental hazards: | |
| · Marine pollutant: | No |
| · 14.6 Special precautions for user | Warning: Gases. |
| · Hazard identification number (Kemler code): | - not classified |
| · EMS Number: | F-D,S-U |
| · Stowage Code | SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: |

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.11.2021

Revision: 23.11.2021

Trade name: Aerosol KH Klarlack

(Contd. of page 8)

- | | |
|---|---|
| <ul style="list-style-type: none"> · Segregation Code | <p>Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.</p> |
| <ul style="list-style-type: none"> · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code | <p>Not applicable.</p> |
| <ul style="list-style-type: none"> · Transport/Additional information: | |
| <ul style="list-style-type: none"> · ADR · Limited quantities (LQ) 1L · Excepted quantities (EQ) Code: E0 <li style="padding-left: 20px;">Not permitted as Excepted Quantity · Transport category 2 · Tunnel restriction code D | |
| <ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) 1L · Excepted quantities (EQ) Code: E0 <li style="padding-left: 20px;">Not permitted as Excepted Quantity | |
| <ul style="list-style-type: none"> · UN "Model Regulation": | <p>UN 1950 AEROSOLS, 2.1</p> |

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
VOC: <840g/l
 - **Directive 2012/18/EU**
 - **Named dangerous substances - ANNEX I** None of the ingredients is listed.
 - **Seveso category P3a FLAMMABLE AEROSOLS**
 - **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
 - **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
 - **National regulations:**
 - **Technical instructions (air):**
- | Class | Share in % |
|--------|------------|
| Wasser | <1 |
| NK | 50-100 |
- **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
 - **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.11.2021

Revision: 23.11.2021

Trade name: Aerosol KH Klarlack

(Contd. of page 9)

H226 Flammable liquid and vapour.
 H280 Contains gas under pressure; may explode if heated.
 H304 May be fatal if swallowed and enters airways.
 H312 Harmful in contact with skin.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H411 Toxic to aquatic life with long lasting effects.

· **Department issuing SDS:** Product safety department

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· *** Data compared to the previous version altered.**