

# Guide Coat Black

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022  
Issue date: 2018-12-31 Revision date: 2025-10-22 Supersedes: 2022-03-08 Version: 4.0

### SECTION 1 Identification

#### 1.1. Product identifier

Product form : Mixture  
Product name : Guide Coat Black  
Product code : 3680100 / REZ261  
Vaporizer : Aerosol

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Automotive refinish  
Intended for general public

#### 1.4. Supplier's details

##### Manufacturer

Peter Kwasny GmbH  
96 Heibronner Str.  
Gundelsheim, 74831  
Germany  
T 49(0) 6269-95-20

##### Distributor

Peter Kwasny, Inc.  
12222 Merit Drive, #130  
Dallas, TX 75251  
USA  
T 1-844-426-6330

##### Distributor

Peter Kwasny Spraypaint Canada Inc  
40 University Avenue, Suite 904  
Toronto, ON, M5J 1T1  
Canada  
T +1 844-426-6330

#### 1.5. Emergency phone number

Emergency number : North America  
INFOTRAC International +1 (352) 323-5000 24 hr

### SECTION 2 Hazard identification

#### 2.1. Classification of the substance or mixture

##### GHS classification

Aerosol, Category 1  
Eye irritation, Category 2A  
Carcinogenicity, Category 2  
Reproductive toxicity, Category 2  
Specific target organ toxicity – Single exposure, Category 3, Narcosis

#### 2.2. Label elements

##### GHS labelling

Hazard pictograms (GHS) :



Signal word (GHS) : Danger

# Guide Coat Black

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Hazard statements (GHS)	: Extremely flammable aerosol Pressurized container; may burst if heated Causes serious eye irritation May cause drowsiness or dizziness Suspected of causing cancer. Suspected of damaging the unborn child.
Precautionary statements (GHS)	: If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing dust, fume, gas, mist, vapours, spray. Wash hands, forearms and face thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves, protective clothing, eye protection, face protection. If exposed or concerned: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C). Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

### 2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

### 2.4. Hazards not otherwise classified

Other hazards which do not result in classification : Contact with the liquefied gas may cause frostbite.

### 2.5. Unknown acute toxicity

Not applicable

## SECTION 3 Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	Conc. (% w/w)
Ethyl acetate	Ethyl acetate Acetic acid, ethyl ester / Ethyl ethanoate / ETHYL ACETATE	CAS-No.: 141-78-6	30 – 60
n-Butane	n-Butane Butane / BUTANE	CAS-No.: 106-97-8	10 – 30

# Guide Coat Black

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Name	Chemical name / Synonyms	Product identifier	Conc. (% w/w)
Propane	Propane Normal propane / PROPANE / n-Propane / R290 / R-290	CAS-No.: 74-98-6	7 - 13
n-Butyl acetate	n-Butyl acetate 1-Butyl acetate / Butyl acetate, n- / Butyl acetate / BUTYL ACETATE / Acetic acid, n-butyl ester / Acetic acid, butyl ester / Butyl ethanoate / N-butyl acetate	CAS-No.: 123-86-4	5 – 10
1-Butanol	1-Butanol n-Butyl alcohol / n-Butanol / Butanol, 1- / 1-Butyl alcohol / 1-Hydroxybutane / Butyl alcohol, n- / Butanol, n- / Butan-1-ol / Normal butyl alcohol / N-BUTYL ALCOHOL / Butyl alcohol	CAS-No.: 71-36-3	0.5 - 1.5
Xylenes (o-, m-, p- isomers)	Xylenes (o-, m-, p- isomers) Benzene, dimethyl- / Dimethylbenzene (mixed isomers) / Xylene / Xylene (all isomers) / Xylene (mixed isomers) / Xylene (o-, m-, p- isomers) / Xylenes / Xylenes (mixed isomers) / Dimethylbenzene / Xylol / Benzene, dimethyl-, mixed isomers / XYLENE / Dimethylbenzenes / Xylene isomers mixture / Dimethylbenzene (2-, 3-, 4-isomers) / Dimethylbenzene (mixed 2-, 3-, 4-isomers) / C8 Disubstituted benzenes / Xylene, mixed isomers / Xylenes (meta-, ortho-, para-) / Xylene (mixture), including m-xylene, o-xylene, p-xylene / Xylene (o-,m-,p- isomer mixture)	CAS-No.: 1330-20-7	0.1 - 1
Ethylbenzene	Ethylbenzene Benzene, ethyl- / Phenylethane / ETHYLBENZENE	CAS-No.: 100-41-4	0.1 - 1

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

## SECTION 4 First-aid measures

### 4.1. Description of necessary first-aid measures

First-aid measures after inhalation	: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
First-aid measures after skin contact	: If skin irritation occurs: Wash skin with plenty of water. Obtain medical attention if irritation persists. If frostbite occurs thaw frosted parts with lukewarm water. Do not rub affected area. Do not use hot water.

# Guide Coat Black

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If frostbite occurs thaw frosted parts with lukewarm water. Do not rub affected area. Do not use hot water.
First-aid measures after ingestion	: Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

### 4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: May cause irritation to the respiratory tract. May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause frostbite on contact with the liquefied gas.
Symptoms/effects after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause frostbite on contact with the liquefied gas.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: Suspected of causing cancer. Suspected of damaging the unborn child.

### 4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
-----------------------------------	--

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Carbon dioxide (CO <sub>2</sub> ). Dry chemical powder. Water spray. Alcohol resistant foam.
Unsuitable extinguishing media	: Do not use water jet.

### 5.2. Specific hazards arising from the chemical

Fire hazard	: Extremely flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon. Irritating vapours. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours.
Explosion hazard	: Vapours may form explosive mixture with air. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: DO NOT fight fire when fire reaches explosives. Evacuate area. Move containers away from the fire area if this can be done without risk. Cool closed containers exposed to fire with water spray.
Protection during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Use water spray to keep fire-exposed containers cool. Vapours are heavier than air and may spread along floors.

## SECTION 6 Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate every possible source of ignition. Use only non-sparking tools. Use special care to avoid static electric charges.
------------------	---

#### For non-emergency personnel

No additional information available

# Guide Coat Black

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

### For emergency responders

Environmental precautions : Prevent entry to sewers and public waters.

### 6.2. Methods and materials for containment and cleaning up

For containment : Stop leak if safe to do so. Remove all sources of ignition. Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment. Do not flush with water or aqueous cleansing agents.

Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

For further information refer to section 8: "Exposure controls/personal protection"

## SECTION 7 Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Take precautionary measures against static discharge. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Do not spray on an open flame or other ignition source. Avoid contact with skin, eyes and clothing. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. When using do not eat, drink or smoke. Handle and open container with care. Use only outdoors or in a well-ventilated area.

Hygiene measures : Take off immediately all contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace. Wash hands, forearms and face thoroughly after handling.

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Hazardous waste due to potential risk of explosion.

### 7.2. Conditions for safe storage, including incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep out of the reach of children. Store locked up. Keep in fireproof place. Store away from direct sunlight or other heat sources. Keep away from clothing and other combustible materials. Do not expose to temperatures exceeding 50 °C/ 122 °F. Protect containers from physical damage. Keep away from incompatible materials. Store in a dry, cool and well-ventilated place.

Specific end uses : Not available.

## SECTION 8 Exposure controls/personal protection

### 8.1. Control parameters

Ethyl acetate (141-78-6)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Ethyl acetate
ACGIH® TLV® TWA	400 ppm
Remark (ACGIH®)	TLV® Basis: URT & eye irr
Regulatory reference	ACGIH 2020

# Guide Coat Black

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Ethyl acetate (141-78-6)	
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	Ethyl acetate
OSHA PEL TWA	1400 mg/m <sup>3</sup>
OSHA PEL TWA	400 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>USA - IDLH - Occupational Exposure Limits</b>	
IDLH	2000 ppm (10% LEL)
<b>USA - NIOSH - Occupational Exposure Limits</b>	
NIOSH REL TWA	1400 mg/m <sup>3</sup>
NIOSH REL TWA	400 ppm
n-Butane (106-97-8)	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH® TLV® STEL	1000 ppm (explosion hazard (Butane, isomers))
<b>USA - IDLH - Occupational Exposure Limits</b>	
IDLH	1600 ppm (>10% LEL)
<b>USA - NIOSH - Occupational Exposure Limits</b>	
NIOSH REL TWA	1900 mg/m <sup>3</sup>
NIOSH REL TWA	800 ppm
Propane (74-98-6)	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	Propane
Remark (ACGIH®)	TLV® Basis: Simple Asphyxiant
ACGIH® chemical category	Simple asphyxiant See Appendix F: Minimal Oxygen Content
Regulatory reference	ACGIH 2024
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	Propane
OSHA PEL TWA	1800 mg/m <sup>3</sup>
OSHA PEL TWA	1000 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>USA - IDLH - Occupational Exposure Limits</b>	
IDLH	2100 ppm (10% LEL)
<b>USA - NIOSH - Occupational Exposure Limits</b>	
NIOSH REL TWA	1800 mg/m <sup>3</sup>
NIOSH REL TWA	1000 ppm
n-Butyl acetate (123-86-4)	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	n-Butyl acetate

# Guide Coat Black

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

<b>n-Butyl acetate (123-86-4)</b>	
ACGIH® TLV® TWA	50 ppm (Butyl acetates, all isomers)
ACGIH® TLV® STEL	150 ppm (Butyl acetates, all isomers)
Remark (ACGIH®)	TLV® Basis: Eye & URT irr
Regulatory reference	ACGIH 2020
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	n-Butyl-acetate
OSHA PEL TWA	710 mg/m³
OSHA PEL TWA	150 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>USA - IDLH - Occupational Exposure Limits</b>	
IDLH	1700 ppm (10% LEL)
<b>USA - NIOSH - Occupational Exposure Limits</b>	
NIOSH REL TWA	710 mg/m³
NIOSH REL TWA	150 ppm
NIOSH REL STEL	950 mg/m³
NIOSH REL STEL	200 ppm
<b>1-Butanol (71-36-3)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	n-Butanol (n-Butyl alcohol)
ACGIH® TLV® TWA	61 mg/m³
ACGIH® TLV® TWA	20 ppm
Remark (ACGIH®)	TLV® Basis: Eye & URT irr
Regulatory reference	ACGIH 2025
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	n-Butyl alcohol
OSHA PEL TWA	300 mg/m³
OSHA PEL TWA	100 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>USA - IDLH - Occupational Exposure Limits</b>	
IDLH	1400 ppm (10% LEL)
<b>USA - NIOSH - Occupational Exposure Limits</b>	
Local name	n-Butyl alcohol
NIOSH REL C	150 mg/m³
NIOSH REL C	50 ppm
US-NIOSH chemical category	Potential for dermal absorption
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))

# Guide Coat Black

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

<b>Ethylbenzene (100-41-4)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	Ethyl benzene
ACGIH® TLV® TWA	20 ppm
Remark (ACGIH®)	TLV® Basis: URT & Eye irr; Kidney eff; Ototoxicity; CNS impair. Notations: OTO (Ototoxicant); A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
ACGIH® chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
Regulatory reference	ACGIH 2025
<b>USA - ACGIH - Biological Exposure Indices</b>	
Local name	Ethyl benzene
BEI	0.15 g/g creatinine Parameter: Sum of mandelic acid and phenylglyoxylic acid - Medium: urine - Sampling time: end of shift (nonspecific)
Regulatory reference	ACGIH 2025
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	Ethyl benzene
OSHA PEL TWA	435 mg/m <sup>3</sup>
OSHA PEL TWA	100 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>USA - IDLH - Occupational Exposure Limits</b>	
IDLH	800 ppm (10% LEL)
<b>USA - NIOSH - Occupational Exposure Limits</b>	
Local name	Ethyl benzene
NIOSH REL TWA	435 mg/m <sup>3</sup>
NIOSH REL TWA	100 ppm
NIOSH REL 10h TWA	100 ppm
NIOSH REL STEL	545 mg/m <sup>3</sup>
NIOSH REL STEL	125 ppm
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH® chemical category	Not Classifiable as a Human Carcinogen
<b>USA - ACGIH - Biological Exposure Indices</b>	
BEI	1.5 g/g creatinine Parameter: Methylhippuric acids - Medium: urine - Sampling time: end of shift (technical or commercial grade)
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	Xylenes (o-, m-, p-isomers)
OSHA PEL TWA	435 mg/m <sup>3</sup>
OSHA PEL TWA	100 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

# Guide Coat Black

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

### 8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station. Provide readily accessible eye wash stations and safety showers.
Environmental exposure controls	: Avoid release to the environment.

### 8.3. Individual protection measures, such as personal protective equipment

<b>Hand protection:</b>
Wear suitable gloves. Consult glove manufacturer's product information on material suitability and material thickness.
<b>Eye protection:</b>
Wear eye/face protection
<b>Skin and body protection:</b>
Wear suitable protective clothing
<b>Respiratory protection:</b>
In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. SDSs cannot provide detailed and complete respiratory protection guidelines. Selection of respiratory protection must be done by a qualified person who has assessed the work environment.

#### Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

## SECTION 9 Physical and chemical properties

### 9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol.
Colour	: Black
Odour	: Characteristic
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: < -18 °C / -0.4 °F
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapour pressure	: 3600 hPa
Relative vapour density at 20°C/ 68 °F	: No data available
Relative density	: No data available
Density	: 0.8 g/cm <sup>3</sup>
Solubility	: Not miscible or difficult to mix.
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Explosive limits	: Lower explosion limit: 1.5 vol % Upper explosion limit: 11.5 vol %
Particle characteristics	: No data available

<b>Ethyl acetate</b>	
Boiling point	77 °C (at 1 atm)
Flash point	-4 °C (closed cup)

# Guide Coat Black

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Ethyl acetate	
Auto-ignition temperature	426.67 °C
Vapour pressure	91.84 hPa (at 18.7 °C)
Particle characteristics	No data available

n-Butane	
Boiling point	-0.5 °C (at 1013 hPa)
Flash point	-60 °C
Auto-ignition temperature	287 °C
Vapour pressure	2200 hPa (at 20 °C)
Particle characteristics	No data available

Propane	
Boiling point	-161.48 °C (at 1013 hPa)
Flash point	-104 °C
Auto-ignition temperature	450 °C
Vapour pressure	600 – 39000 hPa (at 20 °C)
Particle characteristics	No data available

n-Butyl acetate	
Boiling point	125 – 126 °C (at 1 atm)
Flash point	22 °C
Auto-ignition temperature	425 °C
Vapour pressure	13 hPa (at 20 °C)
Particle characteristics	No data available

1-Butanol	
Boiling point	119 °C (at 1013 hPa)
Flash point	35 °C (closed cup)
Auto-ignition temperature	343 °C
Vapour pressure	0.658 hPa (at 20 °C)
Particle characteristics	No data available

Ethylbenzene	
Boiling point	136.1 °C (at 1013.3 hPa)
Flash point	12.8 °C (closed cup)
Auto-ignition temperature	432 °C (at 1013 hPa)
Vapour pressure	9.5 hPa (at 20 °C)
Particle characteristics	No data available

# Guide Coat Black

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Xylenes (o-, m-, p- isomers)	
Boiling point	138.3 – 141.4 °C
Auto-ignition temperature	465 – 525 °C
Vapour pressure	8.8 – 11.9 hPa (at 25 °C)
Particle characteristics	No data available

### 9.2. Data relevant with regard to physical hazard classes (supplemental)

VOC content : 96.7 %  
Percent Solids : 3.3 %

## SECTION 10 Stability and reactivity

### 10.1. Reactivity

No dangerous reactions known under normal conditions of use.

### 10.2. Chemical stability

Stable under normal conditions. Extremely flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

### 10.3. Possibility of hazardous reactions

Reacts with acids, alkalis and oxidising agents.

### 10.4. Conditions to avoid

Heat. Sparks. Open flame. Direct sunlight. Ignition sources. Incompatible materials.

### 10.5. Incompatible materials

Strong oxidizers.

### 10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon. Irritating vapours.

## SECTION 11 Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified.  
Acute toxicity (dermal) : Not classified.  
Acute toxicity (inhalation) : Not classified.

Ethyl acetate (141-78-6)	
LD50 oral rat	5620 mg/kg (Source: NLM_CIP)
LD50 oral	4934 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 18000 mg/kg (Source: JAPAN_GHS)
LC50 inhalation rat	4000 ppm/4h

  

n-Butane (106-97-8)	
LC50 inhalation rat	658 g/m <sup>3</sup> (Exposure time: 4 h Source: NLM_CIP)

# Guide Coat Black

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

<b>Propane (74-98-6)</b>	
LC50 inhalation rat	> 800000 ppm (Exposure time: 15 min Source: ECHA_API)
<b>n-Butyl acetate (123-86-4)</b>	
LD50 oral rat	10768 mg/kg (Source: NLM_CIP)
LD50 dermal rabbit	> 17600 mg/kg (Source: NLM_CIP)
LC50 inhalation rat	0.74 mg/l/4h
LC50 Inhalation - Rat (Vapours)	1.86 mg/l/4h
<b>1-Butanol (71-36-3)</b>	
LD50 oral rat	700 mg/kg (Source: JAPAN_GHS)
LD50 oral	2100 mg/kg
LD50 dermal rabbit	3402 mg/kg (Source: JAPAN_GHS)
LD50 dermal	3400 mg/kg
LC50 inhalation rat	> 8000 ppm/4h
<b>Ethylbenzene (100-41-4)</b>	
LD50 oral rat	3500 mg/kg (Source: JAPAN_GHS)
LD50 dermal rabbit	15400 mg/kg (Source: JAPAN_GHS)
LC50 inhalation rat	17.4 mg/l/4h
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
LD50 oral rat	3500 mg/kg (Source: JAPAN_GHS)
LD50 dermal rabbit	> 4350 mg/kg (Source: JAPAN_GHS)
LD50 dermal	1700 mg/kg
LC50 inhalation rat	29.08 mg/l/4h
LC50 Inhalation - Rat (Vapours)	27.57 mg/l/4h
Skin corrosion/irritation	: Not classified.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified.
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Suspected of causing cancer.
<b>Ethylbenzene (100-41-4)</b>	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity
In OSHA Hazard Communication Carcinogen list	Yes
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
IARC group	3 - Not classifiable

Reproductive toxicity : Suspected of damaging fertility or the unborn child.  
STOT-single exposure : May cause drowsiness or dizziness.

# Guide Coat Black

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Ethyl acetate (141-78-6)	
STOT-single exposure	May cause drowsiness or dizziness.
n-Butyl acetate (123-86-4)	
STOT-single exposure	May cause drowsiness or dizziness.
1-Butanol (71-36-3)	
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
Xylenes (o-, m-, p- isomers) (1330-20-7)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified.
Ethyl acetate (141-78-6)	
LOAEL (oral, rat, 90 days)	3600 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 795.2600 (Subchronic Oral Toxicity Test)
NOAEL (oral, rat, 90 days)	900 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 795.2600 (Subchronic Oral Toxicity Test)
1-Butanol (71-36-3)	
LOAEL (oral, rat, 90 days)	500 mg/kg bodyweight Animal: rat
NOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat
Ethylbenzene (100-41-4)	
NOAEL (oral, rat, 90 days)	75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Xylenes (o-, m-, p- isomers) (1330-20-7)	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
Aspiration hazard	: Not classified.
Guide Coat Black	
Vaporizer	Aerosol
Viscosity, kinematic	No data available
Ethyl acetate (141-78-6)	
Viscosity, kinematic	0.5 mm <sup>2</sup> /s
1-Butanol (71-36-3)	
Viscosity, kinematic	3.641 mm <sup>2</sup> /s
Ethylbenzene (100-41-4)	
Viscosity, kinematic	0.6 mm <sup>2</sup> /s Temp.: 'other:' Parameter: 'kinematic viscosity (in mm <sup>2</sup> /s)' Remarks on result: 'other:'
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract. May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause frostbite on contact with the liquefied gas.

# Guide Coat Black

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Symptoms/effects after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause frostbite on contact with the liquefied gas.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: Suspected of causing cancer. Suspected of damaging the unborn child.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

## SECTION 12 Ecological information

### 12.1. Ecotoxicity

Ecology - general	: May cause long-term adverse effects in the aquatic environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified.
Hazardous to the aquatic environment, long-term (chronic)	: Not classified.

Ethyl acetate (141-78-6)	
LC50 - Fish [1]	220 – 250 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
EC50 - Crustacea [1]	560 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 - Fish [2]	484 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through] Source: IUCLID)
NOEC (chronic)	2.4 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
n-Butyl acetate (123-86-4)	
LC50 - Fish [1]	100 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static] Source: EPA)
LC50 - Fish [2]	17 – 19 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
EC50 72h - Algae [1]	674.7 mg/l (Species: Desmodesmus subspicatus)
1-Butanol (71-36-3)	
LC50 - Fish [1]	1730 – 1910 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: IUCLID)
EC50 - Crustacea [1]	1983 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 - Fish [2]	1740 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: IUCLID)
EC50 - Crustacea [2]	1897 – 2072 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 72h - Algae [1]	> 500 mg/l (Species: Desmodesmus subspicatus)
EC50 96h - Algae [1]	> 500 mg/l (Species: Desmodesmus subspicatus)
NOEC (chronic)	4.1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic crustacea	4.1 mg/l
Ethylbenzene (100-41-4)	
LC50 - Fish [1]	11 – 18 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: EPA)
EC50 - Crustacea [1]	1.8 – 2.4 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 - Fish [2]	4.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static] Source: EPA)
EC50 72h - Algae [1]	4.6 mg/l (Species: Pseudokirchneriella subcapitata)

# Guide Coat Black

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

<b>Ethylbenzene (100-41-4)</b>	
EC50 72h - Algae [2]	2.6 – 11.3 mg/l (Species: Pseudokirchneriella subcapitata [static])
EC50 96h - Algae [1]	> 438 mg/l (Species: Pseudokirchneriella subcapitata)
EC50 96h - Algae [2]	1.7 – 7.6 mg/l (Species: Pseudokirchneriella subcapitata [static])
LOEC (chronic)	1.7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC (chronic)	0.96 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC chronic crustacea	0.956 mg/l
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
LC50 - Fish [1]	13.4 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
EC50 - Crustacea [1]	3.82 mg/l (Exposure time: 48 h - Species: water flea)
LC50 - Fish [2]	2.661 – 4.093 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: EPA)
EC50 - Crustacea [2]	0.6 mg/l (Exposure time: 48 h - Species: Gammarus lacustris)
LOEC (chronic)	3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'

### 12.2. Persistence and degradability

<b>Guide Coat Black</b>	
Persistence and degradability	Not established.
<b>Ethyl acetate (141-78-6)</b>	
Persistence and degradability	Rapidly degradable
<b>n-Butane (106-97-8)</b>	
Persistence and degradability	Rapidly degradable
<b>Propane (74-98-6)</b>	
Persistence and degradability	Rapidly degradable
<b>n-Butyl acetate (123-86-4)</b>	
Persistence and degradability	Rapidly degradable
<b>1-Butanol (71-36-3)</b>	
Persistence and degradability	Rapidly degradable
<b>Ethylbenzene (100-41-4)</b>	
Persistence and degradability	Rapidly degradable
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
Persistence and degradability	Rapidly degradable

### 12.3. Bioaccumulative potential

<b>Guide Coat Black</b>	
Bioaccumulative potential	Not established.

# Guide Coat Black

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Ethyl acetate (141-78-6)	
BCF - Fish [1]	(30 dimensionless)
Partition coefficient n-octanol/water	0.73 (at 20 °C (at pH 7))
n-Butane (106-97-8)	
Partition coefficient n-octanol/water	2.31 (at 20 °C (at pH 7))
Propane (74-98-6)	
Partition coefficient n-octanol/water	1.09 (at 20 °C (at pH 7))
n-Butyl acetate (123-86-4)	
Partition coefficient n-octanol/water	1.81 (at 23 °C)
1-Butanol (71-36-3)	
BCF - Fish [1]	(0.64 dimensionless)
Partition coefficient n-octanol/water	1 (at 25 °C (at pH 7))
Ethylbenzene (100-41-4)	
BCF - Fish [1]	(15 dimensionless)
Partition coefficient n-octanol/water	3.6 (at 20 °C (at pH 7.84))
Xylenes (o-, m-, p- isomers) (1330-20-7)	
BCF - Fish [1]	0.6 – 15
Partition coefficient n-octanol/water	2.77 – 3.15

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Ozone	: Not classified.
Fluorinated greenhouse gases	: No
Other information	: No other effects known.

## SECTION 13 Disposal considerations

Product/Packaging disposal recommendations	: Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. Container under pressure. Do not drill or burn even after use.
Additional information	: Flammable vapours may accumulate in the container.

## SECTION 14 Transport information

In accordance with DOT / TDG

### 14.1. UN Number

UN-No. (DOT)	: UN1950
UN-No. (TDG)	: UN1950

# Guide Coat Black

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

### 14.2. UN Proper Shipping Name

Proper Shipping Name (DOT) : Aerosols  
Proper Shipping Name (TDG) : AEROSOLS

### 14.3. Transport hazard class(es)

#### DOT

Transport hazard class(es) (DOT) : 2.1  
Hazard labels (DOT) : 2.1



#### TDG

Transport hazard class(es) (TDG) : 2.1  
Hazard labels (TDG) : 2.1



### 14.4. Packing group

Packing group (DOT) : Not applicable  
Packing group (TDG) : Not applicable

### 14.5. Environmental hazards

Other information : No supplementary information available.

### 14.6. Transport in bulk

Not applicable

### 14.7. Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.

#### DOT

UN-No. (DOT) : UN1950  
DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.  
DOT Packaging Exceptions (49 CFR 173.xxx) : 306  
DOT Packaging Non Bulk (49 CFR 173.xxx) : None  
DOT Packaging Bulk (49 CFR 173.xxx) : None  
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg  
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg  
DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.  
DOT Vessel Stowage Other : 25 - Protected from sources of heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

#### TDG

UN-No. (TDG) : UN1950

# Guide Coat Black

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

TDG Special Provisions	: 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment), 107 - (1) These Regulations, except for Parts 1 and 2, do not apply to the offering for transport, handling or transport of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL. (2) Subsection (1) does not apply to self-defence spray.
Explosive Limit and Limited Quantity Index	: 1 L
Excepted quantities (TDG)	: E0
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 75 L
Emergency Response Guide (ERG) Number	: 126

## SECTION 15 Regulatory information

### 15.1. Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

### 15.2. International regulations

No additional information available

### 15.3. State regulations



#### WARNING:

This product can expose you to Carbon black, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## SECTION 16 Other Information

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Revision date	: 2025-10-22
Issue date	: 2018-12-31
Other information	: None.
Prepared by	: Nexreg Compliance Inc. <a href="http://www.Nexreg.com">www.Nexreg.com</a>



#### Indication of changes:

SDS update.

SDS HazCom 2024 - WHMIS 2022 (Nexreg) 2025

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.