

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Page 1/10



Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Haftgrund grau (D)



- *PBT*: Not applicable.
- **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

· Dangerous components:		
	acetone	25-<50%
	dimethyl ether 🚸 Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	10-<25%
	(Cor	td. on page 3)

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Haftgrund grau (D)

CAS: 74-98-6	propane	ntd. of page 5-<10%
EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	5- 10 /0
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane (containing ≤ 0,1 % butadiene (203-450-8)) ♦ Flam. Gas IA, H220; Press. Gas (Comp.), H280, EUH018	5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane (containing ≤ 0,1 % butadiene (203-450-8)) Flam. Gas IA, H220; Press. Gas (Comp.), H280, EUH018	2.5-<5%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-xxxx	n-butyl acetate 🚸 Flam. Liq. 3, H226; ᡧ STOT SE 3, H336, EUH066	2.5-<5%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-xxxx	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226	2.5-<5%
CAS: 9004-70-0 Reg.nr.: no Reach No. availlable	nitrocellulose with water(not less than 25% water, by mass)	2.5-<5%
CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46-xxxx	ethyl acetate Flam. Liq. 2, H225;	1-<2.5%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx	xylene, mixture of isomers Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	1-<2.5%
CAS: 64-17-5 EINECS: 200-578-6 Reg.nr.: 01-2119457610-43-xxxx	ethanol 🚸 Flam. Liq. 2, H225; 🚸 Eye Irrit. 2, H319	1-<2.5%
CAS: 7397-62-8 EINECS: 230-991-7 Reg.nr.: 01-2119514685-36-xxxx	butyl glycollate 🚸 Repr. 2, H361; 🔗 Eye Dam. 1, H318	<1%

SECTION 4: First aid measures

• 4.1 Description of first aid measures

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media -
- Suitable extinguishing agents: Cool container whit water
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 4)

⁻ GB

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

(Contd. of page 3)

Trade name: Aerosol Haftgrund grau (D)

· 5.3 Advice for firefighters

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

• 6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

6.4 Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:
- Observe official regulations on storing packagings with pressurised containers.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm

Long-term value: 1210 mg/m³, 500 ppm

115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm

Long-term value: 766 mg/m³, 400 ppm

106-97-8 butane (containing ≤0,1 % butadiene (203-450-8))

- WEL Short-term value: 1810 mg/m³, 750 ppm
 - Long-term value: 1450 mg/m^3 , 600 ppm
 - Carc (if more than 0.1% of buta-1.3-diene)

(Contd. on page 5)

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Haftgrund grau (D)

		(Contd. of page
123-	86-4 n-butyl acetate	
WEL	Short-term value: 966 mg/m³, 200 ppm	
	Long-term value: 724 mg/m ³ , 150 ppm	
108-	65-6 2-methoxy-1-methylethyl acetate	
WEL	Short-term value: 548 mg/m ³ , 100 ppm	
	Long-term value: 274 mg/m ³ , 50 ppm	
	Sk	
141-	78-6 ethyl acetate	
WEL	Short-term value: 1468 mg/m ³ , 400 ppm	
	Long-term value: 734 mg/m ³ , 200 ppm	
1330	-20-7 xylene, mixture of isomers	
WEL	Short-term value: 441 mg/m ³ , 100 ppm	
	Long-term value: 220 mg/m ³ , 50 ppm	
	Sk; BMGV	
64-1	7-5 ethanol	
WEL	Long-term value: 1920 mg/m³, 1000 ppm	
·Ingr	edients with biological limit values:	
1330	-20-7 xylene, mixture of isomers	
BMC	W 650 mmol/mol creatinine	
	Medium: urine	
	Sampling time: post shift	
	Parameter: methyl hippuric acid	
· Addi	tional information: The lists valid during the making were used as basis.	
· 8.2 E	Exposure controls	
	opriate engineering controls No further data; see item 7.	
	vidual protection measures, such as personal protective equipment	
· Gene	eral protective and hygienic measures:	
Keep	away from foodstuffs, beverages and feed.	
Imme	ediately remove all soiled and contaminated clothing	
Wash	h hands before breaks and at the end of work.	
Avoi	d contact with the eyes.	
	d contact with the eyes and skin.	
Avoi	iratory protection:	



When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

• Hand protection

Protective gloves



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material

Gloves must be changed after every contamination.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6) GB

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Haftgrund grau (D)

- (Contd. of page 5) • For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:
- butyl rubber, 0,7mm · Eye/face protection
- Safety glasses

*

Tightly sealed goggles

SECTION 9: Physical and chemical properties

• 9.1 Information on basic physical and chemical p	ronerties
· General Information	10101005
· Physical state	Aerosol
· Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
• Melting point/freezing point:	Undetermined.
• Boiling point or initial boiling point and boiling	e nacionninea.
range	-44 °C
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	2.6 Vol % (67-64-1 acetone)
· Upper:	18.6 Vol % (115-10-6 dimethyl ether)
· Flash point:	<0 °C
· Ignition temperature:	235 °C
· Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic:	Not determined.
· Solubility	1107 acromitica.
· water:	Not miscible or difficult to mix.
• Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C:	3,400 hPa (115-10-6 dimethyl ether)
· Density and/or relative density	5,100 hi u (115-10-0 uineinyt ener)
· Relative density	Not determined.
· Vapour density	Not determined.
• 9.2 Other information	
· Appearance:	
· Form:	Aerosol
Important information on protection of health an	d
environment, and on safety.	
Auto-ignition temperature:	Product is not selfigniting.
• Explosive properties:	Product is not explosive. However, formation of
	explosive air/vapour mixtures are possible.
	Not determined.
Solvent content:	07.0.0
• Organic solvents:	87.9 %
	With propellant gas. Content given by weight.
\cdot VOC (EU)	87.87 %
· Solids content:	11.0 %
	(Contd. on page 7)
	G

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Haftgrund grau (D)

	(Contd. of page
Change in condition	
Evaporation rate	Not applicable.
Information with regard to physical hazard	classes
Explosives	Void
Flammable gases	Void
Aerosols	Extremely flammable aerosol. Pressurised container
	May burst if heated.
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flamm	able
gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Serious eye damage/irritation Causes serious eye irritation.
- · STOT-single exposure May cause drowsiness or dizziness.
- · 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.

(Contd. on page 8)

GB

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Haftgrund grau (D)

(Contd. of page 7)

• **vPvB:** Ikke relevant.

· 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

· 12.7 Other adverse effects

· Additional ecological information:

· General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

*

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN number or ID number · ADR, IMDG, IATA	UN1950
	0111930
• 14.2 UN proper shipping name	1050 (55 0 0 0 0
· ADR · IMDG	1950 AEROSOLS AEROSOLS
· IATA	AEROSOLS AEROSOLS, flammable
	ALKOSOLS, Juliinable
· 14.3 Transport hazard class(es)	
$\cdot ADR$	
· Class	2 5F Gases.
·Label	2.1
· IMDG, IATA	
· Class	2.1 Gases.
· Label	2.1
· 14.4 Packing group	
$\cdot ADR, IMDG, IATA$	Void
	not classified
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Gases.
• Hazard identification number (Kemler code):	-
-	not classified
· EMS Number:	F- D , S - U
	(Contd. on page

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Haftgrund grau (D) (Contd. of page 8) SW1 Protected from sources of heat. · Stowage Code SW2 Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 · Segregation Code litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. · 14.7 Maritime transport in bulk according to IMO instruments Not applicable. • Transport/Additional information: · ADR · Limited quantities (LQ) lLCode: E0 • Excepted quantities (EQ) Not permitted as Excepted Quantity · Transport category 2 • Tunnel restriction code D · IMDG lL \cdot Limited quantities (LQ) · Excepted quantities (EQ) Code: E0 Not permitted as Excepted Quantity · UN "Model Regulation": UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture VOC: <840g/l
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:

· Technical instructions (air):

Class	Share in %
NK	50-100

- Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H201 Explosive; mass explosion hazard.

H220 Extremely flammable gas.

(Contd. on page 10)

⁻ GB

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Haftgrund grau (D)

	(Contd. of page 9)
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause respiratory irritation. May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
	8 In use may form flammable/explosive vapour-air mixture.
EUH060	6 Repeated exposure may cause skin dryness or cracking.
· Departn	nent issuing SDS: Product safety department
· Abbrevi	ations and acronyms:
	lement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the
	mal Transport of Dangerous Goods by Rail)
	ternational Civil Aviation Organisation
	cord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the
	nal Carriage of Dangerous Goods by Road) tempting al Manitime Code for Dangerous Coode
	ternational Maritime Code for Dangerous Goods ernational Air Transport Association
	bally Harmonised System of Classification and Labelling of Chemicals
	European Inventory of Existing Commercial Chemical Substances
	European List of Notified Chemical Substances
	mical Abstracts Service (division of the American Chemical Society)
	sistent, Bioaccumulative and Toxic
	y Persistent and very Bioaccumulative
	Explosives – Division 1.1
	s 1A: Flammable gases – Category 1A : Aerosols – Category 1
	s - Category 3
	s (Comp.): Gases under pressure – Compressed gas
	2: Flammable liquids – Category 2
	. 3: Flammable liquids – Category 3
Acute Tox	. 4: Acute toxicity – Category 4
	2: Skin corrosion/irritation – Category 2
	1: Serious eye damage/eye irritation – Category 1
	2: Serious eye damage/eye irritation – Category 2
	Reproductive toxicity – Category 2 3: Specific target organ toxicity (single exposure) – Category 3
	2: Specific target organ toxicity (repeated exposure) – Category 5
Asp. Tox.	1: Aspiration hazard – Category 1
	compared to the previous version altered.
=	