


Printing date 15.11.2022

Version number 1

Revision: 15.11.2022



Page 1/9

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Markierungsfarben weiss (59450067)



· vPvB: Not applicable.

# **SECTION 3: Composition/information on ingredients**

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46-xxxx	ethyl acetate	25-<50%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-xxxx	acetone Flam. Liq. 2, H225;	10-<25%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane 🚸 Flam. Gas IA, H220; Press. Gas (Comp.), H280, EUH018	10-<25%
	(Cor	ntd. on page 3

- GB

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Markierungsfarben weiss (59450067)

	(Co	ntd. of page 2)
	butane (containing $\leq 0,1$ % butadiene (203-450-8))	10-<25%
EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	🚸 Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane (containing ≤ 0,1 % butadiene (203-450-8)) ♦ Flam. Gas IA, H220; Press. Gas (Comp.), H280, EUH018	5-<10%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-xxxx	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226	1-<2.5%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

# **SECTION 4: First aid measures**

• 4.1 Description of first aid measures

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- $\cdot$  4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media -
- · Suitable extinguishing agents: Cool container whit water
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

### **SECTION 6:** Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
  See Section 7 for information on safe handling.
  See Section 8 for information on personal protection equipment.
  See Section 13 for disposal information.

# **SECTION 7: Handling and storage**

- 7.1 Precautions for safe handling Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace.
- *Information about fire and explosion protection:* Do not spray onto a naked flame or any incandescent material.

(Contd. on page 4)

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

#### Trade name: Aerosol Markierungsfarben weiss (59450067)

(Contd. of page 3)

Keep ignition sources away - Do not smoke. Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles:

- Observe official regulations on storing packagings with pressurised containers.
- Information about storage in one common storage facility: Not required.

· Further information about storage conditions: None.

• 7.3 Specific end use(s) No further relevant information available.

# SECTION 8: Exposure controls/personal protection

### · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

### 141-78-6 ethyl acetate

WEL Short-term value: 1468 mg/m<sup>3</sup>, 400 ppm Long-term value: 734 mg/m<sup>3</sup>, 200 ppm

#### 67-64-1 acetone

WEL Short-term value: 3620 mg/m<sup>3</sup>, 1500 ppm

Long-term value: 1210 mg/m<sup>3</sup>, 500 ppm

#### 106-97-8 butane (containing ≤0,1 % butadiene (203-450-8))

WEL Short-term value: 1810 mg/m<sup>3</sup>, 750 ppm Long-term value: 1450 mg/m<sup>3</sup>, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m<sup>3</sup>, 100 ppm Long-term value: 274 mg/m<sup>3</sup>, 50 ppm Sk

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Appropriate engineering controls No further data; see item 7.

- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin.

• Respiratory protection:



When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

· Hand protection

Protective gloves



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Markierungsfarben weiss (59450067)

(Contd. of page 4)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- · Material of gloves Nitrile rubber, NBR
- **Penetration time of glove material** Gloves must be changed after every contamination. The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- $\cdot$  For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:
- butyl rubber, 0,7mm
- **Eye/face protection** Safety glasses



Tightly sealed goggles

# **SECTION 9: Physical and chemical properties**

• 9.1 Information on basic physical and chemical p	ronartias		
• General Information	Topernes		
· Physical state	Aerosol		
· Colour:	According to product specification		
· Odour:	<i>Characteristic</i>		
· Odour threshold:	Not determined.		
• Melting point/freezing point:	Undetermined.		
• Boiling point or initial boiling point and boiling	onacierminea.		
range	-44 °C		
· Flammability	Not applicable.		
· Lower and upper explosion limit			
· Lower:	1.5 Vol % (106-97-8 butane (containing $\leq 0,1$ %		
	butadiene (203-450-8)))		
· Upper:	13 Vol % (67-64-1 acetone)		
· Flash point:	$\leq 0 ^{\circ}C$		
· Ignition temperature:	460 °C (75-28-5 isobutane (containing $\leq 0,1$ %		
Ignuton temperature.	butadiene (203-450-8)))		
· Decomposition temperature:	Not determined.		
· pH	Not determined.		
· Viscosity:	1107 acromatica.		
· Kinematic viscosity	Not determined.		
· Dynamic:	Not determined.		
· Solubility			
· water:	Not miscible or difficult to mix.		
• Partition coefficient n-octanol/water (log value)	Not determined.		
· Vapour pressure at 20 °C:	3,600 hPa (74-98-6 propane)		
• Density and/or relative density			
· Relative density	Not determined.		
· Vapour density	Not determined.		
• 9.2 Other information			
· Appearance:			
· Form:	Aerosol		
	(Contd. on page 6)		

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

	(Contd. of page 5
Important information on protection of heal	th and
environment, and on safety.	
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation o
	explosive air/vapour mixtures are possible.
	Not determined.
Solvent content:	
Organic solvents:	84.7 %
	With propellant gas. Content given by weight.
VOC (EU)	84.74 %
Solids content:	10.0 %
Change in condition	
Evaporation rate	Not applicable.
Information with regard to physical hazard of	classes
Explosives	Void
Flammable gases	Void
Aerosols	Extremely flammable aerosol. Pressurised container
	May burst if heated.
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flamm	
gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals Desensitised explosives	Void Void

# **SECTION 10: Stability and reactivity**

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

# **SECTION 11: Toxicological information**

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Serious eye damage/irritation Causes serious eye irritation.
- · STOT-single exposure May cause drowsiness or dizziness.

(Contd. on page 7)

GB

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Markierungsfarben weiss (59450067)

# $\cdot$ 11.2 Information on other hazards

• Endocrine disrupting properties

None of the ingredients is listed.

# **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Ikke relevant.
- · 12.6 Endocrine disrupting properties
- The product does not contain substances with endocrine disrupting properties.
- $\cdot$  12.7 Other adverse effects
- Additional ecological information:
- · General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

#### **SECTION 13: Disposal considerations**

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number ADR, IMDG, IATA	UN1950	
14.2 UN proper shipping name		
ADR	1950 AEROSOLS	
IMDG	AEROSOLS	
IATA	AEROSOLS, flammable	
ADR		
Class	2 5F Gases.	
Label	2.1	

(Contd. of page 6)

Revision: 15.11.2022

Printing date 15.11.2022 Version number 1 Trade name: Aerosol Markierungsfarben weiss (59450067) (Contd. of page 7) · IMDG, IATA 2.1 Gases. · Class · Label 2.1 · 14.4 Packing group · ADR, IMDG, IATA Void not classified · 14.5 Environmental hazards: • Marine pollutant: No · 14.6 Special precautions for user Warning: Gases. · Hazard identification number (Kemler code): not classified · EMS Number: F-D, S-USW1 Protected from sources of heat. · Stowage Code SW2 Clear of living quarters. · Segregation Code SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. · 14.7 Maritime transport in bulk according to IMO instruments *Not applicable.* • Transport/Additional information: · ADR · Limited quantities (LQ) lLCode: E0 • Excepted quantities (EQ) Not permitted as Excepted Quantity

· Transport category 2 · Tunnel restriction code D ·IMDG · Limited quantities (LQ) lLCode: E0 · Excepted quantities (EQ) Not permitted as Excepted Quantity · UN "Model Regulation": UN 1950 AEROSOLS, 2.1

# **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture VOC: <840g/l

· Directive 2012/18/EU

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- $\cdot$  Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

(Contd. on page 9)

GB

Printing date 15.11.2022

Version number 1

Revision: 15.11.2022

Trade name: Aerosol Markierungsfarben weiss (59450067)

(Contd. of page 8)

 $\cdot$  Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· National regulations:

· Technical instructions (air):

Class	Share in %
NK	50-100

· Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

CON CONTRACTOR		-	<u> </u>	
SECTION		0 0 10 1 10 1	to was at	0.70
		1 X 24 <b>100</b> A 1 A		
	101 011		011100000	~ ~ ~

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

EUH018 In use may form flammable/explosive vapour-air mixture.

EUH066 Repeated exposure may cause skin dryness or cracking.

# · Department issuing SDS: Product safety department

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

: Aerosols – Category 3

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

• \* Data compared to the previous version altered.