# Safety data sheet
**according to 1907/2006/EC, Article 31**

*Printing date 08.12.2023* *Version number 1* *Revision: 08.12.2023*

* 
## SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name: Aerosol Kupfer-Gold-Effekt**

· **(Article number) product ID.:** REZ53
· **1.2 Relevant identified uses of the substance or mixture and uses advised against**
· **Sector of Use**
SU21 Consumer uses: Private households / general public / consumers
SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· **Application of the substance / the mixture:** painting
· **Uses advised against** No further relevant information available.

· **1.3 Details of the supplier of the safety data sheet**
· **Manufacturer/Supplier:**
Peter Kwasny GmbH
Heilbronner Str. 96
D-74831 Gundelsheim
Tel.: 0049-(0)6269-95-20
E-mail: labor@kwasny.de

· **Further information obtainable from:** Product safety department

· **1.4 Emergency telephone number:** Tel.:+49 6269 95 20
· **national:**
National Poisons Information Service, Birmingham
Tel.: 844 892 0111
· **K-Nr.** 0001

* 
## SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**
· **Classification according to Regulation (EC) No 1272/2008**

flame

Aerosol 1 H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.

health hazard

STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.

environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 2)

# Safety data sheet
## according to 1907/2006/EC, Article 31

*Printing date 08.12.2023* *Version number 1* *Revision: 08.12.2023*

***Trade name: Aerosol Kupfer-Gold-Effekt***

(Contd. of page 1)

| | |
|---|---|
| *Skin Irrit. 2* | *H315 Causes skin irritation.* |
| *Eye Irrit. 2* | *H319 Causes serious eye irritation.* |
| *STOT SE 3* | *H335 May cause respiratory irritation.* |
| *Asp. Tox. 1* | *H304 May be fatal if swallowed and enters airways.* |

· ***2.2 Label elements***
· ***Labelling according to Regulation (EC) No 1272/2008***
*The product is classified and labelled according to the GB CLP regulation.*
· ***Hazard pictograms***

GHS02 GHS07 GHS08 GHS09

· ***Signal word*** *Danger*

· ***Hazard-determining components of labelling:***
*xylene, mixture of isomers*
*ethylbenzene*
· ***Hazard statements***
*H222 Extremely flammable aerosol.*
*H229 Pressurised container: May burst if heated.*
*H315 Causes skin irritation.*
*H319 Causes serious eye irritation.*
*H335 May cause respiratory irritation.*
*H373 May cause damage to the hearing organs through prolonged or repeated exposure.*
*H411 Toxic to aquatic life with long lasting effects.*
· ***Precautionary statements***

| | |
|---|---|
| *P101* | *If medical advice is needed, have product container or label at hand.* |
| *P102* | *Keep out of reach of children.* |
| *P103* | *Read carefully and follow all instructions.* |
| *P210* | *Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.* |
| *P211* | *Do not spray on an open flame or other ignition source.* |
| *P251* | *Do not pierce or burn, even after use.* |
| *P260* | *Do not breathe vapours/spray.* |
| *P271* | *Use only outdoors or in a well-ventilated area.* |
| *P273* | *Avoid release to the environment.* |
| *P302+P352* | *IF ON SKIN: Wash with plenty of water.* |
| *P305+P351+P338* | *IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.* |
| *P312* | *Call a POISON CENTER/doctor if you feel unwell.* |
| *P332+P313* | *If skin irritation occurs: Get medical advice/attention.* |
| *P337+P313* | *If eye irritation persists: Get medical advice/attention.* |
| *P391* | *Collect spillage.* |
| *P410+P412* | *Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.* |
| *P501* | *Dispose of contents/container in accordance with local/regional/national/international regulations.* |

· ***Additional information:***
*Without adequate ventilation, explosive atmosphere/gas mix may be created.*
*Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.*

(Contd. on page 3)

# Safety data sheet
## according to 1907/2006/EC, Article 31

Printing date 08.12.2023 Version number 1 Revision: 08.12.2023

**Trade name: Aerosol Kupfer-Gold-Effekt**

(Contd. of page 2)

EUH208 Contains methyl methacrylate, n-butyl methacrylate. May produce an allergic reaction.
· **Information concerning particular hazards for human and environment:** 1272/2008/EC,II, 3.2
· **2.3 Other hazards**
· **Results of PBT and vPvB assessment**
· **PBT:** Not applicable.
· **vPvB:** Not applicable.

* 
## SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**
· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

| | | |
|---|---|---|
| CAS: 1330-20-7<br>EINECS: 215-535-7<br>Reg.nr.: 01-2119488216-32-xxxx | xylene, mixture of isomers<br>Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 | 25-<50% |
| CAS: 74-98-6<br>EINECS: 200-827-9<br>Reg.nr.: 01-2119486944-21-xxxx | propane<br>Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018 | 10-<25% |
| CAS: 106-97-8<br>EINECS: 203-448-7<br>Reg.nr.: 01-2119474691-32-xxxx | butane (containing ≤ 0,1 % butadiene (203-450-8))<br>Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018 | 10-<25% |
| CAS: 100-41-4<br>EINECS: 202-849-4<br>Reg.nr.: 01-2119489370-35-xxxx | ethylbenzene<br>Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332 | 5-<10% |
| CAS: 75-28-5<br>EINECS: 200-857-2<br>Reg.nr.: 01-2119485395-27-xxxx | isobutane (containing ≤ 0,1 % butadiene (203-450-8))<br>Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018 | 5-<10% |
| CAS: 7440-50-8<br>EINECS: 231-159-6 | copper<br>Aquatic Chronic 1, H410; Acute Tox. 4, H302; Eye Irrit. 2, H319 | 2.5-<5% |
| CAS: 7440-66-6<br>EINECS: 231-175-3<br>Reg.nr.: 01-2119467174-37-xxxx | zinc powder -zinc dust (pyrophoric)<br>Aquatic Chronic 1, H410 | 1-<2.5% |
| CAS: 80-62-6<br>EINECS: 201-297-1<br>Reg.nr.: 01-2119452498-28-xxxx | methyl methacrylate<br>Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335 | ≥0.1-<1% |
| CAS: 97-88-1<br>EINECS: 202-615-1<br>Reg.nr.: 01-2119486394-28-xxxx | n-butyl methacrylate<br>Flam. Liq. 3, H226; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335 | ≥0.1-<1% |

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

* 
## SECTION 4: First aid measures

· **4.1 Description of first aid measures**
· **General information:** Immediately remove any clothing soiled by the product.
· **After inhalation:** Supply fresh air; consult doctor in case of complaints.
· **After skin contact:** Immediately rinse with water.
· **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
· **After swallowing:** If symptoms persist consult doctor.

(Contd. on page 4)

# Safety data sheet
## according to 1907/2006/EC, Article 31



(Contd. of page 3)

· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
· **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

* 
## SECTION 5: Firefighting measures

· **5.1 Extinguishing media** -
· **Suitable extinguishing agents:** Cool container whit water
· **5.2 Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
· **5.3 Advice for firefighters**
· **Protective equipment:** Mouth respiratory protective device.

* 
## SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
· **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
· **6.3 Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
· **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

* 
## SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**
Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
· **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Keep respiratory protective device available.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· **7.2 Conditions for safe storage, including any incompatibilities**
· **Storage:**
· **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurised containers.
· **Information about storage in one common storage facility:** Not required.
· **Further information about storage conditions:** None.
· **7.3 Specific end use(s)** No further relevant information available.



(Contd. on page 5)

# Safety data sheet
## according to 1907/2006/EC, Article 31

*Printing date 08.12.2023* *Version number 1* *Revision: 08.12.2023*

***Trade name: Aerosol Kupfer-Gold-Effekt***

(Contd. of page 4)

* 

## SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

| · **Ingredients with limit values that require monitoring at the workplace:** | |
|---|---|
| **1330-20-7 xylene, mixture of isomers** | |
| WEL | Short-term value: 441 mg/m³, 100 ppm<br>Long-term value: 220 mg/m³, 50 ppm<br>Sk; BMGV |
| **106-97-8 butane (containing ≤0,1 % butadiene (203-450-8))** | |
| WEL | Short-term value: 1810 mg/m³, 750 ppm<br>Long-term value: 1450 mg/m³, 600 ppm<br>Carc (if more than 0.1% of buta-1.3-diene) |
| **100-41-4 ethylbenzene** | |
| WEL | Short-term value: 552 mg/m³, 125 ppm<br>Long-term value: 441 mg/m³, 100 ppm<br>Sk |
| **80-62-6 methyl methacrylate** | |
| WEL | Short-term value: 416 mg/m³, 100 ppm<br>Long-term value: 208 mg/m³, 50 ppm |

| · **Ingredients with biological limit values:** | |
|---|---|
| **1330-20-7 xylene, mixture of isomers** | |
| BMGV | 650 mmol/mol creatinine<br>Medium: urine<br>Sampling time: post shift<br>Parameter: methyl hippuric acid |

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**
· **Appropriate engineering controls** No further data; see section 7.
· **Individual protection measures, such as personal protective equipment**
· **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.
· **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

· **Hand protection**
Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 6)

# Safety data sheet
## according to 1907/2006/EC, Article 31

Printing date 08.12.2023 Version number 1 Revision: 08.12.2023

**Trade name: Aerosol Kupfer-Gold-Effekt**

(Contd. of page 5)

· **Penetration time of glove material**
Gloves must be changed after every contamination.
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
· **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**
butyl rubber, 0,7mm
· **Eye/face protection**
Safety glasses

Tightly sealed goggles

* 
## SECTION 9: Physical and chemical properties

| | |
|---|---|
| · **9.1 Information on basic physical and chemical properties** | |
| · **General Information** | |
| · **Physical state** | Aerosol |
| · **Colour:** | According to product specification |
| · **Odour:** | Characteristic |
| · **Odour threshold:** | Not determined. |
| · **Melting point/freezing point:** | Undetermined. |
| · **Boiling point or initial boiling point and boiling range** | -44 °C |
| · **Flammability** | Not applicable. |
| · **Lower and upper explosion limit** | |
| · **Lower:** | 1 Vol % (1330-20-7 xylene, mixture of isomers) |
| · **Upper:** | 10.9 Vol % (74-98-6 propane) |
| · **Flash point:** | <0 °C |
| · **Auto-ignition temperature:** | 365 °C (106-97-8 butane (containing ≤ 0,1 % butadiene (203-450-8))) |
| · **Decomposition temperature:** | Not determined. |
| · **pH** | Not determined. |
| · **Viscosity:** | |
| · **Kinematic viscosity** | Not determined. |
| · **Dynamic:** | Not determined. |
| · **Solubility** | |
| · **water:** | Not miscible or difficult to mix. |
| · **Partition coefficient n-octanol/water (log value)** | Not determined. |
| · **Vapour pressure at 20 °C:** | 3,600 hPa (74-98-6 propane) |
| · **Density and/or relative density** | |
| · **Relative density** | 0.82 g/cm³ |
| · **Vapour density** | Not determined. |

| | |
|---|---|
| · **9.2 Other information** | |
| · **Appearance:** | |
| · **Form:** | Aerosol |
| · **Important information on protection of health and environment, and on safety.** | |
| · **Ignition temperature:** | Product is not selfigniting. |
| · **Explosive properties:** | Product is not explosive. However, formation of explosive air/vapour mixtures are possible.<br>Not determined. |

(Contd. on page 7)

# Safety data sheet
## according to 1907/2006/EC, Article 31

*Printing date 08.12.2023* *Version number 1* *Revision: 08.12.2023*

***Trade name: Aerosol Kupfer-Gold-Effekt***

(Contd. of page 6)

| | |
|---|---|
| · **Solvent content:** | |
| · **Organic solvents:** | 86.2 %<br>With propellant gas. Content given by weight. |
| · **VOC (EU)** | (<840g/l)<br>86.05 % |
| · **Solids content:** | 13.9 % |
| · **Change in condition** | |
| · **Evaporation rate** | Not applicable. |

| | |
|---|---|
| · **Information with regard to physical hazard classes** | |
| · **Explosives** | Void |
| · **Flammable gases** | Void |
| · **Aerosols** | Extremely flammable aerosol. Pressurised container: May burst if heated. |
| · **Oxidising gases** | Void |
| · **Gases under pressure** | Void |
| · **Flammable liquids** | Void |
| · **Flammable solids** | Void |
| · **Self-reactive substances and mixtures** | Void |
| · **Pyrophoric liquids** | Void |
| · **Pyrophoric solids** | Void |
| · **Self-heating substances and mixtures** | Void |
| · **Substances and mixtures, which emit flammable gases in contact with water** | Void |
| · **Oxidising liquids** | Void |
| · **Oxidising solids** | Void |
| · **Organic peroxides** | Void |
| · **Corrosive to metals** | Void |
| · **Desensitised explosives** | Void |

## SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.
· **10.2 Chemical stability**
· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
· **10.3 Possibility of hazardous reactions** No dangerous reactions known.
· **10.4 Conditions to avoid** No further relevant information available.
· **10.5 Incompatible materials:** No further relevant information available.
· **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

* 
## SECTION 11: Toxicological information

· **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
· **Acute toxicity** Based on available data, the classification criteria are not met.

| · **LD/LC50 values relevant for classification:** | | |
|---|---|---|
| **ATE (Acute Toxicity Estimates)** | | |
| Oral | LD50 | 10,220 mg/kg |
| Dermal | LD50 | 4,835 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 21.5 mg/l |

| **1330-20-7 xylene, mixture of isomers** | | |
|---|---|---|
| Oral | LD50 | 3,523 mg/kg (rat) |

(Contd. on page 8)

# Safety data sheet
## according to 1907/2006/EC, Article 31

Printing date 08.12.2023 Version number 1 Revision: 08.12.2023

**Trade name: Aerosol Kupfer-Gold-Effekt**

(Contd. of page 7)

| | | |
|---|---|---|
| Dermal | LD50 | 2,000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 11 mg/l (rat)<br>4h |

· **Skin corrosion/irritation** Causes skin irritation.
· **Serious eye damage/irritation** Causes serious eye irritation.
· **STOT-single exposure** May cause respiratory irritation.
· **STOT-repeated exposure** May cause damage to the hearing organs through prolonged or repeated exposure.
· **Aspiration hazard** May be fatal if swallowed and enters airways.
· **11.2 Information on other hazards**

| · **Endocrine disrupting properties** |
|---|
| None of the ingredients is listed. |

* 
## SECTION 12: Ecological information

· **12.1 Toxicity**
· **Aquatic toxicity:** No further relevant information available.
· **12.2 Persistence and degradability** No further relevant information available.
· **12.3 Bioaccumulative potential** No further relevant information available.
· **12.4 Mobility in soil** No further relevant information available.
· **12.5 Results of PBT and vPvB assessment**
· **PBT:** Not applicable.
· **vPvB:** Ikke relevant.
· **12.6 Endocrine disrupting properties**
The product does not contain substances with endocrine disrupting properties.
· **12.7 Other adverse effects**
· **Remark:** Toxic for fish
· **Additional ecological information:**
· **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms

* 
## SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**
· **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**
· **Recommendation:** Disposal must be made according to official regulations.

* 
## SECTION 14: Transport information

| | |
|---|---|
| · **14.1 UN number or ID number** | |
| · **ADR, IMDG, IATA** | UN1950 |
| · **14.2 UN proper shipping name** | |
| · **ADR** | 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS |
| · **IMDG** | AEROSOLS, MARINE POLLUTANT |

(Contd. on page 9)

# Safety data sheet
## according to 1907/2006/EC, Article 31

*Printing date 08.12.2023* *Version number 1* *Revision: 08.12.2023*

***Trade name: Aerosol Kupfer-Gold-Effekt***

(Contd. of page 8)

| | |
|---|---|
| · ***IATA*** | *AEROSOLS, flammable* |
| · ***14.3 Transport hazard class(es)*** | |
| · ***ADR*** | |
| | |
| · ***Class*** | *2 5F Gases.* |
| · ***Label*** | *2.1* |
| · ***IMDG*** | |
| | |
| · ***Class*** | *2.1 Gases.* |
| · ***Label*** | *2.1* |
| · ***IATA*** | |
| | |
| · ***Class*** | *2.1 Gases.* |
| · ***Label*** | *2.1* |
| · ***14.4 Packing group*** | |
| · ***ADR, IMDG, IATA*** | *Void*<br>*not classified* |
| · ***14.5 Environmental hazards:*** | |
| · ***Marine pollutant:*** | *Yes*<br>*Symbol (fish and tree)* |
| · ***Special marking (ADR):*** | *Symbol (fish and tree)* |
| · ***14.6 Special precautions for user*** | *Warning: Gases.* |
| · ***Hazard identification number (Kemler code):*** | *-*<br>*not classified* |
| · ***EMS Number:*** | *F-D,S-U* |
| · ***Segregation groups*** | *(SGG7) Heavy metals and their salts (including their organometallic compounds), (SGG15) powdered metals* |
| · ***Stowage Code*** | *SW1 Protected from sources of heat.*<br>*SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.* |
| · ***Segregation Code*** | *SG69 For AEROSOLS with a maximum capacity of 1 litre:*<br>*Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.*<br>*For AEROSOLS with a capacity above 1 litre:*<br>*Segregation as for the appropriate subdivision of class 2.*<br>*For WASTE AEROSOLS:*<br>*Segregation as for the appropriate subdivision of class 2.* |

(Contd. on page 10)

# Safety data sheet
## according to 1907/2006/EC, Article 31

Printing date 08.12.2023 Version number 1 Revision: 08.12.2023

**Trade name: Aerosol Kupfer-Gold-Effekt**

(Contd. of page 9)

| | |
|---|---|
| · **14.7 Maritime transport in bulk according to IMO instruments** | Not applicable. |
| · **Transport/Additional information:** | |
| · **ADR** | |
| · **Limited quantities (LQ)** | 1L |
| · **Excepted quantities (EQ)** | Code: E0<br>Not permitted as Excepted Quantity |
| · **Transport category** | 2 |
| · **Tunnel restriction code** | D |
| · **IMDG** | |
| · **Limited quantities (LQ)** | 1L |
| · **Excepted quantities (EQ)** | Code: E0<br>Not permitted as Excepted Quantity |
| · **UN "Model Regulation":** | UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS |

* 
## SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
VOC: <840g/l
· **Poisons Act**

· **Regulated explosives precursors**
None of the ingredients is listed.

· **Regulated poisons**
None of the ingredients is listed.

· **Reportable explosives precursors**
None of the ingredients is listed.

· **Reportable poisons**
None of the ingredients is listed.

· **Directive 2012/18/EU**
· **Named dangerous substances - ANNEX I** None of the ingredients is listed.
· **Seveso category**
P3a FLAMMABLE AEROSOLS
E2 Hazardous to the Aquatic Environment
· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

· **National regulations:**

· **Technical instructions (air):**

| Class | Share in % |
|---|---|
| III | 2.5-<5 |
| NK | 50-100 |

· **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.



(Contd. on page 11)

# Safety data sheet
## according to 1907/2006/EC, Article 31

*Printing date 08.12.2023* *Version number 1* *Revision: 08.12.2023*

***Trade name: Aerosol Kupfer-Gold-Effekt***

(Contd. of page 10)

* 
## SECTION 16: Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*
*The safety data sheet may only be passed on to third parties for the manufacturer's brands.*

· **Relevant phrases**
H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
H410 Very toxic to aquatic life with long lasting effects.
EUH018 In use may form flammable/explosive vapour-air mixture.

· **Department issuing SDS:** Product safety department
· **Abbreviations and acronyms:**
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
ATE: Acute toxicity estimate values
Flam. Gas 1A: Flammable gases – Category 1A
Aerosol 1: Aerosols – Category 1
: Aerosols – Category 3
Press. Gas (Comp.): Gases under pressure – Compressed gas
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
· *** Data compared to the previous version altered.**