

# 2K FillClean Series G

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Issue date: 5/30/2017

Revision date: 3/8/2022 update 01/13/2023

Supersedes: 7/31/2019

Version: 2.0

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Product name : 2K FillClean Series G  
Product code : 3680086 / REZ190

#### 1.2. Recommended use and restrictions on use

Recommended use : Automotive refinish

#### 1.3. Supplier

##### Manufacturer

Peter Kwasny GmbH  
96 Heibronner Str.  
Gundelsheim, 74831 - Germany  
T 49(0) 6269-95-20

##### Distributor

Peter Kwasny Inc.  
62-64 Enter Lane  
Islandia, NY 11749  
T 1-844-726-6330 (toll free North America)

##### Distributor

Peter Kwasny Spraypaint Canada Inc  
40 University Avenue, Suite 904  
Toronto, ON M5J 1T1

#### 1.4. Emergency telephone number

Emergency number : 352-323-3500 (24h / 7 days a week)

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS classification

Flam. Aerosol 1  
Press. Gas (Liq.)  
Eye Irrit. 2A  
Skin Sens. 1  
Carc. 2  
Repr. 2  
STOT SE 3  
Simple Asphy

#### 2.2. GHS Label elements, including precautionary statements

##### GHS labelling

Hazard pictograms (GHS) :



Signal word (GHS) :

Danger

Hazard statements (GHS) :

Extremely flammable aerosol.  
Contains gas under pressure; may explode if heated.

# 2K FillClean Series G

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Precautionary statements (GHS)	<p>May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May displace oxygen and cause rapid suffocation</p> <p>: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash hands, forearms and face thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.</p>
--------------------------------	---

### 2.3. Other hazards which do not result in classification

Other hazards which do not result in classification : Contact with the liquefied gas may cause frostbite.

### 2.4. Unknown acute toxicity

Not applicable

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
Dimethyl ether	Dimethyl ether Methane, oxybis- / Methyl ether / Wood ether / Methoxymethane / Methane, 1,1'-oxybis- / DIMETHYL ETHER / Oxybismethane / Dimethyl oxide / Butylene	CAS-No.: 115-10-6	30 – 60
Ethyl acetate	Ethyl acetate Acetic acid, ethyl ester / Ethyl ethanoate / ETHYL ACETATE	CAS-No.: 141-78-6	10 – 30

# 2K FillClean Series G

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Name	Chemical name / Synonyms	Product identifier	%
n-Butyl acetate	n-Butyl acetate 1-Butyl acetate / Butyl acetate, n- / Normal butyl acetate / Butyl acetate / BUTYL ACETATE / Acetic acid, n-butyl ester / Acetic acid, butyl ester / Butyl ethanoate / Acetato de n-butilo	CAS-No.: 123-86-4	7 – 13
Hexamethylene diisocyanate homopolymer	Hexamethylene diisocyanate homopolymer 1,6-Diisocyanatohexane homopolymer / Hexamethylene diisocyanate, oligomers / Hexane, 1,6-diisocyanato-, homopolymer / Isocyanic acid, hexamethylene ester, polymers / Hexamethylene diisocyanate polymer / HDI polyisocyanate / Poly(hexamethylene diisocyanate) / Polymeric hexamethylene diisocyanate / HDI oligomers / HDI oligomers, isocyanurate	CAS-No.: 28182-81-2	7 – 13
Solvent naphtha, petroleum, light aromatic	Solvent naphtha, petroleum, light aromatic Solvent naphtha (petroleum), light aromatic / Light aromatic solvent naphtha / Aromatic 100 / Hydrocarbons, C9, aromatics / Aromatic naphtha, type I / Solvent naphtha, petroleum, light aromatic- low boiling point hydrogen treated naphtha / Light aromatic solvent naphtha (petroleum) (C8-10) / Solvent naphtha, petroleum, light aromatic (A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8-10 and boiling in the range of approximately 135-210°C.) / Solvent naphtha (petroleum), light aromatic; Low boiling point naphtha - unspecified [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).] / Solvent naphtha (petroleum), light aromatic, hydrotreated	CAS-No.: 64742-95-6	1 – 5
Xylenes (o-, m-, p- isomers)	Xylenes (o-, m-, p- isomers) Benzene, dimethyl- / Dimethylbenzene (mixed isomers) / Xylene / Xylene (all isomers) / Xylene (mixed isomers) / Xylene (o-, m-, p- isomers) / Xylenes / Xylenes (mixed isomers) / Dimethylbenzene / Xylol / Benzene, dimethyl-, mixed isomers / XYLENE / Dimethylbenzenes / Xylene isomers mixture / Dimethylbenzene (2-, 3-, 4-isomers) / Dimethylbenzene (mixed 2-, 3-, 4-isomers) / C8 Disubstituted benzenes / Xylene, mixed isomers / Xylenes (meta-, ortho-, para-) / Xylene (mixture), including m-xylene, o-xylene, p-xylene	CAS-No.: 1330-20-7	0.5 – 1.5
Ethylbenzene	Ethylbenzene Benzene, ethyl- / Phenylethane / ETHYLBENZENE	CAS-No.: 100-41-4	0.1-1

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

# 2K FillClean Series G

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### SECTION 4: First-aid measures

#### 4.1. Description of first aid measures

First-aid measures after inhalation	: If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. Give oxygen or artificial respiration if necessary.
First-aid measures after skin contact	: IF ON SKIN: Wash with plenty of Water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If frostbite occurs thaw frosted parts with lukewarm water. Do not rub affected area. Do not use hot water.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If frostbite occurs thaw frosted parts with lukewarm water. Do not rub affected area. Do not use hot water.
First-aid measures after ingestion	: Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

#### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: May cause irritation to the respiratory tract. May cause drowsiness or dizziness. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Symptoms of oxygen deficiency include respiratory difficulty, headache, dizziness, nausea, unconsciousness or death.
Symptoms/effects after skin contact	: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause an allergic skin reaction. May cause frostbite on contact with the liquefied gas.
Symptoms/effects after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause frostbite on contact with the liquefied gas.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: Suspected of causing cancer. Suspected of damaging fertility or the unborn child.

#### 4.3. Immediate medical attention and special treatment, if necessary

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry chemical powder. Carbon dioxide (CO <sub>2</sub> ).
Unsuitable extinguishing media	: Do not use water jet.

#### 5.2. Specific hazards arising from the chemical

Fire hazard	: Extremely flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon. Oxides of nitrogen. Hydrogen cyanide. Irritating vapours. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours.
Explosion hazard	: Vapours may form explosive mixture with air. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. Ruptured cylinders may rocket.

#### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Move containers away from the fire area if this can be done without risk. DO NOT fight fire when fire reaches explosives. Evacuate area.
Protection during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Use water spray to keep fire-exposed containers cool. Vapours are heavier than air and may spread along floors.

# 2K FillClean Series G

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate every possible source of ignition. Use only non-sparking tools. Use special care to avoid static electric charges.

##### 6.1.1. For non-emergency personnel

No additional information available

##### 6.1.2. For emergency responders

No additional information available

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters.

#### 6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so. Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.

Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

#### 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Hazardous waste due to potential risk of explosion.

Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Take precautionary measures against static discharge. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Do not spray on an open flame or other ignition source. Avoid contact with skin, eyes and clothing. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. When using do not eat, drink or smoke. Handle and open container with care. Use only outdoors or in a well-ventilated area.

Hygiene measures : Take off immediately all contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace. Wash hands, forearms and face thoroughly after handling.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep out of the reach of children. Store locked up. Keep in fireproof place. Store away from direct sunlight or other heat sources. Keep away from clothing and other combustible materials. Do not expose to temperatures exceeding 50 °C/ 122 °F. Protect containers from physical damage. Keep away from incompatible materials. . Store in a dry, cool and well-ventilated place.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

# 2K FillClean Series G

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

2K FillClean Series G	
No additional information available	
Dimethyl ether (115-10-6)	
No additional information available	
Ethyl acetate (141-78-6)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Ethyl acetate
ACGIH OEL TWA [ppm]	400 ppm
Remark (ACGIH)	TLV® Basis: URT & eye irr
Regulatory reference	ACGIH 2020
USA - OSHA - Occupational Exposure Limits	
Local name	Ethyl acetate
OSHA PEL TWA [1]	1400 mg/m <sup>3</sup>
OSHA PEL TWA [2]	400 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - IDLH - Occupational Exposure Limits	
IDLH [ppm]	2000 ppm (10% LEL)
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	1400 mg/m <sup>3</sup>
NIOSH REL TWA [ppm]	400 ppm
n-Butyl acetate (123-86-4)	
USA - ACGIH - Occupational Exposure Limits	
Local name	n-Butyl acetate
ACGIH OEL TWA [ppm]	50 ppm (Butyl acetates, all isomers)
ACGIH OEL STEL [ppm]	150 ppm (Butyl acetates, all isomers)
Remark (ACGIH)	TLV® Basis: Eye & URT irr
Regulatory reference	ACGIH 2020
USA - OSHA - Occupational Exposure Limits	
Local name	n-Butyl-acetate
OSHA PEL TWA [1]	710 mg/m <sup>3</sup>
OSHA PEL TWA [2]	150 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - IDLH - Occupational Exposure Limits	
IDLH [ppm]	1700 ppm (10% LEL)
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	710 mg/m <sup>3</sup>
NIOSH REL TWA [ppm]	150 ppm
NIOSH REL STEL	950 mg/m <sup>3</sup>

# 2K FillClean Series G

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

<b>n-Butyl acetate (123-86-4)</b>	
NIOSH REL STEL [ppm]	200 ppm
<b>Hexamethylene diisocyanate homopolymer (28182-81-2)</b>	
No additional information available	
<b>Solvent naphtha, petroleum, light aromatic (64742-95-6)</b>	
No additional information available	
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH chemical category	Not Classifiable as a Human Carcinogen
<b>USA - ACGIH - Biological Exposure Indices</b>	
BEI	1.5 g/g creatinine Parameter: Methylhippuric acids - Medium: urine - Sampling time: end of shift
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	Xylenes (o-, m-, p-isomers)
OSHA PEL TWA [1]	435 mg/m <sup>3</sup>
OSHA PEL TWA [2]	100 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>Ethylbenzene (100-41-4)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
<b>USA - ACGIH - Biological Exposure Indices</b>	
BEI	0.15 g/g creatinine Parameter: Sum of mandelic acid and phenylglyoxylic acid - Medium: urine - Sampling time: end of shift (nonspecific)
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	Ethyl benzene
OSHA PEL TWA [1]	435 mg/m <sup>3</sup>
OSHA PEL TWA [2]	100 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1 OSHA Annotated Table Z-1
<b>USA - IDLH - Occupational Exposure Limits</b>	
IDLH [ppm]	800 ppm (10% LEL)
<b>USA - NIOSH - Occupational Exposure Limits</b>	
NIOSH REL TWA	435 mg/m <sup>3</sup>
NIOSH REL TWA [ppm]	100 ppm
NIOSH REL STEL	545 mg/m <sup>3</sup>
NIOSH REL STEL [ppm]	125 ppm

### 8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station. Provide readily accessible eye wash stations and safety showers.
Environmental exposure controls	: Avoid release to the environment.

# 2K FillClean Series G

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### 8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

Wear suitable gloves resistant to chemical penetration

#### Eye protection:

Wear eye/face protection

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

#### Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol.
Colour	: Clear
Odour	: Characteristic
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: < -18 °C (-0.4 °F)
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.76 g/cm <sup>3</sup>
Solubility	: No data available
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

### 9.2. Other information

No additional information available



# 2K FillClean Series G

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No dangerous reactions known under normal conditions of use.

#### 10.2. Chemical stability

Stable under normal conditions. Extremely flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

Heat. Sparks. Open flame. Direct sunlight. Overheating. Incompatible materials.

#### 10.5. Incompatible materials

Oxidizing materials. Acids. Alkalis.

#### 10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon. Oxides of nitrogen. Hydrogen cyanide. Irritating vapours.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified.

Acute toxicity (dermal) : Not classified.

Acute toxicity (inhalation) : Not classified.

#### Dimethyl ether (115-10-6)

LC50 inhalation rat	164000 ppm/4h
---------------------	---------------

ATE CA (Gases (except aerosol dispensers and lighters))	164000 ppmv/4h
---	----------------

#### Ethyl acetate (141-78-6)

LD50 dermal rabbit	> 18000 mg/kg
--------------------	---------------

LC50 inhalation rat	4000 ppm/4h
---------------------	-------------

ATE CA (oral)	4934 mg/kg bodyweight
---------------	-----------------------

ATE CA (Gases (except aerosol dispensers and lighters))	4000 ppmv/4h
---	--------------

#### n-Butyl acetate (123-86-4)

LD50 oral rat	10768 mg/kg
---------------	-------------

LD50 dermal rabbit	> 17600 mg/kg
--------------------	---------------

LC50 inhalation rat	0.74 mg/l/4h
---------------------	--------------

ATE CA (oral)	10768 mg/kg bodyweight
---------------	------------------------

#### Hexamethylene diisocyanate homopolymer (28182-81-2)

LD50 oral rat	> 2500 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)
---------------	---

# 2K FillClean Series G

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

<b>Hexamethylene diisocyanate homopolymer (28182-81-2)</b>	
LD50 dermal rat	> 2000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: other:
LC50 inhalation rat	18500 mg/m <sup>3</sup> (Exposure time: 1 h)
ATE CA (Gases (except aerosol dispensers and lighters))	4500 ppmv/4h
ATE CA (vapours)	18.5 mg/l/4h
ATE CA (dust,mist)	1.5 mg/l/4h
<b>Solvent naphtha, petroleum, light aromatic (64742-95-6)</b>	
LD50 oral rat	8400 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	> 6193 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Remarks on results: other:
LC50 inhalation rat	3400 ppm/4h
ATE CA (oral)	8400 mg/kg bodyweight
ATE CA (Gases (except aerosol dispensers and lighters))	3400 ppmv/4h
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
LD50 oral rat	3500 mg/kg
LC50 inhalation rat	29.08 mg/l/4h
ATE CA (oral)	3500 mg/kg bodyweight
ATE CA (Dermal)	1700 mg/kg bodyweight
ATE CA (Gases (except aerosol dispensers and lighters))	4500 ppmv/4h
ATE CA (vapours)	11 mg/l/4h
ATE CA (dust,mist)	1.5 mg/l/4h
<b>Ethylbenzene (100-41-4)</b>	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	15400 mg/kg
LC50 inhalation rat	17.4 mg/l/4h
ATE CA (oral)	3500 mg/kg bodyweight
ATE CA (Dermal)	15400 mg/kg bodyweight
ATE CA (Gases (except aerosol dispensers and lighters))	4500 ppmv/4h
ATE CA (vapours)	17.4 mg/l/4h
ATE CA (dust,mist)	1.5 mg/l/4h

Skin corrosion/irritation	: Not classified.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified.

# 2K FillClean Series G

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Carcinogenicity : Suspected of causing cancer.

<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
IARC group	3 - Not classifiable

<b>Ethylbenzene (100-41-4)</b>	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity
In OSHA Hazard Communication Carcinogen list	Yes

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

STOT-single exposure : May cause drowsiness or dizziness.

<b>Ethyl acetate (141-78-6)</b>	
STOT-single exposure	May cause drowsiness or dizziness.

<b>n-Butyl acetate (123-86-4)</b>	
STOT-single exposure	May cause drowsiness or dizziness.

<b>Hexamethylene diisocyanate homopolymer (28182-81-2)</b>	
STOT-single exposure	May cause respiratory irritation.

<b>Solvent naphtha, petroleum, light aromatic (64742-95-6)</b>	
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.

<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified.

<b>Ethyl acetate (141-78-6)</b>	
LOAEL (oral, rat, 90 days)	3600 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 795.2600 (Subchronic Oral Toxicity Test)
NOAEL (oral, rat, 90 days)	900 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 795.2600 (Subchronic Oral Toxicity Test)

<b>Solvent naphtha, petroleum, light aromatic (64742-95-6)</b>	
NOAEL (oral, rat, 90 days)	600 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)

<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)

<b>Ethylbenzene (100-41-4)</b>	
NOAEL (oral, rat, 90 days)	75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified.

<b>2K FillClean Series G</b>	
Vaporizer	Aerosol

# 2K FillClean Series G

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Symptoms/effects after inhalation	: May cause irritation to the respiratory tract. May cause drowsiness or dizziness. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Symptoms of oxygen deficiency include respiratory difficulty, headache, dizziness, nausea, unconsciousness or death.
Symptoms/effects after skin contact	: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause an allergic skin reaction. May cause frostbite on contact with the liquefied gas.
Symptoms/effects after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause frostbite on contact with the liquefied gas.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: Suspected of causing cancer. Suspected of damaging fertility or the unborn child.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

<b>Dimethyl ether (115-10-6)</b>	
LC50 - Fish [1]	> 4.1 g/l (Exposure time: 96 h - Species: Poecilia reticulata [semi-static])
EC50 - Crustacea [1]	> 4.4 g/l Test organisms (species): Daphnia magna
<b>Ethyl acetate (141-78-6)</b>	
LC50 - Fish [1]	220 – 250 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 - Crustacea [1]	560 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 - Fish [2]	484 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
NOEC (chronic)	2.4 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
<b>n-Butyl acetate (123-86-4)</b>	
LC50 - Fish [1]	100 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
LC50 - Fish [2]	17 – 19 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
<b>Solvent naphtha, petroleum, light aromatic (64742-95-6)</b>	
LC50 - Fish [1]	9.22 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 - Crustacea [1]	6.14 mg/l (Exposure time: 48 h - Species: Daphnia magna)
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
LC50 - Fish [1]	13.4 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 - Crustacea [1]	3.82 mg/l (Exposure time: 48 h - Species: water flea)
LC50 - Fish [2]	2.661 – 4.093 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 - Crustacea [2]	0.6 mg/l (Exposure time: 48 h - Species: Gammarus lacustris)
LOEC (chronic)	3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'
<b>Ethylbenzene (100-41-4)</b>	
LC50 - Fish [1]	11 – 18 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])

# 2K FillClean Series G

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Ethylbenzene (100-41-4)	
EC50 - Crustacea [1]	1.8 – 2.4 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 - Fish [2]	4.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static])
LOEC (chronic)	1.7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC (chronic)	0.96 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC chronic crustacea	0.956 mg/l

### 12.2. Persistence and degradability

2K FillClean Series G	
Persistence and degradability	Not established.

### 12.3. Bioaccumulative potential

2K FillClean Series G	
Bioaccumulative potential	Not established.

Dimethyl ether (115-10-6)	
Partition coefficient n-octanol/water	-0.18

Ethyl acetate (141-78-6)	
BCF - Fish [1]	30
Partition coefficient n-octanol/water	0.6

n-Butyl acetate (123-86-4)	
Partition coefficient n-octanol/water	1.81 (at 23 °C)

Xylenes (o-, m-, p- isomers) (1330-20-7)	
BCF - Fish [1]	0.6 – 15
Partition coefficient n-octanol/water	2.77 – 3.15

Ethylbenzene (100-41-4)	
BCF - Fish [1]	15
Partition coefficient n-octanol/water	3.2

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Other information : No other effects known.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. Container under pressure. Do not drill or burn even after use.

Additional information : Flammable vapours may accumulate in the container.

# 2K FillClean Series G

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### SECTION 14: Transport information

In accordance with DOT / TDG

#### 14.1. UN number

DOT NA No : UN1950  
UN-No. (TDG) : UN1950

#### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Aerosols

#### 14.3. Transport hazard class(es)

##### DOT

Transport hazard class(es) (DOT) : 2.1  
Hazard labels (DOT) : 2.1



##### TDG

Transport hazard class(es) (TDG) : 2.1  
Hazard labels (TDG) : 2.1



#### 14.4. Packing group

Packing group (DOT) : Not applicable  
Packing group (TDG) : Not applicable

#### 14.5. Environmental hazards

Other information : No supplementary information available.

#### 14.6. Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.

##### DOT

UN-No.(DOT) : UN1950  
DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.  
DOT Packaging Exceptions (49 CFR 173.xxx) : 306  
DOT Packaging Non Bulk (49 CFR 173.xxx) : None  
DOT Packaging Bulk (49 CFR 173.xxx) : None  
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg  
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg  
DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.  
DOT Vessel Stowage Other : 25 - Protected from sources of heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

# 2K FillClean Series G

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

<b>TDG</b>	
UN-No. (TDG)	: UN1950
TDG Special Provisions	: 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment), 107 - (1) These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL. (2) Subsection (1) does not apply to self-defence spray.
Explosive Limit and Limited Quantity Index	: 1 L
Excepted quantities (TDG)	: E0
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 75 L
Emergency Response Guide (ERG) Number	: 126

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

### 15.2. International regulations

No additional information available

### 15.3. US State regulations

**⚠ WARNING:** This product can expose you to Ethylbenzene, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## SECTION 16: Other information

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Revision date	: 03/08/2022
Other information	: None.
Prepared by	: Nexreg Compliance Inc. <a href="http://www.Nexreg.com">www.Nexreg.com</a>



### Full text of H-statements

Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Aerosol 1	Flammable aerosols, Category 1

# 2K FillClean Series G

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Full text of H-statements	
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
Repr. 2	Reproductive toxicity, Category 2
Simple Asphy	Simple Asphyxiant
Skin Sens. 1	Skin sensitisation, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis

Indication of changes:
SDS update . GHS classification.

SDS HazCom 2012 - WHMIS 2015 (Nexreg) 2021

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.