according to 1907/2006/EC, Article 31

Printing date 12.12.2022

Version number 2 (replaces version 1)

Revision: 12.12.2022

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Auto-K Feinspachtel styrolreduziert
- · valid for: REZ892
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- No further relevant information available.
- · Application of the substance / the mixture Knife filler/ Surfacer

#### · 1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier: Peter Kwasny GmbH
- Heilbronner Štr. 96 D-74831 Gundelsheim Tel.: +49 (0) 6269-95-20 Fax: +49 (0) 6269 95 70 E-mail: labor@kwasny.de www.kwasny.de
- 1.4 Emergency telephone number: Emergency telephone number: +49 6269 95 20 National Poisons Information Service, Birmingham: 844 892 0111

#### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

· 2.2 Label elements

#### · Labelling according to Regulation (EC) No 1272/2008

- The product is classified and labelled according to the GB CLP regulation.
- · Hazard pictograms



· Signal word Warning

• Hazard-determining components of labelling: Styrene

(Contd. on page 2)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.12.2022

Revision: 12.12.2022

#### Trade name: Auto-K Feinspachtel styrolreduziert

	(Contd. of page 1)		
maleic anhydride			
	of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-		
methylphenyl)am			
· Hazard stateme			
	le liquid and vapour.		
H315 Causes sl			
	erious eye irritation.		
	e an allergic skin reaction.		
	d of damaging the unborn child.		
	e damage to the hearing organs through prolonged or repeated exposure.		
· Precautionary s			
P101	If medical advice is needed, have product container or label at hand.		
P102	Keep out of reach of children.		
P103	Read carefully and follow all instructions.		
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.		
P260	Do not breathe dust/fume/gas/mist/vapours/spray.		
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.		
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or			
	shower].		
P305+P351+P33	8 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if		
	present and easy to do. Continue rinsing.		
P501	Dispose of contents/container in accordance with local/regional/national/international		
	regulations.		
· 2.3 Other hazards			
· Results of PBT and vPvB assessment			
· PBT: Not applicable			

· **PBT:** Not applicable.

· vPvB: Not applicable.

### **SECTION 3: Composition/information on ingredients**

#### · 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

<ul> <li>Dangerous components:</li> </ul>		
CAS: 100-42-5 EINECS: 202-851-5 Reg.nr.: 01-2119457861-32	Styrene Flam. Liq. 3, H226;  Repr. 2, H361d; STOT RE 1, H372; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	5-<10%
CAS: 25013-15-4 EINECS: 246-562-2 Reg.nr.: 01-2119622074-50	vinyltoluene Flam. Liq. 3, H226;  Asp. Tox. 1, H304;  Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412	2.5-<10%
CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46	Ethyl acetate Flam. Liq. 2, H225; () Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	<2.5%
EC number: 911-490-9	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]- Eye Dam. 1, H318;  Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥0.1-<1%
		(Contd. on page

according to 1907/2006/EC, Article 31

Printing date 12.12.2022

Version number 2 (replaces version 1)

Revision: 12.12.2022

Trade name: Auto-K Feinspachtel styrolreduziert

CAS: 108-31-6       maleic anhydride       ≥0.001-<0.1%         EINECS: 203-571-6       Resp. Sens. 1, H334; STOT RE 1, H372; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1A, H317, EUH071       Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.001 %		potassium 2-ethylhexanoate 🗞 Repr. 2, H361d; 🔶 Eye Dam. 1, H318; 🚸 Skin Irrit. 2, H315	(Contd. of page 2) <1%
	EINECS: 203-571-6 Reg.nr.: 01-2119472428-31	♦ Resp. Sens. 1, H334; STOT RE 1, H372; ♦ Skin Corr. 1B, H314; Eye Dam. 1, H318; ♦ Acute Tox. 4, H302; Skin Sens. 1A, H317, EUH071	≥0.001-<0.1%

#### **SECTION 4: First aid measures**

· 4.1 Description of first aid measures

· General information: Immediately remove any clothing soiled by the product.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately rinse with water.

· After eye contact:

- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

#### **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away.
  6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
  6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

(Contd. on page 4)

GB

according to 1907/2006/EC, Article 31

Printing date 12.12.2022

#### Version number 2 (replaces version 1)

Revision: 12.12.2022

#### Trade name: Auto-K Feinspachtel styrolreduziert

(Contd. of page 3)

#### **SECTION 7: Handling and storage**

• **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.

 Information about fire - and explosion protection: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.

• 7.2 Conditions for safe storage, including any incompatibilities

Storage:

· Requirements to be met by storerooms and receptacles: No special requirements.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.

· Storage class: 3

• 7.3 Specific end use(s) No further relevant information available.

#### **SECTION 8: Exposure controls/personal protection**

#### · 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

## 100-42-5 Styrene WEL Short-term value: 1080 mg/m³, 250 ppm

Long-term value: 430 mg/m³, 100 ppm

#### 141-78-6 Ethyl acetate

WEL Short-term value: 1468 mg/m<sup>3</sup>, 400 ppm Long-term value: 734 mg/m<sup>3</sup>, 200 ppm

#### 108-31-6 maleic anhydride

WEL Short-term value: 3 mg/m<sup>3</sup> Long-term value: 1 mg/m<sup>3</sup> Sen

· Additional information: The lists valid during the making were used as basis.

#### · 8.2 Exposure controls

- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes.

Avoid contact with the eyes and skin.

#### **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 5)

GB

according to 1907/2006/EC, Article 31

Version number 2 (replaces version 1)

Revision: 12.12.2022

Trade name: Auto-K Feinspachtel styrolreduziert

#### Hand protection

Printing date 12.12.2022

(Contd. of page 4)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Eye/face protection



Tightly sealed goggles

## **SECTION 9: Physical and chemical properties**

$^{\cdot}$ 9.1 Information on basic physical and chemical p	roperties
· General Information	
· Physical state	Fluid
· Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
<ul> <li>Melting point/freezing point:</li> </ul>	Undetermined.
Boiling point or initial boiling point and boiling	
range	145.2 °C (100-42-5 Styrene)
· Flammability	Flammable.
· Lower and upper explosion limit	
Lower:	Not determined.
· Upper:	Not determined.
Flash point:	31 °C (DIN EN ISO 1523:2002)
Ignition temperature:	480 °C (DIN 51794)
Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic at 20 °C:	80,000-90,000 mPas
Solubility	
· water:	Not miscible or difficult to mix.
<ul> <li>Partition coefficient n-octanol/water (log value)</li> </ul>	Not determined.
Vapour pressure at 20 °C:	6 hPa (100-42-5 Styrene)
Density and/or relative density	
Density at 20 °C:	1.786 g/cm³ (DIN EN ISO 2811-1)
· Relative density	Not determined.
· Vapour density	Not determined.
• 9.2 Other information	
· Appearance:	
· Form:	Fluid
	(Contd. on page

according to 1907/2006/EC, Article 31

Printing date 12.12.2022

Version number 2 (replaces version 1)

Revision: 12.12.2022

Trade name: Auto-K Feinspachtel styrolreduziert

	(Contd. of page
Important information on protection of healt	th and
environment, and on safety.	
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosiv air/vapour mixtures are possible.
Solvent content:	
VOC (EC)	1.50 %
Solids content (weight-%):	84.9 %
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical hazard cl	asses
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flamma	able
gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

#### **SECTION 10: Stability and reactivity**

• **10.1 Reactivity** No further relevant information available.

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

#### **SECTION 11: Toxicological information**

- $\cdot$  11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Based on available data, the classification criteria are not met.
- · Skin corrosion/irritation Causes skin irritation.
- Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- **Reproductive toxicity** Suspected of damaging the unborn child.
- **STOT-repeated exposure** May cause damage to the hearing organs through prolonged or repeated exposure.

(Contd. on page 7)

according to 1907/2006/EC, Article 31

Printing date 12.12.2022

#### Version number 2 (replaces version 1)

Revision: 12.12.2022

(Contd. of page 6)

List II

Trade name: Auto-K Feinspachtel styrolreduziert

## 11.2 Information on other hazards Endocrine disrupting properties

128-37-0 Butylated hydroxytoluene

#### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) : hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

#### **SECTION 13: Disposal considerations**

#### · 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number		
ADR, IMDG, IATA	UN3269	
14.2 UN proper shipping name		
ADR	UN3269 POLYESTER RESIN KIT	
IMDG, IATA	POLYESTER RESIN KIT	
14.3 Transport hazard class(es)		
ADR		
Class	3 (F3) Flammable liquids.	

according to 1907/2006/EC, Article 31

Printing date 12.12.2022

Version number 2 (replaces version 1)

Revision: 12.12.2022

Trade name: Auto-K Feinspachtel styrolreduziert

	(Contd. of page 7)
·Label	3
· IMDG, IATA	
· Class	3 Flammable liquids.
·Label	3
<ul> <li>· 14.4 Packing group</li> <li>· ADR, IMDG, IATA</li> </ul>	III
· 14.5 Environmental hazards:	Not applicable.
<ul> <li>14.6 Special precautions for user</li> <li>Hazard identification number (Kemler code):</li> <li>EMS Number:</li> <li>Stowage Category</li> </ul>	Warning: Flammable liquids. 30 F-E, <u>S-E</u> A
• 14.7 Maritime transport in bulk according to IMC	
instruments	Not applicable.
· Transport/Additional information:	
<ul> <li>ADR</li> <li>Limited quantities (LQ)</li> <li>Transport category</li> <li>Tunnel restriction code</li> </ul>	5L 3 E
<ul> <li>IMDG</li> <li>Limited quantities (LQ)</li> </ul>	5L
· UN "Model Regulation":	UN 3269 POLYESTER RESIN KIT, 3, III

#### **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

· National regulations:

Additional classification according to Decree on Hazardous Materials, Annex II:

Class Share in %

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H225 Highly flammable liquid and vapour.

(Contd. on page 9)

GB

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.12.2022

Version number 2 (replaces version 1)

Revision: 12.12.2022

Trade name: Auto-K Feinspachtel styrolreduziert

		(Contd. of page 8)	
H226	Flammable liquid and vapour.		
H302	Harmful if swallowed.		
H304	May be fatal if swallowed and enters airways.		
H314	Causes severe skin burns and eye damage.		
H315	Causes skin irritation.		
H317	May cause an allergic skin reaction.		
H318	Causes serious eye damage.		
H319	Causes serious eye irritation.		
H332	Harmful if inhaled.		
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.		
H335	May cause respiratory irritation.		
H336	May cause drowsiness or dizziness.		
H361d	Suspected of damaging the unborn child.		
H372	Causes damage to organs through prolonged or repeated exposure.		
H412	Harmful to aquatic life with long lasting effects.		
	6 Repeated exposure may cause skin dryness or cracking.		
	1 Corrosive to the respiratory tract.		
	ication according to Regulation (EC) No 1272/2008	hatanaa data aaaandina ta	
	issification of the mixture is generally based on the calculation method using su	ibstance data according to	
	tion (EC) No 1272/2008.		
	riations and acronyms:	ant Concerning the Internetic set	
	cord relatif au transport international des marchandises dangereuses par route (European Agreem of Dangerous Goods by Road)	ient Concerning the International	
	ternational Maritime Code for Dangerous Goods		
	ernational Air Transport Association		
	obally Harmonised System of Classification and Labelling of Chemicals		
	European Inventory of Existing Commercial Chemical Substances		
	European List of Notified Chemical Substances emical Abstracts Service (division of the American Chemical Society)		
	latile Organic Compounds (USA, EU)		
	sistent, Bioaccumulative and Toxic		
	ry Persistent and very Bioaccumulative		
	. 2: Flammable liquids – Category 2		
	ι. 3: Flammable liquids – Category 3 x. 4: Acute toxicity – Category 4		
	r. 1B: Skin corrosion/irritation – Category 1B		
	2: Skin corrosion/irritation – Category 2		
	1. 1: Serious eye damage/eye irritation – Category 1		
	2: Serious eye damage/eye irritation – Category 2		
•	ns. 1: Respiratory sensitisation – Category 1 s. 1: Skin sensitisation – Category 1		
	s. 1A: Skin sensitisation – Category 1A		
	Repr. 2: Reproductive toxicity – Category 2		
STOT SE	STOT SE 3: Specific target organ toxicity (single exposure) – Category 3		
	STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1		
	STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration bazard – Category 1		
	Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3		
	compared to the previous version altered.		
	· · · · · · · · · · · · · · · · · · ·	GB	