

2K DTS Filler Medium Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Issue date: 6/19/2017

Revision date: 4/5/2022 update 01/13/2023

Supersedes: 7/31/2019

Version: 2.1

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : 2K DTS Filler Medium Gray
Product code : 3684262 / REZ934

1.2. Recommended use and restrictions on use

Recommended use : Automotive refinish

1.3. Supplier

Manufacturer

Peter Kwasny GmbH
96 Heibronner Str.
Gundelsheim, 74831 - Germany
T 49(0) 6269-95-20

Distributor

Peter Kwasny Inc.
62-64 Enter Lane
Islandia, NY 11749
T 1-844-726-6330 (toll free North America)

Distributor

Peter Kwasny Spraypaint Canada Inc
40 University Avenue, Suite 904
Toronto, ON M5J 1T1

1.4. Emergency telephone number

Emergency number : 352-323-3500 (24h / 7 days a week)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS classification

Flam. Aerosol 1
Press. Gas (Liq.)
Skin Irrit. 2
Eye Irrit. 2A
Skin Sens. 1
Carc. 2
Repr. 2
STOT SE 3
STOT RE 2
Simple Asphy

2.2. GHS Label elements, including precautionary statements

GHS labelling

Hazard pictograms (GHS) :



Signal word (GHS) :

Danger

2K DTS Filler Medium Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Hazard statements (GHS)	: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs (hearing organs) through prolonged or repeated exposure. May displace oxygen and cause rapid suffocation
Precautionary statements (GHS)	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Wash hands, forearms and face thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

no additional information available

2.4. Unknown acute toxicity

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
Dimethyl ether	Dimethyl ether Methane, oxybis- / Methyl ether Dimethyl oxide	CAS-No.: 115-10-6	15 – 40
n-Butyl acetate	n-Butyl acetate 1-Butyl acetate	CAS-No.: 123-86-4	5 – 10

2K DTS Filler Medium Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Name	Chemical name / Synonyms	Product identifier	%
Acetone	Acetone Dimethyl ketone / 2-Propanone	CAS-No.: 67-64-1	5 – 10
Xylenes (o-, m-, p- isomers)	Xylenes (o-, m-, p- isomers) Benzene, dimethyl- / Xylene / Xylene (all isomers) / Xylene (mixed isomers)	CAS-No.: 1330-20-7	5 – 10
Titanium Dioxide	Titanium Dioxide C.I. 77891 / C.I. Pigment White 6 / Titanium oxide (TiO ₂) / CI 77891 / Titanium(IV) oxide / C.I. Pigment White 7 / Pigment White 6 / Titanium dioxide nanoparticles / Titanium oxide / Titanium dioxide(2)	CAS-No.: 13463-67-7	3 – 7
Hexamethylene diisocyanate homopolymer	Hexamethylene diisocyanate homopolymer 1,6-Diisocyanatohexane homopolymer / Hexamethylene diisocyanate, oligomers / Hexane, 1,6- diisocyanato-, homopolymer / Isocyanic acid, hexamethylene ester, polymers / Hexamethylene diisocyanate polymer / HDI polyisocyanate / Poly(hexamethylene diisocyanate) / Polymeric hexamethylene diisocyanate / HDI oligomers / HDI oligomers, isocyanurate	CAS-No.: 28182-81-2	1 – 5
Bisphenol A-epichlorohydrin polymer	Bisphenol A-epichlorohydrin polymer Bisphenol A-epichlorohydrin, reaction product / Reaction product: bisphenol A, epichlorohydrin epoxy resin / Reaction product: bisphenol-A-(epichlorohydrin); epoxy resin (number average molecular weight ≤ 700)	CAS-No.: 25068-38-6	1 – 5
Methyl isoamyl ketone	Methyl isoamyl ketone Hexan-2-one, 5-methyl- / 2-Hexanone, 5-methyl- / Isoamyl methyl ketone / Isopentyl methyl ketone	CAS-No.: 110-12-3	1 – 5
Ethylbenzene	Ethylbenzene Benzene, ethyl- / Phenylethane / ETHYLBENZENE	CAS-No.: 100-41-4	1 – 5
Propylene glycol monomethyl ether acetate	Acetate, 1-methoxy-2-propyl / Acetic acid, 2-methoxy- 1-methylethyl ester	CAS-No.: 108-65-6	1 – 5
Zinc oxide (ZnO)	Zinc oxide (ZnO) Zinc oxide	CAS-No.: 1314-13-2	0.5 - 1.5

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. Give oxygen or artificial respiration if necessary.
First-aid measures after skin contact	: IF ON SKIN: Wash with plenty of Water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

2K DTS Filler Medium Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Symptoms/effects after inhalation	: May cause irritation to the respiratory tract. May cause drowsiness or dizziness. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Symptoms of oxygen deficiency include respiratory difficulty, headache, dizziness, nausea, unconsciousness or death.
Symptoms/effects after skin contact	: Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs (hearing organs) through prolonged or repeated exposure.

4.3. Immediate medical attention and special treatment, if necessary

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	: Do not use water jet.

5.2. Specific hazards arising from the chemical

Fire hazard	: Extremely flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon. irritating vapours. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours.
Explosion hazard	: Vapours may form explosive mixture with air. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. Ruptured cylinders may rocket.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: DO NOT fight fire when fire reaches explosives. Evacuate area. Move containers away from the fire area if this can be done without risk.
Protection during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Use water spray to keep fire-exposed containers cool. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate every possible source of ignition. Use only non-sparking tools. Use special care to avoid static electric charges.
------------------	---

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters.

2K DTS Filler Medium Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

6.3. Methods and material for containment and cleaning up

- For containment : Stop leak if safe to do so. Remove all sources of ignition. Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.
- Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Hazardous waste due to potential risk of explosion.
- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Use only non-sparking tools. Take precautionary measures against static discharge. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid contact with skin, eyes and clothing. Do not breathe dust/fume/gas/mist/vapours/spray. Do not swallow. When using do not eat, drink or smoke. Handle and open container with care. Use only outdoors or in a well-ventilated area.
- Hygiene measures : Take off immediately all contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace. Wash hands, forearms and face thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed.
- Storage conditions : Keep out of the reach of children. Store locked up. Keep in fireproof place. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store away from direct sunlight or other heat sources. Protect containers from physical damage. Store in a dry, cool and well-ventilated place.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2K DTS Filler Medium Gray	
No additional information available	
Dimethyl ether (115-10-6)	
No additional information available	
n-Butyl acetate (123-86-4)	
USA - ACGIH - Occupational Exposure Limits	
Local name	n-Butyl acetate
ACGIH OEL TWA [ppm]	50 ppm (Butyl acetates, all isomers)
ACGIH OEL STEL [ppm]	150 ppm (Butyl acetates, all isomers)
Remark (ACGIH)	TLV® Basis: Eye & URT irr
Regulatory reference	ACGIH 2020

2K DTS Filler Medium Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

n-Butyl acetate (123-86-4)	
USA - OSHA - Occupational Exposure Limits	
Local name	n-Butyl-acetate
OSHA PEL TWA [1]	710 mg/m ³
OSHA PEL TWA [2]	150 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - IDLH - Occupational Exposure Limits	
IDLH [ppm]	1700 ppm (10% LEL)
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	710 mg/m ³
NIOSH REL TWA [ppm]	150 ppm
NIOSH REL STEL	950 mg/m ³
NIOSH REL STEL [ppm]	200 ppm
Acetone (67-64-1)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	250 ppm
ACGIH OEL STEL [ppm]	500 ppm
ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA - ACGIH - Biological Exposure Indices	
BEI	25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift (nonspecific)
USA - OSHA - Occupational Exposure Limits	
OSHA PEL TWA [1]	2400 mg/m ³
OSHA PEL TWA [2]	1000 ppm
USA - IDLH - Occupational Exposure Limits	
IDLH [ppm]	2500 ppm (10% LEL)
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	590 mg/m ³
NIOSH REL TWA [ppm]	250 ppm
Xylenes (o-, m-, p- isomers) (1330-20-7)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA - ACGIH - Biological Exposure Indices	
BEI	1.5 g/g creatinine Parameter: Methylhippuric acids - Medium: urine - Sampling time: end of shift
USA - OSHA - Occupational Exposure Limits	
Local name	Xylenes (o-, m-, p-isomers)
OSHA PEL TWA [1]	435 mg/m ³
OSHA PEL TWA [2]	100 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

2K DTS Filler Medium Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Titanium Dioxide (13463-67-7)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Titanium dioxide
ACGIH OEL TWA	10 mg/m ³
Remark (ACGIH)	TLV® Basis: LRT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
ACGIH chemical category	Not Classifiable as a Human Carcinogen
Regulatory reference	ACGIH 2020
USA - OSHA - Occupational Exposure Limits	
Local name	Titanium dioxide (Total dust)
OSHA PEL TWA [1]	15 mg/m ³ (total dust)
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - IDLH - Occupational Exposure Limits	
IDLH	5000 mg/m ³
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	2.4 mg/m ³ (CIB 63-fine) 0.3 mg/m ³ (CIB 63-ultrafine, including engineered nanoscale)
Hexamethylene diisocyanate homopolymer (28182-81-2)	
No additional information available	
Bisphenol A-epichlorohydrin polymer (25068-38-6)	
No additional information available	
Methyl isoamyl ketone (110-12-3)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	20 ppm
ACGIH OEL STEL [ppm]	50 ppm
USA - OSHA - Occupational Exposure Limits	
OSHA PEL TWA [1]	475 mg/m ³
OSHA PEL TWA [2]	100 ppm
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	240 mg/m ³
NIOSH REL TWA [ppm]	50 ppm
Ethylbenzene (100-41-4)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
USA - ACGIH - Biological Exposure Indices	
BEI	0.15 g/g creatinine Parameter: Sum of mandelic acid and phenylglyoxylic acid - Medium: urine - Sampling time: end of shift (nonspecific)
USA - OSHA - Occupational Exposure Limits	
Local name	Ethyl benzene

2K DTS Filler Medium Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Ethylbenzene (100-41-4)	
OSHA PEL TWA [1]	435 mg/m ³
OSHA PEL TWA [2]	100 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1 OSHA Annotated Table Z-1
USA - IDLH - Occupational Exposure Limits	
IDLH [ppm]	800 ppm (10% LEL)
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	435 mg/m ³
NIOSH REL TWA [ppm]	100 ppm
NIOSH REL STEL	545 mg/m ³
NIOSH REL STEL [ppm]	125 ppm
Propylene glycol monomethyl ether acetate (108-65-6)	
No additional information available	
Zinc oxide (ZnO) (1314-13-2)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Zinc oxide
ACGIH OEL TWA	2 mg/m ³ (respirable particulate matter)
ACGIH OEL STEL	10 mg/m ³ (respirable particulate matter)
Remark (ACGIH)	TLV® Basis: Metal fume fever
Regulatory reference	ACGIH 2021
USA - OSHA - Occupational Exposure Limits	
Local name	Zinc oxide
OSHA PEL TWA [1]	5 mg/m ³ (fume) 15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - IDLH - Occupational Exposure Limits	
IDLH	500 mg/m ³
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	5 mg/m ³ (dust and fume)
NIOSH REL STEL	10 mg/m ³ (fume)
NIOSH REL C	15 mg/m ³ (dust)

8.2. Appropriate engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station. Provide readily accessible eye wash stations and safety showers.
- Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

2K DTS Filler Medium Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Hand protection:
Wear suitable gloves resistant to chemical penetration
Eye protection:
Wear eye/face protection
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol.
Colour	: Grey.
Odour	: Characteristic
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: < -18 °C (-0.4 °F)
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.96 g/cm ³
Solubility	: No data available
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

2K DTS Filler Medium Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

10.2. Chemical stability

Stable under normal conditions. Extremely flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat. Incompatible materials. Sparks. Open flame. Direct sunlight.

10.5. Incompatible materials

Oxidizing materials. Acids. Alkalis.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon. irritating vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified.
Acute toxicity (dermal) : Not classified.
Acute toxicity (inhalation) : Not classified.

Dimethyl ether (115-10-6)

LC50 inhalation rat	164000 ppm/4h
ATE CA (Gases (except aerosol dispensers and lighters))	164000 ppmv/4h

n-Butyl acetate (123-86-4)

LD50 oral rat	10768 mg/kg
LD50 dermal rabbit	> 17600 mg/kg
LC50 inhalation rat	0.74 mg/l/4h
ATE CA (oral)	10768 mg/kg bodyweight

Acetone (67-64-1)

LD50 oral rat	5800 mg/kg bodyweight Animal: rat, Animal sex: female
LD50 dermal rabbit	> 15700 mg/kg
LC50 inhalation rat	76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4
ATE CA (oral)	5800 mg/kg bodyweight

Xylenes (o-, m-, p- isomers) (1330-20-7)

LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	> 4350 mg/kg
LC50 inhalation rat	29.08 mg/l/4h
ATE CA (oral)	3500 mg/kg bodyweight
ATE CA (Dermal)	1700 mg/kg bodyweight

2K DTS Filler Medium Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Xylenes (o-, m-, p- isomers) (1330-20-7)	
ATE CA (Gases (except aerosol dispensers and lighters))	4500 ppmv/4h
ATE CA (vapours)	11 mg/l/4h
ATE CA (dust,mist)	1.5 mg/l/4h
Titanium Dioxide (13463-67-7)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure), Guideline: EPA OPPTS 870.1100 (Acute Oral Toxicity)
LC50 inhalation rat	5.09 mg/l/4h
ATE CA (vapours)	5.09 mg/l/4h
ATE CA (dust,mist)	5.09 mg/l/4h
Hexamethylene diisocyanate homopolymer (28182-81-2)	
LD50 oral rat	> 2500 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)
LD50 dermal rat	> 2000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: other:
LC50 inhalation rat	18500 mg/m ³ (Exposure time: 1 h)
ATE CA (Gases (except aerosol dispensers and lighters))	4500 ppmv/4h
ATE CA (vapours)	18.5 mg/l/4h
ATE CA (dust,mist)	1.5 mg/l/4h
Bisphenol A-epichlorohydrin polymer (25068-38-6)	
LD50 oral rat	11400 mg/kg
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))
LD50 dermal rabbit	20 ml/kg (Toxnet)
ATE CA (oral)	11400 mg/kg bodyweight
ATE CA (Dermal)	23200 mg/kg bodyweight
Methyl isoamyl ketone (110-12-3)	
LD50 oral rat	> 3200 mg/kg
LD50 dermal rabbit	10 ml/kg
LC50 inhalation rat	17.8 mg/l (Exposure time: 6 h)
ATE CA (Dermal)	10000 mg/kg bodyweight
ATE CA (Gases (except aerosol dispensers and lighters))	4500 ppmv/4h
ATE CA (vapours)	17.8 mg/l/4h
ATE CA (dust,mist)	1.5 mg/l/4h

2K DTS Filler Medium Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	15400 mg/kg
LC50 inhalation rat	17.4 mg/l/4h
ATE CA (oral)	3500 mg/kg bodyweight
ATE CA (Dermal)	15400 mg/kg bodyweight
ATE CA (Gases (except aerosol dispensers and lighters))	4500 ppmv/4h
ATE CA (vapours)	17.4 mg/l/4h
ATE CA (dust,mist)	1.5 mg/l/4h
Propylene glycol monomethyl ether acetate (108-65-6)	
LD50 oral rat	8532 mg/kg
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	> 5 g/kg
LC50 inhalation rat	19.596 mg/l 4 h
ATE CA (oral)	8532 mg/kg bodyweight
ATE CA (Gases (except aerosol dispensers and lighters))	4500 ppmv/4h
ATE CA (vapours)	19.596 mg/l/4h
ATE CA (dust,mist)	1.5 mg/l/4h
Zinc oxide (ZnO) (1314-13-2)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 inhalation rat	> 5700 mg/m ³ (Exposure time: 4 h)
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Suspected of causing cancer.
Xylenes (o-, m-, p- isomers) (1330-20-7)	
IARC group	3 - Not classifiable
Bisphenol A-epichlorohydrin polymer (25068-38-6)	
NOAEL (chronic, oral, animal/male, 2 years)	15 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other:MITI, Japanese ministry of international trade and industry, February 1998, Remarks on results: other:Effect type: toxicity (migrated information)

2K DTS Filler Medium Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Bisphenol A-epichlorohydrin polymer (25068-38-6)	
NOAEL (chronic, oral, animal/female, 2 years)	100 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other:MITI, Japanese ministry of international trade and industry, February 1998, Remarks on results: other:Effect type: toxicity (migrated information)
Ethylbenzene (100-41-4)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity
In OSHA Hazard Communication Carcinogen list	Yes
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
Acetone (67-64-1)	
LOAEL (animal/female, F0/P)	11298 mg/kg bodyweight Animal: mouse, Animal sex: female
NOAEL (animal/male, F0/P)	900 mg/kg bodyweight Animal: rat, Animal sex: male, Remarks on results: other:Generation not specified (migrated information)
STOT-single exposure	: May cause drowsiness or dizziness.
n-Butyl acetate (123-86-4)	
STOT-single exposure	May cause drowsiness or dizziness.
Acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.
Xylenes (o-, m-, p- isomers) (1330-20-7)	
STOT-single exposure	May cause drowsiness or dizziness.
Hexamethylene diisocyanate homopolymer (28182-81-2)	
STOT-single exposure	May cause respiratory irritation.
Methyl isoamyl ketone (110-12-3)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: May cause damage to organs (hearing organs) through prolonged or repeated exposure.
Xylenes (o-, m-, p- isomers) (1330-20-7)	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
Ethylbenzene (100-41-4)	
NOAEL (oral, rat, 90 days)	75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Propylene glycol monomethyl ether acetate (108-65-6)	
NOAEL (oral, rat, 90 days)	≥ 1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

2K DTS Filler Medium Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Zinc oxide (ZnO) (1314-13-2)	
LOAEL (dermal, rat/rabbit, 90 days)	75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
NOAEL (oral, rat, 90 days)	31.52 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Aspiration hazard : Not classified.

2K DTS Filler Medium Gray	
Vaporizer	Aerosol

Symptoms/effects after inhalation	: May cause irritation to the respiratory tract. May cause drowsiness or dizziness. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Symptoms of oxygen deficiency include respiratory difficulty, headache, dizziness, nausea, unconsciousness or death.
Symptoms/effects after skin contact	: Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs (hearing organs) through prolonged or repeated exposure.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

Dimethyl ether (115-10-6)	
LC50 - Fish [1]	> 4.1 g/l (Exposure time: 96 h - Species: Poecilia reticulata [semi-static])
EC50 - Crustacea [1]	> 4.4 g/l Test organisms (species): Daphnia magna

n-Butyl acetate (123-86-4)	
LC50 - Fish [1]	100 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
LC50 - Fish [2]	17 – 19 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])

Acetone (67-64-1)	
LC50 - Fish [1]	4.74 – 6.33 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 - Crustacea [1]	10294 – 17704 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 - Fish [2]	6210 – 8120 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 - Crustacea [2]	12600 – 12700 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

Xylenes (o-, m-, p- isomers) (1330-20-7)	
LC50 - Fish [1]	13.4 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 - Crustacea [1]	3.82 mg/l (Exposure time: 48 h - Species: water flea)
LC50 - Fish [2]	2.661 – 4.093 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])

2K DTS Filler Medium Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Xylenes (o-, m-, p- isomers) (1330-20-7)	
EC50 - Crustacea [2]	0.6 mg/l (Exposure time: 48 h - Species: Gammarus lacustris)
LOEC (chronic)	3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'
Titanium Dioxide (13463-67-7)	
LC50 - Fish [1]	155 mg/l Test organisms (species): other:Japanese Medaka
EC50 - Crustacea [1]	19.3 mg/l Test organisms (species): Daphnia magna
EC50 - Other aquatic organisms [1]	> 100 mg/l Test organisms (species):
EC50 - Crustacea [2]	27.8 mg/l Test organisms (species): Daphnia magna
LOEC (chronic)	5 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 2.92 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
Bisphenol A-epichlorohydrin polymer (25068-38-6)	
LC50 - Fish [1]	1.2 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	≈ 2 mg/l Test organisms (species): Daphnia magna
LOEC (chronic)	1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.3 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
Methyl isoamyl ketone (110-12-3)	
LC50 - Fish [1]	159 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
Ethylbenzene (100-41-4)	
LC50 - Fish [1]	11 – 18 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 - Crustacea [1]	1.8 – 2.4 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 - Fish [2]	4.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static])
LOEC (chronic)	1.7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC (chronic)	0.96 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC chronic crustacea	0.956 mg/l
Propylene glycol monomethyl ether acetate (108-65-6)	
LC50 - Fish [1]	161 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 - Crustacea [1]	> 500 mg/l (Exposure time: 48 h - Species: Daphnia magna)
NOEC (chronic)	≥ 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	47.5 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'
Zinc oxide (ZnO) (1314-13-2)	
LC50 - Fish [1]	1.55 mg/l (Exposure time: 96 h - Species: Danio rerio [static])

12.2. Persistence and degradability

2K DTS Filler Medium Gray	
Persistence and degradability	Not established.

2K DTS Filler Medium Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

12.3. Bioaccumulative potential

2K DTS Filler Medium Gray

Bioaccumulative potential	Not established.
---------------------------	------------------

Dimethyl ether (115-10-6)

Partition coefficient n-octanol/water	-0.18
---------------------------------------	-------

n-Butyl acetate (123-86-4)

Partition coefficient n-octanol/water	1.81 (at 23 °C)
---------------------------------------	-----------------

Acetone (67-64-1)

BCF - Fish [1]	0.69
----------------	------

Partition coefficient n-octanol/water	-0.24
---------------------------------------	-------

Xylenes (o-, m-, p- isomers) (1330-20-7)

BCF - Fish [1]	0.6 – 15
----------------	----------

Partition coefficient n-octanol/water	2.77 – 3.15
---------------------------------------	-------------

Methyl isoamyl ketone (110-12-3)

Partition coefficient n-octanol/water	1.88
---------------------------------------	------

Ethylbenzene (100-41-4)

BCF - Fish [1]	15
----------------	----

Partition coefficient n-octanol/water	3.2
---------------------------------------	-----

Propylene glycol monomethyl ether acetate (108-65-6)

Partition coefficient n-octanol/water	0.43
---------------------------------------	------

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : No other effects known.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. Container under pressure. Do not drill or burn even after use.

Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

In accordance with DOT / TDG

14.1. UN number

DOT NA No : UN1950

UN-No. (TDG) : UN1950

2K DTS Filler Medium Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Aerosols

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 2.1

Hazard labels (DOT) : 2.1



TDG

Transport hazard class(es) (TDG) : 2.1

Hazard labels (TDG) : 2.1



14.4. Packing group

Packing group (DOT) : Not applicable

Packing group (TDG) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.

DOT

UN-No.(DOT) : UN1950

DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.

DOT Packaging Exceptions (49 CFR 173.xxx) : 306

DOT Packaging Non Bulk (49 CFR 173.xxx) : None

DOT Packaging Bulk (49 CFR 173.xxx) : None

DOT Quantity Limitations Passenger aircraft/rail (49

CFR 173.27) : 75 kg

DOT Quantity Limitations Cargo aircraft only (49

CFR 175.75) : 150 kg

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

DOT Vessel Stowage Other : 25 - Protected from sources of heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

TDG

UN-No. (TDG) : UN1950

2K DTS Filler Medium Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

TDG Special Provisions : 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment), 107 - (1) These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL.
(2) Subsection (1) does not apply to self-defence spray.

Explosive Limit and Limited Quantity Index : 1 L
Excepted quantities (TDG) : E0
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index : 75 L
Emergency Response Guide (ERG) Number : 126

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

15.2. International regulations

No additional information available

15.3. US State regulations

⚠ WARNING: This product can expose you to Ethylbenzene, which is known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Revision date : 04/05/2022
Other information : None.
Prepared by : Nexreg Compliance Inc.
www.Nexreg.com



Full text of H-statements

Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Aerosol 1	Flammable aerosols, Category 1

2K DTS Filler Medium Gray

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Full text of H-statements	
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
Repr. 2	Reproductive toxicity, Category 2
Simple Asphy	Simple Asphyxiant
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Indication of changes:
SDS update . GHS classification.

SDS HazCom 2012 - WHMIS 2015 (Nexreg) 2021

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.