

# 1K UV Blender

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022  
Issue date: 2019-10-10 Revision date: 2025-10-10 Version: 3.0

### SECTION 1 Identification

#### 1.1. Product identifier

Product form : Mixture  
Product name : 1K UV Blender  
Product code : 3680091 / REZ1050  
Vaporizer : Aerosol

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Automotive refinish

#### 1.4. Supplier's details

##### Manufacturer

Peter Kwasny GmbH  
96 Heibronner Str.  
Gundelsheim, 74831  
Germany  
T 49(0) 6269-95-20

##### Distributor

Peter Kwasny Spraypaint Canada Inc  
40 University Avenue, Suite 904  
Toronto, ON, M5J 1T1  
Canada  
T +1 844-426-6330

##### Distributor

Peter Kwasny, Inc.  
12222 Merit Drive, #130  
Dallas, TX 75251  
USA  
T 1-844-426-6330

#### 1.5. Emergency phone number

Emergency number : North America  
INFOTRAC International +1 (352) 323-5000 24 hr

### SECTION 2 Hazard identification

#### 2.1. Classification of the substance or mixture

##### GHS classification

Aerosol, Category 1  
Serious eye damage/eye irritation, Category 2A  
Specific target organ toxicity – Single exposure, Category 3, Narcosis  
Simple asphyxiant, Category 1

#### 2.2. Label elements

##### GHS labelling

Hazard pictograms (GHS) :



Signal word (GHS) :

Danger

Hazard statements (GHS) :

Extremely flammable aerosol  
Pressurized container; may burst if heated

# 1K UV Blender

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Precautionary statements (GHS)	<p>Causes serious eye irritation May cause drowsiness or dizziness May displace oxygen and cause rapid suffocation</p> <p>: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing dust, fume, gas, mist, vapours, spray. Wash hands, forearms and face thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves, protective clothing, eye protection, face protection If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C). Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.</p>
--------------------------------	---

### 2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

### 2.4. Hazards not otherwise classified

No additional information available

### 2.5. Unknown acute toxicity

Not applicable

## SECTION 3 Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	Conc. (% w/w)
Dimethyl ether	Dimethyl ether Methane, oxybis- / Methyl ether / Wood ether / Methoxymethane / Methane, 1,1'-oxybis- / DIMETHYL ETHER / Oxybismethane / Dimethyl oxide / Dimethylether	CAS-No.: 115-10-6	45 – 70
Ethyl acetate	Ethyl acetate Acetic acid, ethyl ester / Ethyl ethanoate / ETHYL ACETATE	CAS-No.: 141-78-6	30 – 60

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

# 1K UV Blender

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

### SECTION 4 First-aid measures

#### 4.1. Description of necessary first-aid measures

First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Give oxygen or artificial respiration if necessary. Call a POISON CENTER/doctor if you feel unwell.
First-aid measures after skin contact	: IF ON SKIN: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

#### 4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: May cause irritation to the respiratory tract. May cause drowsiness or dizziness. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Symptoms of oxygen deficiency include respiratory difficulty, headache, dizziness, nausea, unconsciousness or death.
Symptoms/effects after skin contact	: May cause skin irritation. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

#### 4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
-----------------------------------	--

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media	: Do not use water jet.

#### 5.2. Specific hazards arising from the chemical

Fire hazard	: Extremely flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon.
Explosion hazard	: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. Vapours may form explosive mixture with air.

#### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Cool closed containers exposed to fire with water spray.
Protection during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).
Other information	: Vapours may be heavier than air and may travel along the ground to a distant ignition source and flash back.

# 1K UV Blender

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

### SECTION 6 Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate every possible source of ignition. Use only non-sparking tools. Use special care to avoid static electric charges.

#### For non-emergency personnel

No additional information available

#### For emergency responders

Environmental precautions : Prevent entry to sewers and public waters.

#### 6.2. Methods and materials for containment and cleaning up

For containment : Stop leak if safe to do so. Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.

Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

For further information refer to section 8: "Exposure controls/personal protection"

### SECTION 7 Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Do not spray on an open flame or other ignition source. Use only outdoors or in a well-ventilated area.

Hygiene measures : Wash contaminated clothing before reuse. Always wash hands after handling the product.

Additional hazards when processed : Do not pierce or burn, even after use. Keep away from sources of ignition - No smoking. Hazardous waste due to potential risk of explosion.

#### 7.2. Conditions for safe storage, including incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep out of the reach of children. Keep container tightly closed. Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place. Store away from direct sunlight or other heat sources. Store in a well-ventilated place.

Specific end uses : Not available.

### SECTION 8 Exposure controls/personal protection

#### 8.1. Control parameters

##### Dimethyl ether (115-10-6)

##### USA - AIHA - Occupational Exposure Limits

WEEL TWA	1000 ppm
----------	----------

##### Ethyl acetate (141-78-6)

##### USA - ACGIH - Occupational Exposure Limits

ACGIH® TLV® TWA	400 ppm
-----------------	---------

# 1K UV Blender

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Ethyl acetate (141-78-6)	
<b>USA - OSHA - Occupational Exposure Limits</b>	
OSHA PEL TWA	1400 mg/m <sup>3</sup>
OSHA PEL TWA	400 ppm
<b>USA - IDLH - Occupational Exposure Limits</b>	
IDLH	2000 ppm (10% LEL)
<b>USA - NIOSH - Occupational Exposure Limits</b>	
NIOSH REL TWA	1400 mg/m <sup>3</sup>
NIOSH REL TWA	400 ppm

### 8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station. Provide readily accessible eye wash stations and safety showers.
Environmental exposure controls	: Avoid release to the environment.

### 8.3. Individual protection measures, such as personal protective equipment

<b>Hand protection:</b>
Wear suitable gloves. Consult glove manufacturer's product information on material suitability and material thickness.
<b>Eye protection:</b>
Wear eye/face protection
<b>Skin and body protection:</b>
Wear suitable protective clothing
<b>Respiratory protection:</b>
In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. SDSs cannot provide detailed and complete respiratory protection guidelines. Selection of respiratory protection must be done by a qualified person who has assessed the work environment.

#### Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

## SECTION 9 Physical and chemical properties

### 9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol.
Colour	: Clear
Odour	: Characteristic
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: < -18 °C (< -0.4 °F)
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapour pressure	: No data available
Relative vapour density at 20°C/ 68 °F	: No data available
Relative density	: No data available

# 1K UV Blender

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Density	: 0.8 g/cm <sup>3</sup>
Solubility	: No data available
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Explosive limits	: No data available
Particle characteristics	: No data available

Dimethyl ether	
Boiling point	-24.9 °C
Flash point	-40.56 °C (closed cup)
Auto-ignition temperature	240 °C
Vapour pressure	5.12 hPa (at 20 °C)
Particle characteristics	No data available

Ethyl acetate	
Boiling point	77 °C (at 1 atm)
Flash point	-4 °C (closed cup)
Auto-ignition temperature	426.67 °C
Vapour pressure	91.84 hPa (at 18.7 °C)
Particle characteristics	No data available

### 9.2. Data relevant with regard to physical hazard classes (supplemental)

Gas group	: Press. Gas (Liq.)
Flame projection length	: > 75 cm < 100 cm
Flashback	: Possible

## SECTION 10 Stability and reactivity

### 10.1. Reactivity

No dangerous reactions known under normal conditions of use.

### 10.2. Chemical stability

Stable under normal conditions. Extremely flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Heat. Sparks. Open flame. Direct sunlight. Overheating. Incompatible materials.

### 10.5. Incompatible materials

Strong oxidizing agents. Acids. Alkalis.

### 10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

# 1K UV Blender

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

### SECTION 11 Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified.  
Acute toxicity (dermal) : Not classified.  
Acute toxicity (inhalation) : Not classified.

Dimethyl ether (115-10-6)	
LC50 inhalation rat	164000 ppm/4h

Ethyl acetate (141-78-6)	
LD50 oral rat	5620 mg/kg (Source: NLM_CIP)
LD50 oral	4934 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 18000 mg/kg (Source: JAPAN_GHS)
LC50 inhalation rat	4000 ppm/4h

Skin corrosion/irritation : Not classified.

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : Not classified.

Germ cell mutagenicity : Not classified.

Carcinogenicity : Not classified.

Reproductive toxicity : Not classified.

STOT-single exposure : May cause drowsiness or dizziness.

Ethyl acetate (141-78-6)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified.

Ethyl acetate (141-78-6)	
LOAEL (oral, rat, 90 days)	3600 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 795.2600 (Subchronic Oral Toxicity Test)
NOAEL (oral, rat, 90 days)	900 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 795.2600 (Subchronic Oral Toxicity Test)

Aspiration hazard : Not classified.

1K UV Blender	
Vaporizer	Aerosol
Viscosity, kinematic	No data available

Dimethyl ether (115-10-6)	
Viscosity, kinematic	No data available

Ethyl acetate (141-78-6)	
Viscosity, kinematic	0.5 mm <sup>2</sup> /s

Symptoms/effects after inhalation : May cause irritation to the respiratory tract. May cause drowsiness or dizziness. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Symptoms of oxygen deficiency include respiratory difficulty, headache, dizziness, nausea, unconsciousness or death.

# 1K UV Blender

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Symptoms/effects after skin contact	: May cause skin irritation. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

## SECTION 12 Ecological information

### 12.1. Ecotoxicity

Ecology - general	: May cause long-term adverse effects in the aquatic environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified.
Hazardous to the aquatic environment, long-term (chronic)	: Not classified.

Dimethyl ether (115-10-6)	
LC50 - Fish [1]	> 4.1 g/l (Exposure time: 96 h - Species: Poecilia reticulata [semi-static] Source: ECHA)
EC50 - Crustacea [1]	> 4.4 g/l Test organisms (species): Daphnia magna
EC50 96h - Algae [1]	154.917 mg/l Test organisms (species): other:green algae

Ethyl acetate (141-78-6)	
LC50 - Fish [1]	220 – 250 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
EC50 - Crustacea [1]	560 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 - Fish [2]	484 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through] Source: IUCLID)
NOEC (chronic)	2.4 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

### 12.2. Persistence and degradability

1K UV Blender	
Persistence and degradability	Not established.

Dimethyl ether (115-10-6)	
Persistence and degradability	Rapidly degradable

Ethyl acetate (141-78-6)	
Persistence and degradability	Rapidly degradable

### 12.3. Bioaccumulative potential

1K UV Blender	
Bioaccumulative potential	Not established.

Dimethyl ether (115-10-6)	
Partition coefficient n-octanol/water	-0.18

Ethyl acetate (141-78-6)	
BCF - Fish [1]	(30 dimensionless)
Partition coefficient n-octanol/water	0.73 (at 20 °C (at pH 7)

# 1K UV Blender

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Ozone : Not classified.  
Fluorinated greenhouse gases : No  
Other information : No other effects known.

## SECTION 13 Disposal considerations

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Container under pressure. Do not drill or burn even after use.  
Additional information : Flammable vapours may accumulate in the container.

## SECTION 14 Transport information

In accordance with DOT / TDG

### 14.1. UN Number

UN-No. (DOT) : UN1950  
UN-No. (TDG) : UN1950


### 14.2. UN Proper Shipping Name

Proper Shipping Name (DOT) : Aerosols (Limited quantity)  
Proper Shipping Name (TDG) : AEROSOLS (LIMITED QUANTITY)

### 14.3. Transport hazard class(es)


#### DOT

Transport hazard class(es) (DOT) : LTD QTY  
Hazard labels (DOT) : LTD QTY



#### TDG

Transport hazard class(es) (TDG) : 2.1  
Hazard labels (TDG) : 2.1



### 14.4. Packing group

Packing group (DOT) : Not applicable  
Packing group (TDG) : Not applicable

### 14.5. Environmental hazards

Other information : No supplementary information available.

# 1K UV Blender

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

### 14.6. Transport in bulk

Not applicable

### 14.7. Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.

**DOT**  
UN-No. (DOT) : UN1950  
DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.  
DOT Packaging Exceptions (49 CFR 173.xxx) : 306  
DOT Packaging Non Bulk (49 CFR 173.xxx) : None  
DOT Packaging Bulk (49 CFR 173.xxx) : None  
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg  
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

DOT Vessel Stowage Other : 25 - Protected from sources of heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

**TDG**  
UN-No. (TDG) : UN1950  
TDG Special Provisions : 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment), 107 - (1) These Regulations, except for Parts 1 and 2, do not apply to the offering for transport, handling or transport of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL.  
(2) Subsection (1) does not apply to self-defence spray.

Explosive Limit and Limited Quantity Index : 1 L  
Excepted quantities (TDG) : E0  
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index : 75 L  
Emergency Response Guide (ERG) Number : 126

## SECTION 15 Regulatory information

### 15.1. Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

### 15.2. International regulations

No additional information available

# 1K UV Blender

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

### 15.3. State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

### SECTION 16 Other Information

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Revision date : 2025-10-10  
Issue date : 2019-10-10  
Other information : None.  
Prepared by : Nexreg Compliance Inc.  
[www.Nexreg.com](http://www.Nexreg.com)



#### Indication of changes:

SDS update.

SDS HazCom 2024 - WHMIS 2022 (Nexreg) 2025

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.