

1K Texture Coating Black

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Date of issue: 10/09/2019

Revision date: 10/09/2019

Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : 1K Texture Coating Black
Product code : 3680224 / REZ1132

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Automotive refinish

1.3. Details of the supplier of the safety data sheet

Manufacturer

Peter Kwasny GmbH
96 Heibronner Str.
Gundelsheim, 74831 - Germany
T 49(0) 6269-95-20

Distributor

Peter Kwasny Inc.
62-64 Enter Lane
Islandia, NY 11749
T 1-844-726-6330 (tollfree North America)

Distributor

Peter Kwasny Spraypaint Canada Inc
2275 Lake Shore Boulevard West, Suite 530
Toronto, ON M8V 3Y3

1.4. Emergency telephone number

Emergency number : 352-323-3500 (24h / 7 days a week)

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

GHS classification

Flam. Aerosol 1
Press. Gas (Liq.)
Skin Irrit. 2
Skin Sens. 1
Carc. 2
Repr. 2
STOT SE 3
STOT RE 2
Simple Asphy

2.2. Label elements

GHS labelling

Hazard pictograms (GHS) :



GHS02

GHS04

GHS07

GHS08

Signal word (GHS) :

Danger

Hazard statements (GHS) :

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. May cause an allergic skin reaction. May cause drowsiness or dizziness. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. May displace oxygen and cause rapid suffocation

Precautionary statements (GHS) :

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Wash hands, forearms and face thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents/container to hazardous

1K Texture Coating Black

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Dimethyl ether	(CAS-No.) 115-10-6	30 - 60
Xylenes (o-, m-, p- isomers)	(CAS-No.) 1330-20-7	10 - 30
Ethylbenzene	(CAS-No.) 100-41-4	5 - 10
Carbon black	(CAS-No.) 1333-86-4	1 - 5
Silane, dichlorodimethyl-, reaction products with silica	(CAS-No.) 68611-44-9	1 - 5
Bisphenol A-epichlorohydrin polymer	(CAS-No.) 25068-38-6	< 1
n-Butyl acetate	(CAS-No.) 123-86-4	< 1

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: IF INHALED: Remove person to fresh air and keep comfortable for breathing. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Call a POISON CENTER/doctor if you feel unwell.
First-aid measures after skin contact	: IF ON SKIN: Wash with plenty of Water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause damage to organs. May cause cancer. Suspected of damaging fertility or the unborn child.
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract. May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media	: Do not use water jet.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Extremely flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon.
Explosion hazard	: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. Vapours may form explosive mixture with air.

1K Texture Coating Black

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

5.3. Advice for firefighters

- Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion.
- Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Cool closed containers exposed to fire with water spray. Vapours are heavier than air and may spread along floors.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate every possible source of ignition. Use only non-sparking tools. Use special care to avoid static electric charges. Isolate from fire, if possible, without unnecessary risk.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.
- Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Do not pierce or burn, even after use. Keep away from sources of ignition - No smoking. Hazardous waste due to potential risk of explosion.
- Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid contact with skin and eyes. Do not breathe dust, fume, gas, mist, spray, vapours. Use only outdoors or in a well-ventilated area. Do not pierce or burn, even after use. Keep away from sources of ignition - No smoking. Do not swallow. When using do not eat or drink. Handle and open container with care. Do not spray on an open flame or other ignition source. Contaminated work clothing should not be allowed out of the workplace.
- Hygiene measures : Wash contaminated clothing before reuse. Wash hands, forearms and face thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed.
- Storage conditions : Keep out of the reach of children. Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place. Store away from direct sunlight or other heat sources. Store locked up. Store in a well-ventilated place. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Dimethyl ether (115-10-6)		
Not applicable		
Bisphenol A-epichlorohydrin polymer (25068-38-6)		
Not applicable		
Silane, dichlorodimethyl-, reaction products with silica (68611-44-9)		
Not applicable		
Xylenes (o-, m-, p- isomers) (1330-20-7)		
ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	ACGIH STEL (ppm)	150 ppm

1K Texture Coating Black

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Xylenes (o-, m-, p- isomers) (1330-20-7)		
ACGIH	Remark (ACGIH)	URT & eye irr; CNS impair
OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm

Ethylbenzene (100-41-4)		
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	Remark (ACGIH)	URT irr; kidney dam (nephropathy)
OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
IDLH	US IDLH (ppm)	800 ppm (10% LEL)
NIOSH	NIOSH REL (TWA) (mg/m ³)	435 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
NIOSH	NIOSH REL (STEL) (mg/m ³)	545 mg/m ³
NIOSH	NIOSH REL (STEL) (ppm)	125 ppm

Carbon black (1333-86-4)		
ACGIH	ACGIH TWA (mg/m ³)	3 mg/m ³ (inhalable particulate matter)
ACGIH	Remark (ACGIH)	Bronchitis
OSHA	OSHA PEL (TWA) (mg/m ³)	3.5 mg/m ³
IDLH	US IDLH (mg/m ³)	1750 mg/m ³
NIOSH	NIOSH REL (TWA) (mg/m ³)	3.5 mg/m ³ 0.1 mg/m ³ (Carbon black in presence of Polycyclic aromatic hydrocarbons)

n-Butyl acetate (123-86-4)		
ACGIH	ACGIH TWA (ppm)	50 ppm (Butyl acetates, all isomers)
ACGIH	ACGIH STEL (ppm)	150 ppm (Butyl acetates, all isomers)
ACGIH	Remark (ACGIH)	Eye & URT irr
OSHA	OSHA PEL (TWA) (mg/m ³)	710 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	150 ppm
IDLH	US IDLH (ppm)	1700 ppm (10% LEL)
NIOSH	NIOSH REL (TWA) (mg/m ³)	710 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	150 ppm
NIOSH	NIOSH REL (STEL) (mg/m ³)	950 mg/m ³
NIOSH	NIOSH REL (STEL) (ppm)	200 ppm

8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Hand protection	: Wear suitable gloves resistant to chemical penetration.
Eye protection	: Safety glasses or goggles are recommended when using product.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Avoid release to the environment.
Other information	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
----------------	----------

1K Texture Coating Black

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Appearance	: Aerosol
Colour	: Black
Odour	: Characteristic
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: < -18 °C/ 0.4 °F
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.8 g/cm ³
Solubility	: No data available
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

Gas group	: Press. Gas (Liq.)
Flame projection length	: >75 cm <100cm
Flashback	: Possible

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions. Extremely flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat. Incompatible materials. Sparks. Open flame. Direct sunlight. Overheating.

10.5. Incompatible materials

Strong oxidizers. Acids. Alkalis.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified.
Acute toxicity (dermal)	: Not classified.
Acute toxicity (inhalation)	: Not classified

Bisphenol A-epichlorohydrin polymer (25068-38-6)

LD50 oral rat	11400 mg/kg
ATE CA (oral)	11400 mg/kg bodyweight

1K Texture Coating Black

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Silane, dichlorodimethyl-, reaction products with silica (68611-44-9)	
LD50 oral rat	> 5000 mg/kg
LC50 inhalation rat	0.45 mg/l/4h
ATE CA (vapours)	0.45 mg/l/4h
ATE CA (dust,mist)	0.45 mg/l/4h

Xylenes (o-, m-, p- isomers) (1330-20-7)	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	> 4350 mg/kg
LD50 dermal	1700 mg/kg
LC50 inhalation rat	29.08 mg/l/4h
LC50 inhalation rat (Vapours - mg/l/4h)	27.57 mg/l/4h
ATE CA (oral)	3500 mg/kg bodyweight
ATE CA (Dermal)	1700 mg/kg bodyweight
ATE CA (Gases)	4500 ppmv/4h
ATE CA (vapours)	11 mg/l/4h
ATE CA (dust,mist)	1.5 mg/l/4h

Ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	15400 mg/kg
LC50 inhalation rat	17.4 mg/l/4h
ATE CA (oral)	3500 mg/kg bodyweight
ATE CA (Dermal)	15400 mg/kg bodyweight
ATE CA (Gases)	4500 ppmv/4h
ATE CA (vapours)	17.4 mg/l/4h
ATE CA (dust,mist)	1.5 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Not classified.
Respiratory or skin sensitisation : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified.
Carcinogenicity : Suspected of causing cancer.

Xylenes (o-, m-, p- isomers) (1330-20-7)	
IARC group	3 - Not classifiable

Ethylbenzene (100-41-4)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity
In OSHA Hazard Communication Carcinogen list	Yes

Carbon black (1333-86-4)	
IARC group	2B - Possibly carcinogenic to humans
In OSHA Hazard Communication Carcinogen list	Yes

Reproductive toxicity : Suspected of damaging fertility or the unborn child.
STOT-single exposure : May cause drowsiness or dizziness.

Xylenes (o-, m-, p- isomers) (1330-20-7)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

Ethylbenzene (100-41-4)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified.

1K Texture Paint Black	
Vaporizer	Aerosol

1K Texture Coating Black

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Symptoms/effects	: May cause damage to organs. May cause cancer. Suspected of damaging fertility or the unborn child.
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract. May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

Xylenes (o-, m-, p- isomers) (1330-20-7)	
LC50 fish 1	13.4 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	3.82 mg/l (Exposure time: 48 h - Species: water flea)
LC50 fish 2	2.661 - 4.093 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 2	0.6 mg/l (Exposure time: 48 h - Species: Gammarus lacustris)
Ethylbenzene (100-41-4)	
LC50 fish 1	11.0 - 18.0 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	1.8 - 2.4 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	4.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static])
NOEC chronic crustacea	0.956 mg/l

12.2. Persistence and degradability

1K Texture Paint Black	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

1K Texture Paint Black	
Bioaccumulative potential	Not established.
Dimethyl ether (115-10-6)	
Partition coefficient n-octanol/water	-0.18
Xylenes (o-, m-, p- isomers) (1330-20-7)	
BCF fish 1	0.6 - 15
Partition coefficient n-octanol/water	2.77 - 3.15
Ethylbenzene (100-41-4)	
BCF fish 1	15
Partition coefficient n-octanol/water	3.2

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : No other effects known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations	: Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
Additional information	: Flammable vapours may accumulate in the container. Hazardous waste due to potential risk of explosion.

SECTION 14: Transport information

Department of Transportation (DOT) and Transportation of Dangerous Goods (TDG)

1K Texture Coating Black

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

In accordance with DOT/TDG

UN-No.(DOT/TDG) : UN1950
Proper Shipping Name (DOT/TDG) : Aerosols
Class (DOT/TDG) : Class 2.1 - Flammable gas 49 CFR 173.115
Hazard labels (DOT/TDG) :



SECTION 15: Regulatory information

15.1. Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

PVC/vinylisobutylether copolymer	CAS-No. 25154-8-2
----------------------------------	-------------------

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories except for:

PVC/vinylisobutylether copolymer	CAS-No. 25154-8-2
----------------------------------	-------------------

15.2. International regulations

No additional information available

15.3. US State regulations

⚠ WARNING: This product can expose you to Ethylbenzene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

Revision date : 10/09/2019
Other information : None.
Prepared by : Nexreg Compliance Inc.
www.Nexreg.com



SDS HazCom 2012 - WHMIS 2015 (NexReg)

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.