

# Solvent Wash

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022  
Issue date: 2018-12-31 Revision date: 2025-10-31 Supersedes: 2022-03-08 Version: 3.0

### SECTION 1 Identification

#### 1.1. Product identifier

Product form : Mixture  
Product name : Solvent Wash  
Product code : 3680090 / REZ90  
Vaporizer : Aerosol

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Automotive refinsh

#### 1.4. Supplier's details

##### Manufacturer

Peter Kwasny GmbH  
96 Heibronner Str.  
Gundelsheim, 74831  
Germany  
T 49(0) 6269-95-20

##### Distributor

Peter Kwasny Spraypaint Canada Inc  
40 University Avenue, Suite 904  
Toronto, ON, M5J 1T1  
Canada  
T +1 844-426-6330

##### Distributor

Peter Kwasny, Inc.  
12222 Merit Drive, #130  
Dallas, TX 75251  
USA  
T 1-844-426-6330

#### 1.5. Emergency phone number

Emergency number : North America  
INFOTRAC International +1 (352) 323-5000 24 hr

### SECTION 2 Hazard identification

#### 2.1. Classification of the substance or mixture

##### GHS classification

Aerosol, Category 1  
Acute toxicity (oral), Category 4  
Eye irritation, Category 2A  
Specific target organ toxicity – Single exposure, Category 3, Narcosis  
Aspiration hazard, Category 1

#### 2.2. Label elements

##### GHS labelling

Hazard pictograms (GHS) :



Signal word (GHS) :

Danger

Hazard statements (GHS) :

Extremely flammable aerosol  
Pressurized container; may burst if heated

# Solvent Wash

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Precautionary statements (GHS)	<p>Harmful if swallowed May be fatal if swallowed and enters airways Causes serious eye irritation May cause drowsiness or dizziness</p> <p>: If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing dust, fume, gas, mist, vapours, spray. Wash hands, forearms and face thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves, protective clothing, eye and face protection. If swallowed: Immediately call a poison center or doctor. Rinse mouth. Do NOT induce vomiting. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C). Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.</p>
--------------------------------	---

### 2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

### 2.4. Hazards not otherwise classified

Other hazards which do not result in classification : Contact with the liquefied gas may cause frostbite.

### 2.5. Unknown acute toxicity

97.5% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)

## SECTION 3 Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	Conc. (% w/w)
Naphtha, petroleum, hydrotreated heavy	Naphtha, petroleum, hydrotreated heavy	CAS-No.: Not available EC-No.: 927-241-2	30 – 60
n-Butane	n-Butane Butane / BUTANE	CAS-No.: 106-97-8	15 - 40

# Solvent Wash

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Name	Chemical name / Synonyms	Product identifier	Conc. (% w/w)
Propane	Propane Normal propane / PROPANE / n-Propane / R290 / R-290	CAS-No.: 74-98-6	10 – 30
1-Butanol	1-Butanol n-Butyl alcohol / n-Butanol / Butanol, 1- / 1-Butyl alcohol / 1-Hydroxybutane / Butyl alcohol, n- / Butanol, n- / Butan-1-ol / Normal butyl alcohol / N-BUTYL ALCOHOL / Butyl alcohol	CAS-No.: 71-36-3	1 – 5

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

### SECTION 4 First-aid measures

#### 4.1. Description of necessary first-aid measures

First-aid measures after inhalation	: If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
First-aid measures after skin contact	: If skin irritation occurs: Wash skin with plenty of water. Obtain medical attention if irritation persists. If frostbite occurs thaw frosted parts with lukewarm water. Do not rub affected area. Do not use hot water.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If frostbite occurs thaw frosted parts with lukewarm water. Do not rub affected area. Do not use hot water.
First-aid measures after ingestion	: IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person.

#### 4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: May cause irritation to the respiratory tract. May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause frostbite on contact with the liquefied gas.
Symptoms/effects after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause frostbite on contact with the liquefied gas.
Symptoms/effects after ingestion	: Harmful if swallowed. May be fatal if swallowed and enters airways. May result in aspiration into the lungs, causing chemical pneumonia. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

#### 4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
-----------------------------------	--

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	: Do not use water jet.

# Solvent Wash

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

### 5.2. Specific hazards arising from the chemical

- Fire hazard : Extremely flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon. Irritating vapours. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours.
- Explosion hazard : Vapours may form explosive mixture with air. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. Ruptured cylinders may rocket.

### 5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Move containers away from the fire area if this can be done without risk. DO NOT fight fire when fire reaches explosives. Evacuate area.
- Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Use water spray to keep fire-exposed containers cool. Vapours are heavier than air and may spread along floors.

## SECTION 6 Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate every possible source of ignition. Use only non-sparking tools. Use special care to avoid static electric charges.

#### For non-emergency personnel

No additional information available

#### For emergency responders

- Environmental precautions : Prevent entry to sewers and public waters.

### 6.2. Methods and materials for containment and cleaning up

- For containment : Stop leak if safe to do so. Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.
- Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

For further information refer to section 8: "Exposure controls/personal protection"

## SECTION 7 Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Take precautionary measures against static discharge. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Do not spray on an open flame or other ignition source. Avoid contact with skin, eyes and clothing. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not swallow. When using do not eat, drink or smoke. Handle and open container with care. Use only outdoors or in a well-ventilated area.
- Hygiene measures : Take off immediately all contaminated clothing and wash it before reuse. Wash hands, forearms and face thoroughly after handling.
- Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Hazardous waste due to potential risk of explosion.

# Solvent Wash

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

### 7.2. Conditions for safe storage, including incompatibilities

Technical measures	: Proper grounding procedures to avoid static electricity should be followed.
Storage conditions	: Keep out of the reach of children. Store locked up. Keep in fireproof place. Store away from direct sunlight or other heat sources. Keep away from clothing and other combustible materials. Do not expose to temperatures exceeding 50 °C/ 122 °F. Protect containers from physical damage. Keep away from incompatible materials. . Store in a dry, cool and well-ventilated place.
Specific end uses	: Automotive refinish.

## SECTION 8 Exposure controls/personal protection

### 8.1. Control parameters

<b>n-Butane (106-97-8)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH® TLV® STEL	1000 ppm (explosion hazard (Butane, isomers))
<b>USA - IDLH - Occupational Exposure Limits</b>	
IDLH	1600 ppm (>10% LEL)
<b>USA - NIOSH - Occupational Exposure Limits</b>	
NIOSH REL TWA	1900 mg/m <sup>3</sup>
NIOSH REL TWA	800 ppm
<b>Propane (74-98-6)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	Propane
Remark (ACGIH®)	TLV® Basis: Simple Asphyxiant
ACGIH® chemical category	Simple asphyxiant See Appendix F: Minimal Oxygen Content
Regulatory reference	ACGIH 2024
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	Propane
OSHA PEL TWA	1800 mg/m <sup>3</sup>
OSHA PEL TWA	1000 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>USA - IDLH - Occupational Exposure Limits</b>	
IDLH	2100 ppm (10% LEL)
<b>USA - NIOSH - Occupational Exposure Limits</b>	
NIOSH REL TWA	1800 mg/m <sup>3</sup>
NIOSH REL TWA	1000 ppm
<b>1-Butanol (71-36-3)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	n-Butanol (n-Butyl alcohol)
ACGIH® TLV® TWA	61 mg/m <sup>3</sup>
ACGIH® TLV® TWA	20 ppm

# Solvent Wash

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

1-Butanol (71-36-3)	
Remark (ACGIH®)	TLV® Basis: Eye & URT irr
Regulatory reference	ACGIH 2025
USA - OSHA - Occupational Exposure Limits	
Local name	n-Butyl alcohol
OSHA PEL TWA	300 mg/m³
OSHA PEL TWA	100 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - IDLH - Occupational Exposure Limits	
IDLH	1400 ppm (10% LEL)
USA - NIOSH - Occupational Exposure Limits	
Local name	n-Butyl alcohol
NIOSH REL C	150 mg/m³
NIOSH REL C	50 ppm
US-NIOSH chemical category	Potential for dermal absorption
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))

### 8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station. Provide readily accessible eye wash stations and safety showers.
Environmental exposure controls	: Avoid release to the environment.

### 8.3. Individual protection measures, such as personal protective equipment

<b>Hand protection:</b>
Wear suitable gloves. Consult glove manufacturer's product information on material suitability and material thickness.
<b>Eye protection:</b>
Wear eye/face protection
<b>Skin and body protection:</b>
Wear suitable protective clothing
<b>Respiratory protection:</b>
In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. SDSs cannot provide detailed and complete respiratory protection guidelines. Selection of respiratory protection must be done by a qualified person who has assessed the work environment.

#### Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

## SECTION 9 Physical and chemical properties

### 9.1. Basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol.
Colour	: Black

# Solvent Wash

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Odour	: Characteristic
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: Not applicable
Flash point	: < -18 °C / -0.4 °F
Relative evaporation rate (butylacetate=1)	: Not applicable
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapour pressure	: 3600 hPa
Relative vapour density at 20°C/ 68 °F	: No data available
Relative density	: No data available
Density	: 0.8 g/cm <sup>3</sup>
Solubility	: No data available
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: product is not self igniting
Decomposition temperature	: No data available
Viscosity, kinematic	: < 20.5 mm <sup>2</sup> /s @ 40 °C / 104 °F
Explosive limits	: Lower explosion limit: 0.6 vol % Upper explosion limit: 10.9 vol %
Explosive properties	: May form flammable/explosive vapour-air mixtures.
Particle characteristics	: No data available

<b>Naphtha, petroleum, hydrotreated heavy</b>	
Boiling point	139 – 164 °C Atm. press.: 1 atm Decomposition: 'no'
Flash point	28 °C Atm. press.: 1 atm
Vapour pressure	0.5 kPa Temp.: 20 °C
Particle characteristics	No data available

<b>n-Butane</b>	
Boiling point	-0.5 °C (at 1013 hPa)
Flash point	-60 °C
Auto-ignition temperature	287 °C
Vapour pressure	2200 hPa (at 20 °C)
Particle characteristics	No data available

<b>Propane</b>	
Boiling point	-161.48 °C (at 1013 hPa)
Flash point	-104 °C
Auto-ignition temperature	450 °C
Vapour pressure	600 – 39000 hPa (at 20 °C)
Particle characteristics	No data available

<b>1-Butanol</b>	
Boiling point	119 °C (at 1013 hPa)
Flash point	35 °C (closed cup)
Auto-ignition temperature	343 °C

# Solvent Wash

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

1-Butanol	
Vapour pressure	0.658 hPa (at 20 °C)
Particle characteristics	No data available

### 9.2. Data relevant with regard to physical hazard classes (supplemental)

VOC content	: 100 %
Gas group	: Press. Gas (Liq.)

## SECTION 10 Stability and reactivity

### 10.1. Reactivity

No dangerous reactions known under normal conditions of use.

### 10.2. Chemical stability

Extremely flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Extreme risk of explosion by shock, friction, fire or other sources of ignition. Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Reacts with acids, alkalis and oxidising agents.

### 10.4. Conditions to avoid

Heat. Sparks. Open flame. Direct sunlight. Ignition sources.

### 10.5. Incompatible materials

Strong oxidizers.

### 10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon. Irritating vapours.

## SECTION 11 Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Harmful if swallowed.
Acute toxicity (dermal)	: Not classified.
Acute toxicity (inhalation)	: Not classified.

Solvent Wash	
ATE US (oral)	700 mg/kg bodyweight
Unknown acute toxicity	97.5% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)

### Naphtha, petroleum, hydrotreated heavy (EC-No.: 927-241-2)

LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	≥ 3160 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

### n-Butane (106-97-8)

LC50 inhalation rat	658 g/m <sup>3</sup> (Exposure time: 4 h Source: NLM_CIP)
---------------------	---

# Solvent Wash

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

<b>Propane (74-98-6)</b>	
LC50 inhalation rat	> 800000 ppm (Exposure time: 15 min Source: ECHA_API)
<b>1-Butanol (71-36-3)</b>	
LD50 oral rat	700 mg/kg (Source: JAPAN_GHS)
LD50 oral	2100 mg/kg
LD50 dermal rabbit	3402 mg/kg (Source: JAPAN_GHS)
LD50 dermal	3400 mg/kg
LC50 inhalation rat	> 8000 ppm/4h
Skin corrosion/irritation	: Not classified.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified.
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Not classified.
Reproductive toxicity	: Not classified.
STOT-single exposure	: May cause drowsiness or dizziness.
<b>Naphtha, petroleum, hydrotreated heavy (EC-No.: 927-241-2)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>1-Butanol (71-36-3)</b>	
STOT-single exposure	May cause drowsiness or dizziness. May cause respiratory irritation.
STOT-repeated exposure	: Not classified.
<b>1-Butanol (71-36-3)</b>	
LOAEL (oral, rat, 90 days)	500 mg/kg bodyweight Animal: rat
NOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat
Aspiration hazard	: May be fatal if swallowed and enters airways.
<b>Solvent Wash</b>	
Vaporizer	Aerosol
Viscosity, kinematic	< 20.5 mm <sup>2</sup> /s @ 40 °C / 104 °F
<b>Naphtha, petroleum, hydrotreated heavy (EC-No.: 927-241-2)</b>	
Viscosity, kinematic	1.06 mm <sup>2</sup> /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm <sup>2</sup> /s)'
<b>n-Butane (106-97-8)</b>	
Viscosity, kinematic	No data available
<b>Propane (74-98-6)</b>	
Viscosity, kinematic	No data available
<b>1-Butanol (71-36-3)</b>	
Viscosity, kinematic	3.641 mm <sup>2</sup> /s

# Solvent Wash

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Symptoms/effects after inhalation	: May cause irritation to the respiratory tract. May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause frostbite on contact with the liquefied gas.
Symptoms/effects after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause frostbite on contact with the liquefied gas.
Symptoms/effects after ingestion	: Harmful if swallowed. May be fatal if swallowed and enters airways. May result in aspiration into the lungs, causing chemical pneumonia. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

## SECTION 12 Ecological information

### 12.1. Ecotoxicity

Ecology - general	: May cause long-term adverse effects in the aquatic environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified.
Hazardous to the aquatic environment, long-term (chronic)	: Not classified.

1-Butanol (71-36-3)	
LC50 - Fish [1]	1730 – 1910 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: IUCLID)
EC50 - Crustacea [1]	1983 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 - Fish [2]	1740 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: IUCLID)
EC50 - Crustacea [2]	1897 – 2072 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 72h - Algae [1]	> 500 mg/l (Species: Desmodesmus subspicatus)
EC50 96h - Algae [1]	> 500 mg/l (Species: Desmodesmus subspicatus)
NOEC (chronic)	4.1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic crustacea	4.1 mg/l

### 12.2. Persistence and degradability

Solvent Wash	
Persistence and degradability	Not established.
Naphtha, petroleum, hydrotreated heavy (EC-No.: 927-241-2)	
Persistence and degradability	Rapidly degradable
n-Butane (106-97-8)	
Persistence and degradability	Rapidly degradable
Propane (74-98-6)	
Persistence and degradability	Rapidly degradable
1-Butanol (71-36-3)	
Persistence and degradability	Rapidly degradable

# Solvent Wash

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

### 12.3. Bioaccumulative potential

#### Solvent Wash

Bioaccumulative potential	Not established.
---------------------------	------------------

#### n-Butane (106-97-8)

Partition coefficient n-octanol/water	2.31 (at 20 °C (at pH 7))
---------------------------------------	---------------------------

#### Propane (74-98-6)

Partition coefficient n-octanol/water	1.09 (at 20 °C (at pH 7))
---------------------------------------	---------------------------

#### 1-Butanol (71-36-3)

BCF - Fish [1]	(0.64 dimensionless)
----------------	----------------------

Partition coefficient n-octanol/water	1 (at 25 °C (at pH 7))
---------------------------------------	------------------------

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Ozone	: Not classified.
Fluorinated greenhouse gases	: No
Other information	: No other effects known.

## SECTION 13 Disposal considerations

Product/Packaging disposal recommendations	: Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. Container under pressure. Do not drill or burn even after use. Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Additional information	: Flammable vapours may accumulate in the container. Hazardous waste due to potential risk of explosion.

## SECTION 14 Transport information

In accordance with DOT / TDG

### 14.1. UN Number

UN-No. (DOT)	: UN1950
UN-No. (TDG)	: UN1950

### 14.2. UN Proper Shipping Name

Proper Shipping Name (DOT)	: Aerosols
Proper Shipping Name (TDG)	: AEROSOLS

### 14.3. Transport hazard class(es)

<b>DOT</b>	
Transport hazard class(es) (DOT)	: 2.1
Hazard labels (DOT)	: 2.1

# Solvent Wash

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022



### TDG

Transport hazard class(es) (TDG) : 2.1  
Hazard labels (TDG) : 2.1



### 14.4. Packing group

Packing group (DOT) : Not applicable  
Packing group (TDG) : Not applicable

### 14.5. Environmental hazards

Other information : No supplementary information available.

### 14.6. Transport in bulk

Not applicable

### 14.7. Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.

### DOT

UN-No. (DOT) : UN1950  
DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.  
DOT Packaging Exceptions (49 CFR 173.xxx) : 306  
DOT Packaging Non Bulk (49 CFR 173.xxx) : 304  
DOT Packaging Bulk (49 CFR 173.xxx) : None  
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : Forbidden  
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg  
DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.  
DOT Vessel Stowage Other : 25 - Protected from sources of heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

### TDG

UN-No. (TDG) : UN1950  
TDG Special Provisions : 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment).  
Explosive Limit and Limited Quantity Index : 1 L  
Excepted quantities (TDG) : E0  
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index : 75 L  
Emergency Response Guide (ERG) Number : 126

# Solvent Wash

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

### SECTION 15 Regulatory information

#### 15.1. Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories

#### 15.2. International regulations

No additional information available

#### 15.3. State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

### SECTION 16 Other Information

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Revision date : 2025-10-31  
Issue date : 2018-12-31  
Other information : None.  
Prepared by : Nexreg Compliance Inc.  
[www.Nexreg.com](http://www.Nexreg.com)



#### Indication of changes:

SDS update.

SDS HazCom 2024 - WHMIS 2022 (Nexreg) 2025

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.