

1K Trim Paint Black Matte

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Date of issue: 08/09/2017

Revision date: 07/31/2019

Version: 1.1

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : 1K Trim Paint Black Matte
Product code : 3680103 / REZ930

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Automotive refinish

1.3. Details of the supplier of the safety data sheet

Manufacturer

Peter Kwasny GmbH
Heilbronner Str. 96
Gundelshheim, 74831 – Germany
T 49(0) 6269-95-20

Distributor

Peter Kwasny Inc.
62-64 Enter Lane
Islandia, NY 11749
T 1-844-726-6330 (toll free North America)

Distributor

Peter Kwasny Spraypaint Canada Inc
2275 Lake Shore Boulevard West, Suite 530
Toronto, ON M8V 3Y3

1.4. Emergency telephone number

Emergency number : 352-323-3500 (24h / 7 days a week)

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

GHS classification

Flam. Aerosol 1
Press. Gas (Liq.)
Eye Irrit. 2A
Carc. 2
Repr. 2
Simple Asphy

2.2. Label elements

GHS labelling

Hazard pictograms (GHS) :



GHS02

GHS04

GHS07

GHS08

Signal word (GHS) :

Danger

Hazard statements (GHS) :

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May displace oxygen and cause rapid suffocation.

Precautionary statements (GHS) :

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash hands, forearms and face thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Store locked up. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

No additional information available

1K Trim Paint Black Matte

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

2.4. Unknown acute toxicity

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % |
|------------------------------|---------------------|-------|
| Acetone | (CAS-No.) 67-64-1 | 30-60 |
| Propane | (CAS-No.) 74-98-6 | 10-30 |
| n-Butyl acetate | (CAS-No.) 123-86-4 | 5-10 |
| Butane | (CAS-No.) 106-97-8 | 5-10 |
| Isobutane | (CAS-No.) 75-28-5 | 1-5 |
| Xylenes (o-, m-, p- isomers) | (CAS-No.) 1330-20-7 | 1-5 |
| 2-Pentanone, 4-methyl- | (CAS-No.) 108-10-1 | 1-5 |
| Ethyl alcohol | (CAS-No.) 64-17-5 | 1-5 |
| Ethylbenzene | (CAS-No.) 100-41-4 | 1-5 |

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
- First-aid measures after skin contact : If skin irritation occurs: Wash skin with plenty of water. Obtain medical attention if irritation persists.
- First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects after inhalation : May cause irritation to the respiratory tract. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Symptoms of oxygen deficiency include respiratory difficulty, headache, dizziness, nausea, unconsciousness or death.
- Symptoms/effects after skin contact : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
- Symptoms/effects after eye contact : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
- Symptoms/effects after ingestion : May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.
- Unsuitable extinguishing media : Do not use water jet.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Extremely flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon.
- Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. Vapours may form explosive mixture with air.
- Reactivity : No dangerous reactions known under normal conditions of use.

5.3. Advice for firefighters

- Firefighting instructions : DO NOT fight fire when fire reaches explosives. Evacuate area.

1K Trim Paint Black Matte

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Use water spray to keep fire-exposed containers cool. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate every possible source of ignition. Use only non-sparking tools. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so. Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Hazardous waste due to potential risk of explosion.

Precautions for safe handling : Avoid contact with skin, eyes and clothing. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Keep away from sources of ignition - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Use only outdoors or in a well-ventilated area.

Hygiene measures : Wash contaminated clothing before reuse. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep out of the reach of children. Store locked up. Store in a well-ventilated place. Store away from direct sunlight or other heat sources. Keep in fireproof place. Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep away from incompatible materials.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| Acetone (67-64-1) | | |
|-------------------|--------------------------------------|------------------------|
| ACGIH | ACGIH TWA (ppm) | 250 ppm |
| ACGIH | ACGIH STEL (ppm) | 500 ppm |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 2400 mg/m ³ |
| OSHA | OSHA PEL (TWA) (ppm) | 1000 ppm |
| IDLH | US IDLH (ppm) | 2500 ppm (10% LEL) |
| NIOSH | NIOSH REL (TWA) (mg/m ³) | 590 mg/m ³ |
| NIOSH | NIOSH REL (TWA) (ppm) | 250 ppm |
| Propane (74-98-6) | | |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 1800 mg/m ³ |
| OSHA | OSHA PEL (TWA) (ppm) | 1000 ppm |

1K Trim Paint Black Matte

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

| Propane (74-98-6) | | |
|---|---------------------------------------|-----------------------------|
| IDLH | US IDLH (ppm) | 2100 ppm (10% LEL) |
| NIOSH | NIOSH REL (TWA) (mg/m ³) | 1800 mg/m ³ |
| NIOSH | NIOSH REL (TWA) (ppm) | 1000 ppm |
| n-Butyl acetate (123-86-4) | | |
| ACGIH | ACGIH TWA (ppm) | 50 ppm |
| ACGIH | ACGIH STEL (ppm) | 150 ppm |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 710 mg/m ³ |
| OSHA | OSHA PEL (TWA) (ppm) | 150 ppm |
| IDLH | US IDLH (ppm) | 1700 ppm (10% LEL) |
| NIOSH | NIOSH REL (TWA) (mg/m ³) | 710 mg/m ³ |
| NIOSH | NIOSH REL (TWA) (ppm) | 150 ppm |
| NIOSH | NIOSH REL (STEL) (mg/m ³) | 950 mg/m ³ |
| NIOSH | NIOSH REL (STEL) (ppm) | 200 ppm |
| Butane (106-97-8) | | |
| ACGIH | ACGIH STEL (ppm) | 1000 ppm (explosion hazard) |
| IDLH | US IDLH (ppm) | 1600 ppm (>10% LEL) |
| NIOSH | NIOSH REL (TWA) (mg/m ³) | 1900 mg/m ³ |
| NIOSH | NIOSH REL (TWA) (ppm) | 800 ppm |
| Isobutane (75-28-5) | | |
| ACGIH | ACGIH STEL (ppm) | 1000 ppm (explosion hazard) |
| NIOSH | NIOSH REL (TWA) (mg/m ³) | 1900 mg/m ³ |
| NIOSH | NIOSH REL (TWA) (ppm) | 800 ppm |
| Xylenes (o-, m-, p- isomers) (1330-20-7) | | |
| ACGIH | ACGIH TWA (ppm) | 100 ppm |
| ACGIH | ACGIH STEL (ppm) | 150 ppm |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 435 mg/m ³ |
| OSHA | OSHA PEL (TWA) (ppm) | 100 ppm |
| 2-Pentanone, 4-methyl- (108-10-1) | | |
| ACGIH | ACGIH TWA (ppm) | 20 ppm |
| ACGIH | ACGIH STEL (ppm) | 75 ppm |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 410 mg/m ³ |
| OSHA | OSHA PEL (TWA) (ppm) | 100 ppm |
| IDLH | US IDLH (ppm) | 500 ppm |
| NIOSH | NIOSH REL (TWA) (mg/m ³) | 205 mg/m ³ |
| NIOSH | NIOSH REL (TWA) (ppm) | 50 ppm |
| NIOSH | NIOSH REL (STEL) (mg/m ³) | 300 mg/m ³ |
| NIOSH | NIOSH REL (STEL) (ppm) | 75 ppm |
| Ethyl alcohol (64-17-5) | | |
| ACGIH | ACGIH STEL (ppm) | 1000 ppm |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 1900 mg/m ³ |
| OSHA | OSHA PEL (TWA) (ppm) | 1000 ppm |
| IDLH | US IDLH (ppm) | 3300 ppm (10% LEL) |
| NIOSH | NIOSH REL (TWA) (mg/m ³) | 1900 mg/m ³ |
| NIOSH | NIOSH REL (TWA) (ppm) | 1000 ppm |

1K Trim Paint Black Matte

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

| Ethylbenzene (100-41-4) | | |
|-------------------------|---------------------------------------|-----------------------|
| ACGIH | ACGIH TWA (ppm) | 20 ppm |
| OSHA | OSHA PEL (TWA) (mg/m ³) | 435 mg/m ³ |
| OSHA | OSHA PEL (TWA) (ppm) | 100 ppm |
| IDLH | US IDLH (ppm) | 800 ppm (10% LEL) |
| NIOSH | NIOSH REL (TWA) (mg/m ³) | 435 mg/m ³ |
| NIOSH | NIOSH REL (TWA) (ppm) | 100 ppm |
| NIOSH | NIOSH REL (STEL) (mg/m ³) | 545 mg/m ³ |
| NIOSH | NIOSH REL (STEL) (ppm) | 125 ppm |

8.2. Exposure controls

| | |
|----------------------------------|--|
| Appropriate engineering controls | : Ensure good ventilation of the work station. |
| Hand protection | : Wear suitable gloves. |
| Eye protection | : Wear eye/face protection. |
| Skin and body protection | : Wear suitable protective clothing. |
| Respiratory protection | : In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. |
| Environmental exposure controls | : Avoid release to the environment. |
| Other information | : Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product. |

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|--|--------------------------------|
| Physical state | : Liquid |
| Appearance | : Aerosol |
| Colour | : Black |
| Odour | : Characteristic |
| Odour threshold | : No data available |
| pH | : No data available |
| Melting point | : No data available |
| Freezing point | : No data available |
| Boiling point | : No data available |
| Flash point | : < -18 °C (-0.4 °F) |
| Relative evaporation rate (butylacetate=1) | : No data available |
| Flammability (solid, gas) | : Extremely flammable aerosol. |
| Vapour pressure | : No data available |
| Relative vapour density at 20 °C | : No data available |
| Relative density | : No data available |
| Density | : 0.74 g/cm ³ |
| Solubility | : No data available |
| Partition coefficient n-octanol/water | : No data available |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |
| Explosive limits | : No data available |
| Explosive properties | : No data available |
| Oxidising properties | : No data available |

9.2. Other information

No additional information available

1K Trim Paint Black Matte

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions. Extremely flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat. Sparks. Open flame. Direct sunlight. Overheating. Incompatible materials.

10.5. Incompatible materials

Oxidizing materials. Acids. Alkalis.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified.

Acute toxicity (dermal) : Not classified.

Acute toxicity (inhalation) : Not classified.

| Acetone (67-64-1) | |
|--------------------------|--|
| LD50 oral rat | 5800 mg/kg |
| LD50 dermal rabbit | > 15700 mg/kg |
| LC50 inhalation rat | 50100 mg/m ³ (Exposure time: 8 h) |

| Propane (74-98-6) | |
|--------------------------|-------------|
| LC50 inhalation rat | 658 mg/l/4h |

| n-Butyl acetate (123-86-4) | |
|-----------------------------------|---------------|
| LD50 oral rat | 10768 mg/kg |
| LD50 dermal rabbit | > 17600 mg/kg |
| LC50 inhalation rat | 390 ppm/4h |

| Butane (106-97-8) | |
|--------------------------|---|
| LC50 inhalation rat | 658 g/m ³ (Exposure time: 4 h) |

| Isobutane (75-28-5) | |
|----------------------------|-------------|
| LC50 inhalation rat | 658 mg/l/4h |

| Xylenes (o-, m-, p- isomers) (1330-20-7) | |
|---|---------------|
| LD50 oral rat | 3500 mg/kg |
| LD50 dermal rabbit | > 4350 mg/kg |
| LC50 inhalation rat | 29.08 mg/l/4h |

| 2-Pentanone, 4-methyl- (108-10-1) | |
|--|-------------|
| LD50 oral rat | 2080 mg/kg |
| LD50 dermal rabbit | 3000 mg/kg |
| LC50 inhalation rat | 8.2 mg/l/4h |

| Ethyl alcohol (64-17-5) | |
|--------------------------------|---------------|
| LD50 oral rat | 7060 mg/kg |
| LC50 inhalation rat | 124.7 mg/l/4h |

| Ethylbenzene (100-41-4) | |
|--------------------------------|--------------|
| LD50 oral rat | 3500 mg/kg |
| LD50 dermal rabbit | 15400 mg/kg |
| LC50 inhalation rat | 17.4 mg/l/4h |

1K Trim Paint Black Matte

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

| | |
|-----------------------------------|----------------------------------|
| Skin corrosion/irritation | : Not classified. |
| Serious eye damage/irritation | : Causes serious eye irritation. |
| Respiratory or skin sensitisation | : Not classified. |
| Germ cell mutagenicity | : Not classified. |
| Carcinogenicity | : May cause cancer. |

| | |
|---|----------------------|
| Xylenes (o-, m-, p- isomers) (1330-20-7) | |
| IARC group | 3 - Not classifiable |

| | |
|--|--------------------------------------|
| 2-Pentanone, 4-methyl- (108-10-1) | |
| IARC group | 2B - Possibly carcinogenic to humans |
| National Toxicology Program (NTP) Status | 1 - Evidence of Carcinogenicity |
| In OSHA Hazard Communication Carcinogen list | Yes |

| | |
|--------------------------------|----------------------------|
| Ethyl alcohol (64-17-5) | |
| IARC group | 1 - Carcinogenic to humans |

| | |
|--|--------------------------------------|
| Ethylbenzene (100-41-4) | |
| IARC group | 2B - Possibly carcinogenic to humans |
| National Toxicology Program (NTP) Status | 1 - Evidence of Carcinogenicity |
| In OSHA Hazard Communication Carcinogen list | Yes |

| | |
|------------------------|--|
| Reproductive toxicity | : Suspected of damaging fertility or the unborn child. |
| STOT-single exposure | : Not classified. |
| STOT-repeated exposure | : Not classified. |
| Aspiration hazard | : Not classified. |

| | |
|----------------------------------|---------|
| 1K Trim Paint Black Matte | |
| Vaporizer | Aerosol |

| | |
|-------------------------------------|--|
| Symptoms/effects after inhalation | : May cause irritation to the respiratory tract. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Symptoms of oxygen deficiency include respiratory difficulty, headache, dizziness, nausea, unconsciousness or death. |
| Symptoms/effects after skin contact | : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. |
| Symptoms/effects after eye contact | : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. |
| Symptoms/effects after ingestion | : May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea. |

SECTION 12: Ecological information

12.1. Toxicity

| | |
|-------------------|---|
| Ecology - general | : May cause long-term adverse effects in the aquatic environment. |
|-------------------|---|

| | |
|--------------------------|--|
| Acetone (67-64-1) | |
| LC50 fish 1 | 4.74 - 6.33 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss) |
| EC50 Daphnia 1 | 10294 - 17704 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static]) |
| LC50 fish 2 | 6210 - 8120 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static]) |
| EC50 Daphnia 2 | 12600 - 12700 mg/l (Exposure time: 48 h - Species: Daphnia magna) |

| | |
|-----------------------------------|--|
| n-Butyl acetate (123-86-4) | |
| LC50 fish 1 | 100 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static]) |
| LC50 fish 2 | 17 - 19 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |

| | |
|---|--|
| Xylenes (o-, m-, p- isomers) (1330-20-7) | |
| LC50 fish 1 | 13.4 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |
| EC50 Daphnia 1 | 3.82 mg/l (Exposure time: 48 h - Species: water flea) |
| LC50 fish 2 | 2.661 - 4.093 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static]) |
| EC50 Daphnia 2 | 0.6 mg/l (Exposure time: 48 h - Species: Gammarus lacustris) |

| | |
|--|--|
| 2-Pentanone, 4-methyl- (108-10-1) | |
| LC50 fish 1 | 496 - 514 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |

1K Trim Paint Black Matte

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

| 2-Pentanone, 4-methyl- (108-10-1) | |
|--|--|
| EC50 Daphnia 1 | 170 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| Ethyl alcohol (64-17-5) | |
| LC50 fish 1 | 12.0 - 16.0 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static]) |
| EC50 Daphnia 1 | 9268 - 14221 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| LC50 fish 2 | > 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static]) |
| EC50 Daphnia 2 | 2 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static]) |
| Ethylbenzene (100-41-4) | |
| LC50 fish 1 | 11.0 - 18.0 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static]) |
| EC50 Daphnia 1 | 1.8 - 2.4 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| LC50 fish 2 | 4.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static]) |

12.2. Persistence and degradability

| 1K Trim Paint Black Matte | |
|----------------------------------|------------------|
| Persistence and degradability | Not established. |

12.3. Bioaccumulative potential

| 1K Trim Paint Black Matte | |
|---|------------------|
| Bioaccumulative potential | Not established. |
| Acetone (67-64-1) | |
| BCF fish 1 | 0.69 |
| Partition coefficient n-octanol/water | -0.24 |
| Propane (74-98-6) | |
| Partition coefficient n-octanol/water | 2.3 |
| n-Butyl acetate (123-86-4) | |
| Partition coefficient n-octanol/water | 1.81 (at 23 °C) |
| Butane (106-97-8) | |
| Partition coefficient n-octanol/water | 2.89 |
| Isobutane (75-28-5) | |
| BCF fish 1 | 1.57 - 1.97 |
| Partition coefficient n-octanol/water | 2.88 (at 20 °C) |
| Xylenes (o-, m-, p- isomers) (1330-20-7) | |
| BCF fish 1 | 0.6 - 15 |
| Partition coefficient n-octanol/water | 2.77 - 3.15 |
| 2-Pentanone, 4-methyl- (108-10-1) | |
| Partition coefficient n-octanol/water | 1.19 |
| Ethyl alcohol (64-17-5) | |
| Partition coefficient n-octanol/water | -0.32 |
| Ethylbenzene (100-41-4) | |
| BCF fish 1 | 15 |
| Partition coefficient n-octanol/water | 3.2 |

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming : No known effects from this product.
Other information : No other effects known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

1K Trim Paint Black Matte

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT) and Transportation of Dangerous Goods (TDG)

In accordance with DOT/TDG

UN-No.(DOT/TDG) : UN1950
Proper Shipping Name (DOT/TDG) : Aerosols
Class (DOT/TDG) : Class 2.1 - Flammable gas 49 CFR 173.115
Hazard labels (DOT/TDG) :



SECTION 15: Regulatory information

15.1. Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

15.2. International regulations

No additional information available

15.3. US State regulations

California Proposition 65 - WARNING: This product can expose you to chemicals including Ethylbenzene and Methyl isobutyl ketone, which are known to the State of California to cause cancer, and Methyl isobutyl ketone, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

Revision date : 07/31/2019
Other information : None.
Prepared by : Nexreg Compliance Inc.
www.Nexreg.com



SDS HazCom 2012 - WHMIS 2015 (NexReg)

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.