

UVA Finishing Glaze

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022
Issue date: 2021-09-15 Revision date: 2025-10-31 Supersedes: 2021-09-15 Version: 2.0

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Product name : UVA Finishing Glaze
Product code : 3680802

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Automotive refinish,

1.4. Supplier's details

Manufacturer

Peter Kwasny GmbH
96 Heibronner Str.
Gundelsheim, 74831
Germany
T 49(0) 6269-95-20

Distributor

Peter Kwasny, Inc.
12222 Merit Drive, #130
Dallas, TX 75251
USA
T 1-844-426-6330

Distributor

Peter Kwasny Spraypaint Canada Inc
40 University Avenue, Suite 904
Toronto, ON, M5J 1T1
Canada
T +1 844-426-6330

1.5. Emergency phone number

Emergency number : North America
INFOTRAC International +1 (352) 323-5000 24 hr

SECTION 2 Hazard identification

2.1. Classification of the substance or mixture

GHS classification

Skin irritation, Category 2
Eye irritation, Category 2A
Skin sensitization, Category 1
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

2.2. Label elements

GHS labelling

Hazard pictograms (GHS) :



Signal word (GHS) :

Warning

Hazard statements (GHS) :

Causes skin irritation
May cause an allergic skin reaction

UVA Finishing Glaze

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Precautionary statements (GHS)	<p>Causes serious eye irritation May cause respiratory irritation : If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Avoid breathing dust, fume, gas, mist, vapours, spray. Wash hands, forearms and face thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves, protective clothing, eye and face protection. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice or attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.</p>
--------------------------------	--

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

Not applicable

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	Conc. (% w/w)
Talc	Talc Talc / Magnesium silicate / Talc (containing no asbestos fibers) / Talc (containing no asbestos) / Talc not containing asbestiform fibres / Talc, not containing asbestos / Talc, containing no asbestos fibres / Talc (nonasbestos form) / Talc (non-asbestos form) / Talc, non-fibrous type / Talc, non fibrous / Talc (containing no asbestos fibres) / Non-asbestiform talc / Talc (not containing asbestos) / C.I. 77718 / TALC / Trimagnesium tetrasilicon undecaoxide hydrate / Talc, non-asbestiform / Talc, non-fibrous / Pigment White 26 / Magnesium silicate, hydrous / Talc, not containing mineral fibers (including asbestos) / Asbestiform talc / Talc powder	CAS-No.: 14807-96-6	30 - 60

UVA Finishing Glaze

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Name	Chemical name / Synonyms	Product identifier	Conc. (% w/w)
Tripropylene glycol diacrylate	Tripropylene glycol diacrylate Acrylic acid, propylenebis(oxypropylene) ester / (1-Methyl-1,2-ethanediy)bis[oxy(methyl-2,1-ethanediy)] diacrylate / 2-Propenoic acid, (1-methyl-1,2-ethanediy)bis[oxy(methyl-2,1-ethanediy)] ester / 2-Propenoic acid, 1,1'-[(1-methyl-1,2-ethanediy)bis[oxy(methyl-2,1-ethanediy)]] ester / Acrylic acid, (1-methyl-1,2-ethanediy)bis[oxy(methyl-2,1-ethanediy)] ester / Tri(propylene glycol) diacrylate / 2-[2-(2-(Acryloyloxy)(methyl)ethoxy)(methyl)ethoxy)(methyl)ethyl acrylate / TRIPROPYLENE GLYCOL DIACRYLATE / Diester of acrylic acid with tripropyleneglycol / tripropylene glycol diacrylate	CAS-No.: 42978-66-5	15 - 40
1-Propanone, 2-hydroxy-2-methyl-1-phenyl-	1-Propanone, 2-hydroxy-2-methyl-1-phenyl- 2-Hydroxy-2-methylpropiophenone / Propiophenone, 2-hydroxy-2-methyl- / 1-Phenyl-2-hydroxy-2-methylpropan-1-one / 2-Hydroxy-2-methyl-1-phenyl-1-propanone / BENZOYL ISOPROPANOL / benzoyl isopropanol / Benzoyl isopropanol	CAS-No.: 7473-98-5	1 – 5
Silica, amorphous	Silica, amorphous Amorphous silica / Silica / Silica, amorphous, fumed / Silica, colloidal / Silicon dioxide / Silicon dioxide, amorphous / SILICA / Silicon(IV) oxide / Un-crystalline silica / Pigment White 27 / Silicon dioxide (amorphous) / Silicon dioxide amorphous / Fumed silica / SOLUM DIATOMEAE / Hydrated silica	CAS-No.: 7631-86-9	1 – 5

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4 First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures after inhalation	: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
First-aid measures after skin contact	: IF ON SKIN: Wash with plenty of Water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
-----------------------------------	--

UVA Finishing Glaze

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Dry chemical. Carbon dioxide (CO₂). Foam.
Unsuitable extinguishing media : Do not use water jet.

5.2. Specific hazards arising from the chemical

- Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon. Toxic gases may be formed.

5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Cool closed containers exposed to fire with water spray.
Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition.

For non-emergency personnel

No additional information available

For emergency responders

- Environmental precautions : Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.2. Methods and materials for containment and cleaning up

- For containment : Dike and contain spill. Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.
Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7 Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area.
Hygiene measures : Take off contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace. Wash hands, forearms and face thoroughly after handling.

7.2. Conditions for safe storage, including incompatibilities

- Storage conditions : Keep out of the reach of children. Keep container tightly closed. Store in a well-ventilated place. Keep only in original packaging. Keep away from heat and direct sunlight. Store locked up.
Storage temperature : < 35 °C (95 °F)
Specific end uses : Automotive refinish.

UVA Finishing Glaze

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Talc (14807-96-6)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH® TLV® TWA	2 mg/m ³ (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter)
ACGIH® chemical category	Not Classifiable as a Human Carcinogen containing no asbestos fibers
USA - OSHA - Occupational Exposure Limits	
Local name	Talc (not containing asbestos) (Silicates (less than 1% crystalline silica))
OSHA PEL TWA	20 mppcf (if 1% Quartz or more, use Quartz limit)
OSHA PEL TWA	20 mppcf
Remark (OSHA)	Table Z-3. CAS No. source: eCFR Table Z-1.
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts
USA - IDLH - Occupational Exposure Limits	
IDLH	1000 mg/m ³ (containing no asbestos and <1% quartz)
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	2 mg/m ³ (containing no Asbestos and <1% Quartz-respirable dust)
Silica, amorphous (7631-86-9)	
USA - IDLH - Occupational Exposure Limits	
IDLH	3000 mg/m ³
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	6 mg/m ³

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station. Ensure that eyewash stations and safety showers are close to the workstation location.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Hand protection:
Wear suitable gloves resistant to chemical penetration. Nitrile rubber gloves. Consult glove manufacturer's product information on material suitability and material thickness.
Eye protection:
Wear eye/face protection
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. SDSs cannot provide detailed and complete respiratory protection guidelines. Selection of respiratory protection must be done by a qualified person who has assessed the work environment.

UVA Finishing Glaze

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Solid
Colour	: Turquoise
Odour	: Acrylic odour
Odour threshold	: No data available
pH	: Not applicable.
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 196 °C (385 °F)
Flammability (solid, gas)	: Not flammable.
Vapour pressure	: No data available
Relative vapour density at 20°C/ 68 °F	: No data available
Relative density	: No data available
Solubility	: Negligible in water.
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Explosive limits	: No data available
Particle characteristics	: No data available

Talc	
Vapour pressure	0 Pa Temp.: 25 °C Remarks on result: 'other:'
Particle characteristics	No data available

Tripropylene glycol diacrylate	
Boiling point	> 120 °C Atm. press.: 1013,25 hPa
Flash point	153 °C (closed cup)
Vapour pressure	< 0.01 hPa (at 20 °C)
Particle characteristics	No data available

1-Propanone, 2-hydroxy-2-methyl-1-phenyl-	
Boiling point	252.1 °C Atm. press.: 1013,25 hPa
Flash point	122 °C Atm. press.: 1013 Pa
Particle characteristics	No data available

Silica, amorphous	
Boiling point	2230 °C
Vapour pressure	13.3 hPa (at 1732 °C)
Particle characteristics	No data available

UVA Finishing Glaze

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat. High temperature. Oxidizing conditions. Direct sunlight. Radiation. Incompatible materials.

10.5. Incompatible materials

Strong alkalis. Strong acids. Alkali metals. Oxidizing materials. Sources of ignition.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon. Toxic gases may be formed.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified.
Acute toxicity (dermal) : Not classified.
Acute toxicity (inhalation) : Not classified.

Talc (14807-96-6)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 inhalation rat	> 2.1 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation)), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity)
Tripropylene glycol diacrylate (42978-66-5)	
LD50 oral rat	6200 mg/kg (Source: NLM_CIP)
LD50 dermal rabbit	> 2 g/kg (Source: NLM_CIP)
1-Propanone, 2-hydroxy-2-methyl-1-phenyl- (7473-98-5)	
LD50 oral rat	1694 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1583 - 1811
LD50 dermal rat	6929 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), 95% CL: 6028 - 7964

UVA Finishing Glaze

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Silica, amorphous (7631-86-9)	
LD50 oral rat	7900 mg/kg (Source: ATSDR)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	> 5000 mg/kg (Source: ECETOC)
LC50 inhalation rat	> 58.8 mg/l/4h
Skin corrosion/irritation	: Causes skin irritation. pH: Not applicable.
Serious eye damage/irritation	: Causes serious eye irritation. pH: Not applicable.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Not classified.
Talc (14807-96-6)	
IARC group	3 - Not classifiable
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity
Silica, amorphous (7631-86-9)	
NOAEL (chronic, oral, animal/male, 2 years)	1800 – 3000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
NOAEL (chronic, oral, animal/female, 2 years)	1800 – 3200 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified.
STOT-single exposure	: May cause respiratory irritation.
Tripropylene glycol diacrylate (42978-66-5)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified.
Talc (14807-96-6)	
NOAEL (oral, rat, 90 days)	100 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 452 (Chronic Toxicity Studies)
Tripropylene glycol diacrylate (42978-66-5)	
LOAEL (dermal, rat/rabbit, 90 days)	20 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study), Guideline: other:
1-Propanone, 2-hydroxy-2-methyl-1-phenyl- (7473-98-5)	
NOAEL (oral, rat, 90 days)	50 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Silica, amorphous (7631-86-9)	
NOAEL (dermal, rat/rabbit, 90 days)	≥ 10000 mg/kg bodyweight Animal: rabbit
Aspiration hazard	: Not classified.
UV Curable Universal Finishing Glaze	
Viscosity, kinematic	No data available

UVA Finishing Glaze

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Talc (14807-96-6)	
Viscosity, kinematic	No data available

Tripropylene glycol diacrylate (42978-66-5)	
Viscosity, kinematic	No data available

1-Propanone, 2-hydroxy-2-methyl-1-phenyl- (7473-98-5)	
Viscosity, kinematic	No data available

Silica, amorphous (7631-86-9)	
Viscosity, kinematic	No data available

Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general	: May cause long-term adverse effects in the aquatic environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified.
Hazardous to the aquatic environment, long-term (chronic)	: Not classified.

Talc (14807-96-6)	
LC50 - Fish [1]	> 100 g/l (Exposure time: 96 h - Species: Brachydanio rerio [semi-static])
LC50 - Fish [2]	110000 mg/l Test organisms (species): other:
EC50 96h - Algae [1]	7202.7 mg/l Test organisms (species): other:
NOEC (chronic)	1459798 mg/l Test organisms (species): other: Duration: '30 d'

Tripropylene glycol diacrylate (42978-66-5)	
EC50 - Crustacea [1]	88.7 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	> 28 mg/l (Species: Desmodesmus subspicatus)

1-Propanone, 2-hydroxy-2-methyl-1-phenyl- (7473-98-5)	
EC50 - Crustacea [1]	> 119 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	1.95 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	1.02 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

UVA Finishing Glaze

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Silica, amorphous (7631-86-9)	
LC50 - Fish [1]	5000 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static] Source: IUCLID)
EC50 - Crustacea [1]	7600 mg/l (Exposure time: 48 h - Species: Ceriodaphnia dubia)
EC50 72h - Algae [1]	440 mg/l (Species: Pseudokirchneriella subcapitata)
LOEC (chronic)	149.2 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

12.2. Persistence and degradability

UV Curable Universal Finishing Glaze	
Persistence and degradability	Not established.
Talc (14807-96-6)	
Persistence and degradability	Rapidly degradable
Tripropylene glycol diacrylate (42978-66-5)	
Persistence and degradability	Rapidly degradable
1-Propanone, 2-hydroxy-2-methyl-1-phenyl- (7473-98-5)	
Persistence and degradability	Rapidly degradable
Silica, amorphous (7631-86-9)	
Persistence and degradability	Rapidly degradable

12.3. Bioaccumulative potential

UV Curable Universal Finishing Glaze	
Bioaccumulative potential	Not established.
Talc (14807-96-6)	
BCF - Fish [1]	(no known bioaccumulation)
Tripropylene glycol diacrylate (42978-66-5)	
BCF - Fish [1]	(no significant bioaccumulation expected)
Partition coefficient n-octanol/water	2 (at 25 °C)
1-Propanone, 2-hydroxy-2-methyl-1-phenyl- (7473-98-5)	
Partition coefficient n-octanol/water	1.62 (at 25 °C (at pH 5.75))
Silica, amorphous (7631-86-9)	
BCF - Fish [1]	(no bioaccumulation expected)

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone	: Not classified.
Fluorinated greenhouse gases	: No
Other information	: No other effects known.

UVA Finishing Glaze

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

SECTION 13 Disposal considerations

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

SECTION 14 Transport information

In accordance with DOT / TDG

14.1. UN Number

UN-No. (DOT) : Not regulated
UN-No. (TDG) : Not regulated


14.2. UN Proper Shipping Name

Proper Shipping Name (DOT) : LIMITED QUANTITY
Proper Shipping Name (TDG) : LIMITED QUANTITY

14.3. Transport hazard class(es)


DOT

Transport hazard class(es) (DOT) : Limited quantity



TDG

Transport hazard class(es) (TDG) : Limited quantity



14.4. Packing group

Packing group (DOT) : Not regulated
Packing group (TDG) : Not regulated

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT

Not regulated

TDG

Not regulated

UVA Finishing Glaze

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

15.2. International regulations

No additional information available

15.3. State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16 Other Information

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Revision date : 2025-10-31
Issue date : 2021-09-15
Other information : None.
Prepared by : Nexreg Compliance Inc.
www.Nexreg.com



Indication of changes:

SDS update.

SDS HazCom 2024 - WHMIS 2022 (Nexreg) 2025

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.