

# Technical Data Sheet



The United States of America:  
by Peter Kwasny Inc.  
62-64 Enter Lane  
Islandia, NY 11749

Distributed in

Canada:  
Peter Kwasny Spraypaint Canada Inc.  
40 University Avenue, Suite 904  
Toronto, ON. M5J 1T1

Toll free North America  
Phone: 1-844-426-6330 / Fax: 1-866-226-6434  
order@kwasny.us / service@kwasny.us  
www.spraymax.com

## SprayMax® 1K Wax & Grease Remover 314 g NET WT. 11.1 oz Art. Nr. 3680094



### Product

#### Description / Purpose

Waterborne cleaning agent, rich in active ingredients and with a reduced solvent content. This high quality product improves the adhesion to any paint coat and reduces the electrostatic effect. High cleaning and degreasing properties.

#### Properties

- Increases adhesion
- Maximum yield
- Uniform distribution
- Strong cleaning and degreasing effect
- Reduces electrostatic effect
- Especially for application of waterborne basecoats and special coatings.

#### Material base

Combination of water and solvent resins

#### Colour

Transparent

#### EPA Coating Category

n.a.

#### CARB Aerosol Rule Coating Category (01/2017)

n.a.

## Substrate

Metal, plastics, glass, old paint and factory paint which has been filled and primed; Coated and uncoated surfaces.


## Processing

### Protection measures




Wear personal protection equipment.  
(respiratory mask / gloves / goggles)  
For more information, see safety data sheet.

### Spraying distance



6 - 8 inches / 15 - 20 cm

### Spray passes




1 light spray coat directly before applying the next paint coat and wipe it immediately using a clean, dry cloth. Only clean small areas in parallel. In case of heavy contamination repeat the cleaning process. Don't use contaminated clothes. Change the clothes more often.

### Processing conditions



Optimum application at 64° F - 77° F (18° C - 25° C) and a relative humidity from 40 - 60 %.

### Finish



After painting, turn the can upside down and spray for 3 - 5 seconds to clean the valve.


## Additional Information

### Important Information



Avoid bumps, friction and impact.

### Shelf Life



60 months

The usage period refers to an unused can that is stored correctly at a temperature of 60° F - 77° F / 15 - 25° C and a relative humidity below 60%. The can must be stored and transported in an upright position in a dry place where it is protected against

chemical and mechanical influences. The safety information on the can and all statutory provisions applicable for the storage site must be observed.

## Disposal



The completely emptied spray cans must be disposed of in the recycling system. Cans with hardened material must be disposed of as special waste.

## Note

For professional use only.

Identification, see safety data sheet.

The contents in this technical data sheet were created with great care and reflect our current state of knowledge. They provide the user with application-specific information and do not promise certain properties. The information is non-binding and we accept no liability for its integrity, accuracy and completeness. They do not relieve the user of their duty to check the suitability of our product for the intended purpose. The warnings printed on our labels must be respected. Our brands and patents are protected by copyright. All rights reserved. We reserve the right to update, amend or supplement the content of the information without prior notice.