Technical Data Sheet

Peter Kwasny GmbH, Heilbronner Str. 96
74831 Gundelsheim / Germany
Phone: +496269 95-0, Fax: +496269 95-80
www.spraymax.com / www.kwasny.com / info@kwasny.de

Auto-K Basic
Filler-primer white
400 ml
Art. No. 233007

Product

Description / Purpose

The product primes and fills in one operation, is universally applicable and easy to sand.The high solids content causes pores and fine grinding grooves are balanced and it becomes one achieve a closed, smooth surface.
The subsequent sanding with fine sanding paper creates an even surface, which is the prerequisite for the successful Top coat creates.

Properties

- Provides a smooth surface
- Guaranteed uniform top coat
- Good adhesion
- High filling capacity
- Very good course
- Fast drying
- Good sandability

Material base	Nitro combination resins
Colour	White
VOC Value (EU)	695 g/l

Substrate

Steel (cleaned and sanded)
Pottery, stone, clay, glass, paper and some plastics.
Here before in an inconspicuous place check compatibility and liability.

Processing

Protection measures

Wear personal protection equipment.
(gloves / goggles)
For more information, see safety data sheet.

Shake

Shake can thoroughly for 2 minutes
- starting from when the mixing balls are heard.

Spraying distance



15 cm - 25 cm
Hold the can as upright as possible.

Spray passes

2 spray coats: approx. 50 - 60 µm

Start spraying outside of the Paint surface and wear evenly in Cross several thin coats on.
Cross coat means spraying on a first horizontal and then one vertical layer.

Flash-off time



Flash time: approx. 2 - 3 min between each spray coat. To avoid overspray is for ensure adequate air supply.

Processing conditions

Optimum application at 18° C - 25° C.
The substrate must be dry and free of dust and grease.

Drying



TG1 dust dry: 15 - 20 min
TG2 dry to touch: 60 min.

Continue

Paintwork:
1. Auto-K Anti-corrosion primer
2. Auto-K Filler / primer
3. Top coat

After drying:
Recoatable with itself, at any time.
With all Auto-K paints, at any time.

Finish



After painting, turn the can upside down and spray for 3 - 5 seconds to clean the valve.

Additional Information

Important Information

Avoid bumps, friction and impact.

Do not spray on synthetic resin painted surfaces, as the paint may pull up.

Shelf Life



10 years
The can must be stored and transported upright, dry and protected from chemical and mechanical influences at a temperature between 15 and 25° C. The safety instructions on the can and all legal regulations at the storage location must be observed.

Disposal

The completely emptied spray cans must be disposed of in the recycling system. Cans with hardened material must be disposed of as special waste.

Note

Before use, the safety instructions must always be read carefully and observed.

The contents in this technical data sheet were created with great care and reflect our current state of knowledge. They provide the user with application-specific information and do not promise certain properties. The information is non-binding and we accept no liability for its integrity, accuracy and completeness. They do not relieve the user of their duty to check the suitability of our product for the intended purpose. The warnings printed on our labels must be respected. Our brands and patents are protected by copyright. All rights reserved We reserve the right to update, amend or supplement the content of the information without prior notice.