



Technical Data Sheet

Peter Kwasny GmbH, Heilbronner Str. 96
74831 Gundelsheim / Germany
Phone: +496269 95-0, Fax: +496269 95-80
www.spraymax.com / www.kwasny.com / info@kwasny.de

Auto-K Special Aluminum spray 400 ml Art. Nr. 233065



Product

Description / Purpose

Auto-K aluminum spray can be used universally, heat-resistant up to 650° C and quick-drying. The spray protects against corrosion and is weatherproof and abrasion resistant. It is ideal for Surface finishing of metallic objects.

Properties

- Weather resistant and abrasion resistant
- Protects against corrosion
- Fast drying

Material base

Silicone resins

Colour

silver

VOC Value (EU)

87,62

Substrate

Metallic objects such as railings, metal bezels, etc.


Processing

Protection measures




Wear personal protection equipment.
(gloves / goggles)
For more information, see safety data sheet.

Shake




Shake can thoroughly for 2 minutes
- starting from when the mixing balls are heard.

Spraying distance




15 cm - 25 cm
Hold the can as upright as possible.

Spray passes




1 spray coat: approx. 15 - 20 µm
Crossing means spraying on a first horizontal and then a vertical layer.

Processing conditions




Optimum application at 18° C - 25° C.
The substrate must be dry and free of dust and grease.

Drying



dust dry: after 30 min
Recoatable with itself at any time.

Finish




After finishing the painting process can turn over and spray valve empty to turn on to avoid sticking of the spray valve.

Additional Information

Important Information

No pre-treatment with primers and no after-treatment with further top coats and clear coats necessary.

Shelf Life



The can is upright, dry and protected from chemical and mechanical influences to be stored and transported between 15 - 25° C.
The safety instructions on the can as well as all legal provisions of the storage location to note.

Disposal



The completely emptied spray cans must be disposed of in the recycling system. Cans with hardened material must be disposed of as special waste.

Note

Before use, the safety instructions must always be read carefully and observed.

The contents in this technical data sheet were created with great care and reflect our current state of knowledge. They provide the user with application-specific information and do not promise certain properties. The information is non-binding and we accept no liability for its integrity, accuracy and completeness. They do not relieve the user of their duty to check the suitability of our product for the intended purpose. The warnings printed on our labels must be respected. Our brands and patents are protected by copyright. All rights reserved We reserve the right to update, amend or supplement the content of the information without prior notice.