

Technical Data Sheet

Peter Kwasny GmbH, Heilbronner Str. 96
74831 Gundelsheim / Germany
Phone: +496269 95-0, Fax: +496269 95-80
www.spraymax.com / www.kwasny.com / info@kwasny.de

SprayTEC Electro Protection Spray 400 ml Art. Nr. 235003



Product

Description / Purpose

SprayTec Electro Protection Spray is specially designed for Automotive electronics and electronic systems developed moisture-free contact grease to the permanent protection of electrical and electronic systems.

SprayTec electrical protection spray prevents creepage and electrical breakdown.

The product has very good adhesion and is a excellent contact, moisture and wear protection.

Vibration and abrasion of the Contact is prevented.

Neutral to plastics.

Properties


- Highly effective protection against grease, dirt and rust
- Protects and maintains electrical contacts of all kinds
- Specially designed for automotive electronics and Electronic Plant developed product
- Neutral to plastics
- Protects against ageing, oxidation and copper corrosion
- Prevents vibration and thus abrasion of the contacts
- As an insulator, prevents leakage currents as well electrical breakdown
- Very good wear protection
- Temperature range from - 50° C to 180° C
- Very good protection against external influences
- High yield

Substrate

In the car, motorcycle and leisure sector.

Processing


Protection measures



Wear personal protection equipment.
(gloves / goggles)


For more information, see safety data sheet.

Shake




Rinse the can thoroughly for about 30 sec. before use shake.

Spray to test



test spraying


Spraying distance



15 cm - 25 cm

Hold the can as upright as possible.

Processing conditions



Optimum application at 18° C - 25° C.


The substrate must be dry and free of dust and grease.

Continue

On the clean contact points thin in one Spray evenly from a distance of approx. 20 - 25 cm.

Provides permanent protection against moisture, dirt, dust, rust, grease deposits, etc.


Finish



After use, turn the can upside down and spray the valve completely empty.

Additional Information

Shelf Life



The can is upright, dry and protected from chemical and mechanical influences to be stored and transported between 15 - 25° C.

The safety instructions on the can as well as all legal provisions of the storage location to note.

Disposal



The completely emptied spray cans must be disposed of in the recycling system. Cans with hardened material must be disposed of as special waste.

Note

Before use, the safety instructions must always be read carefully and observed.

The contents in this technical data sheet were created with great care and reflect our current state of knowledge. They provide the user with application-specific information and do not promise certain properties. The information is non-binding and we accept no liability for its integrity, accuracy and completeness. They do not relieve the user of their duty to check the suitability of our product for the intended purpose. The warnings printed on our labels must be respected. Our brands and patents are protected by copyright. All rights reserved We reserve the right to update, amend or supplement the content of the information without prior notice.