

Technical Data Sheet

Peter Kwasny GmbH, Heilbronner Str. 96
74831 Gundelsheim / Germany
Phone: +496269 95-0, Fax: +496269 95-80
www.spraymax.com / www.kwasny.com / info@kwasny.de

SprayTEC Cavity sealant Spray can 500 ml Art. Nr. 235504



Product

Description / Purpose

SprayTec cavity sealing is a highly effective wax-based preservation product. For a run-free application, for immediate processing as a spray or ready-to-use funnel bottle with the suction air or airless gun. The product forms an amber-colored, transparent layer and permanently protects all cavities against the effects of the weather. Can also be used as protection for various metal objects are used. It has the highest corrosion resistance and excellent creep properties.

Properties

- Special protection against rust, splash water, road salt and other weather influences
- Highest corrosion resistance after DIN 53210SS
- Outstanding adhesion
- Effectively stops water infiltration and displaces moisture
- Outstanding creep properties (especially in hard-to-reach places)
- Effectively protects against heat and cold (from 5 - 35° C)
- Also suitable as protection for metal objects
- Allows spray probe or long spray tube use even in hard-to-reach places

Colour brown transparent
VOC Value (EU) 73,00

Substrate

Cars, trucks, vehicles, caravans, tanks, boats, etc., especially for repair work, sills, bars, doors, side panels, hoods, disguises etc.


Processing

Protection measures




Wear personal protection equipment. (gloves / goggles)
 For more information, see safety data sheet.

Shake




Shake the can thoroughly for 3 minutes before use.

Spray to test




test spraying

Spraying distance



20 cm - 30 cm
 Hold the can as upright as possible.

Spray passes




Spray the product in several layers.

Processing conditions



Optimum application at 18° C - 25° C.
 The substrate must be dry and free of dust and grease.

Drying



dry to touch: after approx. 3 - 4 hour
 fully dried: after 24 hour

Continue


The surface to be treated must be thoroughly cleaned of penetrating oil, tar and wax residue.
 Removal possible with white spirit.
 Mask off areas not to be sprayed generously.

NOT on the engine, transmission, braking point and Spray exhaust pipes.

Splashes on the body immediately with one remove a rag soaked in gasoline or petroleum.

After complete solidification with each Paint system can be painted over.

Finish




After use, turn the can upside down and spray the valve completely empty.

Clean used tools accordingly.

Additional Information

Shelf Life



The can is upright, dry and protected from chemical and mechanical influences to be stored and transported between 15 - 25° C.

The safety instructions on the can as well as all legal provisions of the storage location to note.

Disposal



The completely emptied spray cans must be disposed of in the recycling system. Cans with hardened material must be disposed of as special waste.

Note

Before use, the safety instructions must always be read carefully and observed.

The contents in this technical data sheet were created with great care and reflect our current state of knowledge. They provide the user with application-specific information and do not promise certain properties. The information is non-binding and we accept no liability for its integrity, accuracy and completeness. They do not relieve the user of their duty to check the suitability of our product for the intended purpose. The warnings printed on our labels must be respected. Our brands and patents are protected by copyright. All rights reserved We reserve the right to update, amend or supplement the content of the information without prior notice.