

Technical Data Sheet

Peter Kwasny GmbH, Heilbronner Str. 96
74831 Gundelsheim / Germany
Phone: +496269 95-0, Fax: +496269 95-80
www.spraymax.com / www.kwasny.com / info@kwasny.de

RACING

Heat resistant 650° black

400 ml

Art. Nr. 288041



Product

Description / Purpose

Racing heat-resistant 650° C is ideally suited for parts on the car and in the home that are subject to high temperatures, such as exhaust pipes, garden grills, heating boilers, cast iron stoves. The product is highly heat resistant, weatherproof and durable.

Properties

- Extremely heat-resistant up to 650° C
- Weather resistant
- Resilient
- Free of heavy metals: no lead, cadmium, chrome

Material base

Silicone resins

Colour

black

VOC Value (EU)

66,61

Substrate

Temperature-stressed metal parts such as e.g. exhaust, barbecue, boiler or cast iron stove. (cleaned, free of dust and grease)


Processing

Protection measures




Wear personal protection equipment.
(gloves / goggles)
For more information, see safety data sheet.

Shake




Shake can thoroughly for 2 minutes
- starting from when the mixing balls are heard.

Spraying distance




15 cm - 25 cm
Hold the can as upright as possible.

Spray passes




1 spray coat: approx. 7 µm
Crossing means spraying on an initially horizontal and then a vertical layer.

Processing conditions



Optimum application at 18° C - 25° C.
The substrate must be dry and free of dust and grease.

Drying




dust dry: after 30 min
Heat SLOWLY.
Paint only hardens at temperatures above +250° C.

Continue

Paintwork:
No pre-treatment with primers.
No post-treatment with further cover and clear coats required.
Recoatable with itself at any time.

Finish




After finishing the painting process can turn over and spray valve empty to turn on to avoid sticking of the spray valve.

Additional Information

Important Information

Heat SLOWLY.
Paint only hardens at temperatures above +250° C.

Shelf Life



The can is upright, dry and protected from chemical and mechanical influences to be stored and transported between 15 - 25° C.
The safety instructions on the can as well as all legal provisions of the storage location to note.

Disposal



The completely emptied spray cans must be disposed of in the recycling system. Cans with hardened material must be disposed of as special waste.

Note

Before use, the safety instructions must always be read carefully and observed.

The contents in this technical data sheet were created with great care and reflect our current state of knowledge. They provide the user with application-specific information and do not promise certain properties. The information is non-binding and we accept no liability for its integrity, accuracy and completeness. They do not relieve the user of their duty to check the suitability of our product for the intended purpose. The warnings printed on our labels must be respected. Our brands and patents are protected by copyright. All rights reserved We reserve the right to update, amend or supplement the content of the information without prior notice.