

Technical Data Sheet

Peter Kwasny GmbH, Heilbronner Str. 96
 74831 Gundelsheim / Germany
 Phone: +496269 95-0, Fax: +496269 95-80
 www.spraymax.com / www.kwasny.com / info@kwasny.de

RACING
Rim spray silver
500 ml
Art. Nr. 288937



Product

Description / Purpose

Racing rim spray is an abrasion-resistant, car wash-resistant product for successful Painting car rims. The product has a high covering power and is resistant to road salt, rockfall etc. In addition to the shades is a Racing rim spray clear coat (Art. no. 288 053) available.

Properties

- For painting car rims
- Particularly high hiding power
- Resistant to road salt, stone chips, etc.
- Abrasion resistant
- Resistant to car washes
- Free of heavy metals: no lead, cadmium, chrome

Material base

Nitro combination paint

Colour

silver

VOC Value (EU)

86,62

Substrate

Metal rims, aluminum rims
 (cleaned, free of dust and grease)


Processing

Protection measures




Wear personal protection equipment.
(gloves / goggles)
For more information, see safety data sheet.

Shake




Shake can thoroughly for 2 minutes
- starting from when the mixing balls are heard.

Spraying distance




15 cm - 25 cm
Hold the can as upright as possible.

Spray passes




2 spray coats: approx. 50 - 60 µm
Crossing means spraying on an initially horizontal
and then a vertical layer.

Processing conditions



Optimum application at 18° C - 25° C.
The substrate must be dry and free of dust and
grease.

Drying




dust dry: after 10 min
dry to touch: after 2 - 3 hour
fully dried: after 12 hours

Continue

Paintwork:
1. Racing anti-corrosion primer
2. Racing universal primer
3. Racing rim spray
Recoat with itself at any time.
With clear coat at any time.


Finish



After finishing the painting process can turn over and
spray valve empty to turn on to avoid sticking of the
spray valve.

Additional Information

Shelf Life



The can is upright, dry and protected from chemical
and mechanical influences to be stored and
transported between 15 - 25° C.
The safety instructions on the can as well as all legal
provisions of the storage location to note.

Disposal



The completely emptied spray cans must be disposed of in the recycling system. Cans with hardened material must be disposed of as special waste.

Note

Before use, the safety instructions must always be read carefully and observed.

The contents in this technical data sheet were created with great care and reflect our current state of knowledge. They provide the user with application-specific information and do not promise certain properties. The information is non-binding and we accept no liability for its integrity, accuracy and completeness. They do not relieve the user of their duty to check the suitability of our product for the intended purpose. The warnings printed on our labels must be respected. Our brands and patents are protected by copyright. All rights reserved We reserve the right to update, amend or supplement the content of the information without prior notice.