

Technical Data Sheet

Peter Kwasny GmbH, Heilbronner Str. 96
74831 Gundelsheim / Germany
Phone: +496269 95-0, Fax: +496269 95-80
www.spraymax.com / www.kwasny.com / info@kwasny.de

SPRAILA
Rim spray gold
400 ml
Art. Nr. 300038



Product

Description / Purpose

Spraila rim sprays are abrasion-resistant products for the reliable painting of car rims.

Spraila wheel rim spray has excellent coverage, is car wash safe and is Resistant to road salt, stone chips etc.

Properties

- High hiding power
- Resistant to road salt, stone chips, etc.
- Abrasion resistant
- Resistant to car washes
- Free of heavy metals: no lead, cadmium, chrome

Material base

Nitro combination paint

Colour

gold

VOC Value (EU)

86,04

Substrate

Car rims, metal, steel, aluminum

Processing


Protection measures



Wear personal protection equipment.
(gloves / goggles)


For more information, see safety data sheet.

Shake




Shake can thoroughly for 2 minutes
- starting from when the mixing balls are heard.

Spraying distance




15 cm - 25 cm
Hold the can as upright as possible.

Spray passes




2 spray coats: approx. 50 - 60 μ m
Crossing means spraying on an initially horizontal and then a vertical layer.

Processing conditions



Optimum application at 18° C - 25° C.
The substrate must be dry and free of dust and grease.

Drying



dust dry: 10 min
dry to touch: after 1 - 2 hours
fully dried: after 6 - 8 days

Continue


Paintwork:

1. Spraila anti-corrosion primer
2. Auto-K Filler / primer or
Auto-K spray putty
3. Rim paint

Recoatable:

With yourself at all times. With clear coat at any time.

Finish



After finishing the painting process can turn over and spray valve empty to turn on to avoid sticking of the spray valve.


Additional Information

Important Information

When painting aluminum rims, please note:

Spray rim paint onto the clean, dust and grease-free and sanded surface.

Shelf Life



The can is upright, dry and protected from chemical and mechanical influences to be stored and transported between 15 - 25° C.

The safety instructions on the can as well as all legal provisions of the storage location to note.

Disposal



The completely emptied spray cans must be disposed of in the recycling system. Cans with hardened material must be disposed of as special waste.

Note

Before use, the safety instructions must always be read carefully and observed.

The contents in this technical data sheet were created with great care and reflect our current state of knowledge. They provide the user with application-specific information and do not promise certain properties. The information is non-binding and we accept no liability for its integrity, accuracy and completeness. They do not relieve the user of their duty to check the suitability of our product for the intended purpose. The warnings printed on our labels must be respected. Our brands and patents are protected by copyright. All rights reserved We reserve the right to update, amend or supplement the content of the information without prior notice.