# Technical Data Sheet

Peter Kwasny GmbH, Heilbronner Str. 96
74831 Gundelsheim / Germany
Phone: +496269 95-0, Fax: +496269 95-80
www.spraymax.com / www.kwasny.com / info@kwasny.de




## belton® hitcolor
## Adhesive ground white + grey 400 ml
## Art. No. 320ZZZ

## Product

**Description / Area of use**

Paint spray program for inexpensive and decorative spray painting in the area of the house, Hobby, garden and workshop.
Belton primer is the ideal preparation for the subsequent top coat on many substrates.
Hitcolor is on on many surfaces well-rounded, compact spray paint range that from primers to common color tones to clear coat is enough.
With Hitcolor, it just gets colorful.

**Product benefits**

- Compact spray paint range
- Renner colors and clear coat
- Weather-resistant, for inside and outside
- Good coverage and levelling
- Simple application
- Fast drying and productive
- Paint cheaply

**Material base**

Nitro combination resins

## Substrate

Metal, wood, ceramics, stone, clay, glass, styrofoam, rattan/raffia, cardboard/paper etc.

## Processing

**Protection measures**




Wear personal protection equipment.
(gloves / goggles)
For more information, see safety data sheet.

**Shake**



Shake can thoroughly for 2 minutes
- starting from when the mixing balls are heard.

**Spraying distance**



15 cm - 25 cm

**Spray passes**




with 2 - 3 cross coats: approx. 40 - 50 µm

**Processing conditions**



The surface to be painted must be clean, dry, free of dust and grease and, in the case of metals, complete be de-rusted. Optimal processing at 18° C - 25° C

**Drying**



dust dry: approx. 20 min
dry to touch: approx. 60 min
fully cured: approx. 12 hours

**Painting structure**

Paintwork metal:
1. belton basic Anti-rust primer (exterior)
2. hitcolor Primer / belton basic universal primer
3. hitcolor hue
4. hitcolor clear coat (optional)

Wood:
1. hitcolor Primer / belton basic wood primer
2. hitcolor hue
3. hitcolor clear coat (optional)

Plastic:


1. hitcolor basic Primer / belton basic plastic primer
2. hitcolor hue
3. hitcolor clear coat (optional)

Styropor:

1. belton basic Styrofoam primer
2. hitcolor hue
3. hitcolor clear coat (optional)

Recoatable with itself at any time. With all hitcolor paints at any time.

**Finish**



After painting, turn the can upside down and spray for 3 - 5 seconds to clean the valve.

## Additional Information


**Please note**



Avoid shocks, friction and impacts.

Please check plastic substrates for compatibility. All other substrates such as stone, clay, ceramics, glass, rattan/raffia, cardboard/paper should be primed with the belton universal primer. Do not spray on synthetic resin painted surface as paint may lift.

**Shelf Life**



10 Years
The can must be stored and transported in an upright position between 15 - 25° C and a relative humidity of not more than 60 % in a dry place where it is protected against chemical and mechanical influences. The safety instructions on the can as well as all legal provisions of the storage location have to be noted.

**Disposal**



The completely emptied spray cans must be disposed of in the recycling system. Cans with hardened material must be disposed of as special waste.

**Note**

Before use, the safety instructions must always be read carefully and observed.

The contents in this technical data sheet were created with great care and reflect our current state of knowledge. They provide the user with application-specific information and do not promise certain properties. The information is non-binding and we accept no liability for its integrity, accuracy and completeness. They do not relieve the user of their duty to check the suitability of our product for the intended purpose. The warnings printed on our labels must be respected. Our brands and patents are protected by copyright. All rights reserved We reserve the right to update, amend or supplement the content of the information without prior notice.