

## Technical Data Sheet

Peter Kwasny GmbH, Heilbronner Str. 96  
74831 Gundelsheim / Germany  
Phone: +496269 95-0, Fax: +496269 95-80  
www.spraymax.com / www.kwasny.com / info@kwasny.de

**belton® Special**  
**Clear coat for all effects**  
**400 ml**  
**Art. Nr. 323399**



### Product

#### Description / Area of use

The special clear coat seals surfaces and objects to be painted with effect sprays, e.g. belton neon, pearl-, diamond-, granite effect, etc. The clear coat ensures permanent and safe protection of the paintwork.

#### Product benefits

- Optimum long-term protection for the paintwork
- Fast drying and permanent high gloss
- Very good flow and easy processing
- Chemical and weather resistant
- Shock and impact resistant
- For indoor and outdoor
- For a perfect finish

#### Material base

Acrylic resins

#### Colour

Colorless, gloss

### Substrate

All belton effect sprays

### Processing


#### Protection measures



Wear personal protection equipment.  
(gloves / goggles)


For more information, see safety data sheet.

## Shake




Shake can thoroughly for 2 minutes  
- starting from when the mixing balls are heard.

## Spraying distance



15 cm - 25 cm

## Spray passes




with 2 - 3 cross coats: approx. 40 - 50 µm

## Processing conditions



The surface to be painted must be clean, dry and free of grease.

## Drying



dust dry: after approx. 20 min  
dry to touch: after approx. 60 min  
fully cured: after approx. 12 hours

## Painting structure


### Paintwork:

1. belton primer  
(specific primers depending on the substrate)
2. belton special effect paints  
(Granite-, Pearl-, Diamond-, Neon-, etc.)
3. belton clear coat for all effects

Recommendation: Stay in the belton system.

Recoatable with itself and all belton paints at any time.

## Finish




After finishing the painting process can turn around and spray the valve empty.

## Additional Information

### Please note

For plastics, please check compatibility beforehand check and prime with belton basic plastic primer.  
Do not spray on synthetic resin painted surfaces, as the paint may pull up.

## Shelf Life



The can is upright, dry and protected from chemical and mechanical influences to be stored and transported between 15 - 25° C.

The safety instructions on the can as well as all legal provisions of the storage location to note.

## Disposal



The completely emptied spray cans must be disposed of in the recycling system. Cans with hardened material must be disposed of as special waste.

## Note

Before use, the safety instructions must always be read carefully and observed.

The contents in this technical data sheet were created with great care and reflect our current state of knowledge. They provide the user with application-specific information and do not promise certain properties. The information is non-binding and we accept no liability for its integrity, accuracy and completeness. They do not relieve the user of their duty to check the suitability of our product for the intended purpose. The warnings printed on our labels must be respected. Our brands and patents are protected by copyright. All rights reserved We reserve the right to update, amend or supplement the content of the information without prior notice.