

Technical Data Sheet

Peter Kwasny GmbH, Heilbronner Str. 96
74831 Gundelsheim / Germany
Phone: +496269 95-0, Fax: +496269 95-80
www.spraymax.com / www.kwasny.com / info@kwasny.de

belton® Special
Radiator paint creamy white
400 ml
Art. Nr. 323452



Product

Description / Area of use

Paint spray resistant to yellowing and temperature up to +80° C. For color embellishment and Painting radiators, towel warmers, hot water pipes, thermo devices, etc.

Especially helpful with spray painting rib radiators.

Product benefits

- Resistant radiator paint
- Long-term protection and color enhancement
- Temperature resistant up to 80°C
- High resistance to yellowing
- Good hiding power and fast drying
- Very good flow and easy processing
- For fin radiators and others temperature-stressed objects

Material base

Nitro combination resins

Substrate

Iron, steel, metals etc.

Processing

Protection measures



Wear personal protection equipment.
(gloves / goggles)
For more information, see safety data sheet.

Shake



Shake can thoroughly for 2 minutes
- starting from when the mixing balls are heard.

Spraying distance



15 cm - 25 cm

Spray passes



with 2 - 3 cross coats: approx. 40 - 50 µm

Processing conditions



The surface to be painted must be clean, dry and
free of grease.

Drying




dust dry: after approx. 20 min
dry to touch: after approx. 60 min
fully cured: after approx. 12 hours

Painting structure

Recoatable with itself at any time.

Finish




After finishing the painting process can turn around
and spray the valve empty.

Additional Information

Please note

Do not use a primer as this does not is temperature
resistant. Do not spray on synthetic resin painted
surfaces, as the paint may pull up.
Varnishing only on cold objects. After this Ventilate
the rooms well when spray painting.

Shelf Life



The can is upright, dry and protected from chemical and mechanical influences to be stored and transported between 15 - 25° C.

The safety instructions on the can as well as all legal provisions of the storage location to note.

Disposal



The completely emptied spray cans must be disposed of in the recycling system. Cans with hardened material must be disposed of as special waste.

Note

Before use, the safety instructions must always be read carefully and observed.

The contents in this technical data sheet were created with great care and reflect our current state of knowledge. They provide the user with application-specific information and do not promise certain properties. The information is non-binding and we accept no liability for its integrity, accuracy and completeness. They do not relieve the user of their duty to check the suitability of our product for the intended purpose. The warnings printed on our labels must be respected. Our brands and patents are protected by copyright. All rights reserved We reserve the right to update, amend or supplement the content of the information without prior notice.