

## Technical Data Sheet

Peter Kwasny GmbH, Heilbronner Str. 96  
74831 Gundelsheim / Germany  
Phone: +496269 95-0, Fax: +496269 95-80  
www.spraymax.com / www.kwasny.com / info@kwasny.de

**belton® Special**  
**Enamel paint spray**  
**400 ml**  
**Art. Nr. 323465**



### Product

#### Description / Area of use

For repairing scratches, minor damage to enamel surfaces or embellishment of old enamel objects, e.g. bowls, buckets or other objects.  
Also for "white household goods". For exterior repairs wash basins, shower and bath tubs.

#### Product benefits

- Special spray paint for enamel surfaces
- For indoor and outdoor
- Good hiding power and fast drying
- Very good flow and easy processing
- Ideal for "old" enamel objects such as bowls, cans etc.
- Also for "white" household goods, e.g. refrigerators, washing machines, etc.

#### Material base

Nitro combination resins

#### Colour

White

### Substrate

Iron, metals

## Processing

### Protection measures



Wear personal protection equipment.  
(gloves / goggles)  
For more information, see safety data sheet.

### Shake



Shake can thoroughly for 2 minutes  
- starting from when the mixing balls are heard.

### Spraying distance



15 cm - 25 cm

### Spray passes




with 2 spray coats: approx. 40 - 50 µm

### Processing conditions



The surface to be painted must be clean, dry and  
free of grease.

### Drying




dust dry: after approx. 20 min  
dry to touch: after approx. 60 min  
fully cured: after approx. 12 hours

### Painting structure

#### Paintwork:

1. belton basic universal primer (optional)
  2. belton special enamel paint spray
- Recoatable with itself at any time and with all belton  
paints.

### Finish




After finishing the painting process can turn around  
and spray the valve empty.

## Additional Information

### Please note

Large-area refinishes, e.g. on bathtubs, washbasins,  
etc., are permanently not possible.  
Do not spray on synthetic resin painted surfaces,  
as the paint may pull up.

## Shelf Life



The can is upright, dry and protected from chemical and mechanical influences to be stored and transported between 15 - 25° C.

The safety instructions on the can as well as all legal provisions of the storage location to note.

## Disposal



The completely emptied spray cans must be disposed of in the recycling system. Cans with hardened material must be disposed of as special waste.

## Note

Before use, the safety instructions must always be read carefully and observed.

The contents in this technical data sheet were created with great care and reflect our current state of knowledge. They provide the user with application-specific information and do not promise certain properties. The information is non-binding and we accept no liability for its integrity, accuracy and completeness. They do not relieve the user of their duty to check the suitability of our product for the intended purpose. The warnings printed on our labels must be respected. Our brands and patents are protected by copyright. All rights reserved We reserve the right to update, amend or supplement the content of the information without prior notice.