

Technical Data Sheet

Peter Kwasny GmbH, Heilbronner Str. 96
74831 Gundelsheim / Germany
Phone: +496269 95-0, Fax: +496269 95-80
www.spraymax.com / www.kwasny.com / info@kwasny.de

belton® Special
Frosted glass effect
400 ml
Art. Nr. 323470



Product

Description / Area of use

Special varnish, with which on transparent Painted objects such as window glass, mirror surfaces, Vases, shower stalls, etc. a milky matt effect is achieved.
Ideal as a privacy screen or for decorative purposes.

Product benefits

- Milky matt finish effect
- Privacy and decoration in one
- Very good flow and easy processing
- Fast drying and high yield
- Weather-resistant, for inside and outside

Material base

Acrylic resin base

Colour

Milky matt

Substrate

Glass, mirrors, shower stalls

Processing


Protection measures



Wear personal protection equipment.
(gloves / goggles)


For more information, see safety data sheet.

Shake




Shake can thoroughly for 2 minutes
- starting from when the mixing balls are heard.

Spraying distance



15 cm - 25 cm

Spray passes




with 3 - 4 cross coats: approx. 20 - 40 µm
(per cross coat 5 - 10 µm)

Processing conditions




Varnish in several thin coats.
The surface to be painted must be clean, dry and free of grease.

Drying



dust dry: after approx. 20 min
dry to touch: after approx. 60 min
fully cured: after approx. 12 hours
Recoatable with itself at any time.

Finish




After finishing the painting process can turn around and spray the valve empty.

Additional Information

Please note

Recommendation: When painting plastics, please check compatibility beforehand and prime with belton-basic plastic primer.

Shelf Life



The can is upright, dry and protected from chemical and mechanical influences to be stored and transported between 15 - 25° C.
The safety instructions on the can as well as all legal provisions of the storage location to note.

Disposal



The completely emptied spray cans must be disposed of in the recycling system. Cans with hardened material must be disposed of as special waste.

Note

Before use, the safety instructions must always be read carefully and observed.

The contents in this technical data sheet were created with great care and reflect our current state of knowledge. They provide the user with application-specific information and do not promise certain properties. The information is non-binding and we accept no liability for its integrity, accuracy and completeness. They do not relieve the user of their duty to check the suitability of our product for the intended purpose. The warnings printed on our labels must be respected. Our brands and patents are protected by copyright. All rights reserved We reserve the right to update, amend or supplement the content of the information without prior notice.