

Technical Data Sheet

Peter Kwasny GmbH, Heilbronner Str. 96 74831 Gundelsheim / Germany Phone: +496269 95-0, Fax: +496269 95-80 www.spraymax.com / www.kwasny.com / info@kwasny.de

> belton® Special Concrete effect 400 ml Art. Nr. 323494



Product

Description / Area of use

High-quality effect spray to achieve a decorative concrete look. The special spray is indoors and outdoors, directly on many surfaces applicable. The concrete effect gives the painted objects a the typical solid concrete look.

Product benefits

- Unique concrete effect for indoors and outdoors
- · High coverage, fast drying
- Excellent adhesion, very good levelling
- · Can be used on many substrates
- · For decorative and creative paintwork
- Concrete effect in trendy industrial loft style
- DO NOT paint over with clear lacquer!

Material base

Colour

Nitro combination base

Concrete grey

Substrate

Metals, wood, plastic, stone, plaster, MDF-boards, etc; Non-ferrous metals, galvanised steel, polystyrene and some plastics must be pretreated with the respective Belton special primer.



Processing

Protection measures



Wear personal protection equipment.

(gloves / goggles)

For more information, see safety data sheet.

Shake



Shake can thoroughly for 2 minutes

- starting from when the mixing balls are heard.

Spraying distance



25 cm - 35 cm

Spray passes

Processing conditions



2 - 3 evenly thin spray coats

approx. 40 - 50 µm



The surface to be painted must be clean, dry and free of grease.

Drying



dust dry: after approx. 10 min

dry to touch: after approx. 35 min

fully cured: after approx. 24 hours

Painting structure

Paintwork metal:

- 1. belton basic anti-rust primer Art.Nr. 323504 or belton basic universal primer Art.Nr. 323501
- 2. belton special concrete effect

DO NOT OVERCOAT WITH CLEAR LACQUER! Wood:

- 1. belton basic wood primer Art.Nr. 323503
- 2. belton special concrete effect

DO NOT OVERCOAT WITH CLEAR LACQUER! Plastic:

- 1. belton basic plastic primer Art.Nr. 323505
- 2. belton special concrete effect

DO NOT OVERCOAT WITH CLEAR LACQUER!



Styrofoam:

- 1. belton basic styrofoam primer Art.Nr. 323506
- 2. belton special concrete effect

DO NOT OVERCOAT WITH CLEAR LACQUER!

Can be recoated with itself at any time.

With 1K top coat (colour tone) after 24 hours drying.

Overcoating with a clear lacquer is not necessary, to permanently preserve the concrete surface look.

Finish



After finishing the painting process can turn around and spray the valve empty.

Additional Information

Please note

Suitable for indoor and outdoor use!

Please check plastic substrates for compatibility.

All other substrates such as stone, clay, ceramics, glass, rattan/bast, cardboard/paper should be primed with the belton universal primer.

Do not spray on synthetic resin painted surfaces, as the paint may pull up.

The surface to be painted must be clean, dry and free of grease.

Shelf Life



The can is upright, dry and protected from chemical and mechanical influences to be stored and transported between 15 - 25° C.

The safety instructions on the can as well as all legal provisions of the storage location to note.

Disposal



The completely emptied spray cans must be disposed of in the recycling system. Cans with hardened material must be disposed of as special waste.



Note

Before use, the safety instructions must always be read carefully and observed.

The contents in this technical data sheet were created with great care and reflect our current state of knowledge. They provide the user with application-specific information and do not promise certain properties. The information is non-binding and we accept no liability for its integrity, accuracy and completeness. They do not relieve the user of their duty to check the suitability of our product for the intended purpose. The warnings printed on our labels must be respected. Our brands and patents are protected by copyright. All rights reserved We reserve the right to update, amend or supplement the content of the information without prior notice.