

Technical Data Sheet

Peter Kwasny GmbH, Heilbronner Str. 96
74831 Gundelsheim / Germany
Phone: +496269 95-0, Fax: +496269 95-80
www.spraymax.com / www.kwasny.com / info@kwasny.de

belton® Basic
Styrofoam primer
150 ml
Art. No. 326077



Product

Description / Area of use

The strong, pore-filling special primer creates a closed, smooth surface, as optimal Preparation for the subsequent top coat.

Product benefits

- Especially for styrofoam
- Pore filling
- Creates smooth surface
- Outstanding adhesion promotion
- Easy processing
- Fast drying
- Very productive

Material base

Special paint resins

Colour


Beige

Substrate

Styrofoam, Styrodur


Processing

Protection measures




Wear personal protection equipment.
(gloves / goggles)
For more information, see safety data sheet.

Shake




Shake can thoroughly for 2 minutes
- starting from when the mixing balls are heard.

Spraying distance



15 cm - 25 cm

Spray passes




with 2 - 3 spray coats: approx. 40 - 50 µm

Processing conditions



The surface to be painted must be clean and dry.

Drying



dust dry: after approx. 20 min

dry to touch: after approx. 60 min

fully cured: after approx. 12 hours

Painting structure


Paintwork:

1. belton basic styrofoam primer
2. Top coat / belton paint spray (color)

Recoatable:

After 3 hours with all belton paints
(including clear paint) with itself at any time.

Finish



After painting, turn the can upside down and spray
for 3 - 5 seconds to clean the valve.


Additional Information

Please note



Avoid shocks, friction and impacts.

Shelf Life



10 Years

The can must be stored and transported in an upright position between 15 - 25° C and a relative humidity of not more than 60% in a dry place where it is protected against chemical and mechanical influences. The safety instructions on the can as well as all legal provisions of the storage location have to be noted.

Disposal



The completely emptied spray cans must be disposed of in the recycling system. Cans with hardened material must be disposed of as special waste.

Note

Before use, the safety instructions must always be read carefully and observed.

The contents in this technical data sheet were created with great care and reflect our current state of knowledge. They provide the user with application-specific information and do not promise certain properties. The information is non-binding and we accept no liability for its integrity, accuracy and completeness. They do not relieve the user of their duty to check the suitability of our product for the intended purpose. The warnings printed on our labels must be respected. Our brands and patents are protected by copyright. All rights reserved We reserve the right to update, amend or supplement the content of the information without prior notice.