

# Technical Data Sheet



The United States of America:  
by Peter Kwasny Inc.  
62-64 Enter Lane  
Islandia, NY 11749

Distributed in

Canada:  
Peter Kwasny Spraypaint Canada Inc.  
40 University Avenue, Suite 904  
Toronto, ON. M5J 1T1

Toll free North America  
Phone: 1-844-426-6330 / Fax: 1-866-226-6434  
order@kwasny.us / service@kwasny.us  
www.spraymax.com

**SprayMax®**  
**2K Clear Matte**  
**318 g NET WT. 11.2 oz**  
**Art. Nr. 3680065**



## Product

### Description / Purpose

2K Clear Coat available in two gloss levels  
(Matt & Satin).  
Developed for the Small Damage Repair  
Process or complete painting of mounting parts.

### Properties

- Very fast drying
- Excellent flow
- Highest chemical and weathering resistance
- Gloss units at 85°: Matt 12 ± 3 / Satin 40 ± 3

### Material base

Two-component acrylic resins  
Activator: aliphatic isocyanates

### Gloss level

Matt,  
12 ± 3 gloss units at 85° measurement angle on  
completely dried basecoats

### Solid content

approx. 25 % by weight relating to the diluted paint

### EPA Coating Category

CCP Clear Coatings Product  
PWR Limit 1.50

### CARB Aerosol Rule Coating Category (01/2017)

TCC Two Component Coating  
PWR Limit 1.20

## Substrate

Solvent and waterborne base coat systems,  
old paint coats dried according to manufacturer's  
instructions (cleaned and sanded).


## Processing

### Protection measures




Wear personal protection equipment.  
(respiratory mask / gloves / goggles)  
For more information, see safety data sheet.

### Shake




Before activating, shake can thoroughly for 2 minutes  
again from when the mixing balls are heard.

### Place red button




Remove the red button from the cap. Turn the can  
by 180° and fit the button onto the pin.

### Press red button




Turn the can upside down and place on a firm  
surface. Press the red button with the palm of your  
hand until it clicks into place.

### Shake




After activating, shake can again thoroughly for  
2 minutes, again from when the mixing balls are  
heard.

### Spray to test




After shaking the can, test spray and check  
compatibility with the surface and the colour.

### Spraying distance




6 - 8 inches / 15 - 20 cm

### Spray passes




Dry film thickness 1.6 mil (40 µm)  
(approx. 1 - 2 spray coats)

### Flash-off time




Flash time:  
approx. 5 min between each spray coat

## Processing conditions




Optimum application at 64° F - 77° F (18° C - 25° C) and a relative humidity from 40 - 60 %.

## Coverage



approx. 5.4 - 8.1 sq ft (0.5 - 0.75 m<sup>2</sup>) / aerosol at approx. 1.2 - 2.0 mil (30 - 50 µm) dry film thickness

## Drying



dust dry: 12 min

dry to touch: 80 min

Do not polish!

Matt clearcoats can generally not be polished - polishing changes the gloss and colour impression.




IR drying possible, Respect technical manual

Forced dry 60 min at 140° F

10 min flash-off time before forced dry

IR drying 15 min


## Pot life



Approx. 48 h at 68° F (20° C) room temperature and a relative humidity of approx. 40 - 50 %.

The processing time depends on the ambient temperature. Higher temperatures reduce the pot life, lower temperatures will prolong it.


## Finish



After painting, turn the can upside down and spray the valve until empty.

## Additional Information

### Shelf Life



36 months (not activated)

The usage period refers to an unused can that is stored correctly at a temperature of 68° F / 20° C and a relative humidity below 60%. The can must be stored and transported in an upright position in a dry place where it is protected against chemical and mechanical influences. The safety information on the can and all statutory provisions applicable for the storage site must be observed.

## Disposal



The completely emptied spray cans must be disposed of in the recycling system. Cans with hardened material must be disposed of as special waste.

## Note

For professional use only.

Identification, see safety data sheet.

The contents in this technical data sheet were created with great care and reflect our current state of knowledge. They provide the user with application-specific information and do not promise certain properties. The information is non-binding and we accept no liability for its integrity, accuracy and completeness. They do not relieve the user of their duty to check the suitability of our product for the intended purpose. The warnings printed on our labels must be respected. Our brands and patents are protected by copyright. All rights reserved. We reserve the right to update, amend or supplement the content of the information without prior notice.