

Technical Data Sheet



The United States of America:
Peter Kwasny Inc.
62-64 Enter Lane,
Islandia, NY 11749

Distributed in

Canada by
Peter Kwasny Spraypaint Canada Inc.
2275 Lakeshore Blvd. West, Suite 530
Toronto, ON. M8V 3Y3

Toll free North America
Phone: 1-844-426-6330 / Fax: 1-866-226-6434
order@kwasny.us / service@kwasny.us
www.spraymax.com

SprayMax®
1K Guide Coat Black
291 g NET WT. 10.3 oz
Art. Nr. 3680100



Product

Description / Purpose

This improves the efficiency of the sanding process and the paint result.

Properties

- Fine homogenous mist
- Even, thin wetting of surface
- Powder-like with good sanding properties
- No clogging of the sandpaper

Material base

Special physically-drying coating resins

Colour

Deep black

EPA Coating Category

NFP Non Flat Paint

PWR Limit 1.40

CARB Aerosol Rule Coating Category (01/2017)

NFC Non Flat Coating

PWR Limit 0.95

Substrate

Old paint and factory paint as well as dried and sandable surfaces i.E. putty, primer, filler (cleaned and sanded)


Processing

Protection measures




Wear personal protection equipment.
(respiratory mask/gloves/goggles)
For more information, see safety data sheet.

Shake




Shake can thoroughly for at least 2 minutes from when the mixing balls are heard.

Spraying distance




6 - 8 inches / 15 - 20 cm

Spray passes




Apply one thin coat onto the surface that is to be sanded.

Processing conditions




Optimum application at 64° F - 77° F (18° C - 25° C) and a relative humidity from 40 - 50 %.

Drying



Ready for sanding: approx. 1 min


The stated values refer to the above-mentioned processing conditions. The level of dryness is determined pursuant to DIN 53150.



Wet or dry sanding together with the substrate.

Additional Information

Shelf Life



60 months

The usage period refers to an unused can that is stored correctly at a temperature of 60° F - 77° F / 15 - 25° C and a relative humidity below 60%. The can must be stored and transported in an upright position in a dry place where it is protected against chemical and mechanical influences. The safety information on the can and all statutory provisions applicable for the storage site must be observed.

Disposal



The completely emptied spray cans must be disposed of in the recycling system. Cans with hardened material must be disposed of as special waste.

Note

For professional use only.

Identification, see safety data sheet.

The contents in this technical data sheet were created with great care and reflect our current state of knowledge. They provide the user with application-specific information and do not promise certain properties. The information is non-binding and we accept no liability for its integrity, accuracy and completeness. They do not relieve the user of their duty to check the suitability of our product for the intended purpose. The warnings printed on our labels must be respected. Our brands and patents are protected by copyright. All rights reserved. We reserve the right to update, amend or supplement the content of the information without prior notice.