

Technical Data Sheet



The United States of America:
by Peter Kwasny Inc.
62-64 Enter Lane
Islandia, NY 11749

Distributed in

Canada:
Peter Kwasny Spraypaint Canada Inc.
40 University Avenue, Suite 904
Toronto, ON. M5J 1T1

Toll free North America
Phone: 1-844-426-6330 / Fax: 1-866-226-6434
order@kwasny.us / service@kwasny.us
www.spraymax.com

SprayMax® UV Primer Cleaner 290 g NET WT. 10.2 oz Art. Nr. 3680290



Product

Description / Purpose

Cleaning agent for thorough removal of the adhesive layer of the SprayMax UV Filler 3680019 after UV drying. SprayMax UV Paint Repair System is comprised of four products that complement each other to complete a repair.

UV Primer Part no 3680019

UV Clear Part no 3680059

UV Spot Blender Part no 3680091

UV Primer Cleaner Part no 3680290

Properties

- Removes the adhesive layer of the UV Primer after UV drying
- Maximum yield
- Even distribution

Material base

Special solvent combination

EPA Coating Category

n.a.

CARB Aerosol Rule Coating Category (01/2017)

n.a.

Substrate

Surfaces primed with SprayMax UV Primer 3680019.


Processing

Protection measures




Wear personal protection equipment.
(respiratory mask / gloves / goggles)
For more information, see safety data sheet.

Spraying distance



6 - 8 inches / 15 - 20 cm

Spray passes




1 - 2 full spray coats onto the UV-hardened
SprayMax UV Filler 3680019.
Wipe with a clean, dry cloth immediately after
application. Do not allow to dry.

Processing conditions



Optimum application at 64° F - 77° F (18° C - 25° C)
and a relative humidity from 40 - 60 %.


Finish



After painting, turn the can upside down and spray
the valve until empty.

Additional Information

Shelf Life



60 months
The usage period refers to an unused can that is
stored correctly at a temperature of 60° F - 77° F /
15 - 25° C and a relative humidity below 60%. The
can must be stored and transported in an upright
position in a dry place where it is protected against
chemical and mechanical influences. The safety
information on the can and all statutory provisions
applicable for the storage site must be observed.

Disposal



The completely emptied spray cans must be dis-
posed of in the recycling system. Cans with hardened
material must be disposed of as special waste.

**Note**

For professional use only.

Identification, see safety data sheet.

The contents in this technical data sheet were created with great care and reflect our current state of knowledge. They provide the user with application-specific information and do not promise certain properties. The information is non-binding and we accept no liability for its integrity, accuracy and completeness. They do not relieve the user of their duty to check the suitability of our product for the intended purpose. The warnings printed on our labels must be respected. Our brands and patents are protected by copyright. All rights reserved. We reserve the right to update, amend or supplement the content of the information without prior notice.