



The United States of America:  
Peter Kwasny Inc.  
62-64 Enter Lane,  
Islandia, NY 11749

Distributed in

Canada by  
Peter Kwasny Spraypaint Canada Inc.  
2275 Lakeshore Blvd. West, Suite 530  
Toronto, ON. M8V 3Y3

Toll free North America  
Phone: 1-844-426-6330 / Fax: 1-866-226-6434  
order@kwasny.us / service@kwasny.us  
www.spraymax.com

**SprayMax®**  
**UV Primer Cleaner**  
**290 g NET WT. 10.2 oz**  
**Art. Nr. 3680290**



## Product

### Description / Purpose

Cleaning agent for thorough removal of the adhesive layer of the SprayMax UV Filler 3680019 after UV drying.

SprayMax UV Paint Repair System is comprised of four products that complement each other to complete a repair

UV Primer Part no 3680019

UV Clear Part no 3680059

UV Spot Blender Part no 3680091

UV Primer Cleaner Part no 3680290

### Properties

- Removes the adhesive layer of the UV Primer after UV drying
- Maximum yield
- Even distribution

### Material base

Special solvent combination



**EPA Coating Category** n.a.  
**CARB Aerosol Rule Coating Category** n.a.  
**(01/2017)**

## Substrate

Surfaces primed with SprayMax UV Primer 3680019.


## Processing

### Protection measures




Wear personal protection equipment.  
(respiratory mask/gloves/goggles)  
For more information, see safety data sheet.

### Spraying distance



6 - 8 inches / 15 - 20 cm

### Spray passes




1 - 2 full spray coats onto the UV-hardened  
SprayMax UV Filler 3680019. Wipe with a clean,  
dry cloth immediately after application.  
Do not allow to dry.

### Processing conditions



Optimum application at 64° F - 77° F (18° C - 25° C)  
and a relative humidity from 40 - 60 %.


### Finish



After painting, turn the can upside down and spray  
the valve until empty.

## Additional Information

### Shelf Life



60 months  
The usage period refers to an unused can that is  
stored correctly at a temperature of 60° F - 77° F /  
15 - 25° C and a relative humidity below 60%. The  
can must be stored and transported in an upright  
position in a dry place where it is protected against  
chemical and mechanical influences. The safety  
information on the can and all statutory provisions  
applicable for the storage site must be observed.

## Disposal



The completely emptied spray cans must be disposed of in the recycling system. Cans with hardened material must be disposed of as special waste.

## Note

For professional use only.

Identification, see safety data sheet.

The contents in this technical data sheet were created with great care and reflect our current state of knowledge. They provide the user with application-specific information and do not promise certain properties. The information is non-binding and we accept no liability for its integrity, accuracy and completeness. They do not relieve the user of their duty to check the suitability of our product for the intended purpose. The warnings printed on our labels must be respected. Our brands and patents are protected by copyright. All rights reserved. We reserve the right to update, amend or supplement the content of the information without prior notice.