

Technical Data Sheet



Peter Kwasny GmbH, Heilbronner Str. 96
74831 Gundelsheim / Germany
Phone: +496269 95-0, Fax: +496269 95-80
www.spraymax.com / www.kwasny.com / info@kwasny.de

SprayMax® 1K Blender clear 400 ml Art. Nr. 680092



Product

Description / Purpose

Blender clear is a special product for homogenous paint transitions in the blending area of 1K / 2K clear coats as well as of 2K topcoats with very good blending results. The blender clear is used immediately after the clear- / topcoat is applied.

Properties

- Seamless edge transitions in the blending area
- Very good solving ability
- No colour deviations
- Dries to a glossy finish, does not need to be polished and therefore very good finish results

Material base

Combination of resins and solvents

VOC Value (EU)

732 g/l

Substrate

Surface in transition zone should be sanded until matt with P 2000 - P 4000

Processing

Protection measures




Wear personal protection equipment.

(respiratory mask/gloves/goggles)


For more information, see safety data sheet.

Shake




Shake can thoroughly for at least 2 minutes from when the mixing balls are heard.

Spraying distance




15 cm - 20 cm

Spray passes




Apply several 1 - 2 light spray passes to the edge of the blending area immediately after application of the 2K clear coat or 2K topcoat to achieve a smooth transition.

Processing conditions




Optimum application at 18° C - 25° C and a relative humidity from 40 - 60 %.

Coverage



approx. 0,5 m²


Finish



After painting, turn the can upside down and spray the valve until empty.

Additional Information

Shelf Life



60 months

The usage period refers to an unused can that is stored correctly at a temperature of 15 - 25 °C and a relative humidity below 60%. The can must be stored and transported in an upright position in a dry place where it is protected against chemical and mechanical influences. The safety information on the can and all statutory provisions applicable for the storage site must be observed.

Disposal



The completely emptied spray cans must be disposed of in the recycling system. Cans with hardened material must be disposed of as special waste.

**Note**

For professional use only.

Identification, see safety data sheet.

The contents in this technical data sheet were created with great care and reflect our current state of knowledge. They provide the user with application-specific information and do not promise certain properties. The information is non-binding and we accept no liability for its integrity, accuracy and completeness. They do not relieve the user of their duty to check the suitability of our product for the intended purpose. The warnings printed on our labels must be respected. Our brands and patents are protected by copyright. All rights reserved We reserve the right to update, amend or supplement the content of the information without prior notice.