

Peter Kwasny GmbH, Heilbronner Str. 96  
74831 Gundelsheim / Deutschland  
Telefon: +496269 95-0, Fax: +496269 95-80  
www.spraymax.com / www.kwasny.com / info@kwasny.de

## SprayMax® 1K Aqua Silicon remover 400 ml Art. Nr. 680094



### Product

#### Description / Purpose

Water-borne cleaning agent, rich in active ingredients and with a reduced solvent content. Ideal for the removal of silicone, grease, oil, wax, dirt, tar, and soot. This high quality product improves the adhesion to any paint coat and reduces the electrostatic effect. High cleaning and degreasing properties. The product is used for the application of waterborne basecoats.

#### Properties

- Increases adhesion
- Maximum yield
- Uniform distribution
- Strong cleaning and degreasing effect
- Reduces electrostatic effect
- Especially for application of waterborne basecoats and special coatings.

#### Material base

Combination of water and solvent resins

#### VOC Value (EU)

687 g/l

### Substrate

Metal, plastics, glass, old paint and factory paintol which have been filled and primed; Coated and uncoated surfaces.


## Processing

### Protection measures




Wear personal protection equipment.  
(respiratory mask/gloves/goggles)  
For more information, see safety data sheet.

### Spraying distance




15 cm - 20 cm

### Spray passes




1 light spray coat directly before you apply the next lacquer coat and wipe it immediately using a clean, dry cloth. Only clean small areas in parallel. In case of heavy contamination repeat the cleaning process. Don't use contaminated clothes. Change the clothes more often.

### Processing conditions



Optimum application at 18°C - 25°C and a relative humidity from 40 - 50 %.


### Finish



After painting, turn the can upside down and spray the valve until empty.

## Additional Information

### Shelf Life



60 months  
The usage period refers to an unused can that is stored correctly at a temperature of 15 – 25 °C and a relative humidity below 60%. The can must be stored and transported in an upright position in a dry place where it is protected against chemical and mechanical influences. The safety information on the can and all statutory provisions applicable for the storage site must be observed.

## Disposal



The completely emptied spray cans must be disposed of in the recycling system. Cans with hardened material must be disposed of as special waste.

## Note

For professional use only.

Identification, see safety data sheet.

The contents in this technical data sheet were created with great care and reflect our current state of knowledge. They provide the user with application-specific information and do not promise certain properties. The information is non-binding and we accept no liability for its integrity, accuracy and completeness. They do not relieve the user of their duty to check the suitability of our product for the intended purpose. The warnings printed on our labels must be respected. Our brands and patents are protected by copyright. All rights reserved We reserve the right to update, amend or supplement the content of the information without prior notice.