

Peter Kwasny GmbH, Heilbronner Str. 96
74831 Gundelsheim / Deutschland
Telefon: +496269 95-0, Fax: +496269 95-80
www.spraymax.com / www.kwasny.com / info@kwasny.de

SprayMax®
UV Cleaner 400 ml
Art. Nr. 680290



Product

Description / Purpose

Cleaning agent for thorough removal of the adhesive layer of the SprayMax UV Filler 680019 after UV drying.

SprayMax-UV Paint Repair is a product system with a specially harmonized formula and effect concept comprising:

UV Filler Art.-Nr. 680019

UV Clearcoat Art.-Nr. 680059

UV BlenderThinner Art.-Nr. 680091

UV Cleaner Art.-Nr. 680290

Properties

- Removes the adhesive layer of the UV Primer after UV drying
- Maximum yield
- Even distribution

Material base

Special solvent combination

VOC Value (EU)


728 g/l

Substrate

Surfaces primed with SprayMax UV Primer 680019.


Processing

Protection measures




Wear personal protection equipment.
(respiratory mask/gloves/goggles)
For more information, see safety data sheet.

Spraying distance



15 cm - 20 cm

Spray passes




1 - 2 full spray coats onto the UV-hardened
SprayMax UV Filler 680019. Wipe with a clean,
dry cloth immediately after application.
Do not allow to dry.

Processing conditions



Optimum application at 18° C - 25° C and a relative
humidity from 40 - 60 %.


Finish



After painting, turn the can upside down and spray
the valve until empty.

Additional Information

Shelf Life



60 months
The usage period refers to an unused can that is
stored correctly at a temperature of 15 - 25 °C and a
relative humidity below 60%. The can must be stored
and transported in an upright position in a dry place
where it is protected against chemical and
mechanical influences. The safety information on the
can and all statutory provisions applicable for the
storage site must be observed.

Disposal



The completely emptied spray cans must be dis-
posed of in the recycling system. Cans with hardened
material must be disposed of as special waste.



Note

For professional use only.

Identification, see safety data sheet.

The contents in this technical data sheet were created with great care and reflect our current state of knowledge. They provide the user with application-specific information and do not promise certain properties. The information is non-binding and we accept no liability for its integrity, accuracy and completeness. They do not relieve the user of their duty to check the suitability of our product for the intended purpose. The warnings printed on our labels must be respected. Our brands and patents are protected by copyright. All rights reserved We reserve the right to update, amend or supplement the content of the information without prior notice.