Art.Nr. 680604

Technical Data Sheet

Peter Kwasny GmbH, Heilbronner Str. 96 74831 Gundelsheim / Germany Phone: +496269 95-0, Fax: +496269 95-80 www.spraymax.com / www.kwasny.com / info@kwasny.de

SprayMax® 1K UNI BLEND 500 ml Art. Nr. 680604

Blend thinner is a special product for homogenous paint transitions in the blending area of 1K / 2K clear coats as well as of 2K topcoats with outstanding blending results.

- · Seamless edge transitions in the blending area
- Superior solving ability
- No colour deviations
- Dries to a matt finish, must be polished
- · Specially for polishing
- Can be polished without edges

Combination of resins and solvents 750 g/l

Surface in transition zone should be sanded until matt with P 2000 - P 4000

Processing

Product

Properties

Material base

Substrate

VOC Value (EU)

Description / Purpose

Protection measures



Version 6/2023

Wear personal protection equipment. (respiratory mask/gloves/goggles) For more information, see safety data sheet.



UNI BL





Spraying distance

15 cm - 20 cm

Spray passes



Apply several 1 - 2 light spray passes to the edge of the blending area immediately after application of the 2K clear coat or 2K topcoat to achieve a smooth transition.

Optimum application at 18° C - 25° C and a relative humidity from 40 - 60 %.

Additional Information

Processing conditions

Shelf Life



60 months

The usage period refers to an unused can that is stored correctly at a temperature of 15 - 25 °C and a relative humidity below 60%. The can must be stored and transported in an upright position in a dry place where it is protected against chemical and mechanical influences. The safety information on the can and all statutory provisions applicable for the storage site must be observed.

Disposal



The completely emptied spray cans must be disposed of in the recycling system. Cans with hardened material must be disposed of as special waste.

For professional use only. Identification, see safety data sheet.

The contents in this technical data sheet were created with great care and reflect our current state of knowledge. They provide the user with application-specific information and do not promise certain properties. The information is non-binding and we accept no liability for its integrity, accuracy and completeness. They do not relieve the user of their duty to check the suitability of our product for the intended purpose. The warnings printed on our labels must be respected. Our brands and patents are protected by copyright. All rights reserved We reserve the right to update, amend or supplement the content of the information without prior notice.

Note