

Technical Data Sheet

Peter Kwasny GmbH, Heilbronner Str. 96
74831 Gundelsheim / Germany
Phone: +496269 95-0, Fax: +496269 95-80
www.spraymax.com / www.kwasny.com / info@kwasny.de

Auto-K paint preparation Elastic filling putty (styrene-reduced)

250 g
Art. Nr. 745420



Product

Description / Purpose

For metal and plastic parts subject to high vibrations, such as mudguards or doors. Also suitable for repairs on dry stone and concrete as well as on objects made of plastic and ceramics. Intermixed with aluminium powder.

Properties

- Ideal for metal + plastic parts subjected to vibration
- Exceptionally elastic and tough
- Good adhesion to parts subject to vibration
- Can also be used on dry stone plastic, ceramic or concrete

Material base

Specific polyester resin

Colour

silver grey met. (without hardener)

Substrate

Steel, iron, various commercial plastics, ceramic, stone, concrete. Carefully clean substrates from dust, grease and separating agents and sand.

Processing


Protection measures



Wear personal protection equipment.
(gloves / goggles)


For more information, see safety data sheet.

Processing conditions



Optimum application at 18° C - 25° C.

Coverage



PU 250 g in set with hardener: 6 pieces per carton

Continue

Carefully clean the substrate of dust, grease and release agent and sand it.

Pot life

approx. 5 min

Finish


Please clean any tools used (spatula blade, mixing cup, etc.) immediately after finishing work (e.g. with acetone / nitro thinner).

Additional Information

Important Information

CAUTION!
Do not return mixed filler back into the can.

Shelf Life



Filler and hardener 1 year at 20° C in the original closed sealed container when stored properly in a dry place.

Disposal



Can and tube with cured material must be disposed of as hazardous waste.

Note

Before use, the safety instructions must always be read carefully and observed.

The contents in this technical data sheet were created with great care and reflect our current state of knowledge. They provide the user with application-specific information and do not promise certain properties. The information is non-binding and we accept no liability for its integrity, accuracy and completeness. They do not relieve the user of their duty to check the suitability of our product for the intended purpose. The warnings printed on our labels must be respected. Our brands and patents are protected by copyright. All rights reserved We reserve the right to update, amend or supplement the content of the information without prior notice.